NCHC Open Hackathons 2024

Day Final

Team5-parallel-minds,NTHU

team-11-parallel-minds

程詩柔

謝之豫



熊恩伶

OpenACC
More Science, Less Programming

OPEN HACKATHONS

NCHC

NARLabs 財團法人國家實驗研究院
國家高速網路與計算中心
National Center for High-performance Computing

NVIDIA

Firefly algorithm (visualization)

1. 設定螢火蟲總數(population),空間維度(dimen),訓練次數(max_iter)
2. 將所有螢火蟲隨機放在空間中並隨機給定亮度(fitness)
3. 每個iteration，每隻螢火蟲都要朝附近最亮的螢火蟲前進(位置更新)
4. 更新所有螢火蟲的亮度(fitness更新)

迴圈時間複雜度　max_iter * population * dimen * population

why is it important? Robot path planning

Firefly algorithm

- textbook: Nature-Inspired Computation in Navigation and Routing Problems Algorithms, Methods and Applications Editors: Xin-She Yang, Yu-Xin Zhao
- Vehicle path planning : Particle swarm optimization algorithm vs Firefly algorithm
- 準確率： Firefly algorithm > Particle swarm optimization algorithm
- 執行時間: Firefly algorithm > Particle swarm optimization algorithm

Goals :

- accelerate firefly algorithm with cuda



Progress -Week1

Stats System View

MPI Event Trace
NVTX GPU Projection Summary
NVTX GPU Projection Trace
NVTX Push/Pop Range Summary
NVTX Push/Pop Range Trace
NVTX Range Kernel Summary
NVTX Range Summary
NVTX Start/End Range Summary
Network Devices Congestion
NvVideo API Summary
OS Runtime Summary

Time	Total Time	Instances	Avg	Med	Min	Max	StdDev	Range
98.9%	329.187 s	50	6.584 s	6.678 s	3.189 s	9.520 s	1.901 s	:fun() calculate fitness
1.1%	3.807 s	6125000	621 ns	320 ns	79 ns	28.061 ms	20.046 µs	:update firefly position
0.0%	403.836 µs	1	403.836 µs	403.836 µs	403.836 µs	403.836 µs	0 ns	:write result file
0.0%	231.226 µs	49	4.718 µs	4.020 µs	1.490 µs	21.599 µs	3.719 µs	:update best fitness
0.0%	134.489 µs	1	134.489 µs	134.489 µs	134.489 µs	134.489 µs	0 ns	:pop initialize
0.0%	4.390 µs	1	4.390 µs	4.390 µs	4.390 µs	4.390 µs	0 ns	:FA() initialize parameter

```cpp
vector<double> fun(const vector<vector<double>>& pop) {
    //nvtxRangePushA("fun() calculate fitness");
    vector<double> result;
    for (int i = 0; i < pop.size(); i++) {
        double funsum = 0;
        for (int j = 0; j < D; j++) {
            double x = pop[i][j];
            funsum += x * x - 10 * cos(2 * M_PI * x);
        }
        funsum += 10 * D;
        result.push_back(funsum);
    }
    return result;
    //nvtxRangePop();
}
```

bottleneck:

fitness亮度更新計算更新耗時最久

strategy:

將fun()寫成kernel放上gpu做運算

OpenACC More Science, Less Programming
OPEN HACKATHONS
NCHC
NARLabs 財團法人國家實驗研究院 國家高速網路與計算中心 National Center for High-performance Computing
NVIDIA

Progress -Week1

將fun_kernel用1024 thread 平行運算

Problem：反而比cpu code 還慢!!

Reason: 平行度太低+頻繁的Memcpy很耗時



low parallelization

Progress -Week2

high parallelization



- 使用1024blocks中的32個wraps
- 每個wrap中的32thread
- WarpReduce

Progress -Week2

problem size population:1024 dimen:512 max_iter 3



Progress -Week2



bottleneck:
kernel計算時間佔10%
剩餘90%均為Memcpy的時間

strategy:
透過將fun_kernel計算前後也放上gpu做運算節省Memcpy時間

Progress -Week3

```
if (fitness[i] > fitness[k]) {
    r_distance += pow(pop[i * fa.D + j] - pop[k * fa.D + j], 2);
    double Beta = fa.B * exp(-fa.G * r_distance);
    double xnew = pop[i * fa.D + j] + Beta * (pop[k * fa.D + j] - pop[i * fa.D + j]) + steps;

    xnew = min(max(xnew, fa.Lb[0]), fa.Ub[0]);
    pop[i * fa.D + j] = xnew;
```

update_pop_kernel

```
    // Update fitness after position update
    fitness = fa.fun(pop);
```

fun_kernel

```
    auto best_iter = min_element(fitness.begin(), fitness.end()); //取得min fitness
    best_ = *best_iter; //取得min fitness
    int arr_ = distance(fitness.begin(), best_iter); //取得min fitness index位置

    for (int j = 0; j < fa.D; j++) {
        best_para_[j] = pop[arr_ * fa.D + j]; //將min_fitness整個dimention位置存入best_para_
    }
}
```

update_best_kernel

Progress -Week3





- 解決Week2遇到的memcpy
- gpu utilization > 90%

Progress -Week3

problem size : population:1024 dimen:512 max_iter 3



Energy Efficiency improvement



What problems have you encountered?

- 平行運算時遇到race condition：謹慎處理data dependency避免同步讀寫資料
- 盡可能減少Memcpy時間
- 能夠運用多個blocks中多個wrap運算提高平行度

Wishlist

- 可以贊助H100給清大的超算團隊嗎?
- 免費cuda教學課程

Final Thoughts

超級值得!!!!

1.讓我更熟悉cuda語法，並成功用cuda加速firefly algorithm

2.知道如何解決Memcpy耗時情況

3.學會cuda加速小技巧 : WarpReduce。

4.更熟悉如何使用nsys profile並解讀report

What’s next?

1.優化fun_kernel : use coalesced memory access

2.優化update_best_kernel : 使用多個blocks平行計算

謝謝大家!!!

OpenACC More Science, Less Programming

OPEN HACKATHONS

NCHC

NARLabs 財團法人國家實驗研究院
國家高速網路與計算中心
National Center for High-performance Computing

NVIDIA