

Task 3

Implementation

AWS	Azure
<ul style="list-style-type: none">- S3 API extremely easy to use- Short, easy to understand commands (E.g. <code>s3.create_bucket()</code>)- DynamoDB very easy to use- Simple commands such as <code>table.Scan()</code>- Filtering is done intuitively with dynamodb conditions (Key, Attr, And)	<ul style="list-style-type: none">- More complete and layered blob API- <code>BlobServiceClient</code>- <code>ContainerClient</code>- <code>BlobClient</code>- Easy commands within clients (E.g. <code>blob_service_client.create_container</code>)- DB API: Currently incomplete. Will finish by Friday, Jan 31st- Filtering: Currently incomplete. Will finish by Friday, Jan 31st

Performance

AWS	Azure
<ul style="list-style-type: none">- Slower than Azure for task 1- 0.61s user- 0.25s system- _____ for task 2 <p>Comparison for task 2 to be completed by Friday</p>	<ul style="list-style-type: none">- Faster than AWS for task 1- 0.43s user- 0.24s system- _____ for task 2 <p>Comparison for task 2 to be completed by Friday</p>

Permissions

AWS	Azure
<ul style="list-style-type: none">- Must include a credentials file in your <code>~/aws/credentials</code>- Aws requires unique names for buckets- Default access is public when creating containers through code	<ul style="list-style-type: none">- Must create environment variable and use it in the code- <code>'AZURE_STORAGE_CONNECTION_STRING'</code>- Azure seems to have less unique name requirements- Default access is private when creating containers through code

Available documentation

AWS	Azure
<ul style="list-style-type: none">- Quickstart guide- Boto3 API docs<ul style="list-style-type: none">- S3 docs- DynamoDB docs- Extensive online forums (E.g. Stackoverflow)	<ul style="list-style-type: none">- Quickstart Guide- Azure Storage docs<ul style="list-style-type: none">- Blob API docs- Table API docs- Less online forums than AWS

Tutorials

AWS	Azure
<ul style="list-style-type: none">- Clear step by step instructions in quick-start guide- Python specific example code for S3 in boto3 docs	<ul style="list-style-type: none">- Clear step by step instructions in quick-start guide- Python specific example code for blob storage API in docs

References

- “Amazon Dynamodb API Reference,” *Amazon AWS Docs*, 15-Jan-2020. [Online]. Available:
<https://docs.aws.amazon.com/amazondynamodb/latest/APIReference/Welcome.html>.
[Accessed: 27-Jan-2020].
- “Get Started With S3,” *Amazon AWS Docs*, 12-Jan-2020. [Online]. Available:
<https://docs.aws.amazon.com/AmazonS3/latest/gsg/GetStartedWithS3.html>.
[Accessed: 27-Jan-2020].
- “How can I convert JSON to CSV?,” *Stack Overflow*, 01-Dec-1959. [Online]. Available:
<https://stackoverflow.com/questions/1871524/how-can-i-convert-json-to-csv>.
[Accessed: 27-Jan-2020].
- Normesta, “Azure Blob storage documentation,” *Microsoft Docs*. [Online]. Available:
<https://docs.microsoft.com/en-us/azure/storage/blobs/>. [Accessed: 27-Jan-2020].

- “python sort list of json by value,” *Stack Overflow*, 01-Nov-1964. [Online]. Available:
<https://stackoverflow.com/questions/26924812/python-sort-list-of-json-by-value>.
[Accessed: 27-Jan-2020].

Task 4

Task 1 Implementation - Below there is a brief step by step guide to the implementation of the task which involved creating buckets/containers and objects/blobs on AWS and Azure and performing basic API commands against them

Step 1: Setting up the environment	
AWS	Azure
<ul style="list-style-type: none">- Create buckets directly in S3 using API	<ul style="list-style-type: none">- Must create storage account before being able to add containers using the interface- Storage account names must be unique
<ul style="list-style-type: none">- Must include aws credentials in order to use api. Done by adding credentials in '<code>~/.aws/credentials</code>' file- Find the credentials in labs.vocareum -> Account details -> show- Credentials expire every 3 hours	<ul style="list-style-type: none">- Uses a connection that is stored as an environment variable on your machine to authenticate. It is called '<code>AZURE_STORAGE_CONNECTION_STRING</code>' in my program- Find connection string in 'access keys' section of storage account- Set by running '<code>export AZURE_STORAGE_CONNECTION_STRING=""</code>' in terminal- Connection does not expire- <code>connect_str = os.getenv('AZURE_STORAGE_CONNECTION_STRING')</code>
<ul style="list-style-type: none">- Can include region in '<code>~/.aws/config</code>'	<ul style="list-style-type: none">- Defaults region to East US for you

Step 2: Creating the containers/buckets	
AWS	Azure
<ul style="list-style-type: none">- Create buckets using s3 API '<code>s3.create_bucket(Bucket=name)</code>'- Container names must be unique	<ul style="list-style-type: none">- Create the equivalent of buckets, which are containers, by using blob Api's '<code>blob_service_client.create_container(name)</code>'- Container names do not need to be unique

Step 3: Creating the objects/blobs	
AWS	Azure
<ul style="list-style-type: none"> - Create objects using 's3.Bucket(name).put_object(Key, Body)' in s3 API - Object names must be unique inside containers - Object names do not need to be unique from container to container 	<ul style="list-style-type: none"> - Create blobs using 'blob_client.upload_blob(file)' - Blob names must be unique inside containers - Blob names do not need to be unique from container to container

Step 4: Display buckets/containers	
AWS	Azure
<ul style="list-style-type: none"> - Get all buckets in aws using API s3.buckets.all() 	<ul style="list-style-type: none"> - Get all containers in Azure using blob API 'blob_service_client.list_containers'

Step 5: Display objects/blobs	
AWS	Azure
<ul style="list-style-type: none"> - All buckets returned from previous step have an objects attribute - Access using "bucket.objects.all()" 	<ul style="list-style-type: none"> - Must create a containerClient using the connection string and then get a list of blobs from that - ContainerClient.from_connection_string(connect_str, container_name=container['name']) - Access using 'container_client.list_blobs()'

Step 6: Download objects/blobs	
AWS	Azure
<ul style="list-style-type: none"> - s3.Bucket(bucketName).download_fileobj(objName, filePathToDownloadTo) 	<ul style="list-style-type: none"> - Create blob_client - file.write(blob_client.download_blob().readall())

Task 2 Implementation - Below there is a brief step by step guide to the implementation of the task which involved building a movie database in AWS and Azure and then querying that database

Step 1: Building the database	
AWS	Azure
<ul style="list-style-type: none"> - Create the database using boto3 resource 'dynamodb' <pre>dynamodb = boto3.resource('dynamodb', region_name='us-east-1')</pre>	<ul style="list-style-type: none"> - Currently incomplete. Will finish by Friday, Jan 31st
<ul style="list-style-type: none"> - Must include aws credentials in order to use api. Done by adding credentials in '~/.aws/credentials' file - Find the credentials in labs.vocareum -> Account details -> show - Credentials expire every 3 hours 	<ul style="list-style-type: none"> - Currently incomplete. Will finish by Friday, Jan 31st
<ul style="list-style-type: none"> - Can include region in '~/.aws/config' 	<ul style="list-style-type: none"> - Currently incomplete. Will finish by Friday, Jan 31st

Step 2: Create table	
AWS	Azure
<pre>dynamodb.create_table(TableName, KeySchema, AttributeDefinitions, ProvisionedThroughput)</pre>	<ul style="list-style-type: none"> - Currently incomplete. Will finish by Friday, Jan 31st

Step 3: Load data into table	
AWS	Azure
<ul style="list-style-type: none"> - Load in json file using 	<ul style="list-style-type: none"> - Currently incomplete. Will finish by

<pre>movies = json.load(json_file, parse_float = decimal.Decimal)</pre> <ul style="list-style-type: none"> - Add data to table using <pre>table = dynamodb.Table('Movies') table.put_item(Item)</pre>	Friday, Jan 31st
--	------------------

Step 4: Get query from user	
AWS	Azure
<ul style="list-style-type: none"> - Get filters for primary key, secondary key or three info columns (rank, rating or running_time_secs) - Get column to sort by and fields to display - Use input() as well as many while loops and try except statements to error check input 	<ul style="list-style-type: none"> - Get filters for primary key, secondary key or three info columns (rank, rating or running_time_secs) - Get column to sort by and fields to display - Use input() as well as many while loops and try except statements to error check input

Step 5: Query database	
AWS	Azure
<ul style="list-style-type: none"> - Use Scan function <pre>table.scan(FilterExpression=fe)</pre> <ul style="list-style-type: none"> - FilterExpression is a combination of searches on primary key, secondary key, or the other filters mentioned in the previous step - Example of fe being constructed: <pre>fe=Key('year').eq('1992') fe=And(fe, Key('title').eq('Movie title'))</pre>	<ul style="list-style-type: none"> - Currently incomplete. Will finish by Friday, Jan 31st

Step 6: Sort result	
AWS	Azure
<ul style="list-style-type: none"> - Use sorted function <p>Ex. sortedResponse = sorted(response['Items'], key=lambda k: k.get('year', 0), reverse=True)</p>	<ul style="list-style-type: none"> - Currently incomplete. Will finish by Friday, Jan 31st

Step 7: Display fields/print to csv	
AWS	Azure
<ul style="list-style-type: none"> - Split fields included by comma - Create csv writer using: <p>csvwriter = csv.writer(csvFile, delimiter=",")</p> <ul style="list-style-type: none"> - Write a row to the csv file using: <p>csvwriter.writerow(ArrayOfItemsInRow)</p>	<ul style="list-style-type: none"> - Currently incomplete. Will finish by Friday, Jan 31st