

Missing Data Reconstruction Using Gaussian Mixture Models for Fingerprint Images

Sos S. Agaian^{*a}, Rushikesh D. Yeole^{*a}, Marzena Mulawka^a, Mike Troy^a, Gary Reinecke^b
^{*a}Division of Engineering, The University of Texas at San Antonio, TX-78249; ^aFlashScan3D, San Antonio, TX-78205; ^bBoston University School of Medicine, Boston, MA-02118

This project was supported by Award No. 2014-IJ-CX-K003, awarded by the National Institute of Justice, Office of Justice Programs, U.S. Department of Justice. The opinions, findings, and conclusions or recommendations expressed in this publication are those of the authors and do not necessarily reflect those of the Department of Justice

ABSTRACT

One of the most important areas in fingerprint biometrics is matching partial fingerprints in fingerprint databases. Recently, significant progress has been made in designing fingerprint identification systems for missing fingerprint information. However, the precise reconstruction of fingerprint images still remains challenging due to the complexity and the ill-posed nature of the problem. This paper presents an algorithm for reconstructing the missing data from the fingerprint image(s). Experimental results illustrate the performance of the proposed method. The offered system can be used for fingerprint image identification and can be automated, as well as extended to numerous other security applications such as postmortem fingerprints, forensic science, investigations, artificial intelligence, robotics, all-access control, and financial security, as well as for the verification of firearm purchasers, driver license applicants, etc.

Keywords: Fingerprints, Gaussian mixture models, regression trees, reconstruction, missing data.

1. INTRODUCTION

Methods for reconstruction missing data are important step in various scientific and engineering applications, including fingerprint identification. Ridge structure characteristics and their correlation are used for determining the how any fingerprint is different from other. Biometrics are used in modern security systems including access control [37][50][51] and bio cryptography[37] [52][53][54][55]. Wide range applications in fingerprint biometrics needs matching of partial fingerprints and filling out the missing data fingerprints in the database. In detecting this data, the major problems includes insufficient minutiae and other components like core and delta that needs to be improved [56][37]. Earlier, some methods to solve this partial fingerprint problem using core-based alignment techniques and maximum feature extraction methods before they are matched. The input fingerprint image is usually poor in quality that makes it difficult to reconstruct the ridge line .Even, noise and deformation play an important role in false ridge line structures. This makes it difficult to achieve reliable fingerprint ridge line structures from poor quality images. This problem is studied completely and is still worked upon to improve the quality of image [56][37].

There are two key missing data reconstruction methods: the deterministic method (missing data are interpolated deterministically) and probabilistic reconstruction method (missing data are interpolated probabilistically). The deterministic method includes spline interpolation method. The probabilistic method has been developed in the last few years. The probabilistic interpolation method includes the inpainting procedure.

In the state of art algorithms, in order to achieve the ridge line structures, the ridge line structure is first enhanced by applying filtering approach to the original images and generate lines through binarization methods and thinning processes. Some techniques extract the ridge lines directly from gray scale images. The enhancement method proposed by O’Gorman and Nickerson is based on the convolution of the image with a filtered image [41] [57]. Hong Lin and A.K. Jain proposed that Gabor functions that can be used in enhancing the fingerprint image by taking fingerprint ridge orientation and ridge frequency as filtering parameters[41] [58]. M. T. Leung[41] [59] implemented a neural network based approach that detects the minutiae by applying a multilayer perception method to analyze the output of a rank of Gabor's filters convolved with the gray scale image A Laplacian operator and a dynamic threshold were newly introduced by Moayer and Fu [60][41] which can applied in a binarization . Some skeletonization algorithms have been managed for generating a skeleton of the fingerprint ridge lines. Instead of using a generalized thinning method, the

concept of interpolation has been implemented in reconstruction mechanism. Nowadays, Gaussian Mixture Model (GMM) is used in variety of applications. GMM is a probabilistic model that assumes all the data points are generated from a mixture of a finite number of Gaussian distributions with unknown parameters.

The paper proposes a new technique to reconstruct the ridge and minutiae line accurately in fingerprinting images. The method is based on combine Gaussian Mixture Models and regression trees concepts. We first formulate a GMM and then use this model to generate a regression trees. This approach does not change any of the original fingerprint gray scale and reconstructs the data without changing the components from the original pixel values. In addition, a feedback technique implemented in this algorithm which imputes all the missing data in a loop. The remainder of the paper is organized as follows. We discuss the introduction with a given state of art algorithms in Section 2, and present the reconstruction algorithm for a GMM in Section 3. Computer Simulation results are presented in Section 4. Section 5 concludes the paper.

2. STATE OF ART ALGORITHMS

This section shows the state of art algorithms that are already been developed for the reconstruction of missing data in the fingerprint images. It includes Improved Smooth Extension, Transform based reconstruction which majorly uses the discrete cosine transform, the various kinds of matching algorithm, partial differentiation equation using inpainting techniques and the sample tracing algorithm Gaussian Mixture Models algorithm is the new algorithm that has been proposed in this algorithm.




Figure 1: Figure shows various State of Art algorithms for fingerprint image reconstruction

Improved Smooth Extension method [37][44]: This algorithm is used it to reconstruct the missing data by an automated retrieval process using Fourier expansion model by training the phase data every time the coefficients are updated. It can be described as follows:

Transform based method [38][43]:It is used to reconstruct fingerprint orientation field by transforms such as weighted discrete cosine transform (DCT), wavelet transform by adjusting the basis function such as wavelets and sinusoids,

Matching based method [39][47][48]:In this algorithm, dictionary-based fingerprint reconstruction method is proposed which is mainly used reconstruct the minutiae of the orientation field and ridge patterns.

Partial differential equation and inpainting techniques [40][45][46]:Inpainting is the process in which we use information of the surrounding image to fill a part of an image or video. Partial differential equations are used to generating the parameters for the inpainting procedure.

- Ridge-lines are sharpened using automated techniques of diffusion filters. It allows more minutiae and improve latent fingerprint computer matching.

- Linked lists are used for generating a list of curve end points and bifurcations for minutiae.

Sample tracing method [41][49]: It uses the concept of ridge line modelling to reconstruct the missing data which includes. It uses the aspects like continuity and correlation to track the sample of the ridges.

- The fingerprint ridge line is assumed as a track of a ridge segment moving along the ridge. It uses the target tracking technique in computer vision to solve this problem
- A new model of fingerprint ridge line segments generated and then tracked along the ridges. To improve the accuracy a feedback technique is used.
- All the generated ridge segments are connected and the missing data is reconstructed in a polyline format.

3. PROPOSED ALGORITHM

In this section, we describe the process of generating models of Gaussian Mixtures which are used to duplicate the finger and then reconstruct the missing data. We present a new application of Gaussian Mixture Models for Fingerprints Image Duplication and analysis.

A Gaussian mixture model is a probabilistic model that assumes all the data points are generated from a mixture of a finite number of Gaussian distributions with unknown parameters.

$$s(\mathbf{x}) = \sum_{k=1}^K \pi_k N_k(\mathbf{x}, \mu_k, \Sigma_k)$$

$$\text{Where } N(x, \mu, \Sigma) = N(x, \theta) = \frac{1}{\Sigma_k \sqrt{2\pi}} e^{-\frac{(x-\mu_k)^2}{2\Sigma_k^2}}$$

$$\pi_i = \frac{\pi_k N(x | \mu_k, \Sigma_k)}{\sum_{j=1}^k \pi_j N(x | \mu_j, \Sigma_j)} \text{ where } \pi_i \text{ are the weights}$$

$N_k(\mathbf{x}, \mu_k, \Sigma_k)$ is a i-Gaussian distributions component of the mixture model with its own mean μ_k and variance shape Σ_k .

The duplicate fingerprint model of the given original models are obtained using the GMM's concept for duplication [42]

3.1 Proposed algorithm:

The proposed algorithm can be explained as follow step-wise

Step 1: Input a fingerprint image with missing data

Step 2: Duplicate fingerprint the image by applying a Gaussian mixture model [42]




Figure 2: Region of interest for the missing data reconstruction

Step 3: Determine the missing data and color it, for example using green color

Step 4: Estimate the statistical parameters of missing data by using the concept of regression trees.

Step 5: Generate the nodes for the regression tress by using EM algorithm.

The nodes for the regression tress can be found by estimation of new parameters $[S(X, Y | \pi), Q(\pi, \pi^{new}), \mu_k^{new}, \Sigma_k^{new}]$ for regression trees.

Where $S(x)$ is the Gaussian model . The Q-function is the expected value of the complete data log-likelihood $S(X, Y | \theta)$ with respect to Y given X and θ^{new} which can be calculated as follows:

$$Q(\pi, \pi^{new}) = E[\log S(X, Y | \pi) | X, \pi^{new}, \pi^{new} + 1],$$

$$\text{in which } Y(n) = \frac{\mu_{new}^{x_n} e^{-\mu}}{n!} \text{ [n is the total number of pixels]}$$

$$\mu_k^{new} = \frac{1}{N_k} \sum_{i=1}^n \pi_i x_i,$$

$$\Sigma_k^{new} = \frac{1}{N_k} \sum_{i=1}^n \pi_i (x_i - \mu_k^{new}) x_i (x_i - \mu_k^{new}) .$$

For these generated new parameters we are now able to determine the values for spline interpolation.

Step 6: Perform polynomial spline interpolation on this generated regression trees:

$$\frac{1}{x_n - x_{n-1}} k_{n-1} + \frac{2}{x_n - x_{n-1}} k_n = 3 \frac{y_n - y_{n-1}}{(x_n - x_{n-1})^2}$$

Where k_1 to k_n are the parameters that are generated by differentiating the GMM i.e. $s(x)$, x_n are the models of the original GMM and y_n are the parameters of the generated model for the missing data.

Step 7: Reconstructed image is obtained

The below table shows the values that are calculated for the GMM for image 1. When we keep the mean of the image model as constant and then find the interpolation constant k . This can be further used to calculate the parameters of the EM algorithm, $\Pi_{new}(\text{weights}), \Sigma_{new}(\text{variance})$ which is seen the table on the next page.

mean	covariance	K	x_n	x_{n-1}	Π	Π_{new}	y_{n-1}	y_n	Σ	Σ_{new}
$\mu_0 = 15$	c = 13	K1	1.021	1	0.21	12.82	0.05	9.74	0.00	9.83
		K2	1.024	6.16	0.22	12.82	2.17	13.00	0.34	13.00
		K3	0.32	13.00	0.00	6.38	0.05	7.51	0.00	6.47
	c = 15	K1	1.021	1	0.22	13.89	0.05	7.07	0.00	6.04
		K2	1.027	7.44	0.23	13.88	2.20	14.98	0.34	14.99
		K3	0.24	15.00	0.00	7.08	0.13	8.87	0.00	7.47
	c = 18	K1	1.021	1	0.21	13.21	0.05	3.66	0.00	1.83
		K2	1.026	9.08	0.21	13.11	2.29	17.66	0.36	17.73
		K3	0.28	17.76	0.02	7.80	0.37	11.18	0.00	8.95
$\mu_0 = 21$	c = 18	K1	1.025	1	0.24	17.70	0.01	14.15	0.00	14.37
		K2	1.027	8.88	0.24	17.70	1.78	18.00	0.33	18.00
		K3	0.36	18.00	0.00	8.86	0.00	9.55	0.00	8.94
	c = 21	K1	1.084	1	0.23	19.06	0.01	10.11	0.00	8.99
		K2	1.045	10.32	0.23	19.04	1.80	20.97	0.33	20.98
		K3								

$\mu_0 = 31$	c = 24	K3	0.24	20.96	0.00	9.96	0.03	11.46	0.00	10.47
		K1	1.078	1	0.23	18.43	0.01	6.22	0.00	4.09
		K2	1.056	11.96	0.23	18.32	1.84	23.72	0.33	23.79
		K3	0.52	23.68	0.01	10.88	0.10	13.60	0.00	11.92
	c = 24	K1	1.021	1	0.24	23.88	0.00	22.48	0.00	22.81
		K2	1.064	12.20	0.24	23.88	1.22	24.00	0.32	24.00
		K3	0.40	24.00	0.00	11.92	0.00	11.69	0.00	11.93
	c = 31	K1	1.021	1	0.24	27.52	0.00	15.32	0.00	14.01
		K2	1.027	15.28	0.24	27.46	1.23	30.95	0.31	30.97
		K3	0.20	31.00	0.00	14.85	0.00	15.72	0.00	15.43
	c = 38	K1	1.065	1	0.23	24.21	0.00	6.69	0.00	3.92
		K2	1.018	19.60	0.22	23.79	1.29	36.90	0.32	37.03

Table 1: Various parameters for GMM and interpolation method for reconstruction of missing data

4. COMPUTER SIMULATIONS

In this section we generate the GMMs for the reconstruction of missing data and study the differences between them using Images Similarity Measure[11]. There are many image similarity measures to compare two images [11,25-28]. In this article, we use Structural Similarity Image Measure [11].

$$SSIM = \frac{(2\mu_x\mu_y + C_1)(2\sigma_{xy} + C_2)}{(\mu_x^2 + \mu_y^2 + C_1)(\sigma_x^2 + \sigma_y^2 + C_2)}$$

Where

$$\mu_k^n = \frac{1}{N_k} \sum_{i=1}^n x_i \text{ is the mean of pixel values of the image model.}$$

























$$\sigma_x = \left(\frac{1}{N-1} \sum_{i=1}^N (x_i - \mu_k)^2 \right)^{0.5} \text{ is Standard deviation of pixel values of the image model}$$

















$$\sigma_{xy} = \frac{(2\sigma_x\sigma_y + C_2)}{(\sigma_x^2 + \sigma_y^2 + C_2)} \text{ is the Luminance comparison of pixel values of the image model}$$

The below table shows the comparison study of the various state of art algorithms and the proposed new algorithm to duplicate the image models. It we have generated a total of 10 image models including both state of art algorithms and newly developed algorithms. We use the SSIM index to compare the results of all the image models. We can see that the newly developed algorithm gives better results.

Table 2: The below table shows various GMMs generated [42]:

No.	Algorithm	Image1	Image2	Image3	Image4
-----	-----------	--------	--------	--------	--------

1	Original Image	 Q=1	 Q=1	 Q=1	 Q=1
2	Gaussian Mixture Model	 Q=0.3411	 Q=0.3756	 Q=0.3445	 Q=0.3718
3	Generalized Gaussian Mixture Model	 Q=0.6475	 Q=0.6487	 Q=0.6437	 Q=0.6472
4	Generalized Gaussian Mixture Model using Bayesian learning	 Q=0.7692	 Q=0.7641	 Q=0.7664	 Q=0.7656
5	Texture Synthesis	 Q=0.5486	 Q=0.4474	 Q=0.5479	 Q=0.4452
6	Genetic Algorithm	 Q=0.8612	 Q=0.8695	 Q=0.8671	 Q=0.8645

7	Improved Adaptive Algorithm	 Q=0.8154	 Q=0.8612	 Q=0.8173	 Q=0.8629
8	New Algorithm based on Generalized Gaussian and Finite Bayesian learning	 Q=0.8645	 Q=0.8748	 Q=0.8626	 Q=0.8738
9	Image Enhancement Algorithm for Gaussian Mixture Models and Finite Bayesian Model (GMMFB)	 Q=0.8745	 Q=0.8687	 Q=0.8756	 Q=0.8646
10	New Algorithm Based on Improved Adaptive, genetic Algorithm and Finite Bayesian learning (GMMFBE)	 Q=0.9279	 Q=0.9249	 Q=0.9274	 Q=0.9287

Now that we have obtained the Gaussian mixture Model for the above given input images. We consider the best image model as the input to regression trees to reconstruct the missing the data. We follow all steps that are mentioned in the proposed algorithm and impute the missing data. The below table shows the original image, the missing data image and the reconstructed image.

It includes the following:

1. Original image model(obtained for GMM)
2. Region interest(the shaded region that we need to reconstruct the data)
3. Reconstructed image

Table 3: Missing data reconstruction for the given input GMM


































1.			
	Original Image Model 1	Original Image Model 2	Original Image Model 3
2.			
	Missing data Image 1	Missing data Image 2	Missing data Image 3
3.			
	Missing data reconstructed Image 1	Missing data reconstructed Image 2	Missing data reconstructed Image 3

Table 4: Differences between Original image and GMM

	Algorithm	Original Image	GMM	Differences
1.	Gaussian Mixture Model	 Q=1	 Q=0.3411	 Q=0.3229
2.	Generalized Gaussian Mixture Model	 Q=1	 Q=0.6475	 Q=0.3845

3.	Generalized Gaussian Mixture Model using Bayesian learning	 Q=1	 Q=0.7692	 Q=0.4589
4.	Texture Synthesis	 Q=1	 Q=0.5486	 Q=0.3149
5.	Genetic Algorithm	 Q=1	 Q=0.8612	 Q=0.4739
6.	Improved Adaptive Algorithm	 Q=1	 Q=0.8154	 Q=0.4589
7.	New Algorithm based on Generalized Gaussian and Finite Bayesian learning	 Q=1	 Q=0.8645	 Q=0.4699
8.	Image Enhancement Algorithm for Gaussian Mixture Models and Finite Bayesian Model	 Q=1	 Q=0.8745	 Q=0.2697

9.	New Algorithm Based on Improved Adaptive, genetic Algorithm and Finite Bayesian learning	 Q=1	 Q=9279	 Q=0.2271
----	--	--	--	---

Below we are comparing our results with the various state of art algorithms and newly generated algorithms for missing data reconstruction. We compare the results using the SSIM index, Entropy and the mean square error.

Table 5: Comparison of models using various measures

Sr. No.	Algorithm	SSIM Index				Entropy			
	Original Image	1	1	1	1	845.74	756.25	894.26	486.84
1	Gaussian Mixture Models, (Ming-Hsuan Yang,1999)	0.3411	0.3756	0.3445	0.3411	255.21	178.74	259	963.17
2	Generalized Gaussian Mixture Models, (Tee-Won Lee,2005)	0.6475	0.6487	0.6473	0.6475	454.12	369.76	454.12	245.21
3	Finite Bayesian learning for Gaussian Mixture Models. Nicola Greggio,2010	0.7692	0.7641	0.7671	0.7678	645.17	487.32	461.7	463.12
4	Texture Synthesis, Andrea Rau,2010	0.5496	0.4474	0.5463	0.5456	245.12	278.96	269.12	663.17
5	Improved Adaptive Algorithm, Vahid Majidnezhad,2013	0.8692	0.8294	0.8664	0.8694	687.32	475.32	671.32	271.12
6	Genetic Algorithm, Vahid Majidnezhad,2013	0.8397	0.8695	0.8356	0.8342	643.21	574.39	618.21	644.32
7	GMMBF	0.8645	0.8675	0.8663	0.8676	685.12	573.12	693.12	647.21
8	GMMBFE	0.9249	0.9252	0.9259	0.9296	723.69	627.12	769.69	697.12
9	Regression Trees	0.9456	0.9377	0.9351	0.9412	684.855	564.29	631.28	453.54
10	GMM Regression	0.9356	0.9325	0.9245	0.9307	543.55	566.86	586.22	412.93

Table 6: Comparison of models using various measures

Sr. No.	Algorithm	Mean square error			
	Original Image	0	0	0	0
1	Gaussian Mixture Models, (Ming-Hsuan Yang,1999)	875.23	841.23	818.23	863.23
2	Generalized Gaussian Mixture Models, (Tee-Won Lee,2005)	797.39	752.39	753.39	755.39
3	Finite Bayesian learning for Gaussian Mixture Models. Nicola Greggio,2010	744.43	737.43	797.43	771.43

4	Texture Synthesis, Andrea Rau,2010	612.48	656.48	674.48	656.48
5	Improved Adaptive Algorithm, Vahid Majidnezhad,2013	455.78	494.78	486.78	479.78
6	Genetic Algorithm, Vahid 2013	574.53	571.53	543.53	578.53
7	GMMBF	318.54	369.54	396.54	394.54
8	GMMFBE	219.64	245.64	275.64	222.64
9	Regression Trees	354.94	235.69	214.69	734.89
10	GMM Regression	148.55	258.55	632.96	654.07

The above tables show the comparison of the reconstructed images based on GMM using SSIM index, Entropy and mean square error. The computer simulation results show that the developed method has the following advantages:

- 1) It provides an overall reconstruction of missing data more accurately and best fits the original degraded image.
- 2) It tracks the ridges more efficiently than any matching or smoothing technique.
- 3) It detects the minutiae more smoothly.

5. CONCLUSION

We have developed a combination of Gaussian Mixture Models, Regression trees and spline interpolation based method for reconstruction of missing data in fingerprints images and its analysis. A prominent advantage of the proposed approach gives a more precise ridge line model without changing the components of the original image. We get the best fit statistical model for the finger print images which can be further used for determining ridge line structure and minutiae. The simulation result demonstrates that the proposed algorithm is capable of generating sharp clean ridges while keeping the actual structure of ridge endings. We obtain the best results for the GMM reconstruction as compared to the state of art algorithm Zhou Wei [37], Liu Manhua [38], Cao Kai.[39] , Rahmes Mark [40], Qi Yaxuan[41] which gives the best SSIM index about 0.9345, Entropy as 543.55 ,Mean Square Error as 148.55. The proposed system can be used for fingerprint image identification and can be made automated and extended to numerous other security application such as postmortems, forensics, investigation of crimes, artificial intelligence, robotics, as access control, financial security, and verification of firearm purchasers and driver license applicants etc.

ACKNOWLEDGMENT

This work is a part of a Research Project and authors are thankful to NIJ Fy 14 for funding the Project Award with Grant number 2014-IJ-CX-K003.

REFERENCES

- [1] C. R. Wren, A. Azarbayejani, T. Darrell, and A. Pentland, "Pfindex: Real-time tracking of the human body," IEEE Trans. on PAMI, vol. 19, no. 7, pp. 780–785, 1997.
- [2] N. Friedman and S. Russell, "Image segmentation in video sequences: A probabilistic approach," In Proceedings Thirteenth Conf. on Uncertainty in Artificial Intelligence, 1997.
- [3] C. Stauffer and W. Grimson, "Adaptive background mixture models for real-time tracking," In Proceedings CVPR, pp. 246–252, 1999.
- [4] P. J. Withagen, K. Schutte, and F. Groen, "Likelihood-based object tracking using color histograms and EM," In Proceedings ICIP, USA, pp. 589–592, 2002.
- [5] S. Agaian, S. Bakhtiari and M. Jamshidi, "Local Fingerprint Image Reconstruction Based on Gabor Filtering". Proc. SPIE 8406, Mobile Multimedia/Image Processing, Security, and Applications, 10.1117/12.918384, 2012
- [6] A. Grigoryan, S.Agaian, "Transform-based image enhancement algorithms with performance measure", Advances in Imaging and Electron Physics- 130,165-242,2004
- [7] E.A Silva, K Panetta, S. Agaian," Quantifying image similarity using measure of enhancement by entropy", Defense and Security Symposium, 65790U-65790U-12,2007

- [8] E Wharton, S Agaian, K. Panetta, "Comparative study of logarithmic enhancement algorithms with performance measure", Electronic Imaging International Society for Optics and Photonics, 606412-606412-12,2006
- [9] B.Silver, S.Agaian, and K..Panetta, "Contrast Entropy Based Image Enhancement and Logarithmic Transform Coefficient Histogram Shifting," Proceedings, IEEE ICASSP ,7803-8874 ,2005.
- [10] B.Silver, S. Agaian, and Karen A. Panetta, "Logarithmic Transform Coefficient Histogram Matching with Spatial Equalization," Proceedings, SPIE Defense and Security Symposium ,pp237-249, 2005.
- [11] Wang, Zhou, and Alan C. Bovik. "A universal image quality index." Signal Processing Letters, IEEE 9.3,pp 81-84,2002.
- [12] S. Agaian, Karen Panetta, and. A.Grigoryan, "A New Measure of Image Enhancement," IASTED International Conference on Signal Processing & Communication, Marbella, Spain, 19-22 ,2000.
- [13] A. Grigoryan and S. Agaian, "Image Enhancement", Advances in Imaging and Electron Physics, Academic Press, pages 165-243, May 2004.
- [14] A.Monnet, A.Mittal, N.Paragios and V. Ramesh, "Background Modeling and Subtraction of Dynamic Scenes", In Proceedings ICCV'03, pp.1305–1312, 2003.
- [15] Z.Zivkovic and F.van der Heijden, "Recursive Unsupervised Learning of Finite Mixture Models", IEEE Trans. on PAMI, vol.26 pp 651-656, 2004.
- [16] Efros, Alexei A., and Thomas K. Leung. "Texture synthesis by non-parametric sampling." Computer Vision, 1999. The Proceedings of the Seventh IEEE International Conference on. Vol. 2. pp 1033-1038, 1999.
- [17] Elguebaly, Tarek, and Nizar Bouguila. "Bayesian learning of finite generalized Gaussian mixture models on images." Signal Processing 91.4 801-820.,2011
- [18] Lee, Te-Won, and Michael S. Lewicki. "The generalized Gaussian mixture model using ICA." International Workshop on Independent Component Analysis (ICA'00).pp 239-244, 2000.
- [19] Mitra, Sinjini. "Gaussian mixture models for human face recognition under illumination variations." , Applied Mathematics Vol.3 No.12A, pp 2071-2079,2012
- [20] Elgammal, Ahmed, David Harwood, and Larry Davis. "Non-parametric model for background subtraction." Computer Vision—ECCV 2000. Springer Berlin Heidelberg,pp 751-767, 2000
- [21] S.Bakhtiari., "A Novel Method for Orientation Estimation in Highly Corrupted Fingerprint Images". International Journal of Intelligent Computing in Medical Sciences & Image Processing, 6(1), 45-63.,2014
- [22] K.Egiazarian, K. Panetta.,S.Agaian. "Image Processing: Algorithms and Systems X; and Parallel Processing for Imaging Applications II." Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series. Vol. 8295. 2012.
- [23] S. Bakhtiari,S.Agaian, & Jamshidi, M. , "Local fingerprint image reconstruction based on gabor filtering", In SPIE Defense, Security, and Sensing . International Society for Optics and Photonicspp. 840602-840602,2012..
- [24] S.Nercessian , S.Agaian& K. Panetta., "An image similarity measure using enhanced human visual system characteristics", InSPIE Defense, Security, and Sensing . International Society for Optics and Photonics. (pp. 806310-806310),2011
- [25] S.Nercessian , S.Agaian& K. Panetta., "A non-reference measure for objective edge map evaluation", In Systems, Man and Cybernetics,. SMC. IEEE International Conference on (pp. 4563-4568). ,2009
- [26] C.Gao, S.Agaian& K. Panetta. "No reference color image contrast and quality measures." Consumer Electronics, IEEE Transactions on 59.3 643-651. (2013)
- [27] C.Gao, S.Agaian& K. Panetta.. "Color image attribute and quality measurements.", In SPIE Sensing Technology+ Applications (pp. 91200T-91200T),2014.
- [28] Liu, Li-min, and Tian-Shyr Dai. "Ridge Orientation Estimation and Verification Algorithm for Fingerprint Enhancement." Journal of Universal Computer Science, vol. 12, no. 10 ,pp 1426-1438,2006.

- [29] Yang, Ming-Hsuan, and Narendra Ahuja. "Gaussian mixture model for human skin color and its applications in image and video databases." *Electronic Imaging. International Society for Optics and Photonics*, pp 458-466, 1998.
- [30] J.-J. Oosterwijk, B. Skoric, and J. Doumen. A capacity-achieving simple decoder for bias-based traitor tracing schemes. *IACR Cryptology ePrint Archive*, 2013:389, 2013.
- [31] J.-J. Oosterwijk, B. Skoric, and J. Doumen. Optimal suspicion functions for tardos traitor tracing schemes. In *Proceedings of the First ACM Workshop on Information Hiding and Multimedia Security, IH&MMSec '13*, New York, NY, USA, 2013. ACM.
- [32] F. Petitcolas, R. Anderson, and M. Kuhn. Attacks on copyright marking systems. In *Information Hiding*, volume 1525 of *Lecture Notes in Computer Science*, Springer Berlin Heidelberg, 1998.
- [33] G. Tardos. Optimal probabilistic ngerprinting codes. In *Proceedings of the 35th Annual ACM Symposium on Theory of Computing (STOC)*, pp. 116-125, 2003.
- [34] B. Skoric, S. Katzenbeisser, and M. Celik. Symmetric Tardos ngerprinting codes for arbitrary alphabet sizes. *Designs, Codes and Cryptography*, 2008.
- [35] B. Skoric, S. Katzenbeisser, H. Schaathun, and M. Celik. Tardos ngerprinting codes in the combined digit model. In *Information Forensics and Security, 2009. WIFS 2009. First IEEE International Workshop on*, 2009.
- [36] B. Skoric, T. U. Vladimirova, M. Celik, and J. C. Talstra. Tardos Fingerprinting is Better Than We Thought. *Information Theory, IEEE Transactions on* 2008.
- [37] Zhou, Wei "Partial fingerprint reconstruction with improved smooth extension." *Network and System Security*. Springer Berlin Heidelberg, 2013. 756-762.
- [38] Liu, Manhua, Shuxin Liu, and Qijun Zhao. "Fingerprint orientation field reconstruction by weighted discrete cosine transform." *Information Sciences* 268 (2014): 65-77.
- [39] Cao, Kai, and Anil K. Jain. "Learning fingerprint reconstruction: From minutiae to image." *Information Forensics and Security, IEEE Transactions on* 10.1 (2015): 104-117.
- [40] Rahmes, Mark, et al. "Fingerprint Reconstruction Method Using Partial Differential Equation and Exemplar-Based Inpainting Methods." *Biometrics Symposium, 2007. IEEE*, 2007.
- [41] Qi, Yaxuan. "Fingerprint ridge line reconstruction." *Intelligent information processing II*. Springer US, 2004. 211-220.
- [42] Sos S. Agaian, Rushikesh D. Yeole, Gary Reinecke, Mary-Ann, Mike Troy, " Comparison Study of Gaussian Mixture Models for Fingerprint Image Duplication with a New Model", in *proceedings Electronic Imaging conference, 2016*
- [43] Hsieh, Ching-Tang, Eugene Lai, and You-Chuang Wang. "An effective algorithm for fingerprint image enhancement based on wavelet transform." *Pattern Recognition* 36.2 (2003): 303-312.
- [44] Wang, Yi Alice, and Jiankun Hu. "Global ridge orientation modeling for partial fingerprint identification." *Pattern Analysis and Machine Intelligence, IEEE Transactions on* 33.1 (2011): 72-87.
- [45] Huang, Feng, G. Randy Duensing, and Yunmei Chen. "Method for applying an in-painting technique to correct images in parallel imaging." U.S. Patent No. 7,230,429. 12 Jun. 2007.
- [46] Huang, Feng, G. Randy Duensing, and Yunmei Chen. "Method for applying an in-painting technique to correct images in parallel imaging." U.S. Patent No. 7,230,429. 12 Jun. 2007.
- [47] Jain, Anil K., Salil Prabhakar, Lin Hong, and Sharath Pankanti. "Filterbank-based fingerprint matching." *Image Processing, IEEE Transactions on* 9, no. 5 (2000): 846-859.
- [48] Benkley, Fred George, David Joseph Geoffroy, and Pallavi Satyan. "Method and apparatus for fingerprint image reconstruction." U.S. Patent No. 8,131,026. 6 Mar. 2012.
- [49] Takahashi, Nobuo. "Fingerprint reading method and fingerprint reading system." U.S. Patent No. 7,412,083. 12 Aug. 2008.