

# Fouille de données

▶ Mesures d'intérêt pour les règles

#### d'association

Philippe Lenca & Stéphane Lallich

philippe.lenca@telecom-bretagne.eu Telecom Bretagne & Université Lyon 2016-2017

# Outline

- Objectives of KDD in a short

### **Outline**

- Objectives of KDD in a short
- Objective interestingness measures
- 3 Objective interestingness measures properties
- 4 Utility of the interestingness properties
- Conclusion
- 6 References

page 2

Philippe Lenca & Stéphane Lallich

Philippe Lenca & Stéphane Lallich

Fouille de données > Mesures d'intérêt



# **Knowledge Discovery in Data Bases**

#### Basic Definitions [PCKW89], [FPSSU96], [KNZ01]...

KDD is a non-trivial (decision aid interactive and iterative) process where user(s) seek to identify valid, novel, potentially useful, and ultimately understandable patterns in data.

KDD must be considered as a process of contextualization : in practice exact definitions of all concepts are required.

→ Our focus is interestingness (valid, novel, useful, understandable).





# **Knowledge Discovery in Data Bases**

#### Classical troubles. .

- [BMUT97] found 6,732 rules with a maximum conviction value (obvious) in Census data: five years old don't work, men don't give birth, etc.
- [Tsu00] found 29,050 rules, out of which only 220 (less than 1%) were considered interesting or surprising by the user
- [WL00] found rules with 40-60% confidence (i.e. low confidence) which were considered novel and more accurate than some doctor's domain knowledge

Qualitative and quantitative troubles.

Philippe Lenca & Stéphane Lallich

Fouille de données > Mesures d'intérêt



## **Knowledge Discovery in Data Bases**

#### Interestingness is perhaps a broad concept [GH06]

- validity (on new data with some degree of certainty)
- novelty (at least to the system and preferably to the user)
- utility (that is, lead to some benefit to the user or task)
- understandability (if not immediately then after some post-processing)
- but also conciseness, coverage, peculiarity, diversity, surprisingness, and actionability.

patterns?

#### How can we help the end-user to select the good patterns (from his point of view)?

Some common approaches:

- measurement :
  - objective interestingness measures [Fre99], [HH00]
  - subjective interestingness measures [ST95]
- redundancy analysis [LGB98]
- visualization tools & human centered processes [BGB03], [DP03], [MBY10]
- domain-driven [Cao10]

 $\hookrightarrow$  Our subject : objective interestingness measures.

Philippe Lenca & Stéphane Lallich

Fouille de données ⊳ Mesures d'intérê



# **Evaluating extracted patterns**

#### Is it easy to define such quantitative measures?

- validity : measures of certainty, robusteness
  - estimated prediction accuracy, confidence on new data
- utility : gain
  - in money saved because of better predictions
  - speedup in response time
- novelty, surprising : more subjective
  - if the pattern contradicts a user expectation
  - · with a stochastic model
- understandability : more subjective
  - estimated by simplicity (size of the pattern)

 $\rightarrow$  Objective measures for rule-based patterns.







# Discovering comprehensible/understandable knowledge

### **Outline**

#### Production rules based models

if conditions then conclusion

#### Popular models

- association rules [AS94]
- class association rules [LHM98]
- decision trees [BFSO84]

(unsupervised paradigm)

(supervised paradigm)

(supervised paradigm)

→ Objective interestingness measures for such models.

page 9

Philippe Lenca & Stéphane Lallich

Fouille de données De Mesures d'intérêt



#### page 10

Philippe Lenca & Stéphane Lallich

Objective interestingness measures

Fouille de données > Mesures d'intérêt




# **Objective interestingness measures**

#### Definition

An objective interestingness measure (OIM) is a function from the space of rules  $\{A \to B\}$  to the space of extended real numbers  $(\mathbb{R} \cup$  $\{-\infty, +\infty\}$ ).

OIM are based on the rules cardinalities (data-driven) :

|   | $A \setminus B$ | 0                | 1        | total          |
|---|-----------------|------------------|----------|----------------|
|   | 0               | $p_{ar{a}ar{b}}$ | ₽āb      | pā             |
|   | 1               | $p_{aar{b}}$     | $p_{ab}$ | p <sub>a</sub> |
| t | otal            | $p_{\bar{b}}$    | $p_b$    | 1              |



 $\hookrightarrow$  Usually functions  $\mu(n, p_a, p_b, p_{ab})$  or  $\mu(n, p_a, p_b, p_{a\bar{b}})$ .

# **Objective interestingness measures**

OIM provide numerical information on the quality of a rule

A rule  $A \rightarrow B$  is said "of quality" when evaluated by an interestingness measure  $\mu$ , if its evaluation by  $\mu$  is greater than a user defined threshold  $\sigma_u$ .

$$\mu(A \to B) \ge \sigma_{\mu} \iff A \to B$$
 is of quality

where  $\sigma_{\mu}$  has to be fixed by the user.

 $\hookrightarrow$  Measures are used to rank, to filter the rules i.e. to select most pertinent rules.




page 12

# **Objective interestingness measures**

A huge number of measures...

#### Eligibility property

Common assertion: the fewer counterexamples (A true and B false) to the rule there are, the higher the interestingness of the rule is. Focus on decreasing measures wrt.  $p_{a\bar{b}}$ , all marginal frequencies being fixed.



 $\hookrightarrow$  Measures like  $\chi^2$ , Pearson's  $r^2$ , J-measure or Pearl's measure are excluded. .

Philippe Lenca & Stéphane Lallich

Fouille de données ⊳ Mesures d'intérêt



# A huge number of measures...

#### Absolute definitions Relative definitions . . . $p_{b/a}$ nn<sub>ab</sub> Lift $n_a n_b$ $p_b \over p_{b/a} - p_b$ $nn_{ab}-n_an_b$ LOE $P | \mathcal{N}(0,1) > \text{IndImp}^{CR/B}$ IPD PS $n_{ab}$ $n(p_{ab}-p_ap_b)$ n<sub>ab</sub> n<sub>ab</sub> n<sub>ab</sub> Seb $p_{a\bar{b}}$ Sup $p_{ab}$ $[i(A \rightarrow B) \times IntImp(A \rightarrow B)]^{1/2}$ THE $nn_{ab}-n_an_b$ $p_{ab}-p_ap_b$ Zhang $\overline{\max}\{n_{ab}n_{\bar{b}},n_bn_{a\bar{b}}\}$ $\max\{p_{ab}p_{\bar{b}};p_b(p_a-p_{ab})\}$


#### Absolute definitions Relative definitions $\frac{p_{b/a}/p_{\bar{b}/a}}{p_{\bar{b}/a}} = \frac{p_{a/b}}{p_{a/b}}$ BF $n_b n_{a\bar{b}}$ $p_b/p_{\bar{b}}$ $p_{a/\bar{b}}$ $n_{ab} \underline{n_b}$ CONFCEN $p_{b/a} - p_b$ na $n_{ab}$ Conf $p_{b/a}$ $p_a p_{\bar{b}}$ Conv $p_{a\bar{b}}$ $n_{ab} - n_{a\bar{b}}$ Tec $\frac{\overline{n_{ab}}}{\log(\frac{nn_{ab}}{n_an_b})}$ $\log \frac{p_{ab}}{p_{a}p_{b}}$ GI $n_a n_b - n n_{ab}$ -IndImp $\sqrt{p_a p_{\bar{b}}}$ $Poisson(\frac{n_a n_{\bar{b}}}{n})$ IntImp $2\tfrac{p_{ab}-p_ap_b}{p_a+p_b-2p_ap_b}$ IQC $2\frac{nn_{ab}}{nn_a+nn_b-2n_an_b}$ $n_{ab}-n_{a\bar{b}}$ $p_{ab}-p_{a\bar{b}}$ MoCo $nn_b$ $p_b$

Philippe Lenca & Stéphane Lallich

Fouille de données > Mesures d'intérêt



# Different measures... different rankings



 $\rightarrow r_{18}$  seems to be "good",  $r_{19}$  seems to be "bad", but  $r_2$ ?



### **Outline**

KDD

OIM

OIM propertie

OIM × proper

Const

D. C.....

- Objectives of KDD in a short
- 2 Objective interestingness measures
- 3 Objective interestingness measures properties
- 4 Utility of the interestingness properties
- Conclusion
- 6 References

page 1

Philippe Lenca & Stéphane Lallich

Fouille de données D Mesures d'intérêt



Does the measure penalizes large B? [PS91]

KDD

page 20

OIM

OIM properties

OIM × properti

Conclusion

Reference

#### Decrease with $p_b$

The interest of  $A \to B$  should be decreasing with the size of B when  $p_{ab}$  and  $p_a$  are given.

beer ightarrow bread, washing machine ightarrow bread.

# Does the measure help to distinguish ${\tt A}\to{\tt B}$ and ${\tt B}\to{\tt A}$ [Fre99]?

D OIN

OIM properties

OIM × properties

Conclusion

eferences

#### Asymmetric processing of A and B

Since the antecedent and the consequent of a rule may have very different significations, it is desirable to make a distinction between measures that evaluate rules A  $\rightarrow$  B differently from rules B  $\rightarrow$  A and those which do not.

|   | $Sex \setminus coat$ | Non red | red | total |
|---|----------------------|---------|-----|-------|
|   | Н                    | 48      | 2   | 50    |
|   | F                    | 32      | 18  | 50    |
| Ī | total                | 80      | 20  | 100   |

if sex=F then red coat 
$$(SUP = 0.18 \ CONF = 0.36 \ LIFT = 1.8)$$
 if red coat then sex=F

(SUP = 
$$0.18 \text{ Conf} = 0.90 \text{ Lift} = 1.8$$
)

where 
$$\mathrm{Sup}(\mathtt{A} o \mathtt{B}) = p_{ab}$$
,  $\mathrm{Conf}(\mathtt{A} o \mathtt{B}) = p_{ab}/p_a$ ,  $\mathrm{Lift}(\mathtt{A} o \mathtt{B}) = rac{p_{ab}}{p_a p_b}$ 

page 19

Philippe Lenca & Stéphane Lallich

Fouille de données D Mesures d'intérêt



# Does the measure help recognizing independence? [PS91]

KDD

(

IM properti

OIM × properties

onclusion

References

$$\mathrm{SUP}(\mathtt{A} o \mathtt{B}) = p_{ab} = 0.72$$
  $\mathrm{Conf}(\mathtt{A} o \mathtt{B}) = p_{b/a} = 0.9$  but  $p_b = 0.9$ 

#### Situation at the independence

- [PS91] proposed that  $\mu(A \rightarrow B) = 0$ PS =  $n(p_{ab} - p_a p_b)$
- [LMVL08] proposed that  $\mu(A \to B) = C$ LIFT =  $\frac{p_{b/a}}{p_b} = \frac{nn_{ab}}{n_an_b} = \frac{\text{Conf}}{p_b} = \frac{p_{ab}}{p_ap_b}$  (which values 1)

 $\hookrightarrow$  It is a first steep but not sufficient.






# Does the measure help recognizing reference situations?

#### Reference situations

Remember :  $\mu(A \to B) \ge \sigma_{\mu} A \to B$  is of quality, how to choose  $\sigma_{\mu}$ ? From value for a logical rule to incompatibility [LMVL08] through independency [PS91] or indetermination [BGBG05]..., not too high (harsh selective), not too low (weak selective).



 $\hookrightarrow$  Take into account some reference value wrt. the user's goal : targeting or prediction, or any other threshold [LVL07]?

Philippe Lenca & Stéphane Lallich


Fouille de données > Mesures d'intérêt



## **Tolerance to counter-examples [GKCG01]**

## Behavior with $p_{a\bar{b}}$ around $0^+$

The user may tolerate a few counter-examples without significant loss of interest. However, the opposite choice could also be preferred to increase the sensitivity to a false positive.



 $\rightarrow$  Robustness issue and origin of the counter-examples? [LLV06].

### Value at reference situations

#### For 3 classical measures:

- $\blacksquare$  Sup(A  $\to$  B) =  $p_{ab}$
- $\blacksquare$  CONF(A  $\to$  B) =  $p_{ab}/p_a$
- LIFT( $A \rightarrow B$ ) =  $\frac{p_{ab}}{p_a p_a}$

|      |                | independency          | equilibrium      |
|------|----------------|-----------------------|------------------|
|      | $p_{aar{b}}=0$ | $p_{ab}=p_a	imes p_b$ | $p_{ab}=p_a/2$   |
| Sup  | $p_{ab}$       | $p_a p_b$             | $p_a/2$          |
| Conf | 1              | $p_b$                 | 1/2              |
| Lift | $1/\rho_b$     | 1                     | $\frac{1}{2p_b}$ |

Philippe Lenca & Stéphane Lallich

Fouille de données > Mesures d'intérêt



## Statistical or descriptive measures [Lal02]

#### Sensitivity to n (total number of records)

The user can prefer to have a measure which is invariant (descriptive measure) or not with the dilatation of data (statistical measures).

A statistical measures will increases with n (for constant rates of A.  $A \rightarrow B, B$ ).

→ Discrimination power issue [Lal02].



page 25

# **Statistical measures and increasing** *n* **[Lal02]**

#### Discrimination power

If a measure depends of n, it loses its discriminating power.

| SOLARFLARE-1  | IntImp | IPD  | $_{ m IIE}$ |
|---------------|--------|------|-------------|
| 0 to 0.95     | 3629   | 5214 | 4019        |
| 0. 95 to 0.99 | 1011   | 145  | 1072        |
| 0.99 to 1     | 762    | 43   | 311         |
| Total         | 5402   | 5402 | 5402        |

#### Solutions:

- weighting by a discriminating index (IIE, [GKCG01])
- contextual functional transformation (IPD, [LA03])

 $\hookrightarrow$  These two solutions have been generalized to be applied whatever the reference threshold is for the confidence [LVL07].

Philippe Lenca & Stéphane Lallich

Fouille de données > Mesures d'intérêt



# Does the semantics of the measure make sense? [LMVL08]

#### Intelligibility criteria

- THE = {[(1  $H^*(B/A)^2$ )(1  $H^*(\bar{A}/\bar{B})^2$ )]<sup>1/4</sup>INTIMP}<sup>1/2</sup> where  $H^*(X/Y) = 1$ , if  $p_{X/y} > \max\{0.5; p_X\}$ ,  $H^*(X/Y) = -p_{X/y} \log_2 p_{X/y} (1 p_{X/y}) \log_2 (1 p_{X/y})$  otherwise
- Conf =  $p_{b/a} = \frac{p_{ab}}{p_a}$

What does it means when the measure values 0.7, when it changes from 0.7 to 0.72?

- with CONF the user may understand that the rule is now true in 72% of cases (or that the rule is not true for 28 % of cases) and that he gains 2 %
- but with THE?

→ Importance of intelligibility/comprehensibility depends on the user/application/domain/context.

# How to fix a threshold? [LMVL08]

#### Easiness to fix a threshold

Even if references situations have been taken into account, it is still difficult to decide on the best threshold value that separates interesting from uninteresting rules.

To establish this property, we can provide a sense of the strength of the evidence against the null hypothesis  $H_0$  (absence of a link between A and B), that is the p-value [LT04] i.e. the threshold  $\sigma_{\mu}$ should be the value exceeded 5 times out of 100 by the measure  $\mu$ in case of independence.

Philippe Lenca & Stéphane Lallich

Fouille de données D Mesures d'intérê



# Does the measure help recognizing robust rules? [LLV06]

| $(r_1)$ A $\setminus$ B | 0   | 1   | total | $(r_2)$ A $\setminus$ B | 0    | 1    | total |
|-------------------------|-----|-----|-------|-------------------------|------|------|-------|
| 0                       | 0.2 | 0.2 | 0.4   | 0                       | 0.18 | 0.32 | 0.5   |
| 1                       | 0.2 | 0.4 | 0.6   | 1                       | 0.1  | 0.4  | 0.5   |
| total                   | 0.4 | 0.6 | 1     | total                   | 0.28 | 0.72 | 1     |

|  | Sup  | Conf | Lift |  |  |
|--|------|------|------|--|--|
| $r_1$  | 0.40 | 0.66 | 1.11 |  |  |
| $r_2$  | 0.40 | 0.80 | 1.11 |  |  |
| Is r <sub>2</sub> better than r <sub>1</sub> ? |      |      |      |  |  |



# Does the measure help recognizing robust rules?

KDD OIM OIM properties OIM×properties Conclusion Reference

| $(r_1) A \setminus B$ | 0   | 1   | total |                | Sup  | Conf | LIFT | $(r_2) A \setminus B$ | 0    | 1    | total |
|-----------------------|-----|-----|-------|----------------|------|------|------|-----------------------|------|------|-------|
| 0                     | 0.2 | 0.2 | 0.4   |                |      |      | 1 11 | 0                     | 0.18 | 0.32 | 0.5   |
| 1                     | 0.2 | 0.4 | 0.6   | $r_1$          | 0.40 | 0.66 | 1.11 | 1                     | 0.1  | 0.4  | 0.5   |
| total                 | 0.4 | 0.6 | 1     | r <sub>2</sub> | 0.40 | 0.80 | 1.11 | total                 | 0.28 | 0.72 | 1     |

#### Robustness criteria [LLV06]

- although having a lower confidence,  $r_1$  may lose 25% of its examples while  $r_2$  may lose only 20% of them, and still have a lift value above 1.0.
- $ightharpoonup r_1$  is more robust when being evaluated in a post-processing step with the lift and a lift threshold of 1.0

 $\hookrightarrow$  To be above the threshold is not sufficient. See also for example works to discover false positive [LPT04] and to filter random noise in transaction data [HH07].

page 30

Philippe Lenca & Stéphane Lallich

Fouille de données De Mesures d'intérêt



# Does the measure help to efficiently find good rules? [AS94]

KDD

OIM

OIM propertie

OIM × propertie

Conclusion

References

#### Pruning property

How to find nuggets (rules with a very small support and a high confidence) [Li06], or rare rules [SVN10]?

For FIM, a solution is to avoid the use of the support and to use a measure with a pruning property, see for example [Li06] and its generalization in [LBLL09].

## Sensitivity to noise, to threshold, etc.?

OIM OIM prop

OIM × properties

Conclusion

ferences

#### Robustness

Four strategies have been proposed:

- experimental approach, using simulation [AK02] [Cad05]
- statistical approach, using statistical tests [LPT04], [RM08]
- formal approach, by studying the derivative of the measures [LLV06], [GDGB07]
- algebraic definition of the robustness by considering the distance between the considered rule and the nearest rule corresponding to the threshold [LBMLL10]

page 31

Philippe Lenca & Stéphane Lallich

Fouille de données > Mesures d'intérê



## Some criteria [LMVL08]

KDD

OIN

OIM propert

OIM × propertie

onclusion

Reference

| Property              | Semantic  | Modalities                  |
|-----------------------|---|-----------------------------|
| g <sub>1</sub>        | asymmetric processing of A and B                | asym, sym                   |
| <b>g</b> 2            | decrease with $p_b$                             | $dec(p_b)$ , no- $dec(p_b)$ |
| <b>g</b> 3            | reference situations : independence             | cst, var                    |
| g <sub>4</sub>        | reference situations : logical rule             | cst, var                    |
| <b>g</b> <sub>5</sub> | linearity with $p_{a\overline{b}}$ around $0^+$ | conv, lin, conc             |
| <b>g</b> 6            | sensitivity to n                                | desc, stat                  |
| <b>g</b> 7            | easiness to fix a threshold                     | easy, hard                  |
| <b>g</b> 8            | intelligibility                                 | a, b, c                     |

 $\hookrightarrow$  Study of qualities and drawbacks of interestingness measures (decision aid, classification).

List of criteria could be extended (robustness, discriminant power, etc.).





# **Evaluation matrix on 20 measures [LMVL08]**

|                  | g <sub>1</sub> | $g_2$         | <b>g</b> 3 | g <sub>4</sub> | <b>g</b> 5 | <b>g</b> 6 | g <sub>7</sub> | g <sub>8</sub> |
|------------------|----------------|---------------|------------|----------------|------------|------------|----------------|----------------|
| BF               | asym           | $dec(n_b)$    | cst        | cst            | conv       | desc       | easy           | a              |
| ConfCen          | asym           | $dec(n_b)$    | cst        | var            | lin        | desc       | easy           | a              |
| Conf             | asym           | $no-dec(n_b)$ | var        | cst            | lin        | desc       | easy           | а              |
| Conv             | asym           | $dec(n_b)$    | cst        | cst            | conv       | desc       | easy           | b              |
| Tec              | asym           | $no-dec(n_b)$ | var        | cst            | conc       | desc       | easy           | b              |
| $_{ m GI}$       | sym            | $dec(n_b)$    | cst        | var            | conc       | desc       | easy           | С              |
| - IndImp         | asym           | $dec(n_b)$    | cst        | var            | lin        | stat       | easy           | С              |
| IntImp           | asym           | $dec(n_b)$    | cst        | var            | conc       | stat       | easy           | С              |
| IQC              | sym            | $dec(n_b)$    | cst        | var            | lin        | desc       | easy           | С              |
| Lap              | asym           | $no-dec(n_b)$ | var        | var            | lin        | desc       | easy           | С              |
| MoCo             | asym           | $dec(n_b)$    | var        | var            | lin        | desc       | easy           | b              |
| Lift             | sym            | $dec(n_b)$    | cst        | var            | lin        | desc       | easy           | a              |
| Loe              | asym           | $dec(n_b)$    | cst        | cst            | lin        | desc       | easy           | b              |
| IPD              | asym           | $dec(n_b)$    | cst        | var            | conc       | stat       | easy           | С              |
| $_{\mathrm{PS}}$ | sym            | $dec(n_b)$    | cst        | var            | lin        | stat       | easy           | b              |
| R                | sym            | $dec(n_b)$    | cst        | var            | lin        | desc       | easy           | b              |
| Seb              | asym           | $no-dec(n_b)$ | var        | cst            | conv       | desc       | easy           | b              |
| Sup              | sym            | $no-dec(n_b)$ | var        | var            | lin        | desc       | easy           | a              |
| THE              | asym           | $dec(n_b)$    | cst        | var            | conc       | stat       | hard           | С              |
| Zhang            | asym           | $dec(n_b)$    | cst        | cst            | conc       | desc       | hard           | С              |


Philippe Lenca & Stéphane Lallich

Fouille de données > Mesures d'intérêt




# Comparison of two classifications [VLL04]

#### [measures × propriety]



### Pre-orders on rules sets



|                | $e_1$      | e <sub>2</sub>  | e <sub>3</sub> | e <sub>5</sub>      | e <sub>5</sub>        |
|----------------|------------|-----------------|----------------|---------------------|-----------------------|
| $f_1$          | {Lap}      |                 | {Sup, MoCo}    |                     |                       |
| $f_2$          | {Tec, Seb, |                 |                |                     |                       |
|                | Conf}      |                 |                |                     |                       |
| f <sub>3</sub> |            |                 |                | {ConfCen, Lift, GI} | {-Indimp, r, PS, IQC} |
| $f_4$          |            | {Loe, Conv, BF} |                |                     |                       |
| $f_5$          |            | {Zhang, TIIE}   |                |                     | {IntImp, IPD}         |

## **Outline**

- 4 Utility of the interestingness properties

Philippe Lenca & Stéphane Lallich

Fouille de données > Mesures d'intérêt




# **Decision Aiding [LMVL08]**

normative criterion order

Selection of the good measures: use of [measures×propriety] and decision maker preferences and a multicriteria decision aid tool.

| g <sub>1</sub> asymmetric           | $asym \succ sym$                                   |
|-------------------------------------|--|
| $g_2$ decrease with $p_b$           | $dec(n_b) \succ no-dec(n_b)$                       |
| g <sub>3</sub> independence         | $\mathtt{cst} \succ \mathtt{var}$                  |
| g <sub>4</sub> logical rule         | $\mathtt{cst} \succ \mathtt{var}$                  |
| $g_7$ easiness to fix $\sigma_\mu$  | $\mathtt{easy} \succ \mathtt{hard}$                |
|                                     |  |
| subjective criterion                | order  |
| $g_5$ linearity with $p_{a\bar{b}}$ | $\mathtt{conc}\succ\mathtt{lin}\succ\mathtt{conv}$ |
|                                     | (tolerance for c-ex)                               |
|                                     | $conv \succ lin \succ conc$                        |
|                                     | (no tolerance for c-ex)                            |
| g <sub>6</sub> sensitivity to n     | $\mathtt{stat} \succ \mathtt{desc}$                |
| g <sub>8</sub> intelligibility      | $a \succ b \succ c$                                |
|                                     |  |







### **Outline**

KDD OIM OIM properties OIM×properties Conclusion References

Objectives of KDD in a short

2 Objective interestingness measures

Objective interestingness measures properties

4 Utility of the interestingness properties

Conclusion

6 References

page 38 Philippe Lenca & Stéphane Lallich

Fouille de données > Mesures d'intérêt



### Readings ...

DD OIM OIM properties OIM×properties Conclusion Reference

Tan, P-N., Kumar, V. and Srivastava, J., Selecting the Right Objective Measure for Association Analysis, Information Systems, 29:(4), pp. 293-313, 2004.

 McGarry, K., A survey of Interestingness Measures for Knowledge Discovery, Knowledge Engineering Review Journal, 20:(1), pp. 39-61, 2005.

 Geng, L., and Hamilton, H.J., Interestingness Measures for Data Mining: A Survey, ACM Computing Surveys, 38(3), Article 9, 2006.

Lenca P., Meyer P., Vaillant B. and Lallich S., On selecting interestingness measures for association rules: user oriented description and multiple criteria decision aid, Eur. J. of Operational Research, 184(2), pp. 610-626, 2008.

 Suzuki E., Pitfalls for Categorizations of Objective Interestingness Measures for Rule Discovery, Statistical Implicative Analysis: Theory and Applications, Springer-Verlag, SCI (127), pp. 383-395, 2008.

### **Conclusion**

D OIM OIM properti

properties

onclusion

References

#### Some key points presented today

- interest of a rule is context dependent
- there are a lot of interestingness measures with very different behaviours
- the user has to select the good ones in order to select the good rules
- proposition of a systematic/characterizing approach
- formal/experimental clustering and analysis of the measures
- applying MCDA methods for measures selection

 $\hookrightarrow$  Theoretical and practical framework leading to useful characterizations and operational applications of interestingness measures.

page 39

Philippe Lenca & Stéphane Lallich

Fouille de données > Mesures d'intérêt



### **Outline**

OIM OIM properties OIM×properti

clusion Ket

- Objectives of KDD in a short
- Objective interestingness measures
- 3 Objective interestingness measures properties
- 4 Utility of the interestingness properties
- Conclusion
- 6 References





### References I

[AK02] J. Azé and Y. Kodratoff.

Evaluation de la résistance au bruit de quelques mesures d'extraction de règles

d'association.

In EGC, pages 143-154, 2002.

[AS94] R. Agrawal and R. Srikant.

Fast algorithms for mining association rules.

In VLDB, pages 487-499, 1994

[BFSO84] L. Breiman, J. Friedman, C. J. Stone, and R. A. Olshen.

Classification and Regression Trees.

J. Blanchard, F. Guillet, and H. Briand. [BGB03]

Exploratory visualization for association rule rummaging.

In Proceedings of the KDD'2003 Workshop on Multimedia Data Mining MDM'03,

pages 107-114, 2003.

J. Blanchard, F. Guillet, H. Briand, and R. Gras. [BGBG05]

Assessing the interestingness of rules with a probabilistic measure of deviation from

In The XIth International Symposium on Applied Stochastic Models and Data

Analysis, pages 191-200, 2005.



page 42

Philippe Lenca & Stéphane Lallich

Fouille de données De Mesures d'intérêt

### References III

[Fre99] A. Freitas.

On rule interestingness measures.

Knowledge-Based Systems journal, pages 309-315, 1999.

[GDGB07]

R. Gras, J. David, F. Guillet, and H. Briand. Stabilité en A.S.I. de l'intensité d'implication et comparaisons avec d'autres indices de

qualité de règles d'association.

In Qualité des Données et des Connaissances, pages 35-43, 2007.

[GH06] L. Geng and H. J. Hamilton.

Interestingness measures for data mining: A survey.

ACM Computing Surveys, 38(3), 2006.

[GKCG01] R. Gras, P. Kuntz, R. Couturier, and F. Guillet.

Une version entropique de l'intensité d'implication pour les corpus volumineux.

Extraction des connaissances et apprentissage (Extraction et Gestion des

[HH00] R. J. Hilderman and H. J. Hamilton.

Applying objective interestingness measures in data mining systems.

In Proceedings of the 4th European Conference on Principles of Data Mining and Knowledge Discovery (PKDD'00), pages 432–439. Springer-Verlag, 2000.



References II

[BMUT97] S. Brin, R. Motwani, J. D. Ullman, and S. Tsur.

Dynamic itemset counting and implication rules for market basket data. In J. Peckham, editor, SIGMOD 1997, Proceedings ACM SIGMOD International

Conference on Management of Data, Tucson, Arizona, USA, pages 255-264. ACM

[Cad05] M. Cadot.

A simulation technique for extracting robust association rules.

In CSDA, pages 143-154, 2005.

[Cao10]

Domain driven data mining: challenges and prospects.

IEEE Trans. on Knowledge and Data Engineering, 22(6):755-769, 2010.

[DP03] T-N. Do and F. Poulet.

Interactive visualization tools for visual data mining.

In R. Bisdorff, editor, 2nd Human Centered Processes Conference, pages 299-304,

Luxembourg, 2003.

[FPSSU96] U.M. Fayyad, G. Piatetsky-Shapiro, P. Smyth, and R. Uthurusamy, editors.

Advances in Knowledge Discovery and Data Mining.

AAAI/MIT Press, 1996

page 43 Philippe Lenca & Stéphane Lallich

Fouille de données D Mesures d'intérêt

Fouille de données > Mesures d'intérêt



References IV

[HH07] M. Hahsler and K. Hornik.

New probabilistic interest measures for association rules.

Intelligent Data Analysis, 11(5):437–455, 2007

[KNZ01] Y. Kodratoff, A. Napoli, and D. Zighed.

Bulletin de l'association française d'intelligence artificielle, Extraction de

connaissances dans des bases de données, 2001.

[LA03] I.C. Lerman and J. Azé.

Une mesure probabiliste contextuelle discriminante de qualité des règles d'association.

In M.-S. Hacid, Y. Kodratoff, and D. Boulanger, editors, Extraction et gestion des connaissances, volume 17 of RSTI-RIA, pages 247-262. Lavoisier, 2003.

[Lal02]

page 45

Mesure et validation en extraction des connaissances à partir des données.

Habilitation à Diriger des Recherches - Université Lyon 2, 2002.

[LBLL09] Y. Le Bras, P. Lenca, and S. Lallich.

On optimal rules mining: a framework and a necessary and sufficient condition for

In Pacific-Asia Conference on Knowledge Discovery and Data Mining, volume 5476 of Lecture Notes in Computer Science, pages 705-712. Springer-Verlag Berlin

Heidelberg, 2009.

Philippe Lenca & Stéphane Lallich



### References V

[LBMLL10] Y. Le Bras, P. Meyer, P. Lenca, and S. Lallich.

A robustness measure of association rules.

In ECML/PKDD, volume 6322 of Lecture Notes in Computer Science, pages 227-242. Springer-Verlag Berlin Heidelberg, 2010.

[LGB98] R. Lehn, F. Guillet, and H. Briand.

Eliminating redundancy in a rule system.

In Eurepean meeting on Cybernetics and System Research, volume 2, pages 793-798,

B. Liu, W. Hsu, and Y. Ma. [LHM98]

Integrating classification and association rule mining.

In Knowledge Discovery and Data Mining, pages 80-86, 1998.

[Li06]

On optimal rule discovery.

IEEE Transformation on Knowledge and Data Engineering, 18(4):460-471, 2006.

[LLV06] P. Lenca, S. Lallich, and B. Vaillant,

On the robustness of association rules.

In The IEEE International Conference on Cybernetics and Intelligent Systems, pages

596-601, June 7-9 2006.



page 46

Philippe Lenca & Stéphane Lallich

Fouille de données D Mesures d'intérêt



### **References VII**

[PCKW89] K. Parsaye, M. Chignell, S. Khoshafian, and H. Wong.

Intelligent Databases; Object-Oriented, Deductive Hypermedia Technologies.

[PS91] G. Piatetsky-Shapiro.

Discovery, analysis and presentation of strong rules.

In G. Piatetsky-Shapiro and W.J. Frawley, editors, *Knowledge Discovery in Databases*, pages 229–248. AAAI/MIT Press, 1991.

[RM08] R. Rakotomalala and A. Morineau.

Statistical Implicative Analysis, Theory and Applications, chapter The TVpercent

principle for the counterexamples statistic, pages 449-462.

Springer, 2008.

A. Silberschatz and A. Tuzhilin.

On subjective measures of interestingness in knowledge discovery.

In Knowledge Discovery and Data Mining, pages 275–281, 1995

[SVN10] Laszlo Szathmary, Petko Valtchev, and Amedeo Napoli.

Finding minimal rare itemsets and rare association rules. In Knowledge Science, Engineering and Management, volume 6291 of Lecture Notes



References VI

[LMVL08] P. Lenca, P. Meyer, B. Vaillant, and S. Lallich.

On selecting interestingness measures for association rules: user oriented description

and multiple criteria decision aid.

European Journal of Operational Research, 184(2):610-626, 2008.

S. Lallich, E. Prudhomme, and O. Teytaud.

Contrôle du risque multiple en sélection de règles d'association significatives.

RNTI-E-2 (EGC 2004), 2:305-316, 2004

S. Lallich and O. Teytaud. [LT04]

Évaluation et validation de l'intérêt des règles d'association.

Revue des Nouvelles Technologies de l'Information (Mesures de Qualité pour la

Fouille de Données), (RNTI-E-1) :193-218, 2004.

[LVL07] S. Lallich, B. Vaillant, and P. Lenca.

A probabilistic framework towards the parameterization of association rule

interestingness measures.

Methodology and Computing in Applied Probability, 9(3):447–463, 2007.

[MBY10] A. Mouakher and S. Ben Yahia.

Anthropocentric visualisation of optimal cover of association rules.

In Concept Lattices and Their Applications, pages 211–222, 2010.

Fouille de données D Mesures d'intérêt



**References VIII** 

Philippe Lenca & Stéphane Lallich

Clinical knowledge discovery in hospital information systems: Two case studies.

In D. A. Zighed, H. J. Komorowski, and J. M. Zytkow, editors, 4th European Conference on Principles of Data Mining and Knowledge Discovery, Lyon, France,

pages 652-656. Springer, 2000.

[VLL04] B. Vaillant, P. Lenca, and S. Lallich,

A clustering of interestingness measures.

In Discovery Science, volume 3245 of Lecture Notes in Artificial Intelligence, pages

290-297. Springer-Verlag, 2004.

[WL00] M. L. Wong and K. S. Leung.

Data mining using grammar based genetic programming and applications.

Kluwer Academic Publishers, 2000





page 47

[Tsu00]