

# STABLEMAX-PPO: FINITE-BUDGET RLHF WITH A MAX-STABILITY TRADE-OFF

**Anonymous authors**

Paper under double-blind review

## ABSTRACT

The deployment objective is a finite-budget order statistic, while the evaluator exposes an uncertain ordinal distribution. We study this mismatch in terminal-reward RLHF with a frozen ordinal Moment RM trained from HelpSteer2 repeated helpfulness ratings and preference pairs. Rather than collapsing this bounded ordinal distribution to a scalar or Gaussian reward, we derive an exact finite-support Best-of- $N$  objective and a one-sided calibration correction for its upper tail. StableMax-PPO turns the resulting exact marginal credit into a PPO update with mean and independent-quality floors, full-categorical KL measurement, and batch-level rollback. The design exposes a tunable operating point: the method retains competitive finite-budget maximum performance while reducing policy drift relative to mean- and group-relative baselines. Its contribution is therefore a principled max-stability trade-off, not a claim of universal dominance or direct human-preference improvement.

## 1 INTRODUCTION

**The deployment mismatch.** Language models are increasingly deployed with a finite generation budget: several responses are sampled and a downstream system returns, reranks, or inspects the best candidate. The deployment objective is therefore a finite-budget order statistic, not the expected score of one response. A mean-improving update can leave the chance of a high-scoring candidate unchanged, whereas direct maximum optimization can concentrate probability in a small and brittle region of the response distribution.

**Why current objectives leave a gap.** Mean-PPO and GRPO provide scalar expected or group-relative feedback; recent max@ $k$ , Best-of- $N$ , and inference-aware policy-gradient methods match the deployment budget but usually collapse the evaluator to a scalar or a nominal distribution (Shao et al., 2024; Guo et al., 2025; Chow et al., 2025; Tang et al., 2025; Walder & Karkhanis, 2025; Bagirov et al., 2025; Li et al., 2026; Poiani et al., 2026). KL-regularized PPO controls policy motion but does not specify which ordinal tail functional should be optimized. These choices leave a concrete gap: an upper-tail objective should preserve the ordinal thresholds, account for calibration error where the maximum is most sensitive, and expose ordinary quality and policy drift as separate measured quantities.

**StableMax-PPO.** Our evaluator interface is a frozen Moment RM trained on the repeated helpfulness ratings and preference pairs in HelpSteer2 (Wang et al., 2024b). It returns a probability vector over  $\{0, 1, 2, 3, 4\}$ : the mean is an ordinary model-implied score, the conditional variance is a diagnostic of disagreement under the repeated-annotation protocol, and the full vector preserves every threshold used by a finite-budget maximum. We introduce StableMax-PPO by placing a one-sided calibration envelope around this vector. The envelope gives an exact robust maximum and, from the same threshold products, an exact leave-one-out marginal credit. A standard PPO realization then adds an independent quality floor, a reference-policy KL penalty, and exact batch rollback when a tentative update exceeds the hard KL level.

The novelty is the resulting evaluator-to-optimizer contract, not the isolated reuse of PPO or KL regularization. The categorical evaluator determines the threshold functional; the envelope specifies its adverse calibration direction; and the same construction yields the response-level credit used by

the policy gradient. The controller keeps this target, ordinary quality, and policy motion separately auditable. Consequently, a maximum gain obtained by changing the evaluator regime, lowering typical quality, or moving far from the reference appears on a different point of the measured frontier rather than being hidden inside one scalar reward. This coupling is the key distinction from adding independent bonuses: the calibration choice changes both the deployment functional and the credit that differentiates it.

We make four contributions: (1) an exact finite- $N$  robust objective for a bounded ordinal evaluator; (2) an exact Rao–Blackwellized marginal credit and score-function identity; (3) a compact PPO controller with quality/KL safeguards and state-complete rollback; and (4) an empirical characterization of the max–stability frontier under shared evaluation and rollback controls. The complete diagnostic record, including unfavorable outcomes, delimits this frontier rather than defining a new success criterion.

## 2 PROBLEM SETUP

We consider response-level RLHF with a fixed Best-of- $N$  budget. The policy parameter  $\theta$  is trainable; the ordinal Moment RM  $\omega$ , scalar Quality RM  $\eta$ , and reference policy  $\pi_{\text{ref}}$  are frozen. For  $x \sim \mathcal{D}$ , responses factor as  $\pi_{\theta}(Y \mid x) = \prod_h \pi_{\theta}(a_h \mid x, a_{<h})$ , and a rollout contains  $Y_{1:N} \stackrel{\text{iid}}{\sim} \pi_{\theta}(\cdot \mid x)$ . Each response receives one terminal evaluation. We assume (A1) conditional independence of rating outcomes across candidates, (A2) frozen evaluators, and (A3) the standard differentiability and likelihood-ratio regularity.

**Deployment target and learning signal.** At deployment the group statistic is the maximum over the  $N$  candidates, whereas policy optimization supplies response-level likelihood ratios. The learning signal must therefore preserve the interaction between candidates before assigning credit to individual responses. This is also why the evaluators remain frozen: a change in the measured frontier should be attributable to the policy and controller, not to a moving target.

### 2.1 FROZEN ORDINAL EVALUATOR

The Moment RM predicts  $p_{\omega,r}(x, y) = \Pr_{\omega}(R = r \mid x, y)$  for  $r \in \mathcal{R} = \{0, 1, 2, 3, 4\}$ , with  $\sum_r p_{\omega,r} = 1$ . We retain the categorical vector because the finite-budget maximum depends on every threshold, use  $\mu_{\omega} = \sum_r r p_{\omega,r}$  for the ordinary-quality floor, and record  $\sigma_{\omega}^2 = \sum_r (r - \mu_{\omega})^2 p_{\omega,r}$  as a model-based disagreement diagnostic under the repeated-annotation protocol in HelpSteer2 (Wang et al., 2024b). The independent scalar Quality RM supplies an external quality check; the complete ordinal-probit parameterization is in Appendix A.

This evaluator choice is part of the method’s interface: the five categories are fixed by the annotation protocol, so the upper endpoint and threshold gaps are not selected after observing policy outcomes. The mean, variance, and categorical vector consequently have separate roles rather than being collapsed into one reward. The variance diagnoses unstable evaluator regions but does not enter the optimized target.

### 2.2 FINITE-BUDGET OBJECTIVE

For candidate  $j$ , write  $F_{\omega,j}(t) = \sum_{r=0}^t p_{\omega,r}(x, Y_j)$ . The nominal expected maximum has the exact finite-support form

$$h_N^{\text{nom}}(x, Y_{1:N}) = \sum_{t=1}^4 \left[ 1 - \prod_{j=1}^N F_{\omega,j}(t-1) \right]. \quad (1)$$

Thus rating noise is integrated out before policy optimization and no Gaussian or sampled-max approximation is introduced. The probability of at least one rating-four response is a secondary diagnostic; the complete ordinal maximum is the primary estimand (Appendix B).

The threshold form defines the signal that the policy must learn. A candidate matters when it reduces the probability that all other responses remain below a threshold, so complementary upper-tail mass can receive credit even when no unique sampled winner exists. Two candidates with the same  $\mu_{\omega}$  can

therefore induce different group gains; a scalar `max@32` objective cannot represent this distinction because it ranks only collapsed scores. The group statistic is converted to response-level credit only after this complementarity has been computed.

### 2.3 CALIBRATION UNCERTAINTY

Because the maximum magnifies upper-tail errors, we estimate a one-sided radius from independent prompt clusters before training. For threshold  $t \in \{0, 1, 2, 3\}$ , let  $D_{g,t}$  be the within-cluster mean of  $\mathbf{1}\{R \leq t\} - F_\omega(t)$ , and let  $\hat{d}_t$  be its mean across clusters. We set  $\varepsilon_{\text{cal}}$  to the maximum positive  $\hat{d}_t$  plus a simultaneous Hoeffding correction, clipped to  $[0, 1]$ ; the exact estimator and its calibration statement are given in Appendix A. For  $\mathcal{U}_\varepsilon(p) = \{q \in \Delta^4 : F_q(t) \leq \min(1, F_p(t) + \varepsilon), t = 0, \dots, 3\}$ , let  $\bar{F}_j(t) = \min(1, F_{\omega,j}(t) + \varepsilon_{\text{cal}})$ , with  $\bar{F}_j(-1) = 0$ ,  $\bar{F}_j(4) = 1$ , and induced mass  $\bar{p}_{j,r} = \bar{F}_j(r) - \bar{F}_j(r-1)$ . The robust objective is

$$h_N^{\text{rob}}(x, Y_{1:N}) = \inf_{q_j \in \mathcal{U}_{\varepsilon_{\text{cal}}}(p_{\omega,j})} \mathbb{E}_q[\max_j R_j] = \sum_{t=1}^4 \left[ 1 - \prod_{j=1}^N \bar{F}_j(t-1) \right], \quad (2)$$

$$J_N^{\text{rob}}(\theta) = \mathbb{E}_{x, Y_{1:N}}[h_N^{\text{rob}}(x, Y_{1:N})].$$

The one-sided envelope is chosen for the maximum’s adverse direction: increasing a candidate CDF decreases the probability of crossing every threshold. It therefore adds low-rating mass without turning disagreement into a reward. Because the radius is fixed on a disjoint calibration split, it is a measurable conservatism knob rather than a policy-dependent tuning preference; when calibration error is small, the robust target approaches the nominal one. Crucially, the envelope changes the threshold probabilities used by both the group target and its marginal credit, so robustness is part of the objective’s definition rather than an auxiliary penalty.

### 2.4 CONSTRAINED POLICY OBJECTIVE

The maximum can improve a few candidates while degrading typical responses or over-optimizing the training evaluator. We therefore optimize  $J_N^{\text{rob}}$  subject to  $M(\theta) = \mathbb{E}[\mu_\omega(x, Y)] \geq m_0$ ,  $Q(\theta) = \mathbb{E}[Q_\eta(x, Y)] \geq q_0$ , and  $\mathbb{E}_x[\text{KL}(\pi_\theta \| \pi_{\text{ref}})] \leq \delta$ :

$$\max_{\theta} J_N^{\text{rob}}(\theta) \quad \text{s.t.} \quad M(\theta) \geq m_0, \quad Q(\theta) \geq q_0, \quad \mathbb{E}_x[\text{KL}(\pi_\theta \| \pi_{\text{ref}})] \leq \delta. \quad (3)$$

The floors are fixed from the reference policy before training, while  $\delta_{\text{hard}}$  is the empirical rollback threshold used by the controller. The independent Quality RM and KL controller keep the measured trade-off auditable under a fixed evaluator.

Each constraint addresses a different failure mode. The nominal-mean floor prevents a tail optimizer from sacrificing the typical response; the independent Quality RM tests whether an improvement transfers beyond the training evaluator; and the KL budget limits how much behavior can change while these scores are being optimized. We consequently report the maximum and drift as separate axes instead of combining them into an arbitrary weighted sum.

The constraints are not folded into the robust maximum: the floors enter through dual credits, the KL term enters the PPO surrogate, and rollback is a binary acceptance rule. We therefore report objective value, constraint residuals, held-out drift, and rejected-step frequency as distinct diagnostics.

**Relation to existing objectives.** StableMax-PPO builds on PPO and prior inference-aware, `pass@k`, `max@k`, and Best-of- $N$  policy-gradient objectives (Chow et al., 2025; Tang et al., 2025; Walder & Karkhanis, 2025; Bagirov et al., 2025; Li et al., 2026; Poiani et al., 2026); it does not claim the first finite-budget maximum. Our comparator matrix instead separates the proposed contract from familiar components: scalar and group-relative baselines change the target, nominal EV removes only calibration robustness, and no-floor variants remove one safeguard. This factorization lets the experiments attribute changes to the evaluator-defined target or to the controller rather than to an undifferentiated stack of PPO heuristics.

### 3 METHOD

The method separates the deployment target from its stabilizers. The target is the robust ordinal maximum; the stabilizers control typical quality and policy motion. This separation makes the max–stability trade-off visible instead of hiding it in a scalar reward weight.

#### 3.1 EXACT ROBUST MAXIMUM AND MARGINAL CREDIT

**Theorem 1** (Exact finite-budget robust maximum). *Under (A1), the envelope distribution  $\bar{p}_j$  simultaneously attains the infimum in eq. (2) for every candidate. Hence the four-term expression is the exact worst-case expected maximum over the full declared product ambiguity set, not a Monte Carlo or Gaussian approximation.*

The theorem is useful computationally: it replaces an optimization over rating tables by four threshold products, so the robust target is evaluated without sampling latent ratings or enumerating  $5^N$  outcomes. For a candidate  $i$ , let  $\bar{R}_i \sim \bar{p}_i$  and  $\bar{M}_{-i} = \max_{j \neq i} \bar{R}_j$ . Its leave-one-out marginal credit is

$$q_i^{\text{rob}} := \mathbb{E}[(\bar{R}_i - \bar{M}_{-i})_+ \mid x, Y_{1:N}] = \sum_{t=1}^4 [1 - \bar{F}_i(t-1)] \prod_{j \neq i} \bar{F}_j(t-1). \quad (4)$$

This is the paper’s central credit construction: it integrates out rating noise but preserves the response-level likelihood ratio, so the policy receives credit only for thresholds at which a candidate can improve the group maximum.

This credit is deliberately leave-one-out rather than winner-take-all. A winner indicator misses a response that raises the chance of crossing a threshold without being the sampled winner; the product over  $j \neq i$  instead measures the room left by the other candidates at each threshold. Prefix and suffix products evaluate all credits in  $O(N|\mathcal{R}|)$  time per prompt, sharing the same tensor kernel used for the deployment statistic. Thus the construction is simultaneously group-aware, response-specific, and practical inside PPO, without enumerating rating tuples or introducing another rating sample.

**Theorem 2** (Exact marginal policy credit). *Under the regularity assumptions,  $q_i^{\text{rob}}$  satisfies*

$$\nabla_{\theta} J_N^{\text{rob}}(\theta) = \mathbb{E} \left[ \sum_{i=1}^N q_i^{\text{rob}} \nabla_{\theta} \log \pi_{\theta}(Y_i \mid x) \right]. \quad (5)$$

*Consequently, the response-level estimator is unbiased before PPO clipping.*

**Why the identity matters.** The identity is the bridge from the group deployment target to a trainable response-level update: latent rating draws are integrated out, while the autoregressive likelihood ratio distributes each candidate’s threshold credit over its tokens. The same cached categorical probabilities therefore define the robust target, every leave-one-out credit, and the disagreement diagnostic. PPO contributes the familiar clipped surrogate; the new object being optimized is the exact evaluator-induced credit in eq. (4).

#### 3.2 CONSTRAINED PPO UPDATE

For dual variables  $\lambda_m, \lambda_q \geq 0$ , the response-level credit used by PPO is

$$\tilde{q}_i = q_i^{\text{rob}} + \frac{\lambda_m}{N} \mu_{\omega}(x, Y_i) + \frac{\lambda_q}{N} Q_{\eta}(x, Y_i), \quad A_i = N[\tilde{q}_i - b_{\psi}(x)]. \quad (6)$$

The factors  $1/N$  match the one-response constraints to the group objective; the prompt-only baseline preserves the score-function identity. We use the standard clipped PPO surrogate and full-categorical token KL. Writing  $\rho_{i,h} = \pi_{\theta}(a_{i,h} \mid s_{i,h}) / \pi_{\text{old}}(a_{i,h} \mid s_{i,h})$ , the update maximizes the standard per-token expression  $\min\{\rho_{i,h} A_i, \text{clip}(\rho_{i,h}, 1 - \epsilon_{\text{PPO}}, 1 + \epsilon_{\text{PPO}}) A_i\}$  averaged over candidates, minus  $\beta_k \widehat{\text{KL}}$ , and divides by the lagged RMS scale. The full implementation, including projected dual updates, is specified in Appendix C.

Before a tentative step, StableMax-PPO snapshots all policy parameters and the complete optimizer state. If the post-update KL on the same rollout states exceeds  $\delta_{\text{hard}}$ , both snapshots are restored; baseline, dual, RMS, and controller states advance only after acceptance. Snapshotting the optimizer moments is necessary for Adam-like optimizers, and the resulting rollback count is comparable across baselines under the shared controller.

### 3.3 STABLEMAX-PPO

---

#### Algorithm 1: StableMax-PPO update

---

**Input:**  $\mathcal{D}, \pi_\theta, \pi_{\text{ref}}, p_\omega, Q_\eta, \varepsilon_{\text{cal}}, m_0, q_0, N, \delta_{\text{hard}}$   
**Output:** Updated policy parameters  $\theta$ .

- 1 Initialize  $b_\psi, \lambda_m, \lambda_q, \beta_{\text{KL}}$  and lagged scale  $s > 0$ ;
- 2 **for**  $k = 1, \dots, T_{\text{pol}}$  **do**
- 3     Roll out  $N$  responses per prompt under  $\pi_{\text{old}}$ ;
- 4     Compute  $\tilde{q}_i$  and  $A_i$  from the closed-form credits;
- 5     Snapshot  $(\theta, \text{Opt})$  and perform one clipped-PPO update;
- 6     **if** *measured post-update*  $\widehat{\text{KL}} > \delta_{\text{hard}}$  **then**
- 7         Restore  $(\theta, \text{Opt})$ ; leave controller state unchanged;
- 8     **else**
- 9         Commit and update  $b_\psi, \lambda_m, \lambda_q, \beta_{\text{KL}}, s$ ;

---

Algorithm 1 is the only algorithm in the paper; the implementation constants and diagnostics are in the supplementary protocol.

## 4 THEORETICAL ANALYSIS

The previous section gives the exact target and its policy-gradient bridge. Here we state the guarantees that explain the role of the calibration radius and the update controller. Proofs are in Appendix A.

### 4.1 CALIBRATION COVERAGE

**Theorem 3** (Calibration-robust lower bound). *Let  $F_j^*$  be the true conditional CDF. If  $F_j^*(t) \leq \bar{F}_j(t)$  for every candidate and  $t \in \{0, 1, 2, 3\}$ , then the true conditional maximum satisfies  $\mathbb{E}_*[\max_j R_j \mid x, Y_{1:N}] \geq h_N^{\text{rob}}(x, Y_{1:N})$ . Without exact coverage, the gap is at most  $4N\xi(x, Y_{1:N})$ , where  $\xi = \max_{j,t}[F_j^*(t) - \bar{F}_j(t)]_+$ .*

The statement is conditional on pointwise envelope coverage. Cluster-level calibration estimates the radius but does not establish coverage for every generated response; the residual  $\xi$  quantifies the resulting loss when the envelope misses. Thus the theorem supplies an operational lower-tail bound under an explicit assumption rather than an informal reliability claim.

### 4.2 DEPENDENCE ON THE CALIBRATION RADIUS

**Proposition 1** (Calibration-radius monotonicity). *For  $0 \leq \varepsilon_1 \leq \varepsilon_2 \leq 1$ ,  $0 \leq J_N^{\text{rob}}(\theta; \varepsilon_1) - J_N^{\text{rob}}(\theta; \varepsilon_2) \leq 4N(\varepsilon_2 - \varepsilon_1)$ , and at  $\varepsilon = 0$ ,  $J_N^{\text{rob}}(\theta; 0) = J_N^{\text{nom}}(\theta)$ .*

The proposition makes  $\varepsilon_{\text{cal}}$  an interpretable target-level knob: increasing it can only make the robust maximum more conservative, with a finite sensitivity bound. This is distinct from tuning a KL coefficient, which changes the optimization path while leaving the target functional fixed.

### 4.3 ROLLBACK INVARIANT

**Proposition 2** (Rollback correctness). *If a tentative update is rejected, restoring the parameter and optimizer snapshots exactly returns the measured rollout-state policy and optimizer to their pre-update values. This is a batch-level invariant, not a population KL guarantee.*

These results separate the method’s roles: the envelope protects the target, the marginal identity makes it optimizable, and rollback controls the measured batch update. The first two are model-conditional statements about the declared evaluator and independence model; the last is an implementation invariant. We therefore treat calibration residuals, held-out KL, and rollback frequency as separate engineering diagnostics.

## 5 EXPERIMENTS

### 5.1 EXPERIMENTAL SETUP

The policy is Qwen2.5-1.5B-Instruct. The frozen ordinal Moment RM and independent Quality RM are Qwen2.5-14B models trained with HelpSteer2 repeated helpfulness ratings and preference pairs (Wang et al., 2024b). We use three confirmatory seeds {314, 2718, 1618},  $N = 32$ , and 512 held-out prompts per seed. Primary baselines are Mean-PPO + Q, GRPO + Q, and Scalar Max@32-PPO + Q; full settings, ablations, and audit records are in Appendix B. We report robust maximum, held-out KL, and rollback frequency because they measure the two sides of the proposed operating point.

### 5.2 MAIN RESULTS

StableMax-PPO reaches a robust expected maximum of 3.458 and held-out KL of 0.034, compared with 3.424 and 0.070 for Mean-PPO. Under the shared rollback controller it rejects 31.0% of tentative updates, versus 58.6% for Mean-PPO and 82.3% for GRPO. GRPO and Scalar max-PPO attain higher robust maxima, so the evidence supports a lower-drift operating point rather than universal dominance.

Table 1: Primary aggregate results (three seeds, 512 prompts per seed).

| Method            | Robust max | 95% CI         | Held-out KL | Rollbacks/900 |
|-------------------|------------|----------------|-------------|---------------|
| StableMax-PPO     | 3.458      | [3.411, 3.506] | 0.034       | 279 (31.0%)   |
| Mean-PPO          | 3.424      | [3.354, 3.517] | 0.070       | 527 (58.6%)   |
| GRPO              | 3.555      | [3.530, 3.578] | 0.094       | 741 (82.3%)   |
| Scalar max-PPO    | 3.517      | [3.476, 3.558] | 0.054       | 285 (31.7%)   |
| Best-of-32 (base) | 3.086      | [3.045, 3.125] | —           | —             |




Figure 1: Robust maximum versus held-out KL. Filled markers are three-seed aggregates; open markers are individual seeds and bars are 95% intervals.

Figure 1 makes the trade-off explicit: StableMax-PPO has lower held-out KL than Mean-PPO and GRPO while retaining a competitive robust maximum, whereas max-oriented comparators remain higher on that endpoint. Rollback frequency is an optimization diagnostic, not a population guarantee.



The aggregate numbers quantify the operating point rather than a universal ranking. Relative to Mean-PPO, StableMax-PPO increases robust maximum by 0.034 while reducing held-out KL from 0.070 to 0.034 (a 51% relative reduction). Relative to Scalar max-PPO, it gives up 0.059 robust-max points while using 0.020 less KL. These are the two axes that the method exposes; collapsing them into one weighted score would conceal the engineering trade-off the experiment is designed to measure.

### 5.3 ABLATION AND STABILITY ANALYSIS

Removing the mean floor increases robust max to 3.508 but raises held-out KL to 0.048; removing the independent quality floor yields 3.467 at KL 0.048. Removing calibration robustification yields 3.421 at KL 0.028. These ablations move along the same frontier and support interpreting the constraints as operating-point controls, not uniformly beneficial reward terms. Per-seed values and the remaining diagnostics are in the appendix.

Table 2 makes the component interpretation explicit. Removing the mean floor buys maximum performance at a measurable drift cost, while removing calibration changes the target itself and therefore cannot be interpreted as a pure optimizer ablation. The independent Quality floor has a smaller endpoint effect but still changes the accepted-update trajectory. These comparisons are why we present StableMax-PPO as a controlled operating point: each safeguard has a distinct failure mode and none should be described as a universally improving reward term.

Table 2: Component ablations (three-seed aggregate). Values are unchanged from the complete supplementary table.

| Variant                   | Robust max | Held-out KL | Rollbacks/900 |
|---------------------------|------------|-------------|---------------|
| StableMax-PPO             | 3.458      | 0.034       | 279 (31.0%)   |
| No mean floor             | 3.508      | 0.048       | 230 (25.6%)   |
| No quality floor          | 3.467      | 0.048       | 329 (36.6%)   |
| No calibration correction | 3.421      | 0.028       | 121 (13.4%)   |

### 5.4 INDEPENDENT EVALUATOR DIAGNOSTICS

To test whether improvements under the target Moment RM transfer to an independent evaluation regime, we compare prompt-matched outputs from StableMax-PPO and Mean-PPO with two frozen evaluators. For each of the three seeds, we form up to 512 pairs of held-out groups, select one response per policy by  $\arg \max_i \mu_\omega(x, Y_i)$ , and score the selected responses with a Qwen2.5-14B judge and RLHFFlow/ArmoRM-Llama3-8B-v0.1. The judge order is randomized and checked in reverse; each evaluator is calibrated on a frozen RewardBench split before it is used. The reported preference is tie-adjusted (0.5 is parity), with the interval obtained by the same three-seed hierarchical bootstrap used for the primary endpoint.

Table 3: Independent generated-output proxy comparisons against Mean-PPO. Preference is tie-adjusted, so 0.5 denotes parity.

| Evaluator             | Preference | 95% CI         |
|-----------------------|------------|----------------|
| Qwen2.5-14B judge     | 0.494      | [0.478, 0.510] |
| ArmoRM-Llama3-8B-v0.1 | 0.502      | [0.458, 0.544] |

Both proxy scores are close to parity with Mean-PPO; both intervals contain 0.5, providing no clear signal of lower response quality. Full 32-response groups are also evaluated on robust/nominal maxima, top-rating probability, and style and upper-tail statistics. These model-based diagnostics are secondary and do not establish absence of reward hacking; fixed lockboxes are preference-retention checks, not new human labels.

## 6 LIMITATIONS

The endpoint is induced by frozen evaluators and no fresh human labels are collected for generated outputs. Model proxies may disagree with humans, the 1.5B/14B capacity gap may induce evaluator shift, and three seeds do not establish scale or domain generalization. The exact product form also assumes conditionally independent rating outcomes across sampled responses and does not model correlated annotation or evaluator errors. The artifact reports these limitations and all unfavorable gates rather than redefining the protocol.

**Reproducibility statement.** The supplementary artifact contains the source, official ICLR style files, protocol, result tables, verification JSON, build commands, and the anonymous repository at <https://github.com/LoveGuys-cmd/rlhf-artifact>. The main paper specifies the objective, algorithm, seeds, metrics, and aggregate results; appendices give proofs and the complete protocol. Model weights, credentials, private data, and other non-redistributable files are excluded.

**AI use statement.** Generative AI tools assisted with paper organization, methodological exposition, language editing, LaTeX and figure formatting, and debugging of analysis code. The authors independently checked all mathematical claims and proofs, verified implementation and numerical values against frozen result files, and reviewed every AI-assisted change. No AI system generated experimental data or replaced author verification.

**Ethics statement.** The study uses model-generated text and existing preference data. It collects no new human-subject data or personal information. Model-based preference proxies are reported as proxies, not as human judgments of newly generated outputs; possible reward-model exploitation and evaluator shift are disclosed in Section 6 and Appendix B.

## REFERENCES

- Farid Bagirov, Mikhail Arkhipov, Ksenia Sycheva, Evgeniy Glukhov, and Egor Bogomolov. The best of N worlds: Aligning reinforcement learning with best-of-N sampling via max@k optimization. *arXiv preprint arXiv:2510.23393*, 2025.
- Yinlam Chow, Guy Tennenholtz, Izzeddin Gur, Vincent Zhuang, Bo Dai, Sridhar Thiagarajan, Craig Boutilier, Rishabh Agarwal, Aviral Kumar, and Aleksandra Faust. Inference-aware fine-tuning for best-of-N sampling in large language models. In *International Conference on Learning Representations*, 2025. arXiv:2412.15287.
- Tilman Gneiting and Adrian E. Raftery. Strictly proper scoring rules, prediction, and estimation. *Journal of the American Statistical Association*, 102(477):359–378, 2007. doi: 10.1198/016214506000001437.
- Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1321–1330. PMLR, 2017.
- Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. DeepSeek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.
- Alex Kendall and Yarin Gal. What uncertainties do we need in Bayesian deep learning for computer vision? In *Advances in Neural Information Processing Systems 30*, pp. 5574–5584, 2017.
- Nathan Lambert, Valentina Pyatkin, Jacob Morrison, LJ Miranda, Bill Yuchen Lin, Khyathi Chandu, Nouha Dziri, Sachin Kumar, Tom Zick, Yejin Choi, Noah A. Smith, and Hannaneh Hajishirzi. RewardBench: Evaluating reward models for language modeling. *arXiv preprint arXiv:2403.13787*, 2024.
- Muheng Li, Jian Qian, and Wenlong Mou. What should post-training optimize? a test-time scaling law perspective. *arXiv preprint arXiv:2605.10716*, 2026.



- Chris Yuhao Liu, Liang Zeng, Jiakai Liu, Rui Yan, Jujie He, Chaojie Wang, Shuicheng Yan, Yang Liu, and Yahui Zhou. Skywork-Reward: Bag of tricks for reward modeling in LLMs. *arXiv preprint arXiv:2410.18451*, 2024.
- Xingzhou Lou, Dong Yan, Wei Shen, Yuzi Yan, Jian Xie, and Junge Zhang. Uncertainty-aware reward model: Teaching reward models to know what is unknown. *arXiv preprint arXiv:2410.00847*, 2024. doi: 10.48550/arXiv.2410.00847.
- Peter McCullagh. Regression models for ordinal data. *Journal of the Royal Statistical Society: Series B (Methodological)*, 42(2):109–127, 1980. doi: 10.1111/j.2517-6161.1980.tb01109.x.
- Riccardo Poiani, Martino Bernasconi, and Andrea Celli. Theoretical foundations of max@k reinforcement learning. *arXiv preprint arXiv:2607.17823*, 2026.
- Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Yang, Junxiao Xu, Muyu Zhang, Y. K. Li, Y. Wu, Daya Guo, et al. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.
- Wangtao Sun, Xiang Cheng, Xing Yu, Haotian Xu, Zhao Yang, Shizhu He, Jun Zhao, and Kang Liu. Probabilistic uncertain reward model. *arXiv preprint arXiv:2503.22480*, 2025.
- Yunhao Tang, Kunhao Zheng, Gabriel Synnaeve, and Rémi Munos. Optimizing language models for inference time objectives using reinforcement learning. In *Proceedings of the 42nd International Conference on Machine Learning*. PMLR, 2025. arXiv:2503.19595.
- Christian Walder and Deep Karkhanis. Pass@K policy optimization: Solving harder reinforcement learning problems. *arXiv preprint arXiv:2505.15201*, 2025.
- Haoxiang Wang, Wei Xiong, Tengyang Xie, Han Zhao, and Tong Zhang. Interpretable preferences via multi-objective reward modeling and mixture-of-experts. *arXiv preprint arXiv:2406.12845*, 2024a.
- Zhilin Wang, Yi Dong, Olivier Delalleau, Jiaqi Zeng, Gerald Shen, Daniel Egert, Jimmy J. Zhang, Makesh Narsimhan Sreedhar, and Oleksii Kuchaiev. HelpSteer2: Open-source dataset for training top-performing reward models. *arXiv preprint arXiv:2406.08673*, 2024b.
- An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, et al. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.
- Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-bench and chatbot arena. In *Advances in Neural Information Processing Systems*, volume 36, 2023.

## A DETAILED THEORETICAL ANALYSIS

### A.1 ORDINAL-PROBIT PARAMETERIZATION

The frozen Moment RM emits a latent location  $m_\omega(x, y)$  and positive scale  $s_\omega(x, y)$ . With frozen cutpoints  $c_1 < \dots < c_4$ , its five-category probabilities are  $p_{\omega,0} = \Phi((c_1 - m_\omega)/s_\omega)$ ,  $p_{\omega,r} = \Phi((c_{r+1} - m_\omega)/s_\omega) - \Phi((c_r - m_\omega)/s_\omega)$  for  $r = 1, 2, 3$ , and  $p_{\omega,4} = 1 - \Phi((c_4 - m_\omega)/s_\omega)$ . The moments used by the policy are  $\mu_\omega = \sum_{r=0}^4 r p_{\omega,r}$  and  $\sigma_\omega^2 = \sum_{r=0}^4 (r - \mu_\omega)^2 p_{\omega,r}$ . Repeated-rating likelihood and disagreement supervise the conditional scale; therefore this variance is a model-based signal of annotation disagreement, not epistemic uncertainty or a stand-alone reward. Proper scoring and calibration are required because the complete categorical distribution enters the finite-budget objective (McCullagh, 1980; Kendall & Gal, 2017; Lou et al., 2024; Sun et al., 2025; Gneiting & Raftery, 2007; Guo et al., 2017).

This parameterization is included to make the evaluator interface reproducible, not to claim a new ordinal-link model. The methodological choice is what the policy does with the frozen output: the

same five probabilities support the nominal mean, threshold products, robust envelope, and disagreement diagnostic. Keeping these uses separate is important because replacing the vector by its mean would make the finite-budget objective and its calibration check unidentifiable.

**Proposition 3** (Finite-support threshold decomposition). *For conditionally independent ratings supported on  $\mathcal{R} = \{0, 1, 2, 3, 4\}$ , eq. (1) is exact, lies in  $[0, 4]$ , and is nondecreasing under first-order stochastic improvement of any candidate. Moreover, eq. (8) is its highest-threshold component.*

The proposition is the finite-support sanity check for the main construction. It also explains why the top-rating diagnostic in the artifact is not a substitute for the reported objective: it is only the  $t = 4$  term, whereas the method trains against all four threshold events. This distinction prevents a policy from appearing successful by concentrating probability only at the highest category while degrading the intermediate ordinal structure.

*Proof.* For any integer-valued  $Z \in \{0, \dots, 4\}$ , the tail-sum identity gives  $\mathbb{E}[Z] = \sum_{t=1}^4 \Pr\{Z \geq t\}$ . Taking  $Z = \max_j R_j$  and using (A1) gives  $\Pr\{\max_j R_j < t \mid x, Y_{1:N}\} = \prod_{j=1}^N F_{\omega,j}(t-1)$ .

Substitution proves eq. (1). Each term lies in  $[0, 1]$ , so the sum lies in  $[0, 4]$ . First-order stochastic improvement decreases a candidate CDF and therefore cannot decrease any summand. At  $t = 4$ ,  $F_{\omega,j}(3) = 1 - p_{\omega,4}(x, Y_j)$ , giving eq. (8).  $\square$

**Proposition 4** (Prompt-cluster calibration statement). *Assume the validation prompt clusters are independent and that the RM is fixed before evaluating them. The radius used in the main text is*

$$\varepsilon_{\text{cal}} = \min \left\{ 1, \max_{t=0,\dots,3} (\hat{d}_t)_+ + \sqrt{\frac{\log(4/\alpha_{\text{cal}})}{2G_{\text{cal}}}} \right\}. \quad (7)$$

*Then, with probability at least  $1 - \alpha_{\text{cal}}$ ,  $\mathbb{E}[D_t] \leq \varepsilon_{\text{cal}}$  simultaneously for  $t = 0, 1, 2, 3$ .*

*Proof.* Conditional on the frozen responses and predictions, changing all binary indicators in a prompt cluster from zero to one changes  $D_{g,t}$  by at most one. Thus each cluster residual lies in an interval of width one. Hoeffding’s inequality gives  $\Pr(\mathbb{E}[D_t] - \hat{d}_t > \sqrt{\log(4/\alpha_{\text{cal}})/(2G_{\text{cal}})}) \leq \alpha_{\text{cal}}/4$ .

A union bound over four thresholds proves the simultaneous event. On that event, every right-hand side is bounded by the unclipped expression in eq. (7). If clipping is active,  $\varepsilon_{\text{cal}} = 1$ , while  $\mathbb{E}[D_t] \leq 1$ , so the claim still holds.  $\square$

**Scope of the calibration proposition.** Proposition 4 is a population-average statement over the validation prompt distribution. It is not a distribution-free, pointwise guarantee that every conditional CDF lies in the ambiguity set. The pointwise premise required by the next theorem is therefore stated explicitly rather than inferred from a small number of repeated ratings.

This scope distinction is operationally relevant. The calibration split controls how the radius is chosen before training, while the theorem in the main text describes what follows if the resulting envelope covers a generated candidate. Conflating these statements would turn an average calibration diagnostic into an unjustified pointwise claim; the artifact keeps the calibration estimate and the conditional robustness guarantee as separate records.

**Proof of Theorem 1.** The envelope  $\bar{F}_j$  is nondecreasing, has boundary values zero and one, and therefore defines a valid categorical distribution. For every feasible  $q_j \in \mathcal{U}$ ,  $F_{q_j}(t) \leq \bar{F}_j(t)$  for  $t = 0, 1, 2, 3$ .

Hence  $q_j$  first-order stochastically dominates  $\bar{p}_j$ , or equivalently  $\bar{p}_j$  is stochastically smallest. The maximum is coordinatewise nondecreasing in its ratings, so replacing every feasible candidate by  $\bar{p}_j$  cannot increase its expectation. The envelope itself is feasible and thus attains the infimum. Applying proposition 3 gives the stated closed form.

**Proof of Theorem 3.** Let  $F_j^*$  be the true conditional CDF. Under the pointwise premise  $F_j^*(t) \leq \bar{F}_j(t)$  for every candidate and threshold, first-order stochastic dominance gives the lower-bound inequality in Theorem 3. For the misspecified case, define  $\xi = \max_{j,t} [F_j^*(t) - \bar{F}_j(t)]_+$ . At each threshold, the true and robust tail-sum terms can differ only through the corresponding CDF products. For  $a_j, b_j \in [0, 1]$ ,  $\prod_j a_j - \prod_j b_j \leq \sum_j (a_j - b_j)_+$ .

Apply this inequality with  $a_j = F_j^*(t - 1)$  and  $b_j = \bar{F}_j(t - 1)$  at each of four thresholds. The discrepancy is at most  $N\xi$  per threshold and therefore at most  $4N\xi$  after summation. Taking outer expectations preserves the resulting inequality  $\mathbb{E}_*[\max_j R_j] \geq h_N^{\text{rob}} - 4N\xi$ .

**Proof of Proposition 1.** Fix a candidate group and threshold  $t$ , and write  $a_j(\varepsilon) = \min\{1, F_{\omega,j}(t - 1) + \varepsilon\}$ . For  $\varepsilon_1 \leq \varepsilon_2$ , the clipping map gives  $0 \leq a_j(\varepsilon_2) - a_j(\varepsilon_1) \leq \varepsilon_2 - \varepsilon_1$ . The telescoping product identity and  $a_j(\varepsilon) \in [0, 1]$  then give  $0 \leq \prod_j a_j(\varepsilon_2) - \prod_j a_j(\varepsilon_1) \leq \sum_j (a_j(\varepsilon_2) - a_j(\varepsilon_1)) \leq N(\varepsilon_2 - \varepsilon_1)$ . Substituting this bound into the four-term tail-sum expression for  $h_N^{\text{rob}}$ , and then taking the expectation over prompts and responses, proves Proposition 1. At  $\varepsilon = 0$ , the envelope equals the nominal CDF, so the exact infimum in Theorem 1 equals  $J_N^{\text{nom}}(\theta)$ .

**Proof of Proposition 2.** Let  $(\theta_0, \text{Opt}_0)$  be the snapshot taken before a tentative update. If the measured rollout-state KL exceeds  $\delta_{\text{hard}}$ , the algorithm assigns  $(\theta, \text{Opt}) \leftarrow (\theta_0, \text{Opt}_0)$ , so both objects equal their pre-update values exactly (up to the semantics of the implementation’s state-copy operation). Because controller-state updates occur only in the accepted branch, a rejected transition also leaves the baseline, dual variables, KL coefficient, and RMS scale unchanged. The statement is conditional on the measured batch and therefore makes no population-level KL claim.

**Proof of Theorem 2.** For nonnegative integer ratings,  $(\bar{R}_i - \bar{M}_{-i})_+ = \sum_{t=1}^4 \mathbf{1}\{\bar{R}_i \geq t, \bar{M}_{-i} < t\}$ . Taking conditional expectations and using (A1) gives  $\Pr\{\bar{R}_i \geq t, \bar{M}_{-i} < t \mid x, Y_{1:N}\} = [1 - \bar{F}_i(t - 1)] \prod_{j \neq i} \bar{F}_j(t - 1)$ ,

which proves eq. (4). For the gradient, fix  $i$  and condition on  $(x, Y_{-i})$ . The group value decomposes as  $h_N^{\text{rob}} = \mathbb{E}[\bar{M}_{-i} \mid x, Y_{-i}] + q_i^{\text{rob}}$ .

The first term is independent of  $Y_i$ , and the score-function identity implies that its product with  $\nabla_\theta \log \pi_\theta(Y_i \mid x)$  has conditional expectation zero. Applying the likelihood-ratio derivative to all  $N$  iid responses and summing the remaining terms proves eq. (5).

**Proposition 5** ( $N = 1$  reduction and complexity). For  $N = 1$ ,  $h_1^{\text{rob}} = q_1^{\text{rob}} = \sum_{r=0}^4 r \bar{p}_{1,r}$ .

Thus the upper-tail reward component reduces exactly to robust mean reward. For general  $N$ , all group values and marginal credits can be computed in  $O(N|\mathcal{R}|)$  time using threshold-wise prefix and suffix products.

This reduction is a useful implementation check: at  $N = 1$ , the method must recover the robust mean and cannot manufacture a group advantage. For  $N > 1$ , the additional terms are exactly the response’s incremental chance of opening a new threshold above the other candidates. The test suite evaluates both regimes, so a change in the group objective cannot be explained by a special-case implementation.

*Proof.* With one candidate, the empty opponent maximum is zero, so  $(\bar{R}_1 - 0)_+ = \bar{R}_1$ . The first equality follows. For complexity, each threshold requires one forward and one backward product scan; there are  $|\mathcal{R}| - 1 = 4$  nontrivial thresholds.  $\square$

## B FULL EXPERIMENTAL PROTOCOL

### B.1 EXPERIMENTAL QUESTIONS

The experiments are designed to answer four predeclared questions:

1. Does StableMax-PPO improve the held-out robust  $\mathbb{E}[\max_{j \leq 32} R_j]$  objective relative to mean optimization and a direct scalar max@32 policy gradient?

2. Are gains preserved under the nominal exact ordinal maximum and the top-rating probability  $\Pr\{\exists j : R_j = 4\}$ ?
3. Do nominal expected rating, independent Quality RM score, and reference-policy KL remain within their predeclared safeguards?
4. Do independent generated-output proxies and existing human-labeled preference diagnostics provide evidence against target-RM exploitation?

No result is used to remove a comparator, redefine a threshold, or select a more favorable protocol.

## B.2 PROTOCOL AUDIT AND SCIENTIFIC INTERPRETATION

The artifact verifier passed for seeds 314, 2718, and 1618. The terminal record preserves every predeclared proxy, non-inferiority, safeguard, and KL outcome for auditability. We interpret these fields as protocol diagnostics that delimit the measured max-stability frontier, not as a universal method ranking or a proof that reward-model exploitation is absent.

The diagnostic vector is read as a decision record rather than a single leaderboard score. A method can satisfy KL and quality safeguards while losing a max comparison, or improve the target reward while degrading an independent proxy. Reporting the vector preserves these distinctions and prevents a favorable endpoint from hiding a failure mode that the method was designed to measure.

## B.3 MODELS, DATA, AND SPLIT DISCIPLINE

The policy is Qwen2.5-1.5B-Instruct (Yang et al., 2024). The frozen Moment RM is a Qwen2.5-14B ordinal model trained from HelpSteer2 repeated helpfulness ratings and preference pairs (Wang et al., 2024b). It exports  $p_{\omega,0:4}$  directly; exposing the category probabilities does not retrain or alter its accepted checkpoint. An independently trained Qwen2.5-14B scalar Quality RM supplies  $Q_\eta$  and has no variance head. Its frozen 4,096-pair confirmation accuracy is 94.60% with a Wilson lower 95% bound of 93.87%.

All policy, reward-model, evaluator, and lockbox splits are content-hashed. Before partitioning RewardBench, we remove prompt and response overlap with the policy and Quality-RM data (Lambert et al., 2024). The remaining calibration, policy-diagnostic, and reserve partitions are also mutually prompt- and response-disjoint. They contain 1,024, 1,024, and 427 pairs, respectively. The sealed Skywork diagnostic contains 4,096 pairs and is excluded from Quality-RM training and selection (Liu et al., 2024).

The Moment RM and policy prompts remain drawn from the same broad HelpSteer2 domain. Disjoint rows prevent direct leakage but do not establish out-of-domain generalization; this is treated as a limitation rather than hidden by the split terminology.

## B.4 FROZEN TRAINING PROTOCOL

The primary response budget is  $N = 32$ . Each trainable confirmatory method uses three seeds  $\{314, 2718, 1618\}$ , 300 policy steps, two prompts per step, 32 responses per prompt, learning rate  $2 \times 10^{-5}$ , one PPO epoch, clip 0.2, LoRA rank 8 with scale 32, sampling temperature 1,  $\text{top}_p = 1$ , maximum prompt length 384, and maximum response length 64. Seed 42 is used only for development and real-GPU smoke tests and is excluded from all confirmatory intervals, gates, and aggregate claims. The target KL is 0.02 and the hard rollback level is 0.04. All methods share the same prompt stream, generation budget, optimizer class, policy architecture, and checkpoint-selection rule.

The non-inferiority floors are frozen before any trainable policy outcome is observed. The reference sample contains 2,048 base-policy responses from 512 independent policy-training prompts, with four responses per prompt. For  $Z \in \{\mu_\omega, Q_\eta\}$ , let  $\bar{Z}_g$  be the four-response prompt mean and let  $L_Z$  be the fifth percentile of 10,000 bootstrap means obtained by resampling prompts. The frozen floor is  $z_0 = L_Z - 0.1s_Z$ , where  $s_Z$  is the response-level standard deviation in the same reference sample. The bootstrap unit, one-sided level, 10,000 draws, sample counts, generation seed, bootstrap seed, and practical margin are all predeclared. A separate prompt-disjoint sample of 512 responses from 128 prompts reports standardized reference-policy shift. It is diagnostic only and cannot accept or reject training.

Table 4: Complete aggregate table. Values are three-seed robust expected maximum, with 95% confidence intervals, held-out KL, and rollback counts.

| Method                           | Robust max | 95% CI         | Held-out KL | Rollbacks/900 |
|----------------------------------|------------|----------------|-------------|---------------|
| StableMax-PPO                    | 3.458      | [3.411, 3.506] | 0.034       | 279 (31.0%)   |
| Mean-PPO                         | 3.424      | [3.354, 3.517] | 0.070       | 527 (58.6%)   |
| GRPO                             | 3.555      | [3.530, 3.578] | 0.094       | 741 (82.3%)   |
| Scalar max-PPO                   | 3.517      | [3.476, 3.558] | 0.054       | 285 (31.7%)   |
| Entropic PPO                     | 3.400      | [3.353, 3.447] | 0.037       | 302 (33.6%)   |
| Nominal EV-PPO                   | 3.421      | [3.377, 3.467] | 0.028       | 121 (13.4%)   |
| StableMax-PPO (no mean floor)    | 3.508      | [3.426, 3.574] | 0.048       | 230 (25.6%)   |
| StableMax-PPO (no quality floor) | 3.467      | [3.402, 3.530] | 0.048       | 329 (36.6%)   |
| Gaussian EV-PPO                  | 3.558      | [3.533, 3.581] | 0.061       | 367 (40.8%)   |
| Top-4 PPO                        | 3.418      | [3.353, 3.499] | 0.042       | 277 (30.8%)   |
| Best-of-32 (base)                | 3.086      | [3.045, 3.125] | —           | —             |

## B.5 COMPARATORS AND ABLATIONS

The ten trainable methods are:

1. **StableMax-PPO**: the complete method in Algorithm 1.
2. **Mean-PPO + Q**: PPO on  $\mu_\omega$  with the same mean, Quality, and KL protocol.
3. **GRPO + Q**: group-relative standardized  $\mu_\omega$  credit with matched safeguards (Shao et al., 2024; Guo et al., 2025).
4. **Scalar Max@32-PPO + Q**: exact leave-one-out scalar max credit  $[\mu_i - \max_{j \neq i} \mu_j]_+$  with matched safeguards (Tang et al., 2025; Walder & Karkhanis, 2025; Bagirov et al., 2025).
5. **Entropic-PPO + Q**: PPO on  $\text{CE}_\tau = -\tau \log \sum_r p_{\omega,r} e^{-r/\tau}$ , using  $\tau = 1$ .
6. **Nominal Ordinal EV-PPO + Q**: exact  $J_{32}^{\text{nom}}$  without the calibration ambiguity set.
7. **StableMax-PPO without mean floor**: ablates nominal-mean non-inferiority.
8. **StableMax-PPO without Quality RM**: ablates the independent quality safeguard and is excluded from constrained-feasibility claims.
9. **Gaussian EV-PPO + Q**: the previous heteroscedastic Gaussian expected-maximum objective, retained as a model-assumption ablation.
10. **Top-4 PPO + Q**: exact optimization of  $\Pr\{\exists j : R_j = 4\}$ , isolating the highest threshold from the complete ordinal maximum.

An eleventh, evaluation-only **Best-of-32** row samples 32 responses from the untrained base policy and ranks them by  $\mu_\omega$ . It is an inference-time reference, not a compute-matched training baseline; its generation and scoring cost is reported separately.

The comparator set is organized to separate three changes that are otherwise easy to conflate: the deployment functional (mean, scalar maximum, top-rating, or full ordinal maximum), the calibration correction, and the stabilizers. The nominal ordinal and Gaussian variants hold the policy optimizer fixed while changing the evaluator assumption; the no-floor variants hold the target fixed while removing one safeguard. This is why the ablations support a causal interpretation of the observed frontier without claiming that any single component is universally beneficial.

## B.6 EVALUATION ENDPOINTS

Every method is evaluated on 512 frozen test prompts with newly generated groups of 32 responses. The primary paired prompt-level endpoint is  $h_{32}^{\text{rob}}$ , exactly matching the StableMax-PPO training objective. Secondary model-based endpoints are  $h_{32}^{\text{nom}}$ ,  $U_{32}^{\text{nom}}$ , candidate-level  $\mu_\omega$ , ordinal variance,  $p_{\omega,4}$ , independent Quality score, reference KL, constraint residuals, accepted updates, and exact rollback counts.

Sensitivity at  $N \in \{1, 2, 4, 8, 16, 32\}$  uses nested prefixes of the same cached 32-response groups. This preserves paired comparisons and avoids regenerating a favorable sample for each  $N$ . The group-level maximum uses all candidates and does not require a selected response. A deployment-style  $\arg \max_i \mu_\omega(x, Y_i)$  response is reported only as a secondary selector diagnostic.



The nested- $N$  evaluation is also a variance-control choice. Reusing the same cached response prefixes makes changes in the endpoint attributable to the budget rather than to a new generation sample. The held-out KL is computed on common base trajectories for the same reason, so a lower value reflects less measured policy motion under a paired protocol rather than an easier test set.

For completeness, the top-category diagnostic used in the cached evaluation is

$$U_N^{\text{nom}}(\theta) := \mathbb{E}_{x, Y_{1:N}} \left[ 1 - \prod_{j=1}^N (1 - p_{\omega, 4}(x, Y_j)) \right]. \quad (8)$$

It is the frozen-model probability that at least one candidate receives rating four. It is not a Gaussian tail approximation and is not the primary estimand; the complete ordinal maximum remains the reported objective.

## B.7 STATISTICAL ANALYSIS AND SUCCESS CRITERIA

All seeds are reported separately. Aggregate uncertainty is estimated by a hierarchical bootstrap that resamples seeds and prompts. Paired prompt-level contrasts additionally report one-sided sign-flip randomization tests and matched-pairs rank-biserial effect sizes. The primary superiority gates require the lower endpoint of a two-sided 95% hierarchical-bootstrap interval for the StableMax-PPO improvement in  $h_{32}^{\text{rob}}$  to exceed zero against Mean-PPO, GRPO + Q, and Scalar Max@32-PPO.

Safeguard success requires the corresponding interval lower endpoints for StableMax-PPO’s candidate nominal mean and independent Quality mean to remain at or above  $m_0$  and  $q_0$ . A point estimate alone cannot satisfy either floor. The complete scientific-success decision requires all predeclared superiority, floor, and generated-output proxy gates; improvement under the target RM alone is insufficient.

## B.8 ANTI-EXPLOITATION AND HUMAN-GROUNDED DIAGNOSTICS

Newly generated outputs are compared with Mean-PPO outputs by two frozen evaluators: the Qwen2.5-14B-Instruct judge and RLHFFlow/ArmoRM-Llama3-8B-v0.1 (Zheng et al., 2023; Wang et al., 2024a). For each seed, the diagnostic aligns up to 512 held-out prompt groups, retains the response selected by  $\arg \max_i \mu_{\omega}(x, Y_i)$  from each 32-response group, and evaluates the matched pair. Qwen judgments use randomized presentation order and a reverse order check; ArmoRM supplies an independent pointwise score. Each evaluator must first pass its frozen RewardBench calibration gate (between 512 and 1,024 calibration pairs, with the frozen split and hashes recorded by the protocol). Pairwise judgments are model-based proxies, not human labels. The complete group-level diagnostic is run separately on all 32 candidates and reports robust/nominal maximum, probability of any rating-4 response, and the paired group delta; selected-response diagnostics additionally report length, character count, repeated-trigram rate, unique-word ratio, refusal behavior, and upper-tail strata.

The aggregate tie-adjusted preference scores against Mean-PPO are 0.494 ([0.478, 0.510]) for Qwen and 0.502 ([0.458, 0.544]) for ArmoRM, where the intervals are three-seed hierarchical-bootstrap 95% intervals. Both scores are near parity and both intervals contain 0.5, so neither evaluator shows a clear quality-degradation signal relative to Mean-PPO. A target-RM increase accompanied by proxy degradation would be evidence consistent with reward-model exploitation; these results do not show that signature, but the model-based design cannot establish its absence.

RewardBench and Skywork chosen-rejected lockboxes contain previously collected human labels. For each policy, length-normalized chosen-rejected policy log-probability accuracy and margin are reported as preference-retention diagnostics. They are not Best-of-32 endpoints and do not label newly sampled policy responses. In particular, a new response cannot be declared human preferred merely because it was generated for a prompt that also appears in a fixed preference benchmark.

No new human annotation is collected in this protocol. Therefore, even if all anti-exploitation gates pass, the permitted claim is *no evidence of exploitation under the measured model-based and existing-label diagnostics*. The experiment cannot establish absence of reward hacking or direct human preference for generated outputs. A blinded group-rating packet is emitted so that fresh human evaluation can be added later without regenerating or selecting outputs.



## B.9 REPRODUCIBILITY AND REPORTING

Code, model adapters, data partitions, floor samples, calibration reports, and protocol files are content-hashed before training. A real-GPU smoke test must execute every declared objective, verify finite applicable metrics, verify constraint activation, and test exact parameter and optimizer rollback. Formal training and evaluation run only after these checks pass. Technical failures are versioned and corrected with regression tests. Unfavorable scientific outcomes are reported without changing seeds, thresholds, comparators, evaluators, or success criteria.

The 1.5B policy is evaluated by 14B reward and proxy models. This capacity gap may improve discrimination but may also create systematic evaluator shift. The three-seed design measures optimization variability; it does not replace replication at other model scales or fresh blinded labels.

## C IMPLEMENTATION DETAILS FOR STABLEMAX-PPO

This appendix records implementation conventions for Algorithm 1; it is not a second algorithm. Model identifiers, seeds, and acceptance thresholds are specified in Appendix B.

For each prompt  $x_b$ , the implementation caches behavior-policy token log probabilities and response masks before evaluating any reward model. The five ordinal probabilities are converted to prefix CDFs. For  $t = 0, \dots, 3$ , the robust envelope is  $\bar{F}_{b,i}(t) = \min\{1, F_{\omega,b,i}(t) + \varepsilon_{\text{cal}}\}$ , with  $\bar{F}_{b,i}(-1) = 0$  and  $\bar{F}_{b,i}(4) = 1$ . The robust probabilities are adjacent differences of this envelope. Prefix and suffix products compute all group values and leave-one-out credits in  $O(BN|\mathcal{R}|)$  time without enumerating rating tuples.

The constrained credit used by the PPO surrogate is  $\tilde{q}_{b,i} = q_{b,i}^{\text{rob}} + \lambda_m \mu_\omega(x_b, Y_{b,i})/N + \lambda_q Q_\eta(x_b, Y_{b,i})/N$ , with  $A_{b,i} = N[\tilde{q}_{b,i} - b_\psi(x_b)]$ . The prompt baseline is fitted only from accepted transitions. Dual variables use projected updates after acceptance; rejected steps leave all controller state unchanged. The lagged RMS scale is computed from accepted credits only, so a rejected outlier cannot change the next normalization factor.

Before the optimizer step, the implementation snapshots all trainable policy parameters and the complete optimizer state, including momentum and adaptive variance buffers. It evaluates full-categorical token KL on the same rollout states after the tentative step. If the hard threshold is exceeded, both snapshots are restored and no baseline, dual, KL-controller, or RMS state is advanced. This is an exact batch-level rollback invariant; it does not imply a population KL bound.

All floating-point reductions use deterministic tensor order where supported. The supplementary code contains tests for ordinal identities, credit reductions, finite metrics, protocol hashes, and rollback restoration.

## D ARTIFACT AND VERIFICATION RECORDS

The machine-readable supplementary files include the aggregate JSON, complete per-seed CSV tables, terminal verification records, and SHA-256 manifest.