eCMD Command Line Interface

Version .3

Contact: Chris Engel / Paul Prahl

IBM Confidential

Table of Contents

1 Introduction

This document has been created using OpenOffice, a copy of the OpenOffice Suite can be obtained from: http://mcweb.boeblingen.de.ibm.com/OpenOffice/

This document describes the eCMD command line set. These commands are all written in C code against the eCMD C-Api and as such can run against any implementation of the eCMD C-Api. Currently this means scripts written to use the eCMD command line will be able to run against GFW for I/P/Z Series or Cronus without any modification.

2 Usage Instructions

2.1 Environment Setup

To run the eCMD command line interface requires a few environment variables be setup prior to executing any commands. The exact method to setup these variables may be different depending on which implementation of the C-Api you plan on running but will be documented here in the future.

2.2 Error Handling

All errors encountered running an eCMD command will display a message to the screen and will return a non-zero return code to the calling shell.

2.3 Required Input Files

eCMD queries all required files (ie scandefs/help text) from the dll that it is using. In the case of IP Series when running on the FSP commands requiring external input files may not run unless a NFS mount is setup to source these files.

2.4 Optional Arguments

All eCMD optional arguments start with a '-' character, these arguments can be specified in any order on the command line.

3 eCMD Common Commands

These are the core command line functions available through the eCMD interface and the syntax of the command. The help text is commented with the text 'Core Common Function' for all commands that are part of the core eCMD subset. Other Series or Cronus specific commands will be specified uniquely as well.

3.1 Common Command Arguments

These are common arguments that are supported on most of the eCMD commands.

3.1.1 Targeting Options

Most eCMD functions use the following commands to specify which chip/node/cage you are trying to target in the system. How these options map to physical hardware will be defined by the eCMD team and documented in a separate document for each product.

The valid targeting options:

- -k# (cage)
- -n# (node)
- -s# (slot)
- -p# (position)
- -c# (core)
- -t# (thread)

These options accept the following number strings:

- -p0   Single digit
- -p1,5,10   Comma separated list
- -p2..7   Range of positions
- -p1,2..5,9 Mixture of single and ranges
- -pall   Target all possible configured positions

The -t (thread) argument takes a special option -talive to specify all alive threads.

3.1.2 Data Output Formatting (-o<format>)

The -o argument is used by eCMD to decide how the data should be displayed to the user. The -o argument takes a format string , the available formats are displayed below:

Left-aligned Hex : -ox

```
FORMAT: X
gr     k0:n0:s0:p00:c0        000000000000000000000000
gr     k0:n0:s0:p01:c0        000000000000000000000000
gr     k0:n0:s0:p02:c0        000000000000000000000000
```

Left-aligned Hex Words : -oxw

```
FORMAT: XW
gr     k0:n0:s0:p00:c0        00000000 00000000 00000000
gr     k0:n0:s0:p01:c0        00000000 00000000 00000000
gr     k0:n0:s0:p02:c0        00000000 00000000 00000000
```

Left-aligned Hex Word Columns : -oxw2

```
FORMAT: XW2
gr     k0:n0:s0:p00:c0
0: 00000000 00000000
2: 00000000
gr     k0:n0:s0:p01:c0
0: 00000000 00000000
2: 00000000
```

Right-aligned Hex : -oxr

```
FORMAT: XR
gr     k0:n0:s0:p00:c0        000000000000000000000000
gr     k0:n0:s0:p01:c0        000000000000000000000000
gr     k0:n0:s0:p02:c0        000000000000000000000000
```

Right-aligned Hex Words : -oxrw

```
FORMAT: XRW
gr     k0:n0:s0:p00:c0        00000000 00000000 00000000
gr     k0:n0:s0:p01:c0        00000000 00000000 00000000
gr     k0:n0:s0:p02:c0        00000000 00000000 00000000
```

Right-aligned Hex Word Columns : -oxrw2

```
FORMAT: XRW2
gr     k0:n0:s0:p00:c0
0: 00000000 00000000
2: 00000000
gr     k0:n0:s0:p01:c0
0: 00000000 00000000
2: 00000000
```

Binary : -ob

```
FORMAT: B
gr     k0:n0:s0:p00:c0        000000000000000000000000000000000000000000000000
gr     k0:n0:s0:p01:c0        000000000000000000000000000000000000000000000000
gr     k0:n0:s0:p02:c0        000000000000000000000000000000000000000000000000
```

Binary Nibbles : -obn

```
FORMAT: BN
gr      k0:n0:s0:p00:c0         0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000
gr      k0:n0:s0:p01:c0         0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000
gr      k0:n0:s0:p02:c0         0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000
```

Binary Nibble Columns : -obn8

```
FORMAT: BN8
gr      k0:n0:s0:p00:c0

    0           1           2           3
    0123 4567 8901 2345 6789 0123 4567 8901
00: 0000 0000 0000 0000 0000 0000 0000 0000
08: 0000 0000 0000 0000 0000 0000 0000 0000
16: 0000 0000 0000 0000 0000 0000 0000 0000
```

Binary Words : -obw

```
FORMAT: BW
gr      k0:n0:s0:p00:c0         00000000000000000000000000000000
00000000000000000000000000000000 00000000000000000000000000000000
gr      k0:n0:s0:p01:c0         00000000000000000000000000000000
00000000000000000000000000000000 00000000000000000000000000000000
```

Binary Word Columns : -obw1

```
FORMAT: BW1
gr      k0:n0:s0:p00:c0

   0         1         2         3
   01234567890123456789012345678901
0: 00000000000000000000000000000000
1: 00000000000000000000000000000000
2: 00000000000000000000000000000000
```

Simulation Outputs : X-States are simulation states that aren't valid on real, choosing one of the following X-State in a hardware environment will just be equivalent to the binary output.

X-State Binary : -obX

```
FORMAT: BX
gr      k0:n0:s0:p00:c0         000000000000000000000000000000000000000000000000
gr      k0:n0:s0:p01:c0         000000000000000000000000000000000000000000000000
gr      k0:n0:s0:p02:c0         000000000000000000000000000000000000000000000000
```

X-State Binary Nibbles : -obXn

```
FORMAT: BXN
gr      k0:n0:s0:p00:c0         0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000
gr      k0:n0:s0:p01:c0         0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000
gr      k0:n0:s0:p02:c0         0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000
```

X-State Binary Nibble Columns : -obXn8

```
FORMAT: BXN8
gr    k0:n0:s0:p00:c0

    0            1            2            3
    0123 4567 8901 2345 6789 0123 4567 8901
00: 0000 0000 0000 0000 0000 0000 0000 0000
08: 0000 0000 0000 0000 0000 0000 0000 0000
16: 0000 0000 0000 0000 0000 0000 0000 0000
```

X-State Binary Words : -obXw

```
FORMAT: BXW
gr    k0:n0:s0:p00:c0       00000000000000000000000000000000
00000000000000000000000000000000 00000000000000000000000000000000
gr    k0:n0:s0:p01:c0       00000000000000000000000000000000
00000000000000000000000000000000 00000000000000000000000000000000
```

X-State Binary Word Columns : -obXw1

```
FORMAT: BXW1
gr    k0:n0:s0:p00:c0

    0         1         2         3
    012345678901234567890123456789012345678901
0: 00000000000000000000000000000000
1: 00000000000000000000000000000000
2: 00000000000000000000000000000000
```

Memory Output : -omem

```
FORMAT: MEM
gr    k0:n0:s0:p00
0000000000000100: FEEDBEEF FEEDBEEF FEEDBEEF FEEDBEEF
0000000000000110: FEEDBEEF FEEDBEEF FEEDBEEF FEEDBEEF
```

Memory Output – Ascii Decode : -omema

```
FORMAT: MEMA
gr    k0:n0:s0:p00
0000000000000100: FEEDBEEF FEEDBEEF FEEDBEEF FEEDBEEF   [THISisTHEasciiTE]
0000000000000110: FEEDBEEF FEEDBEEF FEEDBEEF FEEDBEEF   [XT.............]
```

Memory Output – Ebcedic Decode : -omeme

```
FORMAT: MEME
gr    k0:n0:s0:p00
0000000000000100: FEEDBEEF FEEDBEEF FEEDBEEF FEEDBEEF   [THISisTHEebcedic]
0000000000000110: FEEDBEEF FEEDBEEF FEEDBEEF FEEDBEEF   [TEXT............]
```

Memory Output – Dcard Format : -odcard

```
FORMAT: DCARD
gr    k0:n0:s0:p00
D 0000000000000100 FEEDBEEFFEEDBEEF 0
D 0000000000000108 FEEDBEEFFEEDBEEF 1
D 0000000000000110 FEEDBEEFFEEDBEEF 0
D 0000000000000118 FEEDBEEFFEEDBEEF 1
```

Spy Enum Output – Only valid with getspy command : -oenum

```
FORMAT: ENUM
gr      k0:n0:s0:p00:c0 OFF
gr      k0:n0:s0:p00:c1 ON
```

3.1.3 Data Input Formatting (-i<format>)

The -i argument is used by eCMD to determine how to read the data provided by the user.

Left-aligned Hex : -iX

Right-aligned Hex : -iXR

Binary : -iB

Spy Enum – Only valid with putspy command : -ienum

3.1.4 Data Input Bit Modifiers (-b<modifier>)

The -b argument allows the user to specify a bit operation to perform on the data, this forces eCMD to do a read-modify-write on the data to perform the operation.

Or : -bor

>   Read data from hardware, or in data specified, write data back to hardware.

And : -band

>   Read data from hardware, and with data specified, write data back to hardware.

3.2 Command Help (-h)

All commands accept the '-h' argument, when specified eCMD will echo back the help text for the command. This text is the same as shown below in this document.

3.3 Quiet Mode (-quiet)

This tells eCMD to run in quiet mode affecting the following things:

- Full command will not be echoed upon completion

- Target will not be echoed on write operations (ie putspy).

3.4 Trace Options (-trace)

All commands accept the -trace argument which allows the user to turn on different traces. The format of the trace is common between all major eCMD plugins but the mechanism for displaying the trace may be different. For example Cronus displays traces to stdout in the shell you are running, where as IP GFW writes traces to logs on the FSP.

The trace option syntax is : **-trace=<mode1>[,<mode2>]**

Example : -trace=scan,prcd

Trace Options :

-trace=scan

> Scan tracing : Displays all ring/scom/spy accesses to the hardware

-trace=prcd

> Procedure tracing : Displays the procedure trace as defined by the "HW control procedure" specification.

3.5 Chip Display/Alter Commands

3.5.1 checkrings

Syntax:

```
Syntax: checkrings <ChipSelect> <RingSelect> [-k#] [-n#] [-s#] [-p#] [-c#]

        ECMD:           Core Common Function

        Function:       checks for stuck bits and verifies scanring length by scanning
                        ones and zeros to scan chain.

        Parameters:
        ------------------------------------------------------------------------------
        ChipSelect      Specifies the chip to operate on.

        RingSelect      Specifies chip ring to operate on.  Use "all" for all rings.
                        For a list of available rings, use the query command.

                        Ex:  ecmdquery rings memctrl
                             ecmdquery rings pu

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                        to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                        to act on all nodes.

        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                        to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                        -pall to act on all chips.

        -c#  [optional] Specify which processor core to act on (0 is default). Specify
                        -call to act on all cores.
        ------------------------------------------------------------------------------

        Example:        checkrings pu all -p0,1 -c0
                        checkrings memctrl int -pall
```

Examples:

```
> checkrings test all
Performing 1's test on testring ...
Performing 0's test on testring ...
Performing 1's test on sgxbs ...
Performing 0's test on sgxbs ...
ecmd.exe checkrings test all
```

3.5.2 getarray

Syntax:

eCMD Command Line Interface

```
Syntax: getarray <ChipSelect> <ArrayName> <ArrayIndex> [NumEntries] [-o<format>]
                              [-k#] [-n#] [-s#] [-p#] [-c#]

        ECMD:           Core Common Function

        Function:       Read the specified chip array.

        Parameters:
        --------------------------------------------------------------------------------
        ChipSelect      Chip to read array data from.

        ArrayName       Name of array to read from.

        ArrayIndex      Array Index in right aligned hex.

        NumEntries[opt] Number of consecutive entries to display
                        Address is incremented by 1

        -o<format>[opt] Output Format : default 'xl'
                        Run 'ecmdquery formats' to view available formats

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                        to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                        to act on all nodes.

        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                        to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                        -pall to act on all chips.

        -c#  [optional] Specify which processor core to act on (0 is default). Specify
                        -call to act on all cores.

        --------------------------------------------------------------------------------

        Examples:       > getarray pu xgpr0 deadbeef80000000 -p0,1 -c1
```

Examples:

3.5.3 getbits

Syntax:

```
Syntax: getbits <ChipSelect> <RingName> <StartPos> <NumBits>  [-exp <data>]
                        [-k#] [-n#] [-s#] [-p#] [-c#] [-o<format>] [-i<format>]

        ECMD:           Core Common Function

        Function:       Long scans bits out of a chip's selected ring. (non-destructive)

        Parameters:
        --------------------------------------------------------------------------------
        ChipSelect      Specifies the chip to operate on.

        RingName        Specifies chip ring to operate on.  For a list of available
```

```
                        rings, use the ecmdquery command.

                        Ex:  ecmdquery rings memctrl
                             ecmdquery rings pu

        StartPos        Specifies starting bit position in Decimal.

        NumBits         Specifies number of bits to get from starting position (Decimal)
                        Specify the keyword 'end' to fetch from startPos to end of ring.

        -exp [optional] Provide expected data.  Returns error if expected != actual.  No
                        error/no data returned if expected == actual.
                        Format specified by -i<format>

        -o<format>[opt] Specifies the format type of the output : default 'b'
                        Run 'ecmdquery formats' to view available formats

        -i<format>[opt] Specifies the format type of expect data : default 'b'
                        Run 'ecmdquery formats' to view available formats

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                        to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                        to act on all nodes.

        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                        to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                        -pall to act on all chips.

        -c#  [optional] Specify which processor core to act on (0 is default). Specify
                        -call to act on all cores.

        -------------------------------------------------------------------------------

        Examples:       getbits pu stat 0 15
                        getbits pu cp_fxu 0 32 -oxw -exp feedbeef
                        getbits memctrl idreg 16 all
```

Examples:

```
> getbits test idreg 0 32
test    k0:n0:s0:p00        idreg(0:31)
0b11111110111011011011111011101111
ecmd.exe getbits test idreg 0 32

> getbits test idreg 0 16 -ox
test    k0:n0:s0:p00        idreg(0:15)
0xFEED
ecmd.exe getbits test idreg 0 16 -ox
```

3.5.4 getcfam

Syntax:

```
Syntax: getcfam <ChipSelect> <CFAMAddr> [-k#] [-n#] [-s#] [-p#]
                              [-o<format>] [-i<format>] [-exp <data> [-mask <data>]]

        ECMD:          Core Common Function

        Function:      Gets CFAM Registers through FSI

        Parameters:
        -------------------------------------------------------------------------------
        ChipSelect     Chip to get CFAM data from.

        CFAMAddr       Address in hex.

        -exp [optional] Provide expected data.  Returns error if expected != actual.  No
                        error/no data returned if expected == actual.

        -mask    [opt] Register data is AND'ed with the mask bits.
                        Only for use with -exp.

        -o<format>[opt] Specifies the format type of the output : default 'xl'
                        Run 'ecmdquery formats' to view available formats

        -i<format>[opt] Specifies the format type of expect and mask data : default 'xl'
                        Run 'ecmdquery formats' to view available formats

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                        to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                        to act on all nodes.

        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                        to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                        -pall to act on all chips.

        -------------------------------------------------------------------------------

        Examples:      > getcfam pu 6 -p0,1
                       > getcfam memctrl 800009 -exp feed0000 -mask ffff0000
```

Examples:

3.5.5 getlatch

Syntax:

```
Sytnax: getlatch <ChipSelect> <RingName> <LatchName> [<Start> <Numbits>] [-exact]
                        [-exp <value>] [-o<format>]
                        [-k#] [-n#] [-s#] [-p#] [-c#]

        ECMD:          Core Common Function

        Function:      Gets values for specified latch names in a ring.  The
                       latch names in the scandef file are searched for the
                       substring LatchName for a match.  Each register containing the
```

```
                        pattern-matched substring will be printed to the screen.

                        With the -exact option, eCMD searches for an exact match, and
                        will return only the first latch that exactly matches (excluding
                        any parentheses).

                        The -nocompress flag turns off concatenation of all latches of
                        a register in the scandef and displays on seperate lines as
                        they appear in the scandef.

         Parameters:
         -------------------------------------------------------------------------------
         ChipSelect      Chip to get data from.

         RingName        Specifies chip ring to operate on.  For a list of available
                         rings, use the ecmdquery command.

                         Ex:  ecmdquery rings memctrl
                              ecmdquery rings pu

         LatchName       Desired latch to find in the ring. (case insensitive)

         Start     [opt] Starting bit position within the latch. Specify with Numbits.
                         NOTE : Not allowed when using -nocompress

         Numbits   [opt] Number of bits to get. Specify along with Start. If out of range,
                         and -exact not selected, prints a warning message instead of the
                         data. If -exact is selected, immediately return an error.
                         NOTE : Not allowed when using -nocompress

         -exact    [opt] No pattern matching. Instead, search for exact latch name.

         -exp [optional] Provide an expected-value as the last argument. Returns error if
                         data miscompare, else nothing.
                         Format specified by -i<format>

         -o<format>[opt] Specifies the format type of both the output and
                         the expect-value
                         Defaults to 'b' for < 8 bits and 'xl' for >= 8 bits.
                         Run 'ecmdquery formats' to view available formats

         -i<format>[opt] Specifies the format type of expect data
                         Run 'ecmdquery formats' to view available formats

         -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                         to act on all cages.

         -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                         to act on all nodes.

         -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                         to act on all slots.

         -p#  [optional] Specify which chip position to act on (0 is default). Specify
                         -pall to act on all chips.

         -c#  [optional] Specify which processor core to act on (0 is default). Specify
                         -call to act on all cores.

         -------------------------------------------------------------------------------

         Examples:       getlatch pu cp_abist LATCH0
                         getlatch pu cp_fpu GCP.PFPU.FP_UNIT0.FP_REG -ox -exact
```

eCMD Command Line Interface

```
-nocompress -expect feed -ix
```

Examples:

```
> getlatch test sgxbs ACCESS
test    k0:n0:s0:p00
ACCESS.SNPBUF 0b0
ecmd.exe getlatch test sgxbs ACCESS
```

3.5.6 getringdump

Syntax:

```
Syntax: getringdump <ChipSelect> <RingName1> [<RingName2> ...]
                                    [-k#] [-n#] [-s#] [-p#] [-c#]

        ECMD:           Core Common Function

        Function:       Gets values for all latchs in the entire scan ring.

        Parameters:
        ------------------------------------------------------------------------
        ChipSelect      Chip to get data from.

        RingName        Specifies one or multiple chip rings to operate on.  For a list
                        of available rings, use the ecmdquery command.

                        Ex:   ecmdquery rings memctrl
                              ecmdquery rings pu

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                        to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                        to act on all nodes.

        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                        to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                        -pall to act on all chips.

        -c#  [optional] Specify which processor core to act on (0 is default). Specify
                        -call to act on all cores.

        ------------------------------------------------------------------------

        Notes:          Output is binary for latches <= 8 bits in length and xl for > 8.

        Examples:       getringdump memctrl int
                        getringdump pu gps_fuse
                        getringdump pu gps_fuse gps_abist cp_ras
```

Examples:

eCMD Command Line Interface

```
> getringdump test sgxbs
test   k0:n0:s0:p00
************************************************
* ECMD Dump scan ring contents, Tue Nov 25 12:58:44 2003
* Position 0:0, test sgxbs Ring
* Chip EC 9999
* Ring length: 573 bits
USE_GBX.CHANNELINL2(0:150) 0xAAAA0000000000000000000000000000000000
USE_ENT_IOS.ERR_SET_GX_BOUNDARY.RECEIVER_LATCH.L2 0b0
USE_ENT_IOS.ERR_SET_GX_BOUNDARY.DRIVER_LATCH.L2 0b0
USE_ENT_IOS.ERR_SET_GX_BOUNDARY.ENABLE_LATCH.L2 0b0
USE_ENT_IOS.SYSTEM_ERR_BOUNDARY.RECEIVER_LATCH.L2 0b0
USE_ENT_IOS.SYSTEM_ERR_BOUNDARY.DRIVER_LATCH.L2 0b0
USE_ENT_IOS.SYSTEM_ERR_BOUNDARY.ENABLE_LATCH.L2 0b0
....
USE_ENT_IOS.DBUGX_OUT_123_BOUNDARY.MXM.BDYRML.L2Q 0b0
USE_ENT_IOS.DBUGX_OUT_123_BOUNDARY.MXM.BDYDML.L2Q 0b0
USE_ENT_IOS.DBUGX_OUT_123_BOUNDARY.MXM.BDYEML.L2Q 0b0
USE_GBX.CHANNELINL2(151:247) 0x00000000000000000000000000
ACCESS.SNPBUF 0b0
ecmd.exe getringdump test sgxbs
```

3.5.7 getscom

Syntax:

```
Syntax: getscom <ChipSelect> <ScanCommAddr> [-v] [-k#] [-n#] [-s#] [-p#] [-c#]
                             [-o<format>] [-i<format>] [-exp <data> [-mask <data>]]

        ECMD:           Core Common Function

        Function:       Gets Scan Communications registers.

        Parameters:
        ----------------------------------------------------------------------------
        ChipSelect      Chip to get scancomm data from.

        ScanCommAddr    Address in hex.

        -exp [optional] Provide expected data.  Returns error if expected != actual.  No
                        error/no data returned if expected == actual.

        -mask    [opt] Scom data is AND'ed with the mask bits. Only for use with -exp.

        -o<format>[opt] Specifies the format type of the output : default 'xl'
                        Run 'ecmdquery formats' to view available formats

        -i<format>[opt] Specifies the format type of expect and mask data : default 'xl'
                        Run 'ecmdquery formats' to view available formats

        -v   [optional] Print out Scan Comm bit meaning if available

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                        to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                        to act on all nodes.

        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
```

```
                      to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                        -pall to act on all chips.

        -c#  [optional] Specify which processor core to act on (0 is default). Specify
                        -call to act on all cores.

        ------------------------------------------------------------------------------

        Examples:        > getscom pu 6 -p0,1
                         > getscom memctrl 800009 -exp feed000000000001 -mask
ffff00000000ffff
```

Examples:

```
> getscom test 800000
test    k0:n0:s0:p00         FEEDBEEFAAAAAAAA
ecmd.exe getscom test 800000

> getscom test 800000 -obn8
test    k0:n0:s0:p00
    0               1               2               3
    0123 4567 8901 2345 6789 0123 4567 8901
00: 1111 1110 1110 1101 1011 1110 1110 1111
08: 1010 1010 1010 1010 1010 1010 1010 1010
16: 0000 0000 0000 0000 0000 0000 0000 0000
ecmd.exe getscom test 800000 -obn8
```

3.5.8 getspy

Syntax:

```
Syntax: getspy <ChipSelect> <SpyName> [<Start> <Numbits>] [-exp <value>]
                         [-o<format>] [-i<format>] [-k#] [-n#] [-s#] [-p#] [-c#]

        ECMD:            Core Common Function

        Function:        Display specified spy, works for edials, idials and aliases.
                         If a spy ecc error is detected all the ecc groupings will be
                         displayed along with a mask showing which bits are in error.

        Parameters:
        ------------------------------------------------------------------------------
        ChipSelect       Chip to get data from.

        SpyName          Desired spy name. (case insensitive)

        Start      [opt] Starting bit position within the spy. Specify with Numbits.
                         Only valid with non-enumerated spy's

        Numbits    [opt] Number of bits to get. Specify along with Start.
                         Only valid with non-enumerated spy's

        -exp [optional] Provides an expected value as the last argument. Returns error
                         only if miscompare.
                         Format specified by -i<format>
```

```
            -o<format>[opt] Specifies the format type of the output
                            Default format for non-enumerated spys : 'xl'
                            Default format for enumerated spys : 'enum'
                            Run 'ecmdquery formats' to view available formats

            -i<format>[opt] Specifies the format type of expect data
                            Default format for non-enumerated spys : 'xl'
                            Default format for enumerated spys : 'enum'
                            Run 'ecmdquery formats' to view available formats

            -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                            to act on all cages.

            -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                            to act on all nodes.

            -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                            to act on all slots.

            -p#  [optional] Specify which chip position to act on (0 is default). Specify
                            -pall to act on all chips.

            -c#  [optional] Specify which processor core to act on (0 is default). Specify
                            -call to act on all cores.

            --------------------------------------------------------------------------------


            Examples:       getspy pu MYALIAS
                            getspy pu REVERSE 16 64 -ox -exp aaaa5555
```

Examples:

3.5.9 pollscom

Syntax:

```
Syntax: pollscom <ChipSelect> <ScanCommAddr> [-exp <data> [-mask <data>]] [-o<format>]
                            [-i<format>] [-limit #[s|c]] [-interval #[s|c]] [-verbose]
                            [-k#] [-n#] [-s#] [-p#] [-c#]

        ECMD:           Core Common Function

        Function:       Repeatedly gets Scan Communications registers until expected data
                        matches actual data or until polling limit is reached.

        Parameters:
        ---------------------------------------------------------------------------
        ChipSelect      Chip to get scancom data from.

        ScanCommAddr    Address in hex.

        -exp    [opt] Provide expected data.  Returns error if expected != actual.  No
                      error/no data returned if expected == actual.

        -mask   [opt] Scom data is AND'ed with the mask bits before checking against
                      expected value.
```

```
        -o<format>[opt] Specifies the format type of the output : default 'xl'
                        Run 'ecmdquery formats' to view available formats

        -i<format>[opt] Specifies the format type of expect and mask data : default 'xl'
                        Run 'ecmdquery formats' to view available formats

        -limit #  [opt] Max polling number in iterations, seconds, or cycles. To specify
                        in seconds, append an 's' to #.  To specify number of cycles for
                        simulation, append a 'c' to #.  If limit is not specified,
                        defaults to 1000 iterations.  If limit = 0, polls indefinitely.
                        If limit = 0 and -interval is not specified, the interval defaults
                        to 5 seconds.

        -interval # [opt] Time between getscoms. To specify in seconds, append an 's'
                        to #.  To specify number of cycles for simulation, append a
                        'c' to # (number of cycles must be > 1000).  If -limit is not
                        specified with -interval, the limit defaults to ~240 seconds
                        or 1 million cycles, depending on how -interval is specified.
                        If neither -limit or -interval are specified, limit defaults to
                        60 seconds and interval defaults to 5 seconds.

        -verbose  [opt] Prints warning message after each getscom if actual != expected.

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                        to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                        to act on all nodes.

        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                        to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                        -pall to act on all chips.

        -c#  [optional] Specify which processor core to act on (0 is default). Specify
                        -call to act on all cores.
        ----------------------------------------------------------------------------

        Examples:       pollscom pu 800009 -exp feed000000000001 -limit 30s -interval 10s
-verbose -p1
                        pollscom pu 800009 -exp feed000000000001 -mask ffff00000000ffff
-limit 10
                        pollscom memctrl 400020 -limit 100000c -interval 5000c
```

Examples:

```
> pollscom test 800000 -exp FEED0000 -limit 5
test    k0:n0:s0:p00:c0:t0 Polling address 800000...
ERROR: (ECMD): Data miscompare occured at address: 00800000
test    k0:n0:s0:p00:c0:t0 Polling address 800000...
Actual          : FEEDBEEF AAAAAAAA 00000000
Expected        : FEED0000
ecmd.exe pollscom test 800000 -exp FEED0000 -limit 5
```

3.5.10 putarray

Syntax:

```
Syntax: putarray <ChipSelect> <ArrayName> <ArrayIndex> <ArrayData> [-i<format>]
                        [-k#] [-n#] [-s#] [-p#] [-c#]

        ECMD:           Core Common Function

        Function:       Write the specified data to the specified chip array.

        Parameters:
        -----------------------------------------------------------------------------
        ChipSelect      Chip to put array data to.

        ArrayName       Name of array to write to.

        ArrayIndex      Array Index in right aligned hex.

        ArrayData       Data to write to array: default "x"
                        Format specified by -i<format>

        -i<format>[opt] Specifies the format type of input data : default 'xl'
                        Run 'ecmdquery formats' to view available formats

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                        to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                        to act on all nodes.

        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                        to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                        -pall to act on all chips.

        -c#  [optional] Specify which processor core to act on (0 is default). Specify
                        -call to act on all cores.

        -----------------------------------------------------------------------------

        Examples:       > putarray pu xgpr0 deadbeef80000000 -p0,1 -c1
```

Examples:

3.5.11 putbits

Syntax:

```
Syntax: putbits <ChipSelect> <RingName> <StartPos> <Data> [-i<format>] [-b<modifier>]
                        [-k#] [-n#] [-s#] [-p#] [-c#]

        ECMD:           Core Common Function

        Function:       Put bits to the specified chip ring.
```

eCMD Command Line Interface

```
        Paramaters:
        --------------------------------------------------------------------------------
        ChipSelect       Specifies the chip to operate on.

        RingName         Specifies chip ring to operate on.  For a list of available
                         rings, use the ecmdquery command.

                         Ex:  ecmdquery rings memctrl
                              ecmdquery rings pu

        StartPos         Specifies starting bit position in Decimal.

        Data             Bits to insert into chip ring.
                         Format specified by -i<format>

        -i<format>[opt] Specifies the format type of input data : default 'b'
                         Run 'ecmdquery formats' to view available formats

        -b<mod>[opt]    Bit modifier to apply to current ring data.
                         Run 'ecmdquery formats' to view available modifiers

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                         to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                         to act on all nodes.

        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                         to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                         -pall to act on all chips.

        -c#  [optional] Specify which processor core to act on (0 is default). Specify
                         -call to act on all cores.

        --------------------------------------------------------------------------------

        Example:        putbits pu int 567 ABAB -ix -p0,1 -c1
                        putbits pu int 23 011X001X -p0 -iX
```

Examples:

3.5.12 putcfam

Syntax:

```
Syntax: putcfam <ChipSelect> <CFAMAddr> [<Start> <Numbits>] <Data> [-i<format>]
                           [-b<modifier>] [-k#] [-n#] [-s#] [-p#]

        ECMD:           Core Common Function

        Function:       Write the specified data to the specified chip CFAM register

        Parameters:
        --------------------------------------------------------------------------------
        ChipSelect      Chip to put CFAM data to.
```

```
CFAMAddr         Address in right aligned hex.

Start     [opt] Starting bit position within the register.  Specify with numbits.

Numbits   [opt] Number of bits to insert. Specify with Start. If Start and Numbits
                are not specified, start = 0 and numbits is calculated from
                length of data string, rest of cfam register is padded with zeros.

Data             Data to insert into Register.
                 Format specified by -i<format>

-i<format>[opt] Specifies the format type of input data : default 'xl'
                Run 'ecmdquery formats' to view available formats

-b<mod>[opt]    Bit modifier to apply to current ring data.
                Run 'ecmdquery formats' to view available modifiers

-k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                to act on all cages.

-n#  [optional] Specify which node to act on (0 is default). Specify -nall
                to act on all nodes.

-s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                to act on all slots.

-p#  [optional] Specify which chip position to act on (0 is default). Specify
                -pall to act on all chips.

                --------------------------------------------------------------------------------

Examples:        > putcfam pu 600000 deadbeef  -p0,1
                 > putcfam memctrl 2010 001001010110 -ib
                 > putcfam l3 40320 00008000 -bor -p12
```

3.5.13 putlatch

Syntax:

```
Syntax: putlatch <ChipSelect> <RingName> <LatchName> [<Start> <Numbits>] <Data>
                        [-i<format>] [-k#] [-n#] [-s#] [-p#] [-c#]

        ECMD:           Core Common Function

        Function:       Puts a value for a specified register into a ring.  The first
                        register in the scandef file that exactly matches the RegName
                        (not including parenthesis) will be used. If the register is
                        broken into multiple lines, the register lengths are
                        concatenated to form one complete register.

        Parmeters:
        --------------------------------------------------------------------------------
        ChipSelect      Chip to put data to.

        RingName        Specifies chip ring to operate on.  For a list of available
                        rings, use the ecmdquery command.

                        Ex:  ecmdquery rings memctrl
                             ecmdquery rings pu
```

```
        LatchName       Desired latchs to put in the ring.

        Start     [opt] Offset at which to begin writing data.  Also specify Numbits.

        Numbits   [opt] Number of bits to insert.  If not specified, start = 0 and
                        numbits is calculated from the length of the Data string.

        Data            Data to be written to the register specified.
                        Format specified by -i<format>

        -i<format>[opt] Specifies the format type of input data : default 'xl'
                        Run 'ecmdquery formats' to view available formats

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                        to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                        to act on all nodes.

        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                        to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                        -pall to act on all chips.

        -c#  [optional] Specify which processor core to act on (0 is default). Specify
                        -call to act on all cores.

        --------------------------------------------------------------------------------

        Example:        putlatch pu cp_fpu GCP.PFPU.FP_UNIT0.FPA_LATCH -ix feed
```

Examples:

3.5.14 putpattern

Syntax:

```
Syntax: putpattern <ChipSelect> <RingType> <Data> [-i<format>]
                                    [-k#] [-n#] [-s#] [-p#] [-c#]

        ECMD:           Core Common Function

        Function:       Puts a repeated pattern to the entire specified chip ring.

        Parameters:
        ----------------------------------------------------------------------------
        ChipSelect      Specifies the chip to operate on.

        RingName        Specifies chip ring to operate on.  For a list of available
                        rings, use the ecmdquery command.

                        Ex:  ecmdquery rings memctrl
                             ecmdquery rings pu

        Data            32bit pattern to write.
                        Format specified by -i<format>
```

```
              -i<format>[opt] Specifies the format type of input data : default 'xr'
                             Run 'ecmdquery formats' to view available formats

              -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                             to act on all cages.

              -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                             to act on all nodes.

              -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                             to act on all slots.

              -p#  [optional] Specify which chip position to act on (0 is default). Specify
                             -pall to act on all chips.

              -c#  [optional] Specify which processor core to act on (0 is default). Specify
                             -call to act on all cores.

              --------------------------------------------------------------------------------

              Example:        putpattern pu int FEEDBEEF -p0,1
```

Examples:

3.5.15 putscom

Syntax:

```
Syntax: putscom <ChipSelect> <ScanCommAddr> [<Start> <Numbits>] <Data> [-i<format>]
                            [-b<modifier>] [-k#] [-n#] [-s#] [-p#] [-c#]

         ECMD:           Core Common Function

         Function:       Write the specified data to the specified chip using scancom.

         Parameters:
         ------------------------------------------------------------------------------
         ChipSelect      Chip to put scancom data to.

         ScanCommAddr    Address in right aligned hex.

         Start    [opt] Starting bit position within the scom.  Specify with numbits.

         Numbits  [opt] Number of bits to insert. Specify with Start. If Start and Numbits
                        are not specified, start = 0 and numbits is calculated from
                        length of data string, rest of Scom register is padded with zeros.

         Data            Data to insert into Scom Register.
                         Format specified by -i<format>

         -i<format>[opt] Specifies the format type of input data : default 'xl'
                         Run 'ecmdquery formats' to view available formats

         -b<mod>[opt]    Bit modifier to apply to current ring data.
                         Run 'ecmdquery formats' to view available modifiers

         -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
```

```
                    to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                    to act on all nodes.

        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                    to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                    -pall to act on all chips.

        -c#  [optional] Specify which processor core to act on (0 is default). Specify
                    -call to act on all cores.

        ------------------------------------------------------------------------------

        Examples:        > putscom pu 600000 deadbeef80000000  -p0,1 -c1
                         > putscom memctrl 2010 001001010110 -ib
                         > putscom l3 40320 0000800000 -bor -p12
```

Examples:

3.5.16 putspy

Syntax:

```
Syntax: putspy <ChipSelect> <SpyName> [<Start> <Numbits>] <Data>  [-i<format>]
                            [-b<modifier>] [-k#] [-n#] [-s#] [-p#] [-c#]

        ECMD:           Core Common Function

        Function:       Write data to a spy.  Works with idial, edial and alias spy's.

        Parameters:
        ------------------------------------------------------------------------------
        ChipSelect      Chip to write data to.

        SpyName         Desired spy name, (case insensitive)

        Start    [opt] Starting bit position within the spy.  Specify with numbits.
                       Only valid with non-enumerated spy's

        Numbits  [opt] Number of bits to insert. Specify with Start. If Start and Numbits
                       are not specified, start = 0 and numbits is calculated from
                       length of data string.
                       Only valid with non-enumerated spy's

        Data            Data to put into spy, either raw data or enum name.
                        Format specified by -i<format>

        -i<format>[opt] Specifies the format type of input data
                        Default format for non-enumerated spys : 'xl'
                        Default format for enumerated spys : 'enum'
                        Run 'ecmdquery formats' to view available formats

        -b<mod>[opt]    Bit modifier to apply to current ring data.
                        Run 'ecmdquery formats' to view available modifiers
```

```
       -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                       to act on all cages.

       -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                       to act on all nodes.

       -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                       to act on all slots.

       -p#  [optional] Specify which chip position to act on (0 is default). Specify
                       -pall to act on all chips.

       -c#  [optional] Specify which processor core to act on (0 is default). Specify
                       -call to act on all cores.

       -------------------------------------------------------------------------------

       Examples:        putspy pu MYALIAS -ixr feedbeeffeeedbeef
                        putspy pu EVERYOTHER 16 4 -ib 1010
                        putspy pu MYEDIAL ENUMVALUE -ienum
```

Examples:

3.5.17 sendcmd

Syntax:

```
Syntax: sendcmd <ChipSelect> <ScanInstrCode> <ScanInstrMod> [-v] [-k#] [-n#] [-s#] [-p#]

       ECMD:            Core Common Function

       Function:        Send a JTAG Instruction to the chip and display
                        instruction status from previous command

       Parameters:
       -------------------------------------------------------------------------------
       ChipSelect       Chip to send ScanInstrCode to.

       ScanInstrCode    Scan instruction code to be sent (in hex).

       ScanInstrMod     Scan instruction modifier (for ACCESS/CFAM).

       -v   [optional] Verbose mode.  Displays the instruction
                       status in an easy-to-read format.

       -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                       to act on all cages.

       -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                       to act on all slots.

       -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                       to act on all nodes.

       -p#  [optional] Specify which chip position to act on (0 is default). Specify
                       -pall to act on all chips.
```

eCMD Command Line Interface

```
            ---------------------------------------------------------------------------

        Notes:          Leading zeros ARE NECESSARY if the command is not a full
                        16 bits (e.g. ACCESS)
                        Only valid with JTAG attached chips

        Example:        sendcmd pu 12 C00008 -p0,1
```

Examples:

3.6 Processor Functions

3.6.1 getfpr

Syntax:

```
Syntax: getfpr <FprStartNum> [<numEntries>] [-k#] [-n#] [-s#] [-p#] [-c#] [-t#]
                                 [-o<format>]

        ECMD:           Core Common Function

        Function:       Gets Processor Architected FPR (Floating Point Register).

        Parameters:
        -------------------------------------------------------------------------------

        FprNum          Fpr Entry to read (Decimal)

        numEntries      Specifies number of entries to get from starting entry (Decimal)

        -o<format>[opt] Specifies the format type of the output : default 'xl'
                        Run 'ecmdquery formats' to view available formats

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                        to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                        to act on all nodes.

        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                        to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                        -pall to act on all chips.

        -c#  [optional] Specify which processor core to act on (0 is default). Specify
                        -call to act on all cores.

        -t#  [optional] Specify which processor thread to act on (0 is default). Specify
                        -tall to act on all threads, -talive to act on all alive threads.

        -------------------------------------------------------------------------------

        Examples:       > getfpr 6 -p0,1
                        > getfpr 0 32 -p10, -t1 -c1
```

3.6.2 getgpr

Syntax:

```
Syntax: getgpr <GprStartNum> [<numEntries>] [-k#] [-n#] [-s#] [-p#] [-c#] [-t#]
                                 [-o<format>]

        ECMD:           Core Common Function
```

```
Function:       Gets Processor GPR (General Purpose Register).

Parameters:
--------------------------------------------------------------------------------

GprNum          Gpr Entry to read (Decimal)

numEntries      Specifies number of entries to get from starting entry (Decimal)

-o<format>[opt] Specifies the format type of the output : default 'xl'
                Run 'ecmdquery formats' to view available formats

-k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                to act on all cages.

-n#  [optional] Specify which node to act on (0 is default). Specify -nall
                to act on all nodes.

-s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                to act on all slots.

-p#  [optional] Specify which chip position to act on (0 is default). Specify
                -pall to act on all chips.

-c#  [optional] Specify which processor core to act on (0 is default). Specify
                -call to act on all cores.

-t#  [optional] Specify which processor thread to act on (0 is default). Specify
                -tall to act on all threads, -talive to act on all alive threads.

--------------------------------------------------------------------------------

Examples:       > getgpr 6 -p0,1
                > getgpr 0 32 -p10, -t1 -c1
```

3.6.3 getspr

Syntax:

```
Syntax: getspr <SprName> [<SprName> ...] [-k#] [-n#] [-s#] [-p#] [-c#] [-t#]
                         [-o<format>]

        ECMD:           Core Common Function

        Function:       Gets Processor SPR (Special Purpose Register).

        Parameters:
        --------------------------------------------------------------------------------

        SprName         Name of SPR to fetch, multiple SPR's can be listed

        -o<format>[opt] Specifies the format type of the output : default 'xl'
                        Run 'ecmdquery formats' to view available formats

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                        to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                        to act on all nodes.
```

```
        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                        to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                        -pall to act on all chips.

        -c#  [optional] Specify which processor core to act on (0 is default). Specify
                        -call to act on all cores.

        -t#  [optional] Specify which processor thread to act on (0 is default). Specify
                        -tall to act on all threads, -talive to act on all alive threads.

        --------------------------------------------------------------------------------

        Examples:       > getspr pu nia msr -p0,1
```

3.6.4 putfpr

Syntax:

```
Syntax: putfpr <FprNum> <Data> [-i<format>] [-k#] [-n#] [-s#] [-p#] [-c#] [-t#]

        ECMD:           Core Common Function

        Function:       Write the specified data to a Processor FPR
                        (Floating Point Register)

        Parameters:
        --------------------------------------------------------------------------------

        FprNum          Fpr Entry to write (Decimal)

        Data            Data to insert into FPR.
                        Format specified by -i<format>

        -i<format>[opt] Specifies the format type of input data : default 'xl'
                        Run 'ecmdquery formats' to view available formats

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                        to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                        to act on all nodes.

        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                        to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                        -pall to act on all chips.

        -c#  [optional] Specify which processor core to act on (0 is default). Specify
                        -call to act on all cores.

        -t#  [optional] Specify which processor thread to act on (0 is default). Specify
                        -tall to act on all threads, -talive to act on all alive threads.

        --------------------------------------------------------------------------------

        Examples:       > putfpr 10 deadbeef80000000  -p0,1 -c1
```

3.6.5 putgpr

Syntax:

```
Syntax: putgpr <GprNum> <Data> [-i<format>] [-k#] [-n#] [-s#] [-p#] [-c#] [-t#]

        ECMD:           Core Common Function

        Function:       Write the specified data to a Processor GPR
                        (General Purpose Register)

        Parameters:
        ----------------------------------------------------------------------------

        GprNum          Gpr Entry to write (Decimal)

        Data            Data to insert into GPR.
                        Format specified by -i<format>

        -i<format>[opt] Specifies the format type of input data : default 'xl'
                        Run 'ecmdquery formats' to view available formats

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                        to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                        to act on all nodes.

        -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                        to act on all slots.

        -p#  [optional] Specify which chip position to act on (0 is default). Specify
                        -pall to act on all chips.

        -c#  [optional] Specify which processor core to act on (0 is default). Specify
                        -call to act on all cores.

        -t#  [optional] Specify which processor thread to act on (0 is default). Specify
                        -tall to act on all threads, -talive to act on all alive threads.

        ----------------------------------------------------------------------------

        Examples:       > putgpr 10 deadbeef80000000  -p0,1 -c1
```

3.6.6 putspr

Syntax:

```
Syntax: putspr <SprName> [<Start> <Numbits>] <Data> [-i<format>]
                         [-b<modifier>] [-k#] [-n#] [-s#] [-p#] [-c#] [-t#]
```

eCMD Command Line Interface

```
ECMD:           Core Common Function

Function:       Write the specified data to a Processor SPR
                (Special Purpose Register).

Parameters:
--------------------------------------------------------------------------------
SprName         Name of SPR to write

Start     [opt] Starting bit position.  Specify with numbits.

Numbits   [opt] Number of bits to insert. Specify with Start. If Start and Numbits
                are not specified, start = 0 and numbits is calculated from
                length of data string, rest of register is padded with zeros.

Data            Data to insert into Register.
                Format specified by -i<format>

-i<format>[opt] Specifies the format type of input data : default 'xl'
                Run 'ecmdquery formats' to view available formats

-b<mod>[opt]    Bit modifier to apply to current ring data.
                Run 'ecmdquery formats' to view available modifiers

-k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                to act on all cages.

-n#  [optional] Specify which node to act on (0 is default). Specify -nall
                to act on all nodes.

-s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                to act on all slots.

-p#  [optional] Specify which chip position to act on (0 is default). Specify
                -pall to act on all chips.

-c#  [optional] Specify which processor core to act on (0 is default). Specify
                -call to act on all cores.

-t#  [optional] Specify which processor thread to act on (0 is default). Specify
                -tall to act on all threads, -talive to act on all alive threads.

--------------------------------------------------------------------------------

Examples:       > putspr nia deadbeef80000000  -p0,1 -c1 -t1
```

3.7 Memory Display/Alter Functions

3.7.1 **getmemdma**

Syntax:

```
Syntax: getmemdma <MemAddress> <NumBytes> [-k#] [-n#] [-o<format>]

       ECMD:          Core Common Function

       Function:      Display the contents of mainstore using either DMA's or PSI

       Parameters:
       -------------------------------------------------------------------------------
       MemAddress     64 Bit address to read from (Hex-Right)

       NumBytes       Number of bytes to fetch (Decimal).

       -o<format>[opt] Specifies the format type of the output : default 'mem'
                       Run 'ecmdquery formats' to view available formats

       -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                       to act on all cages.

       -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                       to act on all nodes.

       -------------------------------------------------------------------------------

       Examples:      > getmemdma 1000 128 -p0
```

3.7.2 **getmemmemctrl**

Syntax:

```
Syntax: getmemmemctrl <MemAddress> <NumBytes> [-k#] [-n#] [-s#] [-p#] [-o<format>]

       ECMD:          Core Common Function

       Function:      Display the contents of mainstore using the Memory Controller.
                      NOTE : This operation typically is not cache coherent.

       Parameters:
       -------------------------------------------------------------------------------
       MemAddress     64 Bit address to read from (Hex-Right)

       NumBytes       Number of bytes to fetch (Decimal).

       -o<format>[opt] Specifies the format type of the output : default 'mem'
                       Run 'ecmdquery formats' to view available formats

       -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                       to act on all cages.
```

```
-n#  [optional] Specify which node to act on (0 is default). Specify -nall
                to act on all nodes.

-s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                to act on all slots.

-p#  [optional] Specify which chip position to act on (0 is default). Specify
                -pall to act on all chips.

     --------------------------------------------------------------------------------

Examples:       > getmemmemctrl 1000 128 -p0
```

3.7.3 getmemproc

Syntax:

```
Syntax: putmemproc <MemAddress> <Data> | -f[d|b]<filename>  [-i<format>]
                                                    [-k#] [-n#] [-s#] [-p#]

     ECMD:           Core Common Function

     Function:       Write the specified data to mainstore using the Processor

     Parameters:
     --------------------------------------------------------------------------------
     MemAddress      64 Bit address to write to (Hex-Right)

     -fd <filename>  Specify full path and filename to file in D-Card format to load

     -fb <filename>  Specify full path and filename to binary file to load

     Data            Data to write into mainstore. Not valid with -f option
                     Format specified by -i<format>

     -i<format>[opt] Specifies the format type of input data : default 'xl'
                     Not valid with -f option
                     Run 'ecmdquery formats' to view available formats

     -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                     to act on all cages.

     -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                     to act on all nodes.

     -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                     to act on all slots.

     -p#  [optional] Specify which chip position to act on (0 is default). Specify
                     -pall to act on all chips.

     --------------------------------------------------------------------------------

Examples:       > putmemproc 10000 deadbeef80000000  -p0,1
```

3.7.4 **putmemdma**

Syntax:

```
Syntax: putmemdma <MemAddress> <Data> | -f[d|b]<filename>  [-i<format>] [-k#] [-n#]

        ECMD:           Core Common Function

        Function:       Write the specified data to mainstore using either DMA's or PSI

        Parameters:
        --------------------------------------------------------------------------------
        MemAddress      64 Bit address to write to (Hex-Right)

        -fd <filename>  Specify full path and filename to file in D-Card format to load

        -fb <filename>  Specify full path and filename to binary file to load

        Data            Data to write into mainstore. Not valid with -f option
                        Format specified by -i<format>

        -i<format>[opt] Specifies the format type of input data : default 'xl'
                        Not valid with -f option
                        Run 'ecmdquery formats' to view available formats

        -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                        to act on all cages.

        -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                        to act on all nodes.

        --------------------------------------------------------------------------------

        Examples:       > putmemdma 10000 deadbeef80000000  -p0,1
```

3.7.5 **putmemmemctrl**

Syntax:

```
Syntax: putmemmemctrl <MemAddress> <Data> | -f[d|b]<filename>  [-i<format>]
                                                        [-k#] [-n#] [-s#] [-p#]

        ECMD:           Core Common Function

        Function:       Write the specified data to mainstore using the Memory Controller
                        NOTE : This operation typically is not cache coherent.

        Parameters:
        --------------------------------------------------------------------------------
        MemAddress      64 Bit address to write to (Hex-Right)

        -fd <filename>  Specify full path and filename to file in D-Card format to load

        -fb <filename>  Specify full path and filename to binary file to load

        Data            Data to write into mainstore. Not valid with -f option
```

```
                    Format specified by -i<format>

    -i<format>[opt] Specifies the format type of input data : default 'xl'
                    Not valid with -f option
                    Run 'ecmdquery formats' to view available formats

    -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                    to act on all cages.

    -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                    to act on all nodes.

    -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                    to act on all slots.

    -p#  [optional] Specify which chip position to act on (0 is default). Specify
                    -pall to act on all chips.

    --------------------------------------------------------------------------------

    Examples:       > putmemmemctrl 10000 deadbeef80000000  -p0,1
```

3.7.6 putmemproc

Syntax:

```
Syntax: putmemproc <MemAddress> <Data> | -f[d|b]<filename>  [-i<format>]
                                                    [-k#] [-n#] [-s#] [-p#]

    ECMD:           Core Common Function

    Function:       Write the specified data to mainstore using the Processor

    Parameters:
    --------------------------------------------------------------------------------
    MemAddress      64 Bit address to write to (Hex-Right)

    -fd <filename>  Specify full path and filename to file in D-Card format to load

    -fb <filename>  Specify full path and filename to binary file to load

    Data            Data to write into mainstore. Not valid with -f option
                    Format specified by -i<format>

    -i<format>[opt] Specifies the format type of input data : default 'xl'
                    Not valid with -f option
                    Run 'ecmdquery formats' to view available formats

    -k#  [optional] Specify which cage to act on (0 is default). Specify -kall
                    to act on all cages.

    -n#  [optional] Specify which node to act on (0 is default). Specify -nall
                    to act on all nodes.

    -s#  [optional] Specify which slot to act on (0 is default). Specify -sall
                    to act on all slots.

    -p#  [optional] Specify which chip position to act on (0 is default). Specify
```

eCMD Command Line Interface

```
                    -pall to act on all chips.

     ---------------------------------------------------------------------------

     Examples:        > putmemproc 10000 deadbeef80000000  -p0,1
```

3.8 Miscellaneous Commands

3.8.1 ecmdquery

Syntax:

```
Syntax: ecmdquery <Mode> [Mode Options]

        ECMD:           Core Common Function

        Function:       Query information from eCMD

        Parameters:
        ----------------------------------------------------------------------
        Mode            Query type to perform

        Mode Values
                        rings ChipSelect [-k#] [-n#] [-s#] [-p#]
                            - Display all rings available for chip

                        formats
                            - Display help text for all available input/output formats

                        chips [-ep]
                            - Display all the chips in the system
                            - Use '-ep' to display in an easier to parse format

                        chipinfo ChipSelect [-k#] [-n#] [-s#] [-p#]
                            - Display info about a particular chip (ex. EC level)

                        version
                            - Display version info about the eCMD Instance you are running

        ----------------------------------------------------------------------

        Example:        ecmdquery rings pu -p0,1
                        ecmdquery formats
```

Examples:

eCMD Command Line Interface

```
> ecmdquery version
================================================
Dll Type        : Cronus
Dll Product     : Unknown
Dll Environment : Hardware
Dll Build Date  : Nov 24 2003 14:19:14
Dll Capi Version : .1
================================================
ecmd.exe ecmdquery version

> ecmdquery rings test

Available rings for test     k0:n0:s0:p00        ec 0:
Ring Names                    Address   Length  Mask Chkable BroadSide ClockState
----------------------------- --------  ------  ---- ------- --------- ----------
idreg                         0x000100  32       N    N         N       UNKNOWN
scancom                       0x000040  64       N    N         N       UNKNOWN
scancomprint                  0x000040  64       N    N         N       UNKNOWN
scancomstat                   0x000080  32       N    N         N       UNKNOWN
bypass32                      0x000010  32       N    N         N       UNKNOWN
access_ec                     0x000200  32       N    N         N       UNKNOWN
crcreg                        0x000020  32       N    N         N       UNKNOWN
gp1                           0x001000  32       N    N         N       UNKNOWN
gp2                           0x002000  32       N    N         N       UNKNOWN
gp3                           0x004000  32       N    N         N       UNKNOWN
testring                      0x800003  128      N    Y         N       UNKNOWN
sgxbs                         0x800009  573      N    Y         N       UNKNOWN
ecmd.exe ecmdquery rings test
```

3.9 Simulation Commands

3.9.1 simaet

Syntax:

```
Syntax: simaet on | off | flush

        ECMD:           Core Common Function

        Function:       Start/Stop Simulation AET logging

        Parameters:
        -------------------------------------------------------------------------------
        on              Enable AET

        off             Disable AET

        flush           Flush AET to disk

        -------------------------------------------------------------------------------

        Example:        simaet on
                        simaet off
```

Examples:

3.9.2 simcheckpoint

Syntax:

```
Syntax: simcheckpoint <checkpoint name>

        ECMD:           Core Common Function

        Function:       Store a checkpoint to the specified file

        Parameters:
        -------------------------------------------------------------------------------
        checkpointname  name to store checkpoint under

        -------------------------------------------------------------------------------

        Example:        simcheckpoint boot
```

Examples:

3.9.3 simclock

Syntax:

```
Syntax: simclock <cycles>

        ECMD:           Core Common Function

        Function:       Clock the simulator

        Parameters:
        --------------------------------------------------------------------------------
        cycles          Number of cycles to clock the simulator

        --------------------------------------------------------------------------------

        Example:        simclock 1000
```

Examples:

3.9.4 simecho

Syntax:

```
Syntax: simecho <message>

        ECMD:           Core Common Function

        Function:       Echo a string to stdout as well as sim logs

        Parameters:
        --------------------------------------------------------------------------------
        message         String to echo to sim

        --------------------------------------------------------------------------------

        Example:        simecho "Hello"
```

Examples:

3.9.5 simexit

Syntax:

```
Syntax: simexit [<rc> <message>]

        ECMD:           Core Common Function

        Function:       Close down a simulation

        Parameters:
        --------------------------------------------------------------------------------

        rc        [opt] Testcase failure return code to pass to simulation
```

```
      message   [opt] Testcase failure message to pass to simulation

               --------------------------------------------------------------------------

      Example:        simexit
```

Examples:

3.9.6 simEXPECTFAC

Syntax:

```
Syntax: simEXPECTFAC <facname> <data> <length> [<row> <offset>] [-i<format>]

      ECMD:           Core Common Function

      Function:       Perform expect on simulation facility using name

      Parameters:
               --------------------------------------------------------------------------
      facname         Must be a facility name

      data            Data for expect on facility
                      Format specified by -i<format>

      length          Bit length of data

      row  [optional] Facility row

      offset    [opt] Facility offset

      -i<format>[opt] Specifies the format type of input data : default 'xr'
                      Run 'ecmdquery formats' to view available formats

               --------------------------------------------------------------------------

      Example:        simEXPECTFAC TITAN.TCKFREQ C 4
```

Examples:

3.9.7 simexpecttcfac

Syntax:

```
Syntax: simexpecttcfac <facname> <data>  [<row> | -subset <startbit> <numbits>]
-i<format>

      ECMD:           Core Common Function

      Function:       Perform expect on a TCFAC Facility

      Parameters:
```

```
        --------------------------------------------------------------------------------
        facname         Must be a facility name

        data            Data for expect
                        Format specified by -i<format>

        row  [optional] Facility row - not valid with -subset

        startbit  [opt] Facility offset - not valid with row

        numbits   [opt] Number of bits from startbit to read - not valid with row

        -i<format>[opt] Specifies the format type of input data : default 'xr'
                        Run 'ecmdquery formats' to view available formats

        --------------------------------------------------------------------------------

        Example:        simexpecttcfac TITAN.TCKFREQ F
```

Examples:

3.9.8 simgetcurrentcycle
Syntax:

```
Syntax: simgetcurrentcycle

        ECMD:           Core Common Function

        Function:       Retrieve the current cycle count

        Parameters:
        --------------------------------------------------------------------------------

        --------------------------------------------------------------------------------

        Example:        simgetcurrentcycle
```

Examples:

3.9.9 simGETFAC
Syntax:

```
Syntax: simGETFAC <facname> <length> [<row> <offset>] [-o<format>]

        ECMD:           Core Common Function

        Function:       Read a Simulation Facility using a facility name

        Parameters:
        --------------------------------------------------------------------------------
```

```
        facname         Must be a facility name

        length          Bit length of symbol to read

        row  [optional] Facility row

        offset    [opt] Facility offset

        -o<format>[opt] Specifies the format type of the output : default 'xr'
                        Run 'ecmdquery formats' to view available formats

        -------------------------------------------------------------------------------

        Example:        simGETFAC TITAN.TCKFREQ 4
```

Examples:

3.9.10 simGETFACX

Syntax:

```
Syntax: simGETFACX <facname> <length> [<row> <offset>]

        ECMD:           Core Common Function

        Function:       Read a Simulation Facility using a facility name
                        Displaying Xstate data. format: 'bX'

        Parameters:
        -------------------------------------------------------------------------------
        facname         Must be a facility name

        length          Bit length of symbol to read

        row  [optional] Facility row

        offset    [opt] Facility offset


        -------------------------------------------------------------------------------

        Example:        simGETFACX TITAN.TCKFREQ 4
```

Examples:

3.9.11 simgettcfac

Syntax:

```
Syntax: simgettcfac <facname> [<row> | -subset <startbit> <numbits>] [-o<format>]

        ECMD:           Core Common Function
```

```
Function:       Read a TCFAC Facility

Parameters:
-------------------------------------------------------------------------------
facname         Must be a facility name

row  [optional] Facility row - not valid with -subset

startbit  [opt] Facility offset - not valid with row

numbits   [opt] Number of bits from startbit to read - not valid with row

-o<format>[opt] Specifies the format type of the output : default 'xr'
                Run 'ecmdquery formats' to view available formats

-------------------------------------------------------------------------------

Example:        simgettcfac TITAN.TCKFREQ
```

Examples:

3.9.12 siminit

Syntax:

```
Syntax: siminit [<checkpoint>]

      ECMD:           Core Common Function

      Function:       Initialize the simulation

      Parameters:
      -------------------------------------------------------------------------------
      checkpoint[opt] Name of checkpoint to load

      -------------------------------------------------------------------------------

      Example:        siminit
                      siminit boot
```

Examples:

3.9.13 simPUTFAC

Syntax:

```
Syntax: simPUTFAC <facname> <data> <length> [<row> <offset>] [-i<format>]

      ECMD:           Core Common Function

      Function:       Write a simulation facility using a name
```

```
        Parameters:
        --------------------------------------------------------------------------------
        facname         Must be a facility name

        data            Data to write to facility
                        Format specified by -i<format>

        length          Bit length of symbol to read

        row  [optional] Facility row

        offset    [opt] Facility offset

        -i<format>[opt] Specifies the format type of input data : default 'xr'
                        Run 'ecmdquery formats' to view available formats

        --------------------------------------------------------------------------------

        Example:        simPUTFAC TITAN.TCKFREQ C 4
```

Examples:

3.9.14 simPUTFACX

Syntax:

```
Syntax: simPUTFACX <facname> <data> [<row> <offset>]

        ECMD:           Core Common Function

        Function:       Write a simulation facility using a name.
                        Write with Xstate data: format 'bX'

        Parameters:
        --------------------------------------------------------------------------------
        facname         Must be a facility name

        data            X-State Data to write to facility

        row  [optional] Facility row

        offset    [opt] Facility offset


        --------------------------------------------------------------------------------

        Example:        simPUTFACX TITAN.TCKFREQ 11XX01
```

Examples:

3.9.15 simputtcfac

Syntax:

```
Syntax: simputtcfac <facname> <data> [<row> <# of rows>] -i<format>

       ECMD:          Core Common Function

       Function:      Put a TCFAC Facility

       Parameters:
       --------------------------------------------------------------------------------
       facname        Must be a facility name

       data           Data to put
                      Format specified by -i<format>

       row  [optional] Facility row

       # of rows [opt] Number of rows to put

       -i<format>[opt] Specifies the format type of input data : default 'xr'
                      Run 'ecmdquery formats' to view available formats

       --------------------------------------------------------------------------------

       Example:       simputtcfac TITAN.TCKFREQ F
```

Examples:

3.9.16 simrestart

Syntax:

```
Syntax: simrestart <checkpoint name>

       ECMD:          Core Common Function

       Function:      Load a checkpoint from the specified file

       Parameters:
       --------------------------------------------------------------------------------
       checkpointname  name to load checkpoint from

       --------------------------------------------------------------------------------

       Example:       simrestart boot
```

Examples:

3.9.17 simSTKFAC

Syntax:

```
Syntax: simSTKFAC <facname> <data> <length> [<row> <offset>] [-i<format>]

       ECMD:          Core Common Function

       Function:      Stick a simulation facility using name

       Parameters:
       -------------------------------------------------------------------------------
       facname        Must be a facility name

       data           Data for operation
                      Format specified by -i<format>

       length         Bit length of data

       row  [optional] Facility row

       offset    [opt] Facility offset

       -i<format>[opt] Specifies the format type of input data : default 'xr'
                       Run 'ecmdquery formats' to view available formats

       -------------------------------------------------------------------------------

       Example:       simSTKFAC TITAN.TCKFREQ C 4
```

Examples:

3.9.18 simstktcfac

Syntax:

```
Syntax: simstktcfac <facname> <data> [<row> <# of rows>] -i<format>

       ECMD:            Core Common Function

       Function:        Stick a TCFAC Facility

       Parameters:
       -------------------------------------------------------------------------------
       facname          Must be a facility name

       data             Data to stick
                        Format specified by -i<format>

       row  [optional] Facility row

       # of rows [opt] Number of rows to stick

       -i<format>[opt] Specifies the format type of input data : default 'xr'
                       Run 'ecmdquery formats' to view available formats
```

```
                    --------------------------------------------------------------------------------
        Example:        simstktcfac TITAN.TCKFREQ F
```

Examples:

3.9.19 simSUBCMD

Syntax:

```
Syntax: simSUBCMD <command>

        ECMD:           Core Common Function

        Function:       Run an rtx SUBCMD

        Parameters:
        --------------------------------------------------------------------------------
        command         rtx command to run

        --------------------------------------------------------------------------------

        Example:        simSUBCMD run left
```

Examples:

3.9.20 simtckinterval

Syntax:

```
Syntax: simtckinterval <interval>

        ECMD:              Core Common Function

        Function:          Adjust the TCK Interval

        Parameters:
        --------------------------------------------------------------------------------
        interval        New Interval

        --------------------------------------------------------------------------------

        Example:        simtckinterval 18
```


3.9.21 simUNSTICK

Syntax:

```
Syntax: simUNSTICK <facname> <length> [<row> <offset>]

       ECMD:          Core Common Function

       Function:      Unstick a Simulation Facility using a name

       Parameters:
       --------------------------------------------------------------------------------
       facname        Must be a facility symbol name

       length         Bit length of symbol

       row  [optional] Facility row

       offset   [opt] Facility offset

       --------------------------------------------------------------------------------

       Example:       simUNSTICK TITAN.TCKFREQ 4
```

Examples:

3.9.22 simunsticktcfac

Syntax:

```
Syntax: simunsticktcfac <facname> <data> [<row> <# of rows>] -i<format>

       ECMD:          Core Common Function

       Function:      Unstick a TCFAC Facility

       Parameters:
       --------------------------------------------------------------------------------
       facname        Must be a facility name

       data           Data to write with unstick
                      Format specified by -i<format>

       row  [optional] Facility row

       # of rows [opt] Number of rows to unstick

       -i<format>[opt] Specifies the format type of input data : default 'xr'
                      Run 'ecmdquery formats' to view available formats

       --------------------------------------------------------------------------------

       Example:       simunsticktcfac TITAN.TCKFREQ F
```

Examples: