

BROADCAST

Code:

Activity_main.xml

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:orientation="vertical"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:gravity="center">

    <Button
        android:id="@+id/btnBroadcast"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Send Broadcast"/>

</LinearLayout>
```

AndroidManifest.xml

```
package com.example.broadcastdemo

import android.content.BroadcastReceiver
import android.content.Context
import android.content.Intent
import android.widget.Toast

class MyReceiver : BroadcastReceiver() {

    override fun onReceive(context: Context, intent: Intent) {

        if (intent.action == "com.hello.broadcastdemo.CUSTOM_INTENT") {
            Toast.makeText(context, text = "Custom Intent Received!", duration = Toast.LENGTH_LONG).show()
        }

    }

}
```

MainActivity.kt

```
</> activity_main.xml  AndroidManifest.xml  MainActivity.kt  MyReceiver.kt

1 package com.example.broadcastdemo
2
3 import android.content.Intent
4 import android.content.IntentFilter
5 import android.os.Bundle
6 import android.widget.Button
7 import androidx.activity.ComponentActivity
8 import androidx.core.content.ContextCompat
9
10 1 Usage
11 class MainActivity : ComponentActivity() {
12
13     3 Usages
14     private lateinit var myReceiver: MyReceiver
15
16     2 Usages
17     private var isReceiverRegistered = false
18
19     @
20     override fun onCreate(savedInstanceState: Bundle?) {
21         super.onCreate(savedInstanceState)
22         setContentView(R.layout.activity_main)
23
24         myReceiver = MyReceiver()
25         val filter = IntentFilter( action = "com.hello.broadcastdemo.CUSTOM_INTENT")
26
27         ContextCompat.registerReceiver(
28             context = this,
29             myReceiver,
30             filter,
31             flags = ContextCompat.RECEIVER_NOT_EXPORTED
32         )
33     }
34 }
```

```
10 class MainActivity : ComponentActivity() {
15     override fun onCreate(savedInstanceState: Bundle?) {
16
17         ContextCompat.registerReceiver(
18             context = this,
19             myReceiver,
20             filter,
21             flags = ContextCompat.RECEIVER_NOT_EXPORTED
22         )
23
24         isReceiverRegistered = true
25
26         findViewById<Button>( id = R.id.btnBroadcast).setOnClickListener {
27             val intent = Intent( action = "com.hello.broadcastdemo.CUSTOM_INTENT")
28             sendBroadcast(intent)
29         }
30     }
31
32     @
33     override fun onDestroy() {
34         super.onDestroy()
35         if (isReceiverRegistered) {
36             unregisterReceiver(myReceiver)
37         }
38     }
39 }
```

MyReceiver.kt

```
1 package com.example.broadcastdemo
2
3 import android.content.BroadcastReceiver
4 import android.content.Context
5 import android.content.Intent
6 import android.widget.Toast
7
8 class MyReceiver : BroadcastReceiver() {
9
10     @
11     override fun onReceive(context: Context, intent: Intent) {
12
13         if (intent.action == "com.hello.broadcastdemo.CUSTOM_INTENT") {
14             Toast.makeText(context, text = "Custom Intent Received!", duration = Toast.LENGTH_LONG).show()
15         }
16     }
17
18 }
```

OUTPUT:

