Code:

```cpp
#include <iostream>
using namespace std;

int main() {
    int yearsOfService, rating, bonus;

    cout << "Enter years of service: ";
    cin >> yearsOfService;

    cout << "Enter performance rating (1-5): ";
    cin >> rating;

    if (yearsOfService >= 10) {
        if (rating >= 4)
            bonus = 20000;
        else if (rating >= 2)
            bonus = 15000;
        else
            bonus = 10000;
    }
    else if (yearsOfService >= 5) {
        if (rating >= 4)
            bonus = 15000;
        else if (rating >= 2)
            bonus = 10000;
        else
            bonus = 5000;
    }
    else {
        if (rating >= 4)
            bonus = 10000;
        else if (rating >= 2)
            bonus = 5000;
        else
```

```cpp
        else
            bonus = 0;
    }

    if (bonus == 0)
        cout << "No Bonus";
    else
        cout << "Bonus: Php " << bonus;

    return 0;
}
```

Output:

```
Enter years of service: 10
Enter performance rating (1-5): 5
Bonus: Php 20000

=== Code Execution Successful ===
```

```
Enter years of service: 10
Enter performance rating (1-5): 2
Bonus: Php 15000

=== Code Execution Successful ===
```

```
Enter years of service: 5
Enter performance rating (1-5): 5
Bonus: Php 15000

=== Code Execution Successful ===
```

```
Enter years of service: 5
Enter performance rating (1-5): 2
Bonus: Php 10000
```

```
Enter years of service: 5
Enter performance rating (1-5): 1
Bonus: Php 5000

=== Code Execution Successful ===
```