Exercise 1

1) Find a upper bound

Second derivative of f(x) is



The maximum value of $\frac{8\left(3x^2-1\right)}{\left(x^2+1\right)^3}$ is 2 at x=-+1



The error made is then ≤ 1/6n^2

2) Please see attached file Exercise1_2.c

It can be compiled using command

gcc Exercise1_2.c -o Exercise1_2

Run command

./Exercise1_2

n

where n is the number of intervals.



3)

Partitioning - process will calculate it own bunch of intervals based on its id of process.

Communications – process 0 will send number of intervals to other processes. Then, calculated values will be summed and final result will be obtained by process 0.

Mapping – algorithm is highly parallelized that is why it not necessary to worry about issues during communication.

Agglomeration – uses at the end of calculation when need to summarize all results from processes. Process with id 0 hold the summarize result.

Please see attached file Exercise1_3.c

It can be compiled using command

mpicc Exercise1_3.c -o Exercise1_3

Run command

mpirun -n kolProcess ./Exercise1_3

n

where n is the number of intervals and kolProcess number of processes



4) Please see attached file Exercise1_4.c

It can be compiled using command

mpicc Exercise1_4.c -o Exercise1_4

Run command

mpirun -n kolProcess ./Exercise1_4

n

where n is the number of intervals and kolProcess number of processes





Exercise 2

1) Please see attached file Exercise2_1.c

It can be compiled using command

gcc Exercise2_1.c -o Exercise2_1

Run command

./Exercise2_1

n

where n is the number of intervals.

```
set@set: /mnt/C4D630CFD630C388/Studing/5-1_Lux/Parallel and Grid Computing/lab2
set@set:/mnt/C4D630CFD630C388/Studing/5-1_Lux/Parallel and Grid Computing/lab2$
gcc Exercise2_1.c -o Exercise2_1
set@set:/mnt/C4D630CFD630C388/Studing/5-1_Lux/Parallel and Grid Computing/lab2$
./
assignment_MPI_Pi.pdf          Exercise1_4.c
Exercise1_2                    Exercise2_1
Exercise1_2.c                  Exercise2_1.c
Exercise1_3                    Exercise2_2.c
Exercise1_3.c                  .fuse_hidden0000010000000001
Exercise1_4                    plotDataExc1_4.txt
set@set:/mnt/C4D630CFD630C388/Studing/5-1_Lux/Parallel and Grid Computing/lab2$
./Exercise2_1
Enter the number of intervals: 1000
Calculated pi 3.1415926535897931
 Error of calculated pi is 0.0000000000000000
set@set:/mnt/C4D630CFD630C388/Studing/5-1_Lux/Parallel and Grid Computing/lab2$
```

2) Approach for parallel programing of this algorithm is the same as for previous algorithm
Please see attached file Exercise2_2.c
It can be compiled using command
mpicc Exercise2_2.c -o Exercise2_2

Run command
mpirun -n kolProcess ./Exercise2_2
n
where n is the number of intervals and kolProcess number of processes

```
set@set: /mnt/C4D630CFD630C388/Studing/5-1_Lux/Parallel and Grid Computing/lab2
set@set:/mnt/C4D630CFD630C388/Studing/5-1_Lux/Parallel and Grid Computing/lab2$
mpicc Exercise2_2.c -o Exercise2_2
set@set:/mnt/C4D630CFD630C388/Studing/5-1_Lux/Parallel and Grid Computing/lab2$
mpirun -n 4 Exercise2_2
[Node 0] Enter the number of intervals: 10000
[Node 0] Calculated pi 3.1415926535897909
 Error of calculated pi is 0.0000000000000022
[Node 0] done!
 Found max process time 0.000485
 Found avr process time 0.000367
 Found min process time 0.000249
set@set:/mnt/C4D630CFD630C388/Studing/5-1_Lux/Parallel and Grid Computing/lab2$
```



Exercise 3

1) Please see attached file Exercise3_1.c

It can be compiled using command
gcc Exercise3_1.c -o Exercise3_1 -lm

Run command
./Exercise3_1
e
where e is the accuracy.



2) Please see attached file Exercise3_2.c

It can be compiled using command
gcc Exercise3_2.c -o Exercise3_2 -lm

Run command
./Exercise3_2
e
where e is the accuracy.



Plot


1
0.9
0.8
0.7
0.6
0.5
0.4
0.3
0.2
0.1
0
0
0.1
0.2
0.3
0.4
0.5
0.6
0.7
0.8
0.9
1