

Wi-Fi

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

http

No.	Source	Length	Protocol	Info
48130	172.18.59.230	267	HTTP	GET /en-US/livetile/preinstall?region=IN&appid=C98EA5B0842D8B9405B8F071E1DA76512D21FE36&FORM=Threshold HTTP/1.1
48131	184.84.106.185	431	HTTP	HTTP/1.1 200 OK
83442	172.18.59.230	299	HTTP	GET /smp_21_ HTTP/1.1
83583	172.18.57.160	137	HTTP/XML	HTTP/1.1 200 OK

< >

> Frame 48130: 267 bytes on wire (2136 bits), 267 bytes captured (2136 bits) on interface \Device\NPF_{481E4C7C-C835-42CE-A0AA-0D66FAD9D849}, id 0

> Ethernet II, Src: IntelCor_99:47:2e (5c:e0:c5:99:47:2e), Dst: Cisco_c8:4d:57 (38:90:a5:c8:4d:57)

> Internet Protocol Version 4, Src: 172.18.59.230, Dst: 184.84.106.185

> Transmission Control Protocol, Src Port: 53030, Dst Port: 80, Seq: 1, Ack: 1, Len: 213

> Hypertext Transfer Protocol

0000 38 90 a5 c8 4d 57 5c e0 c5 99 47 2e 08 00 45 00 8...MW\...G...E-
0010 00 fd 47 54 40 00 80 06 a7 a0 ac 12 3b e6 b8 54 ..GT@...;..T
0020 6a b9 cf 26 00 50 8f 3e cc 1e 6a 2b 00 0e 50 18 j..&..P>..j+..P
0030 02 01 10 99 00 00 47 45 54 20 2f 65 6e 2d 55 53GE T /en-US
0040 2f 6c 69 76 65 74 69 6c 65 2f 70 72 65 69 6e 73 /livetile/preins
0050 74 61 6c 6c 3f 72 65 67 69 6f 6e 3d 49 4e 26 61 tall?reg ion=IN&a
0060 70 70 69 64 3d 43 39 38 45 41 35 42 30 38 34 32 ppid=C98 EA5B0842
0070 44 42 42 39 34 30 35 42 42 46 30 37 31 45 31 44 DBB9405B BF071E1D
0080 41 37 36 35 31 32 44 32 31 46 45 33 36 26 46 4f A76512D2 1FE36&FO
0090 52 4d 3d 54 68 72 65 73 68 6f 6c 64 20 48 54 54 RM=Thres hold HTT
00a0 50 2f 31 2e 31 0d 0a 43 6f 6e 6e 65 63 74 69 6f P/1.1..C onnectio
00b0 6e 3a 20 4b 65 65 70 2d 41 6c 69 76 65 0d 0a 55 n: Keep- Alive..U
00c0 73 65 72 2d 41 67 65 6e 74 3a 20 4d 69 63 72 6f ser-Agen t: Micro
00d0 73 6f 66 74 2d 57 4e 53 2f 31 30 2e 30 0d 0a 48 soft-wms /10.0..H
00e0 6f 73 74 3a 20 74 69 6c 65 2d 73 65 72 76 69 63 ost: tile-servic
00f0 65 2e 77 65 61 74 68 65 72 2e 6d 69 63 72 6f 73 e.weathe r.micros

Hypertext Transfer Protocol: Protocol

Packets: 87912 • Displayed: 4 (0.0%) Profile: Default

Type here to search

26°C Partly sunny 11:14 30-01-2023



ssdp

No.	ssdp	Source	Length	Protocol	Info
1428	28.426612	172.20.13.243	522	SSDP	NOTIFY * HTTP/1.1
1440	28.432507	172.20.5.73	217	SSDP	M-SEARCH * HTTP/1.1
1473	29.459955	172.20.0.156	167	SSDP	M-SEARCH * HTTP/1.1
1474	29.462211	172.20.10.255	167	SSDP	M-SEARCH * HTTP/1.1
1475	29.462211	172.20.1.16	167	SSDP	M-SEARCH * HTTP/1.1
1481	29.462211	172.20.9.125	217	SSDP	M-SEARCH * HTTP/1.1
1487	29.463061	172.20.14.121	167	SSDP	M-SEARCH * HTTP/1.1
1497	30.465777	172.20.1.142	167	SSDP	M-SEARCH * HTTP/1.1
1498	30.467252	172.20.1.59	167	SSDP	M-SEARCH * HTTP/1.1
1501	30.467252	172.20.5.73	217	SSDP	M-SEARCH * HTTP/1.1
1503	30.469849	172.20.3.193	167	SSDP	M-SEARCH * HTTP/1.1

> Frame 592: 167 bytes on wire (1336 bits), 167 bytes captured (1336 bits) on interface \Device\NPF_{481E4C7C-C835-42CE-A0AA-0D66FAD9DB49}, id 0
> Ethernet II, Src: aa:af:78:23:41:34 (aa:af:78:23:41:34), Dst: IPv4mcast_7f:ff:fa (01:00:5e:7f:ff:fa)
> Internet Protocol Version 4, Src: 172.20.0.246, Dst: 239.255.255.250
> User Datagram Protocol, Src Port: 41672, Dst Port: 1900
> Simple Service Discovery Protocol

```
0000 01 00 5e 7f ff fa aa af 78 23 41 34 08 00 45 00  ..^.....x#A4..E.
0010 00 99 53 bc 40 00 01 11 88 93 ac 14 00 f6 ef ff  ..S.@.....
0020 ff fa a2 c8 07 6c 00 85 8a 21 4d 2d 53 45 41 52  ....1..!M-SEAR
0030 43 48 20 2a 20 48 54 54 50 2f 31 2e 31 0d 0a 48  CH * HTTP/1.1..H
0040 4f 53 54 3a 20 32 33 39 2e 32 35 35 2e 32 35 35  OST: 239 .255.255
0050 2e 32 35 30 3a 31 39 30 30 0d 0a 4d 41 4e 3a 20  .250:190 0..MAN:
0060 22 73 73 64 70 3a 64 69 73 63 6f 76 65 72 22 0d  "ssdp:discover"
0070 0a 4d 58 3a 20 31 0d 0a 53 54 3a 20 75 72 6e 3a  .MX: 1..ST: urn:
0080 64 69 61 6c 2d 6d 75 6c 74 69 73 63 72 65 65 6e  dial-multiscreen
0090 2d 6f 72 67 3a 73 65 72 76 69 63 65 3a 64 69 61  -org:service:dia
00a0 6c 3a 31 0d 0a 0d 0a 1:1....
```

Simple Service Discovery Protocol: Protocol

Packets: 1551 · Displayed: 51 (3.3%)

Profile: Default

