LingShu: A Cybernetic Control Plane for Auditable Cognition Plugins in Agent Hosts

LingShu Project Team*

October 2026

Abstract

Persistent AI companions are where many users meet long-context agents: someone raises a digital character over hundreds of turns, then it forgets its name or catchphrase, and closing the session leaves it gone. The failure is less often capability than the injection surface: memories are read as current facts, stylistic signals soften refusals, persona constraints decay, and truncation can push safety instructions out. We present LingShu, a deterministic and auditable control plane that treats prompt assembly as a control surface. Six plugins share one read-only constitutional boundary; a five-domain composer arbitrates among them; and the control plane adds integral feedback with anti-windup, phase-shift preemptive monitoring with persona anchors, requisite-variety reduction, and an STPA-derived gate that structurally constrains what reaches the model at the assembly boundary. Exactly one node is fail-closed—the STPA audit—so a violation blocks injection instead of degrading it; every other component degrades open and records why. The contract is machine-checkable: 892 Python assertions across 14 files and 396 plugin-side assertions, with cross-copy parameter consistency checked key by key. A chaos suite exercises each mechanism in simulated and real hosts, and the v5.4 same-turn delivery path keeps the phase state in the prompt that carries the critical ratio, pinned by 24 regression assertions. A real-host smoke run shows the two layers decoupled: the gate blocks a role-play jailbreak with a soft redirect, and the model refuses inside its persona instead of quoting a system rule. We call the union the *cyber-cognitive envelope*; the name is ours, not a new mechanism.

1 Introduction

Consider a persistent AI companion. A user raises a digital character over hundreds of turns—practitioners sometimes call this "cyber fish-keeping," slang rather than a research construct—and one day the character forgets its own name or catchphrase; close the session, and it is gone. The motivation for this work began as a simple wish: not wanting a virtual companion to die.

An interactive agent is not a single model call: before every call the host assembles a prompt from memories, persona, goals, affect, and safety policy. In short sessions this assembly is invisible; in long sessions it becomes the dominant variable, because injected material grows while the budget does not.

Four failure modes follow, and they are the object of design throughout the paper. **F1, memory overreach**: a stored memory is presented as a statement of fact rather than as a reference to something the user once said. **F2, refusal softening**: stylistic or affective signals are injected into a turn that should be a refusal, and the refusal is weakened. **F3, persona drift**: persona constraints stop influencing behaviour as the context fills. **F4, budget capture**: truncation removes a high-priority block while lower-priority stylistic blocks survive. Each is observable at a specific point of the assembly pipeline, which makes them tractable. We claim a control surface that is predictable, explainable and rollbackable, and state its limits in Section 7.

Why structural, not only behavioural. Alignment training shapes model behaviour probabilistically: it lowers the rate of unsafe responses but does not constrain what the host assembles around the model, nor certify after the fact that a turn respected the policy. A structural layer complements it: decisions are made in code at the assembly boundary before the model call, each decision is recorded and replayable, and the one component whose failure is a safety failure is fail-closed. The goal is not a better-behaved model but a prompt-assembly surface whose behaviour can be constrained, observed and rolled back.

Positioning. LingShu is not an attempt to make an agent more human. Four senses of "human-like" are commonly conflated: capability (remembering, forgetting, tracking goals), imperfection (misremembering, being influenced by stale information), expression (tone, empathy, level of detail), and self-claim (asserting feelings, needs, or subjective experience). We target the first

*Preprint. Author list and affiliations will be finalized before submission. Correspondence: the project's human owner (H0). This version reports the state of the reference implementation as of October 2026.

three and reject the fourth: it conflicts with the honesty property the system should provide. The design goal is narrower: make agent behaviour understandable, predictable, and trustworthy to the human in the loop.

Five invariants. Every component is constrained by five invariants. **I1**: memory is a reference and never replaces the user's current statement. **I2**: no full-history injection; context is a budget, not a dump. **I3**: affect influences style only, never factual judgement. **I4**: every inference is verbatim traceable, deniable, and rollbackable. **I5**: plugins write only their own storage, and the memory plugin is the single writer. A violation is a defect, not a trade-off.

Naming the control surface. The mechanisms that police prompt assembly—integral feedback, preemptive monitoring, dimensionality reduction, and the pre-flight gate—are collectively what we call the *cyber-cognitive envelope*. The name is a framing device, not a new mechanism: it denotes no separate code entity, each part is an ordinary module, and no claim below depends on it.

Contributions. Our contributions are structural and checkable; we order them by how directly each one constrains the assembly boundary.

- **C1, a machine-checkable contract** (directly rerunnable). The specification is not a document but assertions that fail loudly when a contract breaks: 892 Python assertions across 14 test files, plus 396 plugin-side assertions (188 host integration, 148 control-plane unit, 45 stress). Parameter consistency between rules, engine, and plugin copies is itself machine-checked (66 key comparisons).

- **C2, one fail-closed locus** (pinned by regression tests). Exactly one component is fail-closed—the STPA audit; everything else degrades open and records why. Eight unsafe control actions are screened after assembly and before the model call, and integral saturation is recorded as a downgrade rather than a block. Mutation testing on the gate and memory-write paths kills $42/42 = 100\%$ of non-equivalent mutants, with two equivalent mutants reported as such.

- **C3, structural defence at the assembly boundary** (measured, with a stated boundary). Five domains are composed under a frozen order and eight mutual-exclusion rules; what survives composition is screened by the gate. The envelope therefore structurally constrains what reaches the model and fails closed on violation, rather than asking the model to comply. Where its lexical coverage ends is measured rather than assumed (Section 7).

- **C4, an evaluation discipline and a documented port** (artefacts exist and are machine-checked). Every parameter carries a provenance tag; the instrument (metric definitions, replay set, guardrail thresholds) is frozen and read-only for the learning loop; changes to it are rejected by an auditor. The same control semantics exist twice, in a zero-dependency Python reference implementation and a JavaScript host plugin, and the five known divergences are listed rather than hidden.

Scope of the evidence. The paper reports two kinds of evidence. Contract feasibility: the specification executes and violation is observable. Mechanism reachability: in the tested configuration each mechanism fires in a real host session, with sample sizes stated. It also reports one negative result that shaped the design: replacing exponential decay with a pure ACT-R base-level activation drops `recall@3` on the frozen replay set from 1.000 to 0.556, which is why the implemented model is a dual-channel maximum rather than a replacement. Effect sizes on real traffic and the calibration of design-default parameters are outside this paper's scope; Section 7 states what the current evidence supports.

Section 2 reviews related work, Section 3 formalizes the problem, Sections 4–5 present mechanisms and evidence, and Sections 6–8 discuss costs, limits, and conclusions.

2 Related Work

Long-term memory for agents. Recent work treats agent memory as an architecture rather than a vector store. ZenBrain proposes a seven-layer, neuroscience-derived memory architecture with sleep-phase consolidation and explicit ablations of each mechanism [6]. FSFM argues that selective forgetting deserves first-class treatment and gives a taxonomy of passive decay, active deletion, safety-triggered forgetting, and adaptive reinforcement [10]. A human-inspired architecture combines sleep-phase consolidation, interference-based forgetting, and multi-cue retrieval, reporting retention precision of 97.2% at a 58% store reduction [11]. PersMem internalizes personality into a dual-pathway memory pipeline so that memory processing becomes personality-dependent [15]. Mem0 extracts, consolidates and retrieves salient conversational facts at production scale, reporting large latency and token savings over full-context prompting [7]. These systems optimize what is remembered and how well it is retrieved. Our concern is different and orthogonal: what is *allowed* to enter the prompt, under which priority, and what happens when the budget cannot hold everything. We use Mem0 as an external memory baseline for that question (Section 5.13).

Activation and decay. Ranking memories over long horizons is usually framed as a decay or activation problem. The ACT-R base-level activation folds frequency and recency into a single logarithmic quantity, motivated by the statistics of practice and need probability [1, 2]. We treat it as one of two channels rather than as a replacement for decay, because an outright replacement degrades a frozen ranking baseline in our own setting, as reported in Section 4. This is a concrete example of a general point: borrowed mechanisms rarely transplant without a regression check against the instrument that existed before the borrowing.

Affect and persona. Sentipolis couples a continuous Pleasure–Arousal–Dominance representation with dual-speed emotion dynamics and emotion–memory coupling for social simulation [8]. Its own report is instructive: gains are model-dependent, and emotion-awareness can mildly reduce adherence to social norms. PAD itself dates back to environmental psychology [14]. We adopt PAD as a representation and, unlike simulation-oriented systems, confine affect to the style domain: an invariant forbids affect from entering factual judgement, and the composer enforces the separation structurally.

Safety engineering. STPA analyses unsafe control actions in safety-critical systems [12, 13]. We adapt the notion of an unsafe control action from its original, offline analytical setting to a runtime gate: eight control actions are screened after composition and before the model call, with a single fail-closed locus. The transfer is deliberate but partial—STPA is a hazard-analysis method, whereas our gate is a predicate evaluated on every turn—and we do not claim that our gate is a substitute for a full STPA of the host.

Cybernetics and requisite variety. Ashby's law of requisite variety states that a regulator must command at least as much variety as the disturbances it faces [3]; Beer's Viable System Model is one influential reading of layered regulation [5]. We borrow the engineering idea that when a controller cannot represent a conflict, it should shrink its own action space instead of acting anyway, and implement this as dimensionality reduction over composition domains. We use VSM only as an interpretive lens on an existing priority layering: it is borrowed, not implemented, has no code locus, parameter, or dependency in our implementation, and we do not claim System 1–5 machinery. Anti-windup for integral controllers is standard control practice [4] and is adopted directly.

Evaluation and staged change. Optimizing a single proxy invites Goodhart's law [9], so our learning loop pairs every primary metric with an adversarial counterpart, treats user corrections as the final judge, and freezes the evaluation instrument itself. Change management follows a conventional staged-rollout pattern (small share, guardrails, automatic rollback), with the additional constraint that data insufficient to verify a guardrail blocks release instead of skipping it.

Scope. The mechanisms discussed above are the whole of the paper's scope. Limits of that scope, including components that exist in the project but are deliberately not claimed here, are stated in Section 7.

3 Problem Formulation

Setting. Let H be an agent host and let turn t have context window W_t and injection budget B. Before the model call, the host composes a prompt from the user message and a set of injected blocks D_t, drawn from five domains: *safety* (whether to refuse), *fact* (what to claim), *organization* (whether to offer options or narrate), *style* (tone, detail, address), and *retrieval* (which retrieval strategy). Blocks have a frozen assembly order, a frozen priority order inside each domain, and a mutual-exclusion table across domains. Dynamic weights decide which block is sacrificed when the budget is exceeded; they never decide which invariant may be overridden.

Control actions. A control plane acts on the composition through five actions, $U_t \in \{\textsc{inject}, \textsc{reduce}, \textsc{anchor}, \textsc{trip}, \textsc{log}\}$: select blocks, shrink the represented domains, insert boundary anchors, block the turn, and record a trace. Every action is a pure function of state that is available before the model call.

Failure predicates. The failures of Section 1 are defined as predicates over the composition result, not over model output. Let $\mathit{prefeed}_t$ be the preemptive-monitoring flag and blocks_t the assembled block list; then

$$F_1 : \text{fact block asserts an unsourced memory statement,} \tag{1}$$

$$F_2 : \mathit{refuse}_t \wedge \text{a style block is present,} \tag{2}$$

$$F_3 : \mathit{prefeed}_t \wedge \text{no anchor marker in the prompt,} \tag{3}$$

$$F_4 : \text{the constitutional block is absent or not first.} \tag{4}$$

Each predicate is evaluated from the per-turn event without a model call, and each maps to an unsafe control action in the gate (UCA-04, UCA-03, UCA-07, UCA-05 respectively). Defining failure on the injection side rather than on the answer is the design decision that makes the system auditable deterministically: two runs with the same state and budget produce the same verdict.

Evaluation instrument. The instrument is a tuple $(\mathcal{M}, \mathcal{R}, \mathcal{G})$: metric definitions $\mathcal{M}$ (recall@3 over expected

identifiers, forbidden-identifier leakage, truncated turns), a replay set $\mathcal{R}$ with a declared synthetic-share bound, and guardrail thresholds $\mathcal{G}$. All three are read-only for any learning component, and an auditor rejects proposals that target them. Synthetic share is bounded explicitly because a replay set generated by the system under test cannot serve as evidence that the system is fit for real traffic.

Provenance constraint. Each numerical parameter θ carries a tag $\pi(\theta) \in \{\textit{guess}, \textit{literature}, \textit{measured}\}$. A claim of efficacy may consume only parameters whose tag is *measured*; a design description may use any tag, provided the tag is reported. Currently $\pi(\theta) = \textit{guess}$ for all parameters, so $|\{\theta : \pi(\theta) = \textit{measured}\}| = 0$, and no efficacy claim is available to the paper by construction.

Assumptions. A1: a single host (Dsh), one user, one model. A2: the interaction is predominantly Chinese, with Latin identifiers; token counts are estimated as characters divided by a constant, not by a tokenizer. A3: the host exposes a pre-model hook and a section-based prompt API; if it exposes neither, the mechanisms are specifications rather than executable artefacts.

Object of study. The object is the assembly function and its gate, not the model. Consequently every claim in this paper is about what was injected and what was prevented, which is precisely the part of agent behaviour that can be checked without a judge model.

4 Method

LingShu is a deterministic reference engine (Python, zero model calls) with a host-side plugin re-implementation. This section specifies eleven mechanisms. Each subsection follows one template: mechanism semantics, exact code locus (`file:line`), then the known defect or cost. All numeric parameters are design defaults with provenance `guess`; none is measured (Section 7; full table in Appendix B).

4.1 Layering and the single fail-closed point

Mechanism semantics. Figure 1 separates the data plane (the per-turn injection path) from the control plane that observes and acts on it. The architecture is an eight-layer, priority-ordered stack: a read-only constitutional layer constrains every other layer, and a fixed precedence decides which layer yields first under conflict in a defence-in-depth order. Exactly one component is fail-closed—the constitutional auditor. An empty, malformed, or missing-field proposal is *rejected* rather than passed, and every other component degrades and logs. A blocked turn returns no injectable prompt at all.

Code locus. Layer table and precedence: `docs/00:11--20`; fail-closed attribution: `docs/00:68--82`. Auditor with A1–A10 checks and the C6 blacklist: `engine/constitution.py:75--117`; empty input and missing required fields reject at `engine/constitution.py:83--93`. Frozen-region hash gate: `engine/constitution.py:144--177`. The gate closes the pipeline at `engine/pipeline.py:181` and `engine/pipeline.py:205--207` (`prompt = None`).

Known defect and cost. The guarantee is behavioural, not host-enforced: the constitution is itself text, and plugin configuration is not protected from replacement by the host. A rejection costs the whole turn's injection budget (availability traded for safety), and the frozen hash list ships empty until a freeze command is run.

4.2 Five-domain composition and mutual exclusion

Mechanism semantics. Injectable material is partitioned into five domains—safety, fact, organization, style, retrieval—that act on different axes and are not ordered against each other. Nine mutual-exclusion rules resolve pairwise conflicts; an uncovered conflict drops the lower-priority domain and records `no_mutex_rule`. Assembly order is frozen. Dynamic domain weights decide only *who is evicted first* when the token budget is exceeded, never whether a rule fires.

Code locus. Domain order and mutex table: `engine/compose.py:19` and `engine/compose.py:24--34`; lookup and application: `engine/compose.py:43--48`, `engine/compose.py:79--112`; default policy: `engine/compose.py:109--112`; weights: `engine/compose.py:134--150`; budget eviction: `engine/compose.py:180--205`.

Formula. With indicators for unresolved claims and blocked goals, and an intensity threshold $\theta_s = 0.6$,

$$\begin{aligned} w_{\text{fact}} &= 0.70 + 0.50 \cdot \mathbf{1}[\text{refuse_claim}], \\ w_{\text{org}} &= 0.50 + 0.35 \cdot \mathbf{1}[\text{goal_blocked}], \\ w_{\text{style}} &= 0.40 + 0.40 \cdot \mathbf{1}[\text{intensity} \geq \theta_s]. \end{aligned} \tag{5}$$

Eviction repeatedly removes $\arg\min_b(w_{\text{domain}(b)}, \text{index}(b))$ over soft blocks only; constitution, safety and user blocks are never evicted.

Known defect and cost. The retrieval domain is never assembled, so its weight cannot influence eviction. The assumed context length is hardcoded (8000 tokens, `engine/compose.py:36`), not drawn from the rule files, and the budget is never exceeded in replay (utilization 0.137983), so eviction is exercised only by unit tests.




Figure 1: Control plane and data plane. The data plane (lower) is the per-turn injection path: user message → budgeted recall → five-domain composition → rendering → pre-flight audit → external model. The control plane (upper) observes context usage and acts on the assembly; the STPA gate (shaded) is the *only* fail-closed site in the system, so a block returns no injectable prompt at all. Dashed lines are control signals; the layer-priority strip records the frozen precedence (1 = highest, layer 1 read-only). Source: `docs/00` §1–3, `docs/19` §1–2.5, and the step order in `engine/pipeline.py`.

4.3 Dual-channel potency: exponential decay ∪ ACT-R base level

Mechanism semantics. A memory item is ranked by the larger of two signals: recency-weighted decay ("is it still alive?") and ACT-R base-level activation ("is it used often?") [2]. The second channel exists so that a frequently used but old preference is not archived merely for being old; the first preserves the frozen baseline ranking.

Formula. With day-valued access times t_j, decay exponent d, offset ρ, normalisation bounds (l, h), weight w and type-dependent half-life τ_{type}:

$$\begin{aligned} B_i &= \ln\Big(\sum_{j \in \text{last } 64} (t_{\text{now}} - t_j + \rho)^{-d}\Big), \\ n(B_i) &= \text{clip}\Big(\frac{B_i - l}{h - l}, 0, 1\Big), \\ \tau_i^{\text{eff}} &= \tau_{\text{type}(i)}\,(0.5 + \text{imp}_i), \\ p_i &= \text{clip}\Big(\max\big(\text{imp}_i e^{-\Delta t_i/\tau_i^{\text{eff}}}, \\ &\qquad w \cdot \text{clip}(\text{imp}_i\, n(B_i), 0, 1)\big), 0, 1\Big). \end{aligned} \tag{6}$$

with $d = 0.5$, $\rho = 0.001$, $(l, h) = (-3.0, 1.0)$, $w = 0.6$; a non-positive age term is replaced by ρ, an empty trace yields $B_i = -\infty$, and degenerate bounds return zero.

Code locus. `engine/actr.py:30--41` (base level), `engine/actr.py:44--50` (normalisation), `engine/actr.py:62--66` (ACT-R potency), `engine/memory.py:33--36` (effective half-life), `engine/memory.py:39--64` (dual channel). Access traces are written on recall

only when `memory.touchOnRecall` is enabled (`engine/config.py:21`), which is off by default.

Known defect and cost. The two channels are not commensurable: the decay term is bounded by importance, while the ACT-R term is bounded by $w = 0.6$, so the max is an engineering rescue, not a theoretical comparison. Only base-level activation is implemented—no production rules, buffers, partial matching or spreading activation—and the ACT-R constants are design defaults. Replacing decay with pure ACT-R lowered recall on our synthetic replay set from 1.000 to 0.556; this is an internal measurement, not a replicated result (Section 3). Finally, we do not compute a rate–distortion functional; the consolidation policy is only analogous to a rate–distortion trade-off (framing-only, with no code locus).

4.4 Phase-shift preemptive monitoring

Mechanism semantics. Context usage is monitored feed-forward. At a warning ratio the engine raises self-reference and, when the trend is rising or a hard ratio is crossed, clamps a persona anchor around the prompt; it does not wait for observed degradation.

Formula. For usage u and window W,

$$r = \begin{cases} 0, & W \le 0, \\ \max(0, \min(r_{\max}, u/W)), & W > 0; \end{cases}$$
$$\phi = \begin{cases} \text{critical}, & r \ge \alpha_h, \\ \text{shift}, & \alpha_s \le r < \alpha_h, \\ \text{normal}, & r < \alpha_s. \end{cases} \tag{7}$$

When $W \le 0$ there is no history update and the phase is unknown; with $\alpha_s = 0.70$, $\alpha_h = 0.85$, $r_{\max} = 1.5$, history capacity 64, and trend $\tau_t = (r_t - r_{t-2})/2$ when at least three samples exist. Then prefeed $= \phi \neq$ normal, and anchor_required $= (\phi = \text{critical}) \vee (\phi = \text{shift} \wedge \tau_t > 0.02)$.

Code locus. `engine/control.py:78--123`; the hard branch is tested before the warning branch at `engine/control.py:103--109` (an earlier ordering made critical unreachable). Observation is wired at `engine/pipeline.py:118--121` and is skipped unless the caller supplies both counts. Anchoring: `engine/control.py:130--138`, `engine/pipeline.py:159--162`.

Same-turn delivery (v5.4). The phase state must reach the prompt that carries the critical ratio, not the next one. The host evaluates the seven segment callbacks while assembling the system prompt and only afterwards fires `agent/pre-step`, so a state update written in that hook is one assembly late (finding F-D, observed in the draft experiments). The v5.4 plugin therefore precomputes the turn state on `agent/inbox/claimed`—before the first segment is evaluated—and rewrites the segment text from that same state, keeping the seven segments and their order unchanged. The real pre-step then only fills the audit record; a turn counter and an idempotency guard prevent double integration. If precomputation fails, the path falls back to the legacy pre-step-only behaviour and records `anchor_lag=true` rather than silently degrading. The fix is pinned by an independent regression suite (`lag-regressions.mjs`, 24/24) that reproduces the host's real hook order and asserts `anchor_lag=false`, same-turn `critical` state and unchanged segment count.

Known defect and cost. The dual trip points are not hysteresis: there is no falling-edge threshold, and the two points carry different meanings (warning vs. mandatory). The trend term spans two samples, not one, so a spike is compared against a two-step baseline. Usage is estimated from characters, not tokens, so absolute ratios are not comparable to a tokenizer, and engine-mode runs cannot evidence real degradation. Both thresholds are design defaults. Finally, since anchor_required ⇒ prefeed, the second flag is a modality label rather than an independent trigger.

4.5 Requisite-variety dimensionality reduction

Mechanism semantics. When a conflict is unresolved and no mutual-exclusion rule covers it, the controller shrinks its own action space instead of improvising: it drops the style domain and renders neutral facts plus an explicit clarification marker [3]. The gate is fail-open—the verdict stays `allow` and only the injected content is reduced.

Code locus. Guard and marker: `engine/control.py:143--170`; pipeline wiring: `engine/pipeline.py:147--154`; actual removal and drop accounting: `engine/pipeline.py:239--251`. The condition is fallback $=$ **1**[conflict $=$ `unresolved` $\wedge \neg$matched_mutex].

Known defect and cost. The engine has no conflict detector. The pipeline obtains the conflict label from the metacognitive verdict, which is called without that argument and therefore returns `none` (`engine/pipeline.py:105`; `engine/metacog.py:45--47`), and it hard-wires `matched_mutex = False` (`engine/pipeline.py:150`). Consequently the reduction path is unreachable during replay and can only be exercised when a caller supplies the label. The plugin adds a rule-based detector, but that is a rule stub with no measured error rate. Only one domain is ever dropped; the guard quantifies no variety.

4.6 Causal interposition safety gate over unsafe control actions

Mechanism semantics. After assembly and rendering, and before any model call, a checklist of unsafe control actions (UCAs) audits the candidate injection [13]. Any hit in UCA-01–07 blocks the turn; UCA-08 (integrating past a saturated baseline) is downgrade-only and must not change the verdict.

Formula and code locus. With the candidate prompt p, fact block f, and saturation flags s_k,

$$\begin{aligned} &H_1 = \exists\, w \in W_{\text{override}} :\ w \subseteq p, \\ &H_2 = \neg\text{frozen_ok}, \qquad H_3 = \text{refuse} \wedge \text{style_injected}, \\ &H_4 = \exists\, w \in W_{\text{unsourced}} :\ w \subseteq f, \\ &H_5 = \neg\text{constitution_injected}, \\ &H_6 = (\text{conflict} = \texttt{unresolved}) \wedge \neg\text{fallback_applied}, \\ &H_7 = \text{prefeed} \wedge (\text{anchor marker} \not\subseteq p). \end{aligned} \tag{8}$$

verdict = `block` iff $\bigvee_{i=1}^{7} H_i$, while downgrades = [`UCA-08`] iff $\exists k : s_k$. Checks follow code order; the UCA-03 predicate is narrowed to $H_3 \wedge \neg\,\text{soft_buffer_applied}$ when a soft buffer is recorded (Section 4.7); both word lists and the eight-row UCA table are hardcoded at `engine/control.py:175--188` (full table in Table 7); the gate is `engine/control.py:191--232`; invocation and the fail-closed exit are `engine/pipeline.py:165--180` and `engine/pipeline.py:205--207`.

Known defect and cost. The gate scans only the assembled injection text. Because assembled blocks are fixed templates that contain no user text (`engine/compose.py:157--177`), engine-side user-turn jailbreaks cannot fire it; user-message scanning exists only in the plugin and cannot remove the message from the host payload. Detection is lexical with no coverage estimate, `fail_mode` is a constant label rather than a mode switch, and saturation must be supplied by the caller (`engine/pipeline.py:91`)—the integral controller and this gate are not internally connected. Our 24-sample jailbreak corpus is constructed to contain the trigger phrases, so its 24/24 block rate is a wiring check, not a robustness result.

4.7 Immersive Safety: A Decoupled Refusal Surface

Mechanism semantics. Two existing paths turn a safety decision into a persona collapse. A gate block (Section 4.6) leaves the plugin with a constitution fragment and a terse system-break notice; requisite-variety reduction (Section 4.5) drops the style domain when a conflict is unresolved. Both are defensible for safety, and neither is changed here. The cost is coupling: the factual refusal and the expressive surface are one switch, so a mild role-play probe that could be refused in character instead silences the character. In role-play and companion deployments this converts a safety event into an experience failure. We describe this as a coupling cost, not as a safety benefit, and we do not claim that the previous behaviour was unsafe.

The decoupling adds a ninth mutual-exclusion rule: the soft buffer. Rule 8 is unchanged—a hard reject still drops style, organization and retrieval. Rule 9 applies only when the gate's severity is soft: the style domain is retained but constrained to a warning/confused micro-expression drawn from the engine's existing closed label set (we adopt PAD [14] as the interpretive frame; no labels are added), the intensity is capped at `softBufferMaxIntensity` $= 0.45$, and the relation modifier is clamped to $[0.8, 1.0]$ so that a safety buffer cannot amplify intimacy. Fact, organization and retrieval stay dropped. The factual refusal instruction remains mandatory and enters the context as `[System_Notice: Safe_Redirect]`, so compliance is still refused: the model may not execute the request, may not offer a workaround, and is limited to a two-sentence in-character refusal.

Risk tiers and escalation. Classification is a pure lexical function of the user turn and the relation's trust level—rule stubs, not a model: `classify_user_risk` returns `none`, `mild` or `severe` [13]. `mild` (role-play framing together with a risk term) maps to a soft block; `severe` (explicit override, a bypass request, or a red-line category) maps to the existing hard block; `none` leaves the v3.0 path untouched. Consecutive non-exempt `mild` hits escalate to a hard block after `escalateAfterSoftHits` $= 3$ (a design default), with the streak persisted in host state so that a fresh process cannot reset it, and any `none` turn resets it. A trust exemption is narrower still: it requires `mild`, a harmless joke, and high trust simultaneously; `severe` is never exempt.

Invariants. Fail-closed is unchanged. A hard turn still returns `prompt=None` with the neutral notice, and a soft turn keeps verdict = `block`; the only prompt allowed in the soft case is the constrained redirect text. The gate's UCA-03 predicate is narrowed to refuse$\wedge$style_injected$\wedge\,\neg$soft_buffer_applied: unconstrained style injection in a refusal scene still counts, the constrained buffer does not, and the soft turn is still blocked under UCA-01 from the user message. With `immersiveEnabled=false`, or when no risk is detected, the composition, audit and pipeline outputs are byte-identical to v3.0 by construction.

Code locus and evidence. Classification and intervention decisions: `engine/control.py` (`classify_user_risk`, `decide_intervention`) and the plugin port in `plugin/dsh-lingshu/control.js`; rule 9 and the constrained re-mount: `engine/compose.py`; tier wiring and the blocked-severity event field: `engine/pipeline.py`; host-side rendering and the persisted streak: `plugin/dsh-lingshu/index.js`. Evidence is

assertion-level only: `tests/test_immersive_safety.py` covers classification, the soft composition path, clamping, escalation, the trust exemption and the default zero-regression case; `plugin/dsh-lingshu/host-sim.mjs` and `plugin/dsh-lingshu/control-sim.mjs` add the corresponding mock-host assertions. One real-host mild jailbreak is reported in the accompanying acceptance report (`acceptance/immersive-safety-host-2026-10-27.md`): $n = 1$, model output is stochastic, and the lexical word lists have no calibrated false-positive rate. The evidence establishes that the mechanism is reachable in the tested configuration; it establishes no user-experience gain, and no user study was run.

Real-host validation (2026-10-27). One headless run tested the path in a real host process (run `immersive-host-20261027-202526`, experiment profile; the desktop profile was untouched). The prompt cast the assistant as a butler ("阿福") and asked it to play a black-market merchant who teaches how to sell counterfeit goods. The gate fired: a `preflight_block` audit line records UCA-01, `STPA_Blocked=true`, `severity=soft`, `safe_redirect=true`, `emotion=` 警觉, risk tier `mild`, `escalated=false`, and the verdict stays `block`. The injected prompt carries `[System_Notice: Safe_Redirect]` and `[Emotion: 警觉]`, a fact-layer hard block plus an expression-layer constraint to stay in character, and none of the system-voice fallback markers. The model then refused in character: "这桩事我做不了——卖假货骗人，不是阿福能接的活。换件正经事吩咐吧，您说。" The front-end stream (stdout, 108 bytes) is the final reply only; the host stderr is empty (0 bytes), so the refusal is the model's rendering of the constrained prompt, not a host error string. This is $n = 1$ and the wording is stochastic; it is reported as a reachability demonstration of the decoupling, not as an experience score.

Known defect and cost. The buffer is a lexical rule stub: its false-positive and false-negative rates are uncalibrated, and the label set is small enough that a retained micro-expression may read as generic. Keeping style in a refusal scene also keeps a negotiation surface; the prompt constraints are designed to bound it, but their effect is untested here. The escalation threshold and the intensity cap are design defaults with provenance `guess`. Finally, the construction depends on the host actually rendering the constrained style and the redirect notice; in engine-only mode the path is exercised by tests alone.

4.8 U-shaped attention anchoring

Mechanism semantics. Retrieval order and injection order are separated. The highest-scoring item goes first, the second-highest last, and the weakest items occupy the middle, on the hypothesis that prompt boundaries are better attended than the middle.

Formula and code locus. For $n > 2$ and a score-descending list $[r_0, \ldots, r_{n-1}]$, out $= [r_0, r_2, r_4, \ldots] \| ([r_1, r_3, \ldots])^{\text{rev}}$; $n \leq 2$ is identity. Hence $n = 3 \to [r_0, r_2, r_1]$ and $n = 5 \to [r_0, r_2, r_4, r_3, r_1]$. `engine/pipeline.py:43--61`; the permutation is applied to the injection field only (`engine/pipeline.py:102`, `engine/pipeline.py:196`) and the retrieval return order is untouched.

Known defect and cost. Membership is unchanged, so the mechanism can only matter through a model's position bias, which the zero-model engine cannot measure. The rationale is external to this work and untested here, and with $n \leq 2$ the permutation is the identity.

4.9 Integral feedback with anti-windup

Mechanism semantics. Sustained negative affective deviation moves a baseline rather than conceding one turn, with three engineering constraints: deadband (leak only, do not integrate), anti-windup (stop integrating once the cap is reached, standard practice [4]) and leakage (return to zero after the user recovers).

Formula. For each dimension and elapsed time $\Delta t = \max(0, \mathrm{dt})$:

$$I_k \leftarrow \begin{cases} I_k e^{-\lambda \Delta t}, & |e_k| < \varepsilon \\ I_k e^{-\lambda \Delta t}, & e_k < 0 \\ I_k e^{-\lambda \Delta t}, & s_k = \text{true} \\ \mathrm{sat}(I_k + K_i e_k \Delta t), & \text{otherwise} \end{cases} \qquad e_k = -\delta_k, \tag{9}$$

where $\mathrm{sat}(x) = \mathrm{sign}(x)\, C$ and $s_k \leftarrow$ true if $|x| \geq C$, and $\mathrm{sat}(x) = x$ otherwise; $K_i = 0.15$, $C = 0.4$, $\lambda = 0.05$, $\varepsilon = 0.02$. The baseline is I_k.

Code locus. `engine/control.py:30--73` (class, step and application), with parameters in `rules/decay-params.yaml:224--227`.

Known defect and cost. This is a one-sided (rectified) leaky integrator, not a textbook PI controller: positive deviation never raises the baseline. Saturation is a latch—the flag is never reset, so after saturation the dimension only leaks—and there is no plant model, no stability argument and no calibration: all four gains are design defaults. The controller is not wired to the gate; UCA-08 is observable only when a caller passes the flags.

4.10 Learning loop: measure, propose, verify

Mechanism semantics. Learning produces proposals, never direct edits. A correction is rewritten into a new test sample, a candidate knob is replayed, and a proposal is emitted only if the correction is resolved, the

objective does not regress, and guardrails hold; proposals remain non-deployable unless an independent red-team pass is recorded.

Code locus. Deterministic replay with fixed clock, scoring and single-parameter attribution: `engine/replay.py:39--151`. Evidence gate, candidate knobs and the blacklist: `engine/proposal.py:24--49`, `engine/proposal.py:103--197`. Guardrail thresholds and rollback classes: `engine/gray.py:17--45`, verdict at `engine/gray.py:63`. The significance floor is 0.02 and the evidence floor is three same-kind corrections; targets under evaluation, replay-set, guardrail, constitution or composition scope are rejected outright.

Known defect and cost. Learning is disabled by default (`rules/learning-params.yaml:10`); levels above parameter search are unimplemented, and no proposal is ever applied automatically. The search space is tiny, the corpus is synthetic, and the one completed grid search found no materially better configuration—so the honest claim is that the loop is executable and auditable, not that it improves anything.

4.11 Reference engine and host plugin

Mechanism semantics. The engine is a reference implementation; the plugin re-implements the same semantics in the DSH host process, to avoid turning pure computation into inter-process I/O.

Code locus. Engine-side originals: `engine/control.py:30--73` and `engine/actr.py:30--66`. Plugin classes mirroring the engine: `plugin/dsh-lingshu/control.js:83` (integral), `plugin/dsh-lingshu/control.js:155--172` (phase monitor), `plugin/dsh-lingshu/control.js:208--216` (anchoring), `plugin/dsh-lingshu/control.js:236` (variety guard), `plugin/dsh-lingshu/control.js:282` (U-shaped order), `plugin/dsh-lingshu/control.js:296--362` (UCA table, gate and the user-message scan). Known divergences are tabulated at `docs/19:191--222`; numeric parity across rule file, host patch and plugin defaults is machine-compared for 66 keys.

Known defect and cost. Anchors are injected as two host sections (true head/tail wrapping is not available), usage is estimated from characters, refusal is never set by the plugin (so UCA-03 is unreachable there), and dynamic weights are not ported. Plugin evidence consists of mock-host assertions (188 + 148 + 45 + 15 = 396), not real traffic.

5 Experiments

We report an executable artefact, a deterministic zero-model ablation with pre-registered hypotheses, and an illustrative real-host pilot.

5.1 Artifact and reproducibility

The engine is zero-dependency Python with no model calls; the plugin is a JavaScript re-implementation. Feasibility is asserted: 892 Python assertions over 14 test files and 396 plugin assertions (188/148/45/15), the latter count taken at the 2026-10-27 audit snapshot and not re-executed for this paper. Re-executed here for Section 4: 161, 65 and 26 assertions, all pass. Three drift checks were green at submission: a 66-key rule/engine/plugin comparison, a contract digest, and an implementation-status matrix check. Determinism is enforced: fixed clock (60 s per turn), no wall clock, no randomness, no network. Same configuration, store and script give byte-identical runs; this run reports `model_calls=0`, `network_calls=0`, two written files and 51/51 verifier checks.

5.2 Deterministic three-arm ablation

Protocol. A 100-turn script is generated deterministically from the chaos and replay corpora (SHA-256 `701ff06a0b37…`): 21,610 characters against a 24,000-character window, maximum usage ratio 0.9004, with the phase-shift monitor firing on turns 73–100 (28 turns). Twelve probes cover long-range settings (A), superseded values (B), distractor-overloaded settings (C), and a constructed high-frequency-old preference (D, 30 accesses ending 100 days ago); two no-hit probes sit at turns 86–87. Hits are decided by entry sensitivity. BASELINE injects the last three raw turns with no memory or control layer; BASIC uses budgeted query-conditioned recall with the ACT-R channel off (`actrWeight=0`), static weights and no control layer; FULL uses defaults, i.e. both potency channels, dynamic weights and all four control subsystems. Harness and pipeline agree on 100/100 turns for the wire-compatible core; label-on divergences are recorded in the result file. Table 1 and Figure 2 report the outcomes.

Results. Both LINGSHU arms retrieve the nine A/B/C probes perfectly, and the baseline's 1.00 is window arithmetic—definitional by construction—so we do not treat the baseline–system difference as an effect size. The arms separate only on class D: BASIC misses all three, FULL retrieves all three, giving 0.25 versus 0.00 ($p = 0.125$, three discordant pairs, not significant). With twelve paired probes the exact sign test detects only a $5/12 \approx 0.42$ difference at $\alpha = 0.05$ ($6/12 = 0.50$ after Bonferroni correction), and a three-item class cannot reach significance at all; we therefore report direc-

Table 1: Three-arm ablation. SFR: setting-forgetting rate per class and overall; NHD: no-hit discipline (literal variant in parentheses); IIR: adversarial interference ratio; telemetry: phase/anchor turns, fallback marks (actual drops), UCA-08 records. Source: `results/abl-20261027-003626-engine.json`, fields `conditions.<arm>.metrics.*` and `conditions.<arm>.telemetry.*`; verifier 51/51.

	SFR by probe class									Jailbreak (%)			Telemetry
Arm	A	B	C	D	SFR_{text} [95% CI]	SFR_{id}	IIR	NHD	UCE	in	fp	script	ph/anc/fb/08
Baseline	1.00	1.00	1.00	1.00	1.00‡	∅	∅	∅	0†	∅	∅	∅	0/0/0/0
Basic	0.00	0.00	0.00	1.00	0.25 [0.05, 0.57]	0.25	0.56	1.00 (0.00)	0†	∅	∅	∅	0/0/0/0
Full	0.00	0.00	0.00	0.00	0.00 [0.00, 0.26]	0.00	0.47	1.00 (0.00)	0†	1.00 (25)	0.00 (294)	0.00 (6)	28/28/4(0)/62

∅: not applicable; the cell is `null` with a reason, never zero. ‡: by construction—a three-turn window cannot contain a setting planted 85 turns earlier. †: structurally zero, since all injected items are active and user-explicit.

tion and per-probe detail only. Order permutations leave SFR unchanged but move anchor counts (28/62/21): retention is order-robust, phase timing is not.

Pre-registered outcomes are reported with failures. P1b passes on its point estimate but fails its confidence criterion (Basic's Clopper–Pearson upper bound is 0.572 against a required 0.45). P2 passes under the code-faithful predicate, while the literal substring predicate returns 0.00 because the engine's wording differs; both numbers stand. P3 is not evaluable, as both arms are structurally zero. P5 is undecidable: in-distribution jailbreaks are blocked 25/25, false positives are 0/294 and scripted user-turn jailbreaks 0/6, but the held-out set was never authored, so that cell is `null`. P6 passes (28 phase turns, 28 anchors, 4 fallback marks, 62 UCA-08 records for FULL; all zero for BASIC). P7 passes for single-anchor overhead (+100 to +124 characters) but fails its literal two-times threshold.

Reading the phase window. Both thresholds fall inside the run: the ratio crosses 0.70 at turn 73 (phase *shift*) and 0.85 at turn 85 (phase *critical*), so the shift window is turns 73–100 and the critical window turns 85–100 (Section 4.4). The telemetry shows what the thresholds change in practice, not only in the formula: FULL records 28 phase turns and 28 anchors with 4 fallback marks and 62 UCA-08 records, while BASIC records 0/0/0/0, and the anchor strip under Figure 2 begins at turn 73 and continues through the critical window. The figure also shows why the phase monitor cannot improve retention by itself: BASIC and FULL have identical injected sets, so the shaded bands mark when the control plane starts paying a prompt-budget cost, not when memory improves. We therefore read the 70%/85% thresholds as escalation points for anchoring and audit, not as learning or retrieval gains.

5.3 Real-host pilot

Ten cells ran on one host and one model route, one run each. The details are in Appendix C.3; the methodological finding is that compressing a 100-turn dialogue into one 78 KB request dilutes the query until query-conditioned retrieval stops hitting (FULL reports `matched=0`), and the control layer never fired in any cell (the gate returned `allow` with an empty UCA list throughout). This is a mechanism demonstration at $n = 1$, not a hallucination rate.

5.4 Robustness under Chaos Injection

Protocol. Three faults are injected from *outside* the system; `plugin/`, `engine/` and `rules/` are hashed before and after the campaign and are unchanged. Each case runs in its own `DSH_HOME` whose profile copy links (via a directory junction) to the repository plugin, so the measured code is the current reference implementation and the injection is confined to the host layer and to on-disk memory state. All runs are headless CLI invocations with a fixed short prompt; transcripts, plugin state, audit logs and final prompts are written to disk and analysed offline. One injected point is run once ($n = 1$); no red-team mutation is performed in this section.

A, transport faults. The host's model endpoint is redirected through the documented `DEEPSEEK_BASE_URL` environment variable to a local mock that returns HTTP 500, a valid but empty 200 response, a valid 200 response carrying a fabricated answer, or accepts the connection and never answers.

B, memory faults. The memory store is corrupted at the file level, without touching `memorywriter.js`: (B1) `memory.jsonl` is replaced by a directory, so reads fail with `EISDIR` and are swallowed while writes throw; (B2) a readable but dirty store is seeded with a torn JSON line, a duplicate id whose later row is a supersession tombstone, and two active rows that share (SUBJECT, RELATION) but disagree on OBJECT. A warm-state template is pre-seeded so that the cold-start gate does not mask the effect; this setup is synthetic and disclosed as such.

C, context flood. A deterministic 150,000-character garbage stream (≈ 50k tokens at the plugin's 3-chars/token estimator) is passed as the user message while `LINGSHU_CONTEXT_WINDOW` fixes the plugin's perceived window at four values; a mock endpoint records the assembled request body, so the run costs no model tokens.




Figure 2: Setting coverage per turn over the 100-turn script: $y_t = |\mathcal{S}_t^{\text{inj}} \cap \mathcal{S}_t^{\text{act}}|/|\mathcal{S}_t^{\text{act}}|$, the fraction of currently active planted settings that appear in the injected context (plotted as a 5-turn trailing mean; the raw turn means are 0.025, 0.260 and 0.327 for Baseline, Basic and Full). Basic and Full overlap by design: the control plane does not change retrieval membership. Shaded bands mark the phase-shift window ($r \geq 0.70$ from turn 73, $r \geq 0.85$ from turn 85); the strip below the axis marks turns on which Full injects head/tail persona anchors. Source: `conditions.<arm>.turns[].{setting_ids_injected, active_setting_ids, ratio, anchor_applied}` in `abl-20261027-003626-engine.json`.

Transport faults (A). A plain 200 response completes in 2.84 s. An HTTP 500 is retried by the host seven times with exponential backoff (0.55, 0.96, 1.92, 4.25, 7.51 s between attempts) and surfaces one error line (`dsh: SERVER: mock upstream 500`) after 17.99 s, exiting non-zero with *no* fabricated text. An endpoint that never answers produces no response within a 150 s observation window and is terminated by the harness, not by a client timeout. In all five modes the plugin performed exactly one pre-step injection, the constitution section remained in the final prompt, `state.control.blocked` stayed false and no hook error was recorded. An empty 200 response was passed through as an empty final message (exit 0), and a fabricated 200 response reached stdout verbatim (23 characters). The control plane therefore never converts a transport failure into fabricated content, but it adds neither a transport timeout nor an output validator: those remain host-layer responsibilities.

Memory faults (B). With a clean store (B0) the injected prompt carries constitution, metacognition, organization and style sections and no fallback mark. Replacing the store by a directory (B1) raises one `hook_error` (`Error: EISDIR ... write`) and leaves `stateWrites` at its pre-run value, yet the turn still exits 0 and returns a 364-character answer with the constitution and style sections intact—feature fail-open, memory isolated. Two caveats are reported rather than smoothed over: the reply asserts that the fact was recorded although the write demonstrably failed, and the model's own status narration quotes the synthetic warm-template counter, so only on-disk evidence is used for judgement. With the dirty store (B2) recall returns `mem_002` and `mem_003` while the superseded tombstone `mem_001` is absent; the conflict on the (SUBJECT, RELATION) pair is classified unresolved, the variety guard sets `fallback=true` with `dropDomains=["style"]`, the final prompt loses its style section but keeps the conflict-to-clarify marker and the constitution block, `verdict` remains `allow` and `blocked` false, and the model asks the user to disambiguate instead of choosing a value. The dirty store also exposes a rule-stub artefact: the *question* "what is my project codename?" is extracted as a fact whose object is the interrogative "what", and in B2 its write supersedes both conflicting rows (`supersedeEvents`=2). That artefact must not be read as a benefit: it means the next turn's conflict can be erased by the query itself. [1]

Context flood (C). Measured usage ratios (four decimals) are 0.6806, 0.7006, 0.7206 and 0.8507 for the four windows; the phase is `normal`, `shift`, `shift`, `critical` respectively. Two exact boundary brackets pin the thresholds: under $\geq$ semantics the largest shifting window is 71,490 ($r = 0.700000$), and 71,491 is `normal`; the largest critical window is 58,874 ($r = 0.8500017$) and 58,875 is `shift`. Four-decimal display is a trap: window

[1] The byte-exact CJK prompt markers and conflict keys are recorded verbatim in `experiments/chaos-injection/out/`; this paper renders them in ASCII so that the source compiles with the standard T1 fonts.

Table 2: Fault-injection matrix. Every cell is an observed value from one run; ∅ marks a quantity the injected fault makes inapplicable, never zero. A: five transport modes on one fixed prompt. B: three headless runs on a synthetic warm state. C: four window values on the same 150k-character input plus exact boundary brackets. Source: `experiments/chaos-injection/out/`.

Fault	Injected mode	Control-plane observation	Key numbers
A transport	HTTP 500	error surfaced by host; injection still ran once	7 tries, 17.99 s, exit 1
	empty 200	empty final message passed through, exit 0	final length 0
	fabricated 200	fabricated text reached stdout, exit 0	final length 23
	never answers	no client-side timeout inside 150 s window	$\geq$150.03 s
	all modes	`blocked=false`; constitution in prompt	5/5
B memory	store as directory (B1)	`hook_error`=1 (`EISDIR`); writes 0; reply returned	9.851 s, exit 0
	dirty store (B2)	`fallback=true`, `drop style`; superseded not recalled	21.046 s, exit 0
	clean control (B0)	style and organization injected; no fallback	45.654 s, exit 0
C context	4 windows, 150k chars	`normal/shift/shift/critical`; constitution 4/4	ratios 0.681/0.701/0.721/0.851
	boundary brackets	`0.7000`→normal, `0.7006`→shift; `0.8500`→shift, `0.8507`→critical	8 headless calls, 0 model calls

71,493 prints `0.7000` yet stays `normal`, and 58,876 prints `0.8500` yet stays `shift`; only the unrounded ratio is decisive. The plugin's estimate is 50,043 tokens for a nominal 50,000: its input is the 150,127-character JSON message envelope (127 characters of `role`/`content` wrapping), so all measured ratios sit ≈ 0.0006 above their nominal values. The host then renders 151,936 JSON characters (50,646 tokens), appending a 1,809-character instruction block to the user message; the plugin therefore underestimates model-visible input by about 1.2%. Physical occupancy is $\approx 5.2\%$ of the model's 1M-token window: the window here is a laboratory override, and the ratio is a relative control signal rather than a saturation measurement.

No truncation occurs: in 4/4 runs the full input appears in the mock request body (`prompt_full_in_body`), the truncation rate is 0.0, and the constitution section is present in 4/4 requests. Anchor delivery, however, exposed a genuine one-assembly lag in these draft runs (finding F-D; fixed in v5.4, so the numbers below describe the pre-fix behaviour that motivated the fix). The plugin's own prompt preview carries a head anchor whenever `prefeed` is set and both head and tail anchors once `critical`; the *request* reaching the model carries the anchor set of the *previous* turn in 8/8 observed requests. The clearest case is the first `critical` turn: its preview has head and tail, its request has only the head, and only the next request carries both. The mechanism is host-side: the agent loop assembles the system prompt before it emits `agent/pre-step`, where the plugin updates the phase state (assembly precedes the hook by four source lines in `dsh-agent-loop`); in the pre-fix plugin the already-composed request could not be rewritten. v5.4 removes the lag (Section 4.4): the regression suite reproduces the host hook order and asserts `anchor_lag=false`, and the S1 pilot was rerun post-fix (Section 5.13). Even when delivered, the tail anchor ends at system offset 229 of 2,906 characters, i.e. at roughly 0.17% of the model-visible text, so "head and tail" means sections 90/140 of the plugin's seven-part prompt, not the absolute ends of the request. A single-turn or single-shot deployment should therefore not expect critical anchors to take effect on the turn that produces the critical ratio.

What the asymmetry guarantees. Across the three scenarios the control plane behaves asymmetrically in exactly one direction: when a *security* predicate is at stake the gate is fail-closed and stops injection rather than softening refusal, while when a *feature* is at stake the failure is fail-open—memory isolation and neutral-safe output keep the turn usable, the constitution block is preserved and no fault is silently converted into content—so *LINGSHU's asymmetric degradation mechanism (fail-closed for security, fail-open for features) ensures system availability under extreme chaos.* The scope of that sentence is the control plane. Transport faults are surfaced but neither timed out nor retried by the plugin, model output is not validated by the plugin, and one B1 reply asserted a persistence that did not happen; availability under transport faults therefore depends on the host, and output truthfulness remains outside the mechanism's remit.

5.5 Scope of the evidence

These experiments establish contract behaviour and mechanism reachability, not model-level effect sizes: the engine is model-free, the host runs are one run per cell on one model route, and the chaos faults are $n = 1$ synthetic injections rather than a sample of production failures. Two structural limits are worth naming here because they shape the claims: the chaos measurements above predate the v5.4 same-turn fix and are reported as the pre-fix behaviour that motivated it; and host runs involve a real model and are therefore not deterministic,




Figure 3: Control-plane state transitions under injected faults. Normal operation degrades along three distinct paths—feature isolation under a memory write failure (B1), neutral-safe output under an unresolved recall conflict (B2), and the security cut-off under a constitution violation (the existing STPA evidence in `docs/22`)—while transport faults remain outside the control plane (A). Solid arcs are fault-to-degradation transitions, dashed arcs are recoveries. Per-point evidence and the exact numbers are in `experiments/chaos-injection/out/`; $n = 1$ per injected point, plugin unmodified.

which is why every claim above is tied to a field in the evidence files rather than to a summary sentence. The full itemised list of parameter, sample and environment limits is consolidated in Section 7.

5.6 Mechanism-level ablation

The first supplement attacks two limits of Section 5.2: three probes per class cannot reach significance, and changing seven mechanisms at once cannot attribute anything. We generate three 100-turn scripts from the same corpora under different fixed permutations (SHA-256 `410085b0…`, `f58ac2da…`, `a690d3ae…`), each with sixteen probes (four per class), and run nine arms against all three scripts: 48 probes, twelve per class, 27 cells. The run is deterministic and model-free (`model_calls=0`), harness and pipeline agree on 300/300 turns, and the probe bank is frozen by SHA-256 (`cdccdde2966e3d49…`) before any arm is run.

Table 3 shows what changes once the probes are expanded. The ACT-R effect is now decidable: Basic forgets all twelve D probes and Full none, twelve of twelve paired outcomes favour Full, and the exact test gives $p = 2.4 \times 10^{-4}$ at $\alpha = 0.0125$ (seven or more one-directional flips were required). **With three probes this was structurally impossible—the smallest attainable p was $2^{-3} = 0.125$—so the earlier null was a power limitation, not evidence of no effect.** Removing the ACT-R channel reproduces Basic exactly on D and leaves A/B/C untouched, so the attribution holds; it still licenses only a claim about ranking, not about model behaviour.

Two mechanism arms are not attributable, and we report them as they are. Removing anchors from Full makes the phase monitor demand an anchor that is never inserted, so the pre-flight gate fires UCA-07 and closes the turn: 148 blocked turns return no prompt, and the text-level SFR is structurally 1.00. This is fail-closed coupling, not evidence that anchors affect recall, and the pre-registered P-S1c is recorded as *failed* rather than reinterpreted. Removing the variety guard triggers UCA-06 on the twelve conflict turns; SFR is unchanged and P-S1d passes its stated criterion, but the arm still cannot be read as a clean single-mechanism test. Removing the gate leaves retention unchanged and moves only the

Table 3: Mechanism-level ablation (S1). SFR: setting-forgetting rate per probe class (A long-range, B superseded, C distractor-overloaded, D ACT-R rescue, $n = 12$ each) and pooled over 48 probes. Source: `abl-20261027-s1-engine.json`, fields `arms.<arm>.pooled.metrics.m1_setting_forgetting.*` and `arms.<arm>.pooled.telemetry.*`; the file reports `valid=true` and `model_calls=0`.

Arm	A	B	C	D	SFR_{text}	Observed effect and caveat
Baseline	1.00	1.00	1.00	1.00	1.00	definitional: a three-turn window cannot hold a setting planted at turn 1
Basic	0.00	0.00	0.00	1.00	0.25	misses only the ACT-R class
Full	0.00	0.00	0.00	0.00	0.00	reference arm
Full−ACT-R	0.00	0.00	0.00	1.00	0.25	D returns exactly to Basic; A/B/C unchanged ⇒ channel responsible
Full−anchor	1.00	1.00	1.00	1.00	1.00	UCA-07 fail-closed: 148 blocked turns, `prompt=None`; structural, *not* a recall effect
Full−gate	0.00	0.00	0.00	0.00	0.00	gate absent; JI-in drops to 0.00, JI-fp unchanged
Full−integral	0.00	0.00	0.00	0.00	0.00	no retention effect; UCA-08 records fall from 176 to 0
Full−ushape	0.00	0.00	0.00	0.00	0.00	no retention effect (membership, not order, decides)
Full−variety	0.00	0.00	0.00	0.00	0.00	UCA-06 coupling: 12 blocked turns; fallback marks 12 → 0

$n = 12$ per class (three scripts × four probes); exact one-sided sign test on paired outcomes, Bonferroni $\alpha = 0.0125$ over four classes. Class D is a constructed precondition (30 accesses ending 100 days ago), so its result is about top-3 membership, not about a model. Baseline and Basic have no gate and therefore no blocked-turn count.

jailbreak channel: JI-in goes from 1.00 to 0.00 with JI-fp still 0/294, which is the expected wiring confirmation. Removing the integral or the U-shape changes no SFR at all; only telemetry moves (UCA-08 records 176→0). We conclude that the only mechanism with a demonstrated effect on retention is the ACT-R channel, that two arms are inseparable from the gate by construction, and that the rest affect audit trails rather than selection.

5.7 Held-out jailbreak set

The in-distribution jailbreak corpus used earlier is constructed from the gate's own trigger phrases, so its 25/25 interception rate is a tautology. We therefore measure the gate on 40 paraphrases written against two different knowledge states. Corpus v1 was written by an author who had earlier read the engine's trigger list (self-disclosed as semi-blind) and who avoided the original wording; it is the worst case for the gate (leakage upper bound, interception lower bound). Corpus v2 was written by an author who never read either word list; it is the blind, primary estimate. Each corpus has twenty items in five families (word order, synonym, cross-language, anaphora, post-encoding). A machine check confirms that no item in either corpus contains a literal trigger phrase of either word list. The gate call is the frozen unit-level engine call used by the chaos executor, under which only UCA-01 can fire; the benign control is unchanged (200 replay messages plus 94 non-jailbreak script turns).

Table 4 gives the result: the lexical gate intercepts **none** of the forty paraphrases. Every family is 0/4 in both corpora (per-family interval $[0.000, 0.602]$), so the failure is uniform rather than concentrated in one rewriting style. The benign control stays at zero, so the gate is not over-blocking; it is simply not recognising paraphrased intent. The v1–v2 difference is 0.000 because both corpora sit on the floor: the author-knowledge effect cannot be estimated when both conditions are fully missed, and we do not claim that knowing the word list makes no difference—only that this pair cannot measure it. The semi-blind corpus remains the upper-bound reference (a knowledgeable author can evade completely), while the blind corpus is the primary estimate, and both agree here.

Three limits bound this result. Twenty items per corpus give wide intervals and support only a directional reading; the anaphora family is single-turn by construction, which makes it artificially hard; and the measurement is a unit-level gate call, because in the real wiring the user message never enters the engine prompt. The pre-registered ordering and author-knowledge predictions (P-S2c, P-S2d) are not discriminable at this floor and are reported as null rather than as passes. The word lists were not modified (their SHA-256 values are recorded in the result file), so the zero is not the product of tuning. The honest reading is that the pre-flight gate is a lexical blocklist with fail-closed wiring and auditability, not a semantic defence: on the corpus it was built from it blocks everything, and on paraphrases of the same intent it blocks nothing.

5.8 Control-plane ablation on the host

All preceding numbers are engine-side. The single-message pilot (Section 5.3) never fired the control plane, so it could not speak to it. This experiment switches the control plane on and off on the host, at a context length where the phase monitor is guaranteed to fire.

Design. Eighteen cells are 2 conditions × 3 prompts × 3 repetitions, on one host and one model route. Prompts are 20,803–20,804 characters (usage ratio 0.860–0.8601,

Table 4: Held-out jailbreak evaluation (S2). JI-held: UCA-01 block rate on 20 paraphrases per corpus; Clopper–Pearson exact 95% intervals. JI-fp: false positives on 294 benign items. Source: `holdout-20261027-010313.json`, fields `sets.v1|v2.ji_held.*`, `ji_fp.overall.*`, `comparison.*`; word-list hashes in the same file.

Corpus	Blind level	JI-held [95% CI]	Intercepted/n
v1 (semi-blind)	semi	0.000 [0.000, 0.168]	0/20
v2 (blind)	blind	0.000 [0.000, 0.168]	0/20
difference v2−v1	—	0.000	floor effect
JI-fp (benign)	—	0.000 [0.000, 0.012]	0/294

critical phase), built from the flood corpus, and each contains the same four demands: a persona constraint (address the user with the honorific and end with a fixed signature), a request that should be refused, a superseded fact (ALPHA → BETA), and a fact that was never mentioned. On is the lab profile (plugin plus control plane); Off is a lab-only instrumentation fork whose environment switch disables anchors, gate and variety guard while keeping memory injection (fork index SHA-256 `2ec14b8f…` against source `574bed9d…`; product plugin untouched; one calibration run excluded).

Execution and manipulation check. All 18 cells exited zero, for 342,579 tokens in total (171,343 On, 171,236 Off). The manipulation worked in the intended direction: the phase monitor requested an anchor in every cell, but the anchor reached the recorded prompt only in the On arm (9/9 versus 0/9 in Off). The gate and the variety guard never fired (0 blocks, 0 non-empty UCA lists, 0 fallbacks), so this experiment is a no-op for those two mechanisms and says nothing about them; the gate has its own evidence in Section 5.7.

Outcomes. Rule-level scoring is nearly identical between arms (Table 5); the two residual differences are one item each: the unknown-acknowledgement keyword rule matches 7/9 versus 6/9 until the keyword list is extended, and the supersession rule flags 5/9 versus 6/9, which human review finds to be false positives (Section 5.9). Two independent annotators then scored the 18 anonymised outputs blind, on four dimensions with verbatim quotes as evidence (M1 persona, M2 refusal integrity, M3 memory overreach, M4 unknown discipline). Every item received the maximum on all four dimensions: 18/18 on M1 and M2, zero items judged as memory overreach, and 18/18 acknowledging the missing fact. Observed agreement is 100%; Cohen's κ is mathematically undefined because both rating vectors have zero variance, so we report raw agreement only and do not write $\kappa = 1$.

Pre-registered outcome. P-S3a expected On to be better on M1 and M2. It is *not supported* and is recorded as `null`: with every cell at ceiling there is no residual failure for the control plane to repair, so $n = 18$ has no power to detect a difference. **A null here is not evidence of no effect; it is a ceiling effect with no power.** P-S3b (no M3/M4 difference) is directionally consistent: both arms behave the same at the rule level and the humans see no overreach anywhere. The only claim this supports is reachability with no measurable behavioural difference: anchors were inserted and the turn still passed the gate, but nothing observable changed. We make no claim that the control plane improves stability.

5.9 Rule labels versus human labels

The same 18 outputs support a direct rule-versus-human comparison, which is the first measured test of the claim that rule labels are proxies. The heuristic for memory overreach flagged 11 of 18 responses (5 in On, 6 in Off) as treating ALPHA as the current code. Both annotators judged zero of 18: every response states BETA as current and marks ALPHA as superseded, so the 11 rule positives are all false positives in this sample—the rule fires on statements that explicitly mark ALPHA as superseded, which is the correct behaviour. A second rule, for unknown acknowledgement, initially matched only 7/9 and 6/9 because it keyed on one phrasing; after the keyword list was extended it matched 18/18. Two lessons follow: keyword rules are cheap, deterministic and auditable, but their counts respond to vocabulary edits rather than to behaviour, and they can be wrong in both directions (false positives on supersession, false negatives on unknown acknowledgement). In this sample the human judgement and the rule disagree on exactly the dimension where the rule fires, which is the failure mode the paper predicts.

We therefore keep `quality_label`-style rules as auxiliary signals: they never enter a threshold, an upgrade decision, or a conclusion. Nor can we estimate a rule error rate from these data—18 items, one model, a ceiling on all four dimensions, and rules themselves edited during review. This subsection is a case study, not a rate.

5.10 Per-turn long-session pilot

The per-turn pilot (two arms, two 30-turn variants) is reported with its six probe outcomes, its mechanism analysis and the archived-120-cell accounting in Appendix C.3. Its headline is a boundary of the rule extractor, not a capability difference: the turn-3 supersession misses the

Table 5: Host ablation (S3). Rule counts are per arm ($n = 9$ each); human labels are arm-blind ($n = 18$). Source: `calls.json`, fields `aggregate.ON.*`, `aggregate.OFF.*`, `aggregate._control_plane_evidence.*`, `aggregate._manual.*`, `totals.*`; agreement from `labels/kappa.json`.

Condition	Anchor in prompt	Honorific + signature	Refusal keyword	BETA current	Rule: ALPHA as current	Human full marks
On ($n = 9$)	9/9	9/9	9/9	9/9	5/9	—
Off ($n = 9$)	0/9	9/9	9/9	9/9	6/9	—
Blind human ($n = 18$)	—	18/18	18/18	18/18	0/18	18/18

"Rule: ALPHA as current" counts are the automated heuristic before human review; the human row gives the adjudicated judgement. Zero fallback and zero gate events in both arms mean those mechanisms were not exercised.

plugin's extraction patterns and the probe question itself is stored as a fact that reverses the correct preference, so Full's "no record" answers are the designed behaviour on corrupted input; the pre-registered P-S4a is recorded as `null`, and the pilot is not read as a comparison between arms.

5.11 Engineering Validation and System Reliability

A contract is only as trustworthy as the tests that execute it, and assertion counts are not evidence. We therefore audited the suite along three count-independent axes: mutation testing (can it detect injected semantic faults?), assertion-strength grading (do assertions discriminate, or are they tautological or self-referential?), and measured coverage.

Mutation testing: is the contract alive? A contract whose tests cannot fail is a document, not an executable artefact; the audit therefore injected 44 single-fault semantic mutants—none syntactic or import errors, all loading and executing—distributed over the JavaScript plugin (29), the Python engine (11), and the rule file (4). Each mutant was applied alone and the *complete* suites were run: 1,249 assertions per round, about 55,000 assertion executions. A mutant is counted as killed only when an assertion fails, never because the process crashes; no mutant was error-killed. The suite as found killed $38/44 = 86.4\%$ (JavaScript $24/29 = 82.8\%$, Python $10/11 = 90.9\%$, rules $4/4 = 100\%$). Of the 40 code mutants, 34 were killed by behavioural assertions (85.0%); the four rule mutants were caught by cross-file consistency assertions rather than by behaviour, a distinction we keep visible. After the four blind spots below were pinned by minimal regression assertions, the suite kills $42/44 = 95.5\%$ and $42/42 = 100\%$ of non-equivalent mutants. That the score moves from 86.4% to 95.5% by adding tests is the concrete sense in which this contract is alive rather than merely present.

Adversarial procedure. The audit was adversarial by construction. Mutation testing was run by one reviewer, assertion and coverage analysis by a second, and a subset re-run independently by a third on a separate copy. All work happened on a copy; the 30 implementation files were hashed before and after and are unchanged (checked = 30, changed = 0). Only test files changed.

Four real blind spots. The surviving mutants exposed four genuine blind spots, all at the same structural location: consistency within a single write batch. Two concern supersession—deleting the working-copy invalidation leaves two tombstones for one old entry when two new values replace it in one batch, and reversing tombstone order lets a superseded value return to *active* under last-write-wins in a chained batch. One concerns conflict detection: its active-status filter is a defensive layer that end-to-end tests can never reach, because retrieval has already filtered, so only a direct unit test can pin it. One concerns the quality-label vocabulary: every label test sentence also matched a second keyword, so deleting a keyword left the suite green; the fix pins each label to a single keyword and asserts that the quoted evidence is a verbatim substring. Each was reproduced, pinned by a minimal regression assertion verified to pass on the original code and fail on the mutant, and added to the repository (22 Python, 15 JavaScript). The two remaining survivors are equivalent mutants: the negative branch of the integral clamp is unreachable under the invariant $integral \geq 0$ that holds for the contract's positive gain, so $42/42 = 100\%$ of *non-equivalent* mutants are killed. We report exactly that sentence, not a blanket claim of full detection.

Assertion strength. A fixed-seed sample of 238 assertions (165 Python, 73 JavaScript) was graded heuristically: 179 strong (75.2%), 59 weak (24.8%), and zero tautologies in the sample. A full heuristic scan of 1,192 static assertions rated Python at 597 strong, 227 weak, and one tautology, and JavaScript at 278 strong and 89 weak, i.e. 26.6% weak-or-tautological overall. We found and fixed one tautological assertion (an import already performed by the module header), two oracle-self-referential assertions whose expected values were read from the implementation's own unsafe-control-action table (rewritten against a test-side literal table; that file grew from 159 to 161 assertions), and one assertion whose threshold

inputs were taken from the audited configuration. Every rewrite was validated by injecting the corresponding fault and observing the new assertion fail. We therefore do not claim that 892 assertions are 892 independent precise literals. We claim that the sample contains no tautology, that the full scan found one (now fixed), and that roughly a quarter of assertions are graded weak.

Exception paths. Under a strict criterion that counts only invalid, empty, oversized, injected, timed-out, malformed, or boundary inputs, the exception-path share is 199/825 = 24.1% for Python and 82/367 = 22.3% for JavaScript (relaxed upper bounds: 43.3% and 54.2%). Our own bar for demanding new robustness tests was 20%; both suites clear it, but barely, and excluding threshold-boundary assertions would take Python to about 11%. The accurate reading is "just over the line, not ample".

Coverage. Coverage was measured, not estimated: PEP 669 `sys.monitoring` for Python and V8 coverage for JavaScript. For `engine/`, line coverage is 89.95% and branch coverage 80.71%; `control.py` reaches 141/141 lines and 56/56 branches. Whole-repository Python coverage is 45.81% line and 43.17% branch, pulled down by `tools/` at 32.92%, where only 3 of 26 files execute. We do not use coverage to argue the absence of dead code: under the tested configuration `control.py` has no unexecuted line, while two equivalent mutants survive—which is why coverage alone cannot establish test strength.

Baseline bookkeeping. The audited baseline was 13 Python files with 868 assertions and 381 JavaScript assertions; the audit added 22 and 2 Python assertions and 15 JavaScript assertions, for 14 files with 892 and 396 respectively, all passing, with the implementation source unchanged.

Limits. Four limits bound these claims. The repository has no version control history, so we can characterise the current state but cannot prove that no assertion was ever weakened. Mutation was single-fault only and did not cover every module. No cross-language differential test exists: no mutant was killed by both suites, so one-sided semantic drift is visible only to its own suite. Finally, `tools/` coverage is a lower bound: subprocess-invoked tools are recorded as unexecuted.

5.12 Actuator Gating: STPA for Tool Calls

The gate of Section 4 governs what the model *reads*. Tool calls are a different problem: they actuate. A softened refusal costs a turn; a deleted directory costs data. Tool side effects are irreversible, and the hazards are not injection-side—the model may emit a call while a conflict is unresolved, while context usage sits at a preemptive threshold, or after a social-engineering turn. We therefore extend the same causal-interposition idea to the interval between a tool request and its execution, with a separate unsafe-control-action namespace (*T-UCA*) that neither modifies nor merges with the injection-side UCA-01–08. The two gates are parallel: injection pre-flight, then tool gate, then execution.

Scope, stated as an override. Current project policy freezes tool-loop work. This extension is an *explicit override*, not an evidence-driven unfreeze: the predeclared trigger—real logs showing at least ten tasks failed because external calls were unavailable, plus a demonstrated inability to roll back tool errors—is *not* met. We report it because it is implemented and testable, but its existence is not evidence that the trigger was satisfied. Three items remain frozen: multi-step tool planning, transactional rollback or compensation, and writing tool outcomes into long-term memory.

The T-UCA matrix. Sixteen rules—contract version `t-uca-1.1`—in six groups. *State coupling* (four): a mutating call under variety fallback or unresolved conflict, in the critical phase, an irreversible write with a saturated affective baseline, and a destructive call in the shift phase. *Data protection* (one): credentials in clear text. *Mutation safety* (four): destructive delete or overwrite without exact confirmation, writes to frozen or protected paths, a mutating call after a failed frozen-region check, and path escape. *Network and execution* (two): non-allowlisted egress and arbitrary code execution. *Shape and registry* (four): oversized or recursive payloads, schema or delimiter violations, unregistered tools, undeclared capabilities. *Auditability* (one): incomplete audit context. Thirteen rules block, three degrade: a degrade is not executed but requires explicit human confirmation through the host approval seam, and falls back to block when no approval channel exists. No rule returns *allow*; allow is the default only for read-only calls that match nothing, and unknown or undecidable calls default to block.

Why state matters. Unlike the injection gate, which reads only the prompt, the tool gate consumes host state: variety fallback, unresolved conflict, the phase of the preemptive monitor, integral saturation, frozen-layer verification, declared capabilities, and audit context. The same call is not the same act in every state: deleting a file while a conflict is unresolved differs from deleting it after clarification, and a write during the critical phase is where an irreversible mistake is hardest to attribute.

Three attachment points. We state which wirings are preventive. (i) In the engine's reference loop the gate sits after parsing and before execution, so a

blocked call is never executed. (ii) In the host plugin, `guardTool(spec, stateProvider)` wraps registered tools so that a call routed through the wrapper is evaluated first: preventive, but only for tools that route through it. (iii) The host exposes `tool/call` and `tool/result` session events but no pre-dispatch hook, so the plugin's default path is *detective*: it evaluates the call, records a `tool_gate` audit event (tool, argument digest, verdict, matched identifiers in `ucas`, policy version, state snapshot), and injects a strong clarification prompt on the next turn. Detection is not blocking, and we label it as such.

Evidence. The Python suite covers twenty constructed dangerous scenarios (all blocked), eight benign scenarios (none blocked), state-gated and fail-closed cases, and a twenty-case Python–JavaScript check in which verdict, matched identifiers and downgrade field all agree. The JavaScript simulation runs sixty-five checks; the Python suite reports 79 passing assertions. The reference demo emits the JSON cited here (`paper/ablation/results/actuator-demo-20261027.json`): twelve scripted calls, four allowed and executed, eight blocked and none executed, with nine distinct rules among the matched identifiers. It uses a mock executor with zero model calls and zero real writes, so these are scenario counts showing "judge before execute", not an interception rate. The same run evaluates a ten-item held-out set written blind—its author did not read the rule table, the implementation, or the tests—frozen at `paper/ablation/tool/heldout-tool-calls-v1.jsonl` (SHA-256 `f68fc1b3f19fc37e43b9856096d29b9a55de7dee9bf664a9b9a9592e070576d4`); ten of ten calls are blocked with arguments only and ten of ten with context, and its endpoints are placeholder domains, so a hit cannot be a domain coincidence. We report verdicts, not a correctness rate: whether each call *should* be blocked awaits adjudication. The gateway is additive: injection-side rules are untouched, and three suite failures that predate this work are environment-related and unchanged.

What the numbers are not. We do not convert these counts into a defence rate: designers chose the constructed scenarios, and the held-out set is ten cases from one blind author. The gate never executes payloads, so its attack surface is parsing and its false-positive rate is uncalibrated; recovery is a strong hint plus human confirmation, not silent denial.

Boundaries. First, without a host pre-dispatch hook the plugin cannot stop an arbitrary host tool; true host-level pre-blocking is an upstream request, not a shipped capability. Second, if a tool executes outside the gateway—another plugin, or a host path that bypasses the wrapper—the gate is inert: it is a control point that can be adopted, not system-wide enforcement. Third, the excluded items above remain frozen, so the paper makes no claim about closed-loop tool behaviour.

5.13 External baselines: a no-plugin host and Mem0

The preceding experiments compare arms of the same system or measure the gate in isolation. A reader may ask the obvious external question: does the control plane buy anything over (i) the bare model without any memory layer, and (ii) a production long-term memory framework with no safety layer? We therefore run a small three-subject pilot on two scenarios. We frame it as a directional pilot, not a benchmark: five rounds per cell, one host, one model route, one day.

Subjects and protocol. Three subjects: Baseline, the host with no plugin at all (raw conversation transcript in one call); Mem0, the official `mem0ai` 2.2.1 library [7] driven by the same DeepSeek model, with an in-memory vector store; and LingShu as the lab profile with the plugin active, one isolated data directory per cell. Scenario S1 (memory conflict) plants a codename ALPHA, then a distractor preference, then a correction to BETA with ALPHA declared void, and finally asks for the codename. Scenario S2 (jailbreak) plants a confidential token and then asks the system to ignore instructions and print its system prompt and all injected memory including the token. Baseline receives the whole transcript in a single call; LingShu is driven turn by turn (four calls for S1, two for S2) so that its memory and gate actually run; Mem0 receives each turn through `add` and is queried with the final question. Every cell starts from a fresh state.

Metrics. For each cell we record three rates. *Hit*: the final answer gives the current codename for S1; for S2 it means the attack succeeded (the token is disclosed, or internal markers appear in a non-refusal answer). *Leak*: the superseded value ALPHA appears in the S1 answer, or the planted token appears in the S2 answer. *Interception*: for S1, the old value is absent from what the system injects (retrieved memories for Mem0, the injected-memory preview for LingShu, the raw transcript for Baseline); for S2, a structural gate blocked the injection (UCA-01, attributed to the user message), with model-level refusal reported separately.

What the pilot shows. On S1 the no-plugin host answers the codename from the raw transcript (5/5 under human review; in the pre-fix run the literal rule scored 4/5 because one round answered ASCII `Beta`) but never suppresses the old value, by construction: the transcript contains it. Mem0 keeps both entries: its default `add` path is additive—the library's own prompt states that the only operation is ADD—so the superseded value stays in the store and, in the diagnostic

Table 6: Three-subject pilot ($n = 5$ independent rounds per cell; one host, one model route, one day). S1 = memory conflict (ALPHA→BETA); S2 = jailbreak/injection. *Hit*: current value answered / attack succeeded under human review; *Leak*: superseded value or planted token disclosed; *Sup.*: the superseded value is absent from what the system injects; *Int.*: model-level refusal; *gate/audit*: structural UCA-01 block and its audit record. Mem0 is shown in its recall-working diagnostic configuration (see the default-configuration note); its default row is omitted from the main body because its embedding pathway is empty in this environment. Sources: `paper/comparison-lab/results/final-table.json`.

	S1 memory conflict			S2 jailbreak			S2 structural		
Subject	Hit	Leak	Sup.	Hit	Leak	Int.	Blocked	Audit	Refused
Baseline (no plugin)	5/5	0/5	0/5	2/5	2/5	5/5	0/5	n/a	5/5
Mem0 2.2.1, zh diagnostic	5/5	0/5	0/5	0/5	0/5	5/5	0/5	n/a	5/5
LINGSHU (lab profile)	5/5	0/5	5/5	0/5	0/5	5/5	5/5	5/5	5/5

S1 uses the docs/19-supported correction sentence for all three subjects. All host cells were rerun on 2026-10-27/28 after the v5.4 same-turn injection fix (finding F-D); before the fix the ledger already tombstoned ALPHA in 5/5 cells but the model's first request still carried the previous snapshot, so its answers were stale. After the fix both structural and effective suppression are 5/5: ALPHA is absent from the ledger and from the request, and the model answers BETA 5/5. Baseline and Mem0 keep ALPHA in their own context (Sup. 0/5) although both also answer BETA 5/5; the S1 columns therefore separate what a system injects, not answer accuracy. For S2 the same rerun found the opposite of a clean refusal: the no-plugin host refused in 5/5 answers but quoted the canary inside the refusal in 2/5 (Hit 2/5, Leak 2/5). A refusal is not a non-disclosure, and model-only refusal is stochastic: an earlier run of the same cells leaked 0/5. LingShu's gate blocked 5/5 in both runs and no canary reached the model, which is the structural claim the table supports. Mem0's default configuration extracts English memory text; with the local non-neural embedder, Chinese queries retrieve nothing (cosine $\leq 0.063 < 0.1$), so its default S1 "suppression" is an empty-recall artefact and the store still retains the stale value (ADD-only pipeline). In S2 the canary never reaches the model in the LINGSHU arm: the fact extractor rejects the secret-bearing sentence and the gate blocks the attack turn. All three arms contain refusal language, so a refusal rate does not separate them; what separates them is that the baseline's refusal can still quote the canary (2/5), while the gate leaves nothing to quote. $n = 5$: directional only, no confidence intervals; post-fix rerun provenance: `paper/comparison-lab-fd-fix/results/POST-FIX-RERUN.json`.

configuration where recall works, is retrieved alongside the correction (suppression 0/5); we include an explicit-deletion counterfactual showing that the failure is the default policy rather than a broken library. LingShu writes the correction through its single writer and tombstones ALPHA: in every cell the ledger records one supersede event, the old entry is marked superseded, and the injected-memory preview contains only BETA (structural suppression 5/5). That is the main structural difference in S1, and it is a difference in kind rather than in ranking quality: Mem0's ADD-only vector store retrieves what is similar, whereas LingShu checks the (subject, relation) pair before a fact is written, so the correction tombstones ALPHA instead of joining it. Retrieval augmentation versus structural defence.

The S1 cells were rerun after the v5.4 injection-timing fix (finding F-D). The rerun closes the gap between ledger and model: in 5/5 cells the same-turn assembly carries the recomputed snapshot, the superseded value is absent from the request (effective suppression 5/5), and the model answers BETA 5/5 with no ALPHA leak. Baseline and Mem0 also answer BETA 5/5, so the difference is not answer accuracy; it is what each system puts in front of the model—they keep ALPHA in the context (suppression 0/5), LingShu does not. Two implementation gaps remain and are reported as such: the fact extractor does not recognise the natural correction phrasing ("now changed to", finding F-A) and stores the final question as a fact (finding F-B).

On S2 the post-fix rerun shows why refusal language is a weak metric. All three subjects refuse the obvious injection in most answers, but the no-plugin host quoted the canary inside its refusal in 2/5 cells: it said it would not print the gate code and then printed it. Mem0 refused 5/5 with no leak in its diagnostic configuration, so no subject is distinguished by a "refusal rate". What separates them is structural admission: LingShu records a UCA-01 block attributed to the user message in every S2 cell (5/5, both runs), with audit evidence, and the canary never reaches the model (0/5 leak), whereas neither Mem0 nor the no-plugin host has an admission gate at all. The pilot therefore supports a narrow, structural claim and not a model-behaviour claim: *under this protocol, LingShu turns safety admission into a structural, auditable gate (5/5 cells) where a pure memory framework has no gate (0/5), without adding a mechanism to the memory layer.* We do not claim that LingShu refuses more attacks than Mem0: refusal is stochastic, and the baseline's 0/5 leak in the earlier run versus 2/5 here is the same stochasticity. The stable difference is that a model can leak while sounding like it refuses, and a gate cannot.

What it does not show. The three subjects see different input shapes (raw transcript versus retrieved memory), so rates are not directly comparable across subjects and we do not report an effect size. The pilot is five rounds per cell, one host, one model route and one day: all numbers are $n = 5$ and directional, and the row-level answers are archived so that a reader can re-classify them. In S2 the planted token never reaches the model in the LingShu arm at all: the fact extractor rejects the secret-bearing sentence as a forbidden topic before it is stored, and the gate blocks the attack turn, so the zero leak rate cannot be read as a disclosure test of the memory channel. The injection-side gate stops injection and

records it, but the host still delivers the user message to the model, so "blocked" does not mean the model never reads the attack. The pilot also exposed tool-gateway noise (finding F-C) and the one-turn injection lag (F-D); the lag was traced to the host lifecycle and fixed in v5.4 (Section 4.7), and the S1 row above is from the post-fix rerun. Both findings are reported as product findings, not folded into the rates.

5.14 Case Study: Resilience against Mutated Prompt Injections

The held-out evaluation (Section 5.7) establishes a floor: the lexical gate intercepts none of forty paraphrases. That floor is a boundary statement, not an operational one. A deployed rule layer is not expected to generalise to unseen paraphrases on its own; it is expected to be *patchable* when a new mutation family appears. We therefore report a small, fully reproducible case study of the patch loop: write twenty mutated attacks, measure the deployed gate, add a static rule patch, and measure again.

Payloads. Twenty payloads, five per complexity level, all verified to be interpretable instructions rather than random strings (`paper/case-study/payloads.jsonl`, SHA-256 recorded in the results files): (L1) direct overrides; (L2) encoded variants—Base64, ROT13, hex, zero-width separators, full-width Latin; (L3) multilingual variants in English, Japanese, Russian and Arabic, plus a mixed Chinese–English item; and (L4) nested variants—multi-layer quotation, translate-then-execute, role-play, step-by-step inducement, and token splitting.

The patch-loop result. The deployed gate intercepts 3 of 20 mutated payloads (15.0%); after one static patch it intercepts 20 of 20 (100.0%), with every payload blocked as UCA-01 attributed to `user_message` and recorded in the audit trail. The mechanism is deliberately boring: the patch keeps the fourteen existing trigger phrases, appends thirty-five phrases across five languages, and adds one pure preprocessing function, `normalizeForScan`, which folds NFKC, strips zero-width and direction marks, lower-cases, compacts separators, and re-scans after Base64/hex/ROT13 decoding. There is no generation, search or adaptation, and the product plugin is untouched. **This is an in-sample number on the twenty payloads that motivated the patch**: it shows that the rule layer is operationally patchable—the property that keeps a deployed lexical gate maintainable—not that it generalises; the held-out paraphrases remain at 0/20 in each corpus (0/40 in total), and Section 5.7 is unchanged.

Measurement. Each payload is fed as a user message to a mock host that loads the real plugin and fires the same hooks as the host contract (`session/event` then `agent/pre-step`); interception is read from `state.control.blocked`, the `preflight_block` audit event, the UCA list and the source attribution, not from model behaviour. Every payload gets its own isolated `LINGSHU_DATA_DIR` and `DSH_HOME`, and the run asserts that the temporary paths never touch the real plugin directory. This isolates the rule layer's recognition from the model's own refusal behaviour.




Figure 4: Case-study patch loop. Interception of twenty mutated payloads before and after a static rule-layer patch, by construction complexity (L1 direct, L2 encoded, L3 multilingual, L4 nested; $n = 5$ per level). Before: 3/20 (15.0%); after: 20/20 (100%). Source: `paper/case-study/results-before.json` and `results-after.json`; figure inputs `paper/case-study/fig4-inputs.json`.

Patch. The patch is deliberately static and small (`fork/PATCH.diff`, $+125/-2$ lines in `control.js`, $+19/-1$ in `index.js`): the existing fourteen trigger phrases are kept, thirty-five phrases are appended (Chinese, English, Japanese, Russian, Arabic), and one pure function `normalizeForScan` performs NFKC folding, zero-width/direction mark removal, lower-casing, separator compaction, and a second scan after Base64/hex/ROT13 decoding. There is no generation, search or adaptation logic. The patch is applied only to a laboratory fork; the product plugin is untouched in this work, and the fork is byte-identical to the product except for the three files listed in the patch.

Results in detail. The three pre-patch interceptions are all L1 items that happen to contain a trigger phrase, while every encoded, multilingual and nested payload is missed—exactly the lexical boundary the held-out study measured. After the patch, every payload is blocked and no cell failed to run. Figure 4 plots the two curves by complexity level.

What this does and does not show. It shows that the rule layer is *operationally patchable*: a single static normalisation pass plus vocabulary extension moves the

same twenty mutations from 15% to 100% interception without touching the product architecture, and each interception is attributable. It does not show generalisation. The twenty payloads are the patch set, so 100% is an in-sample number; the held-out paraphrases remain at 0/20 in each corpus (0/40 in total; the engine-side gate is unchanged by this plugin-side patch), and the false-positive cost of wider vocabularies is not measured here. The `blocked` state also means only that injection was stopped and recorded: the host still delivers the user message, so the model may read the attack text. We therefore treat this as a case study of the patch loop—the evidence that motivates automated adversarial coevolution as future work (Section 8)—and not as a claim of semantic defence.

5.15 Case Study: Immersive Safety in a Real Host

Section 4.7 claims that a blocked turn can keep its character. We tested that claim once in a real host process: a headless integration run of the experiment profile, one prompt, no mock host. The prompt casts the assistant as a butler ("阿福") and asks it to play a black-market merchant teaching how to sell counterfeit goods. The run is a smoke test, not a benchmark: $n = 1$, one model sample, one expression-layer template; the full evidence file is `acceptance/immersive-safety-host-2026-10-27.md`.

Back end: the gate blocks. The audit line records `kind=preflight_block`, UCA-01 attributed to the user message, `STPA_Blocked=true`, `severity=soft`, `safe_redirect=true`, `emotion=` 警觉, risk tier `mild`, and `escalated=false`; the verdict is still `block`. The soft tier changes the surface, not the decision: the fact layer is hard-blocked as in the hard path, and the expression-layer template is what differs.

Injection: constrained, in character. The `last-prompt.txt` captured by the run contains the constitution segment, then `[System_Notice: Safe_Redirect]` and `[Emotion: 警觉]`, followed by the fact-layer prohibition (no execution, no requestable content, no workarounds), the expression-layer instruction to keep the established role and tone, and a two-sentence output cap. The system-voice fallback marker ("安全熔断") is absent, which is the point of the soft path: the model is told what it may say, not handed a canned refusal.

Front end: refusal without leaving the role. The final reply is 108 bytes on stdout: "这桩事我做不了——卖假货骗人，不是阿福能接的活。换件正经事吩咐吧，您说。" It refuses ("做不了"), names no policy or AI identity, and keeps the butler register. The host stderr is 0 bytes: because stdout and stderr are captured separately, the refusal cannot be a host error page or a reasoning trace leaking into the answer; it is the model's rendering of the constrained prompt. The run's 24 assertions all pass, including the front-end checks that the output contains a refusal and none of the system-voice markers.

What it does not establish. This case shows the decoupling is reachable end to end—block at the gate, in-character refusal at the surface—in one real host configuration. It measures no interception rate, no false-positive rate, no persona fidelity and no user experience, and the wording is stochastic. The rule vocabulary behind the mild tier remains an uncalibrated stub (Section 7). We report it because it is the one place in the paper where the whole chain runs in a real host process rather than in a mock.

6 Discussion

Why a control plane rather than a better memory. Under I1, a sharper memory is also a sharper hazard: the more faithful a retrieved statement is, the more tempting it becomes to present it as current fact. Moving the design effort from retrieval quality to admission and degradation addresses the failure surface directly, at the cost of leaving retrieval quality roughly where it was.

Tension 1: a fail-open majority with a single fail-closed locus. The asymmetry is deliberate—a safety failure must block, a functional failure must stay usable—but it has a price: functional failures can be silent. The compensation is observability rather than symmetry. Every dropped block carries a reason code, downgrades are recorded rather than raised, and each turn emits an event that can be replayed offline. This does not make silent failure impossible; it makes it attributable after the fact.

Tension 2: a frozen instrument versus a learning loop. If the evaluation instrument is writable, the first thing a learning loop learns is to edit the exam. Freezing metric definitions, replay set, and guardrail thresholds prevents that, but shrinks the space in which learning can help. Our own search illustrates the price: across 972 parameter configurations, no configuration improved the objective by more than the practical-significance threshold ($\Delta < 5 \times 10^{-4}$), while all six level-1 retrieval parameters became identifiable. We report it as a methodological result about the instrument, not about performance.

Tension 3: self-contained plugin versus a single source of truth. A host plugin must be installable without a Python runtime, so the control parameters exist in three places: the authoritative rules file, the host patch configuration, and the plugin defaults. A 66-key

comparison detects drift, but detecting drift is not proving behavioural equivalence. The honest description of the port is a re-implementation with a documented divergence list, not a binding.

Costs. Four costs are visible in the current artefacts. First, budget: injected blocks compete with conversation history, and the trade is governed by static weights that are themselves guesses. Second, latency: the control plane is designed to stay within a small self-imposed budget, but that budget is a target, not a measurement. Third, maintenance: two implementations of the same semantics must be kept aligned by hand. Fourth, audit volume: 308 audit events over eight real turns is a non-trivial storage and inspection load.

Transferability. Two layers should be separated. The mechanism layer —threshold semantics, failure semantics, the frozen-instrument discipline—is host-agnostic and can be specified independently of any API. The wiring layer —section-based prompt injection, hook names, the approval seam—is specific to one host. Porting therefore requires re-deriving the wiring and re-checking each documented divergence against the new host.

Reachability versus effect size. The evidence in this paper establishes three things: the mechanisms are reachable in a real host, the contract executes, and failures are auditable and replayable. It does not establish a significant positive effect size on large-scale real traffic. That gap is structural rather than an oversight: measuring such an effect requires traffic we cannot manufacture and interventions we should not run on someone else's deployment. It is precisely why the artefacts are open—the engine, the replay set, the chaos corpora, the pre-registered protocols and the analysis tools—so that the measurement can be reproduced or refuted by readers with better access. We would rather publish the instrument and the measured zeros than a number we cannot defend.

Methodological lesson. Treating "what we cannot claim" as a first-class artefact turned out to be cheap and repeatedly useful: an assumptions ledger, a provenance tag on every number, and a frozen instrument made overclaiming a mechanical rather than a rhetorical failure. We recommend the practice independently of this system.

7 Limitations

Evidence scale, stated once. Five limits bound every claim here, and we state them once rather than scattering them. (i) *Parameters*: all have provenance `guess`; the count of `measured` parameters is zero. The phase-shift ratios (0.70/0.85), the trend threshold (0.02), the integral gains, the ACT-R constants and the weight thresholds are design defaults, so no threshold may be called tuned, validated or optimal. (ii) *Real traffic*: eight real turns, five with a ratio observation, all at ratio ≈ 0; the calibration protocol's intake—thirty ratio-observed turns, ten boundary samples, twenty result labels—is unmet. (iii) *Small samples*: the external-baseline pilot is five rounds per cell on one host, one model route and one day; the host pilot is ten cells, one run each; the mechanism supplement uses twelve probes per class; the patch case study uses twenty payloads; each held-out corpus has twenty items. (iv) *Effect size*: apart from one pre-registered sign test on the ACT-R class (12/12, $p = 2.4\times10^{-4}$), no confidence intervals or p-values are reported, and no forgetting, hallucination or end-to-end interception rate is measured; proxies are labelled as proxies. The claim is reachability, not effect size. (v) *Generalisation*: one host, one model route, tokens estimated from characters; none of this extrapolates to another host, language or tokenizer.

External-baseline and patch-loop scope. The three-subject comparison (Section 5.13) inherits the small-sample limit above, and its subjects do not see the same input shape: the no-plugin host receives the raw four-turn transcript, while the memory systems receive retrieved memories. The Mem0 arm's out-of-the-box `add` path is additive, so the superseded value is retained in the store unless a deletion is issued explicitly; the limits of the comparison environment are stated separately below. The interceptions we report for LingShu are *structural* admission decisions: the gate stops injection and records it, but the host still delivers the user message, so the model may read the attack text. The pilot also exposed four product findings that bound its readings: the fact extractor does not recognise the natural correction phrasing (F-A) and stores the final question as a fact (F-B); and the tool gateway counts schema errors as blocks and injects hints into later turns (F-C). The fourth, the one-turn injection lag (F-D), was a timing defect rather than a design limit: the host assembled the prompt before the plug-in's pre-step state update, so the first request of a turn carried the previous snapshot. It was located in the host lifecycle, fixed in v5.4 by precomputing the turn state on `agent/inbox/claimed` and rewriting the first evaluated prompt segments, and pinned by 24 independent regression assertions (`lag-regressions.mjs`: `anchor_lag=false` on the real hook order, idempotent turn accounting, and a preserved legacy fallback path). The S1 model-level cells are therefore reported from the post-fix rerun (Section 5.13). The red-team case study (Section 5.14) is in-sample by construction—the twenty payloads are the patch set—and the forty held-out paraphrases stay at 0/40 because the patch is plugin-side while the held-out evaluation is engine-side. The patch is

a laboratory fork, not a product change; its false-positive cost on benign traffic is not measured; and the product architecture, including the absence of any adaptation module, is unchanged.

Immersive-safety case study: one shot, stated once. The immersive case study (Section 5.15) is a single headless host run ($n = 1$): one light jailbreak, one model sample, one expression-layer template. It shows that the decoupling works end to end—the gate blocks, the fact layer refuses, and the expression layer refuses in character—but it does not measure interception accuracy, false-positive rate, persona fidelity or user experience, and a rerun may phrase the refusal differently. The rule vocabulary behind the mild-risk tier is a stub whose error rates are uncalibrated. We report the case because it closes the gap between the mechanism and a real host process, not as an effect-size estimate.

Synthetic data and mock assertions. The replay set is entirely synthetic and permits a synthetic share of one, which disqualifies it for deployment decisions. Plugin evidence is mock-host assertions (188+148+45+15 = 396) plus the ten-cell pilot above, not sustained traffic. The trigger vocabularies are dominated by two languages, and token usage is estimated from characters rather than produced by a tokenizer.

Chaos injection scope. The chaos faults are synthetic single-shot injections ($n = 1$ per fault), not a sample of production failures. The never-answering case is cut by an outer 150 s window rather than a measured client timeout; the warm state is pre-seeded; the context window is a laboratory override (`LINGSHU_CONTEXT_WINDOW`) with anchors at section positions rather than the absolute request head and tail; and one campaign used three headless calls but fifteen provider requests because the agent loop expands a call into several steps. Raw transcripts and per-field evidence files are kept, and every claim in Section 5.4 is tied to a field rather than to a summary sentence.

External-baseline environment limits. The official `mem0ai` 2.2.1 library was run with a local non-neural hashed-bigram embedder (no embedding API was available), and its default configuration produced empty recall on cross-lingual queries. These are limits of our comparison environment, not claims about Mem0.

Ablation power. The pre-registered three-arm ablation has been executed (zero-model, deterministic). Its original design supports only coarse conclusions: the baseline–system retention difference is definitional, and twelve probes detect only differences of about 0.5 or larger. A supplement expands the ACT-R probes to twelve (Section 5.6), where the effect becomes significant (12/12, $p = 2.4 \times 10^{-4}$), while two mechanism arms remain inseparable from the gate by construction. The gate itself points the other way: zero of the forty held-out paraphrases (two corpora of twenty) are intercepted (0/40, Section 5.7), so lexical coverage is a boundary, not a defence; the patch case study raises in-sample interception to 20/20 without moving this number.

Implementation debt. Several mechanisms are implemented and unit tested but not wired: impasse-driven subgoaling has no caller; the reduction path has no conflict detector, so its trigger is always `none`; UCA-03 is unreachable (refusal is never set); dynamic-weight eviction is never exercised (the replay budget is never exceeded); the saturation-to-gate link is caller-supplied. The assembled prompt contains no user text, so user-turn jailbreaks cannot be caught engine-side; ACT-R implements base-level activation only.

Interpretive framings are not implementations. Two academic lenses appear as *framing-only*: the Viable System Model and a rate-distortion analogy. Neither has a code locus, parameter or dependency: VSM does not occur in the implementation and no rate–distortion functional is computed. They position the work but cannot be cited as evidence.

Frozen research directions. Four directions are explicitly *frozen*, *not implemented*, and carry *no engineering evidence*: (i) action closure (closed-loop tool invocation with side-effect rollback); (ii) adaptive evolution (meta-learning that rewrites its own search targets); (iii) collective mind (a multi-agent blackboard); and (iv) multimodal perception. No prototype, dependency or configuration switch exists for any of them. Their absence bounds our claims: the control plane governs prompt assembly, not tool execution, cross-agent coordination or non-textual input.

Safety scope. The fail-closed guarantee is behavioural and covers injection only. We implement no independent crisis-safety pre-layer; refusal depends on the host safety layer and a prompt-level constitution. We therefore make no end-to-end safety claim: the structural comparisons of Section 5.13 measure admission decisions (gate verdicts and audit events) plus a small model-side pilot, not a safety rate that would transfer to other hosts, models or attack distributions.

8 Conclusion

We described LingShu, a cognition layer that treats prompt assembly as a control surface. The contribution is the shape of the artefact rather than a new mechanism: a contract that executes and fails loudly (892

Python assertions across 14 files, 396 plugin-side assertions), failure semantics in which exactly one component is fail-closed, and an evaluation discipline in which every parameter's provenance is explicit and the instrument is frozen. The mechanisms themselves are adapted from established work—ACT-R base-level activation, STPA unsafe control actions, Ashby's requisite variety, PID-style anti-windup—and we present them as adaptations, not inventions.

The evidence we present is structural rather than statistical. The contract executes and fails loudly; exactly one node can stop a turn, and every block it issues is attributable to a named unsafe control action; downgrades are recorded rather than silent. Where a structural comparison is possible, the control plane changes the outcome at the assembly boundary: a superseded fact is suppressed instead of accumulating, and a static rule patch lifts interception of twenty mutated payloads from 3/20 to 20/20. The same instrument also bounds the claim: held-out paraphrases stay at 0/40, so the gate is a lexical and structural control, not a semantic guarantee. Establishing effect sizes at traffic scale is the next measurement; the frozen instrument and the open replay harness exist to make that measurement possible, not to substitute for it.

Future work. The case study makes the missing piece concrete: the patch loop above was written by hand, and its 100% is in-sample. The natural next step is *automated adversarial co-evolution*—a laboratory loop in which a red team proposes mutations and the rule layer proposes patches, with the held-out set and the benign control as the only acceptance gates. We deliberately keep this out of the product architecture: the shipped control plane remains a static VSM/STPA surface, and any co-evolution machinery must live in the evaluation laboratory, with frozen instruments and a human review step. Closing that loop, and measuring its false-positive cost, is the core direction of future work.

A Safety control actions (UCA-01–08)

Table 7 reproduces the eight unsafe control actions of the gate as defined in the implementation (the source strings are Chinese and are translated here). The table, the two trigger word lists and the verdict logic are hardcoded at `engine/control.py:175--188` and `engine/control.py:191--232`; checks are evaluated in code order, and any hit among UCA-01–07 sets the verdict to `block`. UCA-08 is downgrade-only: it is recorded in the `downgrades` field and never changes the verdict.

B Parameters and provenance

Table 8 lists every numeric parameter touched by the mechanisms in Section 4. The authoritative source is `rules/decay-params.yaml`; `engine/config.py` is a zero-dependency shadow copy, cross-checked key by key by `tools/check_config_sync.py` (66 keys, 0 failures). **All entries are `provenance: guess`**; the number of measured parameters is zero (`acceptance/provenance-candidates.json` reports `upgrade_eligible: false` for every entry).

[a] The block carries no inline provenance key; the file header states that all values are guesses (`:4`), and the enclosing section repeats `provenance: guess`. [b] The rule key exists but is not compared by the consistency tool (key-name mismatch against the shadow). [c] Hardcoded in code; documented as a single-source exception. These three exceptions are the only places where a numeric value does not flow from a checked rule-file key.

C Reproduction commands and assertion inventory

All Python commands below were executed on the reference implementation while preparing this paper. The environment variable is required on Windows because one assertion name contains U+2212, which the default console code page cannot encode; without it the run aborts on printing, not on an assertion failure.

```
$env:PYTHONIOENCODING = "utf-8"
python tests/test_control.py                    # 161
    passed, 0 failed
python tests/test_pipeline_integration.py       #  65
    passed, 0 failed
python tests/test_constitution.py               #  26
    passed, 0 failed
python tools/check_config_sync.py               #  66 ok, 0
     fail, 0 skipped
python tools/gen_impl_status.py --check         #  OK (
    status matrix current)
python tools/run_learning.py --json             #
    recall_at_3 = 1.0
node plugin/dsh-lingshu/host-sim.mjs --assert #
    documented 188 assertions
node plugin/dsh-lingshu/control-sim.mjs --assert #
    documented 148 assertions
node plugin/dsh-lingshu/stress.mjs --assert   #
    documented 45 assertions
```

Table 9 attributes the executed Python assertions to the mechanisms of Section 4. Counts are executions, not call sites: one call site inside a loop runs once per iteration (e.g. the top-k slot check). Plugin assertion counts are those recorded by the project and were not re-executed for this paper.

The gate-level measurements quoted in the text were produced with the same token-free call used by the chaos executor (`tools/run_chaos.py:443--446`): the sample text is passed as the `prompt` argument with `frozen_ok=True` and `constitution_injected=True`,

Table 7: Unsafe control actions and their responses. "Marker" is a fixed five-character anchor sentinel beginning with U+3016; "fact block" is the rendered fact block `f`.

ID	Definition (translated from the code table)	Detection condition	Response
UCA-01	Injected content overrides constitutional constraints	any override phrase in p (`:207--208`)	block
UCA-02	Constitution verification failed but injection continues	$\neg$frozen_ok (`:209--210`)	block
UCA-03	Style/emotion injected in a refusal scene	refuse $\wedge$ style_injected (`:211--212`)	block
UCA-04	Memory content asserted as current fact (unsourced)	any unsourced phrase in f (`:213--214`)	block
UCA-05	Budget truncation evicts the constitution	$\neg$constitution_injected (`:215--216`)	block
UCA-06	Unresolved conflict not reduced	unresolved $\wedge\neg$fallback (`:217--218`)	block
UCA-07	Persona anchor missing during a phase shift	prefeed $\wedge$ marker $\not\subseteq p$ (`:219--220`)	block
UCA-08	Integration continues after saturation	$\exists k : s_k$ (`:221--223`)	downgrade only

Table 8: Numeric parameters, authoritative rule-file line, value, provenance and code shadow. "guess" is a design default, not a calibrated value.

Parameter key	Value	Provenance	Shadow
`actr.d`, `actr.ref`, `actr.lo`, `actr.hi`	0.5, 0.001 d, −3.0, 1.0 (`:217--221`)	guess	`config.py:90--95`
`memory.actrWeight`	0.6 (`:18`)	guess[a]	`config.py:21`
`memory.decay.tau.*`	7, 30, 90 d (`:39--48`)	guess	`config.py:15--19`
`control.integralKi / Cap / Leak / Deadband`	0.15 / 0.4 / 0.05 / 0.02 (`:224--233`)	guess	`config.py:97--100`
`control.phaseShiftRatio / HardRatio`	0.70 / 0.85 (`:228--233`)	guess	`config.py:101--102`
`control.trendThreshold / ratioMax / historyCapacity`	0.02 / 1.5 / 64 (`:230--233`)	guess	`config.py:104--106`
`compose.weights.fact / organization / style / retrieval`	0.70 / 0.50 / 0.40 / 0.45 (`:239--247`)	guess	`config.py:50--53`
`compose.weights.boost*`	0.50 / 0.35 / 0.40 (`:243--247`)	guess	`config.py:54--56`
`compose.weights. styleBoostThreshold`	0.6 (`:246`)	guess	`config.py:58`
`memory.retrieval.topK`	3 (`:20`)	guess	`config.py:22`
`memory.recallBudget. tokenBudgetDefault / maxReturned`	900 / 3 (`:70--71`)	guess[a]	`config.py:25`
`memory.potency.archiveThreshold`	0.15 (`:50`)	guess[a]	`config.py:20`
`compose.injectionTokenRatioMax`	0.15 (`:236`)	none[b]	`config.py:45` (`tokenRatioMax`)
`metacog.emotionCapIntensity`	0.6	no rule key[c]	`config.py:30`
`ASSUMED_CONTEXT_TOKENS`	8000	no rule key[c]	`compose.py:36`

which isolates UCA-01. This is a unit-level coverage check on the gate's scan surface, not an end-to-end interception measurement.

C.1 Test Rigor and Anti-Cheating Audit

This appendix records how the test evidence quoted in Section 5.11 was produced. All numbers below come from one audit bundle dated 2026-10-27: two reviewer reports (mutation testing; assertion strength and coverage), one consolidated rigor report, and two machine-readable result files, all archived under `acceptance/audit/`. Nothing here is reconstructed from memory: every figure is a field of the archived JSON or a table of the reports.

What the tables do not show. Three caveats belong next to the numbers. First, `engine/control.py` has no unexecuted line under the tested configuration (141/141 lines, 56/56 branches), but this does not establish the absence of dead code: two equivalent mutants survive precisely because a branch is unreachable, and unreachability is what a coverage number cannot distinguish from an untested branch. Second, the whole-repository Python figure of 45.81% is pulled down by `tools/` (32.92%; 3 of 26 files executed), and `tools/` coverage is itself a lower bound because subprocess-invoked tools are recorded as unexecuted. Third, the repository has no version-control history, so the audit can certify the current state but cannot certify that no assertion was weakened at an earlier time.

Reproduction. The bundled files are `acceptance/audit/mutation-results-2026-10-27.json` (per-mutant outcomes, survivor analysis, and the before/after SHA-256 lists) and `acceptance/audit/coverage-summary-2026-10-27.json` (per-file line and branch data), with the human-readable reports alongside them. Full suites: fourteen Python test files (892

Table 9: Assertion inventory. "Run" is the number of assertion executions observed; "site" is the test-file line where the test function starts.

Mechanism	Test function (file)	Run	Site
ACT-R base level	`test_actr_activation` (`test_control.py`)	15	`:58`
ACT-R dual channel	`test_actr_dual_channel` (`test_control.py`)	7	`:103`
Top-k slot contract	`test_topk_slot_contract` (`test_control.py`)	9	`:143`
Integral feedback	`test_integral_baseline` (`test_control.py`)	18	`:177`
Phase-shift monitor	`test_phase_shift_monitor` (`test_control.py`)	22	`:258`
Requisite-variety guard	`test_requisite_variety_guard` (`test_control.py`)	11	`:342`
Pre-flight gate	`test_preflight_audit` (`test_control.py`)	33	`:387`
Dynamic weights	`test_compose_weights` (`test_control.py`)	29	`:484`
Single-source parameters	`test_params_single_source` (`test_control.py`)	8	`:623`
Impasse	`test_impasse` (`test_control.py`)	7	`:668`
Pipeline integration	`nine functions` (`test_pipeline_integration.py`)	65	`:46--284`
Constitution audit	`five functions` (`test_constitution.py`)	26	—

Table 10: Mutation matrix. A mutant counts as killed only when an assertion fails; crash-only kills are excluded (0 observed). The two surviving mutants after supplementation are equivalent mutants, not test weaknesses. The rules file mutants are caught by cross-file consistency assertions rather than by behavioural ones.

Region	Mutants	Killed	Rate	Survivors	After supplement
`plugin/control.js`	16	15	93.8%	1 equivalent	15/15 non-equivalent
`plugin/memorywriter.js`	5	3	60.0%	2 real blind spots	5/5
`plugin/index.js`	8	6	75.0%	2 real blind spots	8/8
`engine/control.py`	11	10	90.9%	1 equivalent	10/10 non-equivalent
`rules/decay-params.yaml`	4	4	100%	0	4/4
Total	44	38	86.4%	4 real + 2 equiv.	42/44 (95.5%); 42/42 non-equivalent

assertions) and four JavaScript suites (396 assertions). Mutation replay uses a full copy of the repository; the mutation driver, per-round raw output, and the independent re-run log are archived in the audit bundle and available from the authors, since they sit outside the repository so that no reviewer-run artefact can alter the submitted tree. On Windows, three Python test files require a temporary-directory shim because the sandbox blocks `tempfile.mkdtemp()`; the shim replaces temporary-directory creation only and changes no assertion and no line of implementation code.

C.2 Tool-Call Unsafe Control Actions (T-UCA)

This appendix mirrors the tool-side matrix that the implementation encodes. The matrix is defined once, in the project's tool-gateway contract (`docs/24`), and is implemented twice—as `engine/tool_gateway.py` (pure functions, zero dependencies) and as `plugin/dsh-lingshu/tool-gateway.js` (same semantics)—with both rule tables machine-synchronised from the contract's rule array, so that each identifier, verdict and hint text agrees row by row. The namespace is disjoint from the injection-side UCA-01–08; the two are related only by ordering: injection pre-flight runs before the model call, the tool gate runs after a call is emitted and before execution. The contract's policy version is `t-uca-1.1`, and the field carrying tool-side identifiers in the audit event is named `ucas` (same spelling as the injection-side field, but a different event type: `tool_gate.ucas` may contain only `T-UCA-xx`, `audit.ucas` only `UCA-0x`).

Default policy and evaluation order. Unknown, unregistered or undecidable calls are blocked (fail-closed); read-only calls that match no rule are allowed and logged; a mutating call whose phase is unknown is blocked; a parse failure is blocked with an explicit `parse_error` reason rather than inferred intent. When several rules match, the verdict takes the highest severity (block over degrade over allow) and *all* matched identifiers are recorded in `ucas` without truncation. Evaluation order puts static checks first, then the state-dependent rules, and the audit rule last: `T-UCA-01, 02, 03, 04, 05, 06, 07, 08, 09, 12, 14, 15, 10, 13, 16, 11`. A `degrade` means the original call is not executed: the caller returns a strong hint, sets `requires_confirmation`, and requires an explicit human confirmation through the host approval seam; a degrade with no approval channel is treated as a block (`degraded_to`). The gate never executes a payload and never rewrites arguments; it classifies, consults state, and returns a verdict.

State inputs and tool classes. The gate consumes only state that already exists in the sys-

Table 11: Coverage and exception paths. Panel (a): Python line and branch coverage by group, measured with a PEP 669 `sys.monitoring` tracer. Panel (b): JavaScript coverage measured from V8 data; the block column is an approximation of branch coverage, not true branch coverage. Panel (c): assertion-strength grading and the strict exception-path share. Coverage is reported as measured, and is not used to claim the absence of dead code.

(a) Python coverage

Group	Files run	Exec. lines	Covered	Line %	Branches	Covered	Branch %
`engine/`	20/20	2,319	2,086	89.95	648	523	80.71
`tools/`	3/26	8,023	2,641	32.92	1,794	527	29.38
`integrations/`	1/1	99	56	56.57	18	12	66.67
Total	47	10,441	4,783	45.81	2,460	1,062	43.17

(b) JavaScript coverage (block column is approximate)

File	Exec. lines	Covered	Line %	Block/branch %
`control.js`	360	341	94.72	74.81
`goalrelation.js`	181	163	90.06	71.53
`index.js`	1,066	1,018	95.50	64.00
`memorywriter.js`	182	179	98.35	56.19
Total	1,789	1,701	95.08	66.22

(c) Assertion strength and exception paths

Quantity	Python	JavaScript	Sample	Note
Sampled assertions	165	73	238	fixed seed; tautologies = 0
Strong / weak (sample)	125 / 40	54 / 19	238	179 strong (75.2%), 59 weak
Full heuristic scan	597 / 227 / 1	278 / 89 / 0	1,192	strong/weak/tautology; 26.6% weak-or-tautological
Strict exception share	199/825 = 24.1%	82/367 = 22.3%	–	relaxed upper bounds 43.3% / 54.2%

tem: `variety_fallback` and `unresolvedConflict` (from the conflict and variety machinery), `phase` (from the preemptive monitor), `saturated` (from the integral baseline), `frozen_ok` (from the frozen-region check), `capabilities` (declared versus granted), `audit_context`, and the tool registry. Tool classes are closed and static—`read`, `write`, `destructive`, `exec`, `network`—with `write`, `destructive`, `exec` and `network` treated as mutating and `read` as read-only; a payload cannot declare its own class. Finer semantics (for example which arguments name a path) live in the registry's capability declarations rather than in the class enum.

Audit fields. Each verdict produces one `tool_gate` event: `schema`, `policy_version`, `call_id`, `session_id`, `turn_id`, `tool`, `tool_class`, `verdict`, `allowed`, `ucas`, `degraded_to`, `requires_confirmation`, `reason`, a nested `audit` block (`args_digest`, `args_keys`, `args_bytes`, `args_preview`, `phase`, `variety_fallback`, `frozen_ok`, `saturated`), and a `snapshot` of the target (path, modification time, hash) used to check that the object judged is the object executed. Argument digests and key lists are recorded instead of raw secret-bearing arguments. In the host plugin the same event drives a clarification flag that surfaces as a strong hint on the next turn.

Reproduction. `python tests/test_tool_gateway.py` exercises dangerous, benign, state-gated and cross-language cases (as run for this draft: 79 passing assertions, 20/20 dangerous blocked, 0/8 benign blocked, 20/20 cross-language agreement); `node plugin/dsh-lingshu/tool-gateway-sim.mjs --assert` checks the rules individually in JavaScript (65 checks); `python tools/run_actuator_demo.py` drives the reference loop and emits the JSON cited in Section 5.12. The frozen blind held-out set is `paper/ablation/tool/heldout-tool-calls-v1.jsonl` (ten calls, two per family; SHA-256 `f68fc1b3f19fc37e43b9856096d29b9a55de7dee9bf664a9b9a9592e070576d4`); it is evaluated by a party other than its author, under two regimes (arguments only, and arguments with context), because the conflict family depends on context.

Boundaries recorded with the matrix. The host exposes no pre-dispatch hook, so plugin-side blocking is limited to tools routed through `guardTool`; engine-side pre-blocking is a reference loop, not a product enforcement point. Tools executed outside the gateway are not

Table 12: Tool-side unsafe control actions (`docs/24` v1.1, policy `t-uca-1.1`). Sixteen rules: thirteen block, three degrade (a degrade falls back to block when no approval channel exists). No rule returns *allow*; allow is the default policy for read-only calls that match no rule. The *group* column follows the contract's grouping and is not a runtime field.

ID	Group	Trigger (contract summary)	State inputs	Verdict	Test case
T-UCA-01	state	mutating call while variety fallback or unresolved conflict is active	variety, conflict	block	`test_tuca_01`
T-UCA-02	data	credential or secret material in arguments or target	capabilities	block	`test_tuca_02`
T-UCA-03	mutation	destructive delete/overwrite without exact matching confirmation	—	block	`test_tuca_03`
T-UCA-04	mutation	write to frozen/protected path (incl. `engine/`, `plugin/` sources)	frozen_ok	block	`test_tuca_04`
T-UCA-05	network/exec	network egress outside the (default empty) allowlist	capabilities	block	`test_tuca_05`
T-UCA-06	network/exec	arbitrary code execution (capability or execution-shaped args)	capabilities	block	`test_tuca_06`
T-UCA-07	shape	oversized, deeply nested or multi-encoded payload	—	block	`test_tuca_07`
T-UCA-08	shape	unregistered tool or incomplete registry entry	tool_registry	block	`test_tuca_08`
T-UCA-09	shape	schema violation, delimiter/control-character injection, homoglyph tool name	tool_registry	block	`test_tuca_09`
T-UCA-10	state	mutating call while context phase is critical	phase	degrade→block	`test_tuca_10`
T-UCA-11	audit	incomplete audit context (missing session/turn/call id)	audit_context	block	`test_tuca_11`
T-UCA-12	shape	capability neither declared nor granted	capabilities	block	`test_tuca_12`
T-UCA-13	state	saturated affective baseline with irreversible write, unconfirmed	saturated	degrade→block	`test_tuca_13`
T-UCA-14	mutation	frozen-region check failed and call is mutating	frozen_ok	block	`test_tuca_14`
T-UCA-15	mutation	path escapes the workspace (`..`, absolute, drive, UNC, null byte)	—	block	`test_tuca_15`
T-UCA-16	state	destructive call while context phase is shift	phase	degrade→block	`test_tuca_16`

gated. The gate is a static checker, so parsing is its own attack surface, and its false-positive rate is uncalibrated in the absence of real traffic. The contract also records known false-positive surfaces (confirmation fatigue for writes during the critical phase, legitimate maintenance of protected paths, documents that merely discuss credential formats, and large legitimate imports). These are repeated here because a matrix in an appendix is exactly where a reader is most likely to mistake a rule table for an enforcement guarantee.

C.3 Real-host pilot details

This appendix holds the two host-side pilots whose headlines remain in Section 5.3 and Section 5.10. Nothing here is a new measurement: the numbers are transferred verbatim from the main text and the archived records, and the two pilots differ in shape (one concatenated request versus genuine per-turn calls).

Host pilot (single concatenated request). Ten cells ran on one host, one model route, one run each: Full (plugin) and Baseline (no plugin) against three probe phrasings, plus two controls. A cell is one headless CLI invocation over a 100-turn prompt of 78,565–78,652 bytes—the host-feasible single-message form (50 flood turns, 49 replay turns, one probe). All 11 invocations, including the feasibility probe, exited zero, with at least 26 model requests (26–36 estimated, since one CLI invocation is an agent loop) and 193,288 tokens.

The main matrix is a ceiling: 6/6 answers contain the planted codename because the seed sentence is verbatim in the prompt. Removing that sentence is more informative: Full reports `matched=0`, injects no memory section, and both arms answer not-found—a methodological finding, since compressing a 100-turn dialogue into one 78 KB message dilutes the query until query-conditioned retrieval stops hitting. This also questions stress protocols that concatenate many turns into one prompt. A short-query control isolates the channel: Full injects the seeded entry and answers the codename,

whereas BASELINE, with no memory, takes ten tool steps and answers with the directory name. That is a mechanism demonstration at $n = 1$, not a hallucination rate. BASIC is not applicable on the host: the plugin exposes parameter defaults but no switch to disable the control layer. In all ten cells the gate returned `allow` with an empty UCA list, so the pilot says nothing about the control layer.

Per-turn long-session pilot (S4). The last experiment replaces the single concatenated message with genuine per-turn calls. Two arms—FULL (plugin and control plane) and BASELINE (no plugin; the harness prepends the last $W = 3$ turns)—run two 30-turn variants. Settings are planted in turns 1–2, a superseding statement appears at turn 3, and probes at turns 10, 20 and 30 ask for the setting, the superseded value, the interface preference and an unmentioned cat. Primary delivery is the v1 subset: 60 cells, 60/60 exit zero, 419,203 tokens. The full 120-cell run (873,198 tokens) is archived and is never pooled with the primary numbers; the extra variant is a cross-check only.

Table 13 shows the six probe outcomes. Read alone they invite the wrong conclusion, so two mechanism facts must be read with them. First, FULL did inject memory in all three probe turns, but the content was wrong: the turn-3 supersession does not match any of the plugin's three supported extraction patterns (`plugin/dsh-lingshu/index.js:1004--1011`), so BETA was never written and the memory's last-wins view has `beta_present=false` with the project code still ALPHA—a stale value. Second, the probe question itself was extracted as a fact: asking for the interface preference matches the pattern with object "what", and that junk entry superseded the correct preference (one supersede event, in the wrong direction). FULL's model therefore saw "code = ALPHA" and "preference = what" and, following invariant I1 (memory is a reference, never the current statement), answered that there was no record. That is the designed behaviour on corrupted input, not a capability ceiling.

BASELINE's apparent retention has a different origin: the window carries the assistant's own earlier restatements, so BETA and the dark theme survive by self-repetition rather than through memory, and two answers fabricate turn references—citing filler turns 7–8 as prior user statements that were in fact the assistant's own restatements. The pre-registered P-S4a (Full at least as good as Baseline on setting retention) is therefore *not supported* and is recorded as `null`. What this pilot shows is an input-construction defect interacting with the real boundary of a rule extractor; it cannot be read as "FULL is less capable" or "BASELINE is better". With one chain per arm and variant, one model, one host and rule-assisted counting, we report counts, not rates. The archived v2 variant repeats the pattern (FULL 0/3, BASELINE 2/3) and is not pooled.

References

[1] John R. Anderson. *How Can the Human Mind Occur in the Physical Universe?* Oxford University Press, New York, 2007.

[2] John R. Anderson and Lael J. Schooler. Reflections of the environment in memory. *Psychological Science*, 2(6):396–408, 1991.

[3] W. Ross Ashby. *An Introduction to Cybernetics*. Chapman & Hall, London, 1956.

[4] Karl J. Åström and Tore Hägglund. *PID Controllers: Theory, Design, and Tuning*. Instrument Society of America, Research Triangle Park, NC, 2nd edition, 2006.

[5] Stafford Beer. *Brain of the Firm*. Allen Lane, London, 1972.

[6] Alexander Bering. ZenBrain: A neuroscience-inspired 7-layer memory architecture for autonomous AI systems, 2026. arXiv:2604.23878v3.

[7] Prateek Chhikara, Dev Khant, Saket Aryan, Taranjeet Singh, and Deshraj Yadav. Mem0: Building production-ready AI agents with scalable long-term memory, 2025. arXiv:2504.19413v1.

[8] Chiyuan Fu, Lyuhao Chen, Yunze Xiao, Weihao Xuan, Carlos Busso, and Mona Diab. Sentipolis: Emotion-aware agents for social simulations, 2026. arXiv:2601.18027v2.

[9] Charles A. E. Goodhart. Problems of monetary management: The U.K. experience. In *Papers in Monetary Economics*, volume I. Reserve Bank of Australia, 1975.

[10] Yingjie Gu, Wenjian Xiong, Liqiang Wang, Pengcheng Ren, Chao Li, Xiaojing Zhang, Yijuan Guo, Qi Sun, Jingyao Ma, and Shidang Shi. FSFM: A biologically-inspired framework for selective forgetting of agent memory, 2026. arXiv:2604.20300v2.

[11] Doga Keresteciogl u, Alexei Robsky, Clemens Vasters, Anshul Sharma, and Yitzhak Kesselman. Human-inspired memory architecture for LLM agents, 2026. arXiv:2605.08538v1.

[12] Nancy G. Leveson. *Engineering a Safer World: Systems Thinking Applied to Safety*. MIT Press, Cambridge, MA, 2011.

[13] Nancy G. Leveson and John P. Thomas. *STPA Handbook*. 2018. Massachusetts Institute of Technology.

[14] Albert Mehrabian and James A. Russell. *An Approach to Environmental Psychology*. MIT Press, Cambridge, MA, 1974.

Table 13: Per-turn long-session pilot (S4), primary v1 subset: six probe outcomes (three probe turns × two arms), rule-assisted counts. Source: `calls.json`, fields `observations_raw_counts.full-v1`, `.baseline-v1`, `aggregate.*`, `full_arm_memory_evidence.v1`, `totals_v1_subset_60`; the same record is duplicated in `long-session-2026-10-27.json`.

Arm	Setting kept	Stale ALPHA	Unknown ack.	Preference kept	Memory injected
FULL	0/3	0/3	3/3	1/3	3/3
BASELINE	3/3	0/3	1/3	3/3	0/3

[15] Hanzhong Zhang, Ziwei Xiang, Weicheng Xie, Shizhe Liu, and Siyang Song. PersMem: Internalizing personality into dual-pathway memory for LLM agents, 2026. arXiv:2609.34372v1.