Group 6

Ankush, Abhinay, Chhavi, David, Disha, Supriya, Madhulata, Parikshit

Power Consumption:
Active Mode: 0.2mA at 1MHz, 1.8V, 25°C
Power-down Mode: 0.1µA
Power-save Mode: 0.75µA (including 32kHz RTC)

Atmel pico Power AT mega 328/P is low power technology.
Widely used in the fabrication of integrated circuits
It has low power consumption and high noise immunity

Ease of Development:

Supported by detailed documentation, development tools, and evaluation kits that aid engineers and developers in programming and debugging.

Versatility and Flexibility:

Automotive, communication systems, sensor interfacing, and smart home device

Enhanced Features:
Includes features like a real-time counter (RTC), multiple communication interfaces, and programmable I/O lines to expand capabilities.

It is an 8-bit microcontroller based on the AVR enhanced RISC architecture.
By executing powerful instructions in a single clock cycle, It achieves throughputs close to 1MIPS per MHz

Features

Timers and Counters: Includes two 8-bit Timer/Counters with separate prescaler and compare mode, and one 16-bit Timer/Counter with separate prescaler, compare mode, and capture mode.

Power Management: ADC, LPM
Internal calibrated oscillator.
External and internal ISR.

ATMEGA328/P

Technology Used:
Designed using CMOS technology for its low power consumption and high noise immunity.
Manufactured using Atmel's high-density non-volatile memory technology, typical of CMOS processes

Inference

Environmental Adaptability:
Operates across a wide voltage range (1.8V to 5.5V) and temperature range (-40°C to 105°C), enhancing reliability in various environmental conditions.

Serial Interfaces: Includes two Master/Slave SPI serial interfaces, one programmable serial USART, and one byte-oriented 2-wire serial interface
Analog Comparator: One on-chip analog comparator.
Interrupt and Wake-up: Supports interrupt and wake-up on pin chang

Real Time Counter (RTC): Comes with a separate oscillator.
PWM Channels: Features six PWM channels.
Analog to Digital Converter (ADC): Offers an 8-channel 10-bit ADC in TQFP and QFN/MLF packages and a 6-channel 10-bit ADC in the PDIP package.

Robust Performance:
Capable of handling demanding tasks with a speed of up to 20 MHz and achieving up to 20 MIPS.
Suitable for both simple and complex applications.

Capacitive Touch Sensing:
Touch sensing can be added to any application by linking the appropriate Atmel QTouch Library for the AVR Microcontroller.

Low Power Consumption:
Designed for efficiency with multiple sleep modes and low power consumption in active and idle states.
Ideal for battery-powered and portable devices.

Control Systems
Motor Control: Employed in controlling motors for drones, RC cars, and other motor-driven devices.
Feedback Systems: Used in feedback control systems where precise control and monitoring are required.

Automotive Applications:
In-Car Electronics: Applied in systems for vehicle diagnostics, infotainment systems, and various in-car control units.
Sensors and Actuators: Controls sensors and actuators for various automotive applications

Supports a wide range of applications including consumer electronics, industrial automation, education, DIY projects, automotive, communication systems, sensor interfacing, and smart home devices.

Applications

Communication Systems:
Serial Communication: Utilized in devices requiring SPI, I2C, and USART communication protocols.
Wireless Modules: Often paired with wireless communication modules like Bluetooth, Wi-Fi, and RF modules for IoT applications.

Sensor Interfacing:
Environmental Monitoring: Used in systems for monitoring temperature, humidity, light, and other environmental parameters.
Health Monitoring: Implemented in wearable health devices and fitness trackers to process data from various health sensors

DIY Projects and Prototyping:
Arduino Platform: The ATmega328/P is the core microcontroller used in Arduino Uno, making it popular among hobbyists and makers for prototyping and building custom electronic projects.
Wearable Technology: Integrated into wearable devices due to its low power consumption and compact size.