

Oil Companies International Marine Forum SIRE Programme

Harmonised Vessel Particulars Questionnaire v6

M/T SMOOTHSEA 21

IMO/LR Number 8776394 OCIMF Id: A-100-019-426

22 May 2023

DISCLAIMER

OCIMF DOES NOT WARRANT OPERATOR IDENTITY AND IS NOT RESPONSIBLE FOR THE CHOICE OF SHIPS INSPECTED, THE INSPECTORS CHOSEN, THE PERFORMANCE OF THE INSPECTIONS OR THE CONTENT OF THE REPORTS, OPERATOR COMMENTS AND/OR VESSEL PARTICULAR QUESTIONNAIRE RESPONSES DISTRIBUTED UNDER THE REVISED PROGRAMME. OCIMF IS INVOLVED ONLY IN THE RECEIPT, ORGANISATION AND DISTRIBUTION OF THE FOREGOING PROGRAMME OUTPUT. OCIMF DOES NOT REVIEW OR EVALUATE SUCH OUTPUT AND EXPRESSES NO OPINION CONCERNING ITS ACCURACY. WHILE OCIMF MAKES EVERY EFFORT TO ENSURE THAT PROGRAMME OUTPUTS ARE RECEIVED, ORGANISED AND DISTRIBUTED IN ACCORDANCE WITH THE SIRE COMPOSITE GUIDELINES, OCIMF ACCEPTS NO LIABILITY FOR FAILURE TO DO SO.

1 General Information

1 General Information

1.1.1 Date this HVPQ document completed 03 May 2023

1.1.2 Vessel identification

1 Name of ship M/T SMOOTHSEA 21

2 LR/IMO number 8776394

1.1.3 Previous names

1.1.4 Flag

1 Flag THAILAND

2 Has the flag been changed?3 What was the previous flag?CHINA

4 Date of last change of flag

1.1.5 Port of Registry Bangkok

1.1.6 Call sign HSB 5956

1.1.7 Ship contacts

1 INMARSAT number -

2 Mobile phone number +666-3267-8830

3 Ship's email address SMOOTHSEA@GMAIL.COM

1.1.8 What is the type of ship as described in Form A or Form B Q1.11 of the IOPPC? Oil Tanker

1.1.9 If other, then specify

1.1.10 What is the Ship's Maritime Mobile Selective Call Identity (MMSI) number? 567002160

1.1.11 Type of Hull Double hull

1.1.12 If other, then specify

1.1.13 P and I Club

1 Name of P and I Club Other (Specify)

2 If other, then specify The Anglo & Eastern Ship Owners P&I Club

Sea Meadow House, Blackburne Highway, (P.O. Box 116), Road Town, Tortola, British

Virgin Islands

3 Amount of P&I Cover 500000000 USD

4 Does P&I Cover include wreck removal? Yes

2 Environmental Information

1.2.1 Energy Efficiency Design Index (EEDI)

1 Does the vessel have an EEDI Rating number? No

2 If yes then provide EEDI rating

3 If No then provide reason

4 Is the EEDI rating verified by Class, 3rd Party or Owner?

1.2.2 Energy Efficiency Existing ship Index for existing Ships (EEXI)

General Information 2/35

1	Does the vessel have an EEXI Rating number?	No
2	If yes then provide EEXI rating	
3	If No then provide reason	
4	Is the EEXI rating verified by Class, 3rd Party or Owner?	
1.2.3	Carbon Intensity Indicator (CII) rating using Annual Efficiency Ratio (AER) of grams of CO2 per dwt-mile)	
1	Does the vessel have a CII Rating number?	No
2	If yes then provide CII rating	
3	If No then provide reason	
4	Is the CII rating verified by Class, 3rd Party or Owner?	
1.2.4	Estimated Index Value (EIV) number	
1	Does the vessel have an EIV Rating number?	No
2	If yes then provide EIV rating	
3	If No then provide reason	
4	Is the EIV rating verified by Class, 3rd Party or Owner?	
3	Ownership and Operation	
1.3.1	Registered Owner	
1	Name	Smooth Sea Co.,Ltd
2	Full address	Talomsin Building(6th Floor) 924 Rama 3 Rd.,Bangpongpang, Yannawa, Bangkok 10120
3	Country	THAILAND
4	Office telephone number	+662 294 8741-4
5	IMO Number (Registered Owner)	
6	Office email address	opt@smoothsea.co.th
7	Contact person	Dr.Tiwa Siwapinyoyos
8	Contact person after hours telephone	+6689-901-2631
9	Number of years this ship has been owned by Registered Owner	4.30 Years
10	Date when registered with current owner	21 March 2017
1.3.2	Technical operator (if different from registered owner)	
1	Name	Smoothsea Co.Ltd
2	Full address	Talomsin Building(6th Floor),924 Rama 3Rd.,Bangpongpang,Yannawa,Bangkok 10120,Thailand
3	Country	THAILAND
4	Office telephone number	+662-294-8741-4
5	IMO Number (Technical Operator)	5488383
6	Office email address	opt@smoothsea.co.th
7	Name of Designated Person Ashore (DPA)	Mr. Yongyot Suwanmanee
8	After-hours telephone number of DPA	+668-1732-5474
9	Emergency callout number	+66(0)-2294-8741-4/+66(0)81-832-4834
10	Date current operator assumed technical control of the ship	21 March 2017
11	Total number of ships of this type (see 1.1.8) operated by this Technical Operator	14
12	Name of previous Technical Operator	N/A

General Information 3/35

1.3.3	Commercial operator (if different from registered owner)	
1	Name	Smoothsea,Co.Ltd
2	Full Address	Talomsin Building(6th Floor)924 Rama3 Rd.,Bangpongpang,Yanawa,Bangkok 10120,Thailand
3	Country	THAILAND
4	Office telephone number	+662-294-8741-4
5	Office email address	opt@smoothsea.co.th
6	Contact person	+6689-901-2631
7	Contact person after hours telephone	Dr.Tiwa Siwapinyoyos
4	Builder	
1.4.1	Builder name	FUJIAN YINE SHIPBUILDING, IND,LTDCHINA
1.4.2	Yard Number	
1.4.3	Date of building contract	12 May 2011
1.4.4	Hull number	
1.4.5	Date on which keel was laid or ship was at a similar stage of construction	12 May 2011
1.4.6	Date launched	01 June 2012
1.4.7	Delivery date as recorded in Form A Q1.5.3 or Form B Q1.8.3 of the IOPPC	01 June 2012
1.4.8	Major hull change	
1	Has a major hull change been undertaken?	No
2	What was the date of completion of the conversion as recorded in Form A Q1.6.3 or Form B Q1.9.3 of the IOPPC?	
3	List what changes were made	
5	Classification	
1.5.1	Classification Society	
1	Classification Society	Unknown
2	Is Classification Society an IACS member?	No
3	Does the ship have dual class?	No
4	Name of the second Classification society	Unknown
5	Is the second Classification Society an IACS member?	No
1.5.2	Class notation	
1	List class notations	TG
2	Provide details of class notations e.g. type of Ice Class	Thailand Marine Department
1.5.3	Change of Classification Society	
1	Has Classification Society changed?	No
2	What was the previous Classification Society?	
3	Date of change	
1.5.4	Dry dock	
1	Date of last dry dock	03 September 2021
2	Date of second last dry dock	25 March 2019

General Information 4/35

	,	
3	Date next dry dock due	03 March 2024
4	Location (Name of yard and port) of last dry dock	Harin Dock Yard Bangkok
1.5.5	In Water Survey (IWS)	
1	Date of last IWS	
2	Date next IWS due	
1.5.6	Special survey	
1	Date of last special survey	03 September 2021
2	Was last special survey an enhanced special survey?	Yes
3	Name of Classification Society who conducted the last Special survey / Enhanced Special Survey	New Construction - Class Unknown
4	Is Classification Society conducting the last Special survey / ESS an IACS member?	No
5	Date next special survey due	03 September 2026
1.5.7	Condition Assessment Programme	
1	Has the vessel been enrolled in a Classification Society Condition Assessment Programme (CAP)?	No
2	Does the ship have a Condition Assessment Programme (CAP) rating?	No
3	What is the latest rating?	
4	Name of Class Society awarding the CAP rating	New Construction - Class Unknown
5	Is Classification Society an IACS member?	No
6	Which areas were covered?	Hull
7	If other, then specify	
1.5.8	Provide the ratings for each area	
1.5.9	Date of completion of CAP survey (This is the date when the survey was actually completed and not the date on the certificate)	
1.5.10	Date of last Thickness Measurements for the Hull	09 March 2021
1.5.11	Date of last annual survey	05 September 2022
1.5.12	Date of Last Intermediate survey	
1.5.13	Is the ship subject to a Continuous Machinery Survey?	No
1.5.14	Does Vessel have any open Conditions of Class?	
1.5.15	List all open Conditions of Class	
1.5.16	Does Vessel have any Memoranda of Class?	
1.5.17	Memoranda of Class	
1.5.18	Does vessel have any flag state dispensations in effect?	
1.5.19	Flag State dispensation of class	
6	Dimensions	
1.6.1	Length Overall (LOA)	69.10 mtrs
1.6.2	Length Between Perpendiculars (LBP)	63.20 mtrs
1.6.3	Extreme breadth	10.75 mtrs

General Information 5/35

1.6.4	Moulded breadth			10.70 mtrs	
1.6.5	Moulded depth			4.50 mtrs	
1.6.6	Keel to masthead			25.30 mtrs	
1.6.7	Does vessel have a collapsible mast?			No	
1.6.8	If yes then Keel to masthead in collapsed	condition			
1.6.9	Height of collapsed mast above waterline	e (air draft) in normal SBT co	ondition		
1.6.10	What is the max. height of mast above w condition?	vaterline (air draft) in norma	l Ballast	22.90 mtrs	
1.6.11	Distance bow to bridge (a)			53.90 mtrs	
1.6.12	Distance bridge front - mid-point manifo	ld (b)		16.20 mtrs	
1.6.13	Distance bridge front to mid-point manif	fold		16.20 mtrs	
1.6.14	Distance bridge front to forward edge of	all manifold racks		16.70 mtrs	
1.6.15	Distance bridge front to aft edge of all m	anifold racks		15.70 mtrs	
1.6.16	Distance bow to mid-point manifold			37.00 mtrs	
1.6.17	Bow to center common line manifold			37.00 mtrs	
1.6.18	Bow to forward edge of all manifold rack	KS:		36.50 mtrs	
1.6.19	Bow to aft edge of all manifold racks:			37.50 mtrs	
1.6.20	Distance stern to mid-point manifold			32.10 mtrs	
1.6.21	Stern to center of common line manifold	I		32.10 mtrs	
1.6.22	Stern to forward edge of all manifold rac	eks		32.60 mtrs	
1.6.23	Stern to aft edge of all manifold racks			31.60 mtrs	
1.6.24	Parallel mid-body information (refer diag	gram)			
		Forward to mid-point	(Mtrs)	Aft to mid-point	(Mtrs)
Light s	inip al ballast	18.80 13.50		13.50 13.80	
	ded summer	20.70		14.50	
1.6.25	At Normal Loaded Condition			35.20 mtrs	
1.6.26	At Summer loadline condition			35.20 mtrs	
1.6.27	At Normal Ballast Condition			33.00 mtrs	
1.6.28	At lightship Condition			31.30 mtrs	
1.6.29	Does ship have a bulbous bow?			Yes	
7	Tonnages				
1.7.1	Net registered tonnage (NRT)			325.00 tonnes	
1.7.2	Gross tonnage			966.00 tonnes	
1.7.3	Other Tonnages				

General Information 6/35

- 1 Suez tonnage
- 2 Suez Canal Gross Tonnage (SCGT)
- 3 Suez Canal Net Tonnage (SCNT)
- 4 Panama Tonnage

8 Loadline Information

1.8.1 Loadline Information

1.8.1 Loadline li	nformation			
	Freeboard (Mtrs)	(mtrs) Draft (mti	rs) (Mtrs) Deadweigh (M/T)	t(M/T) Displacement (M/T) (M/T)
Summer	0.45	4.05	1224.30	2062.70
Tropical	1.56			
Normal loaded con	dition 0.45	4.05	1224.30	2062.70
Lightship	2.30	2.20	0.00	1184.60
Normal Ballast Co	ndition 2.10	2.40	458.40	1296.70
1.8.2 Fresh Wat	er Allowance (FWA) at Sui	nmer Draft	87.60 m	m
1.8.3 Tonnes pe	r Centimetre Immersion (ΓPC) at Summer Draft	5.88 tor	nnes
1.8.4 Normal ba	llast conditions			
	Freeboard (Mtrs)	(mtrs) Draft (mt	rs) (Mtrs) Deadweigh (M/T)	t (M/T) Displacement (M/T) (M/T)
Normal Full Ballast	Condition 2.10	4.05	1224.30	2062.70
1.8.5 Multiple d	eadweights			
1 Have mul	tiple deadweights been as	signed?	No	
1 Have ma	,			
	all assigned deadweights			
1.8.6 If yes, list		dwt?		

9 Recent Operational History

- 1.9.1 Has the ship traded continuously without requirement for unscheduled repairs Yes since the last dry-dock, except for normal maintenance?
- 1.9.2 Unscheduled repairs
 - 1 Have unscheduled repairs been carried out since the last special survey or scheduled drydocking, whichever more recent?
 - 2 What was the nature of the repairs?
 - 3 Date of last unscheduled repairs as per 1.9.2.1
- 1.9.3 Has ship been involved in a pollution, grounding, collision or allision incident No during the past 12 months?
- 1.9.4 If yes, provide details (see table)
- 1.9.5 Has the ship had any other incidents during the past 12 months?
- 1.9.6 If yes, provide details (see table)
- 1.9.7 If there is additional information relating to features of the ship or operational characteristics that may be of interest, please record details here.
- 1.9.8 Port State Control
 - 1 Date of last Port State Control Inspection

General Information 7/35

- 2 Port of last Port State Control Inspection
- 3 Has the vessel been detained during the last 36 months? No
- 1.9.9 If yes provide details

2 Certificates

1 Certificates

2.1.1	Register number	60000747

- 2.1.2 Does the vessel have an International Ballast Water Management Certificate? No
- 2.1.3 If no, then describe how ship complies with the "International Convention for the Control and Management of Ships' Ballast Water and Sediments"?
- 2.1.4 Type of tanker. If the ship is not an oil tanker specify the type as recorded in Product Carrier Part B Sect 1.11 of the IOPPC

2.1.5 Certificate dates

	Date Issued	Date Expires	Last Annual	Last Intermediate	Date of endorsement
Safety Equipment Certificate	05 October 2021	02 September 2026	05 September 2022		
Safety Radio Certificate	05 October 2021	02 September 2026	05 September 2022		
Safety Construction Certificate	05 October 2021	02 September 2026	05 September 2022		
Loadline Certificate	05 October 2021	02 September 2026	05 September 2022		
International Oil Pollution Prevention Certificate (IOPPC)	05 October 2021	02 September 2026	05 September 2022		
Safety Management Certificate (SMC)	05 October 2021	04 October 2026			
Document of Compliance (DOC)	09 February 2022	15 February 2027	15 February 2023		
Minimum safe manning document	20 August 2019				

2 Publications

2.2.1 Publications

Certificates 8/35

	Edition Number
IMO Safety of Life at Sea Convention (SOLAS 74)	2020
International Life Saving Appliance Code (LSA Code)	2017
International Code for Fire Safety Systems (FSS Code)	2015
IMO International Code of Signals (SOLAS V-Reg 21)	2005
IMO International Convention for the Prevention of Pollution from Ships (MARPOL 73/78)	2022
IMO Ships Routeing	-
IMO International Regulations For Preventing Collisions at Sea (COLREGS)	2003
IMO Standards of Training, Certification and Watchkeeping (STCW Convention)	2017
OCIMF/ICS/IAPH International Safety Guide for Oil Tankers and Terminals (ISGOTT)	6th 2020
OCIMF Mooring Equipment Guidelines	4th 2018
OCIMF Effective Mooring	4th 2019
International Safety Management Code (ISM Code)	2018
ICS Bridge Procedures Guide	6 th 2022
IAMSAR Vol.3	2022 edition
ISPS Code	2003
Guidelines for the control of Drugs and alcohol on board ships	1995

3 Crew

1 Crew Management

3.1.1	What is the minimum number of certified officers to be car the Minimum Safe Manning Document?	ried as recorded in	4
3.1.2	Crew employment by the Ship Operator		
1	Is the Master employed by the Ship Operator?		Yes
2	Are the officers employed by the Ship Operator?		Yes
3	Are the ratings employed by the Ship Operator?		Yes
3.1.3	List the nationality/nationalities of the ratings onboard		
Nationa	Nationality Count		
THAILAND		14	
3.1.4	What is the working language used on the Ship?		Thai
3.1.5	Manning agent for Officers		
3.1.6	Manning Agents		
1	Are manning agent(s) wholly or partially owned by Operat	or?	No
2	If No, does Operator have selection rights?		No
3.1.7	Does the Operator maintain personnel files on officers assi	gned to its vessels?	Yes
3.1.8	What is the retention rate for officers for the past 3 years?		80.00 Percent
3.1.9	What is the minimum number of ratings to be carried as sp Minimum Safe Manning Document?	ecified in the	4

Crew 9/35

3.1.10	Manning agent for Ratings (if different to Officers)	
3.1.11	Does the Operator maintain personnel files on ratings assigned to its ships?	Yes
3.1.12	What is the retention rate for ratings for the past 3 years?	80.00 Percent
2	Crew Continuity	
3.2.1	Do senior officers return to the same ship on a rotational basis?	Yes
3.2.2	Are senior officers rotated on ships of similar class within company fleet?	Yes
3.2.3	Are junior officers and ratings rotated on ships of similar class within company fleet?	Yes
3.2.4	If senior officers do not return to same ship on a rotational basis, are changes of Master, Chief Officer, Chief Engineer and Second Engineer organised to avoid a full change of officers at same time?	Yes
3	Training	
3.3.1	Are Masters and Chief Engineers required to attend company office before and/or after each tour of duty?	Yes
3.3.2	Does operator hold regular training seminars ashore for officers?	Yes
3.3.3	Are training seminars provided for officers and ratings?	Yes
3.3.4	What courses, exceeding statutory requirements, are provided by the Operator:	
1	For senior officers	Safety Officer onboard, Bridge Team Management, On board Training, ISPS Training
2	For junior officers	Bridge Team Management, On-board Training, In-house Seminor, ISPS Training
3	For ratings	Safe working on Tanker

4 Navigation and communications

1 Navigation

4.1.1 Navigation equipment fitted onboard?

	Yes/No	Туре	Description	Maker	Model	Serial Number	Software	Firmware version
Magnetic Compass	Yes			DAIKO KEIK	I SR165PKK	1170		
Gyro Compass	Yes			TOKIMEC	TG-500	11377		
Gyro Autopilot	Yes			TOKYO KEIKI	PR-21-2	11515		
Radar 1	Yes	x-band		FURONO	FAR-2117- 20AF	4317-4020		
Radar 2	Yes	x-band		FURONO	FR-1510	3366-3571		
Radar plotting equipment	No							
Arpa	No							
Depth Sounder with recorder	Yes		Digital Display	FURONO	FE-701	2232-2555		

	·	,			
speed/o	distance or	No			
doppler	rlog	No			
Docking doppler	g approach r	No			
Rudder indicate		Yes	TOKIMEC	PR-2000	GLT-5242
RPM in	dicator	Yes	HANCHIN DIESEL	KYOWA KEIKI	E16705
	lable pitch er indicator	Yes			
Bow thi		No			
Stern th		No			
Rate of indicate		No			
Navtex	indicator	No			
Global p system	positioning	Yes	XINO	XF-607	GPS- 60716E001 6
Differer	ntial GPS	No	NSR	NGR-1000	GR-160023
Display	ation System	No			
Course	Recorder	No			
Integrat Navigat (INS)	ted ion System	No			
Off cou Gyro	rse alarm -	Yes	TOKIMEC	TG-5000	11377
Off cou Magnet	rse alarm - tic	No			
Engine	Order Logger	No			
Anemo		Yes	NEI NIPPOI	N	11265
Weathe	er Fax	No			
4.1.2	Is a repeating magnetic	compass fitted?		No	
4.1.3	Is there at least one rad?	ar operating in the 9 GHz frequency ba	and (3cm/x b	and) Yes	
4.1.4	Are the 3 GHz (10cm/S telectronic switching unit	pand) and 9Ghz (3cm / X band) radars t?	fitted with ar	n Yes	
4.1.5	Is the ECDIS the primary	means of navigation?		No	
4.1.6	Does ship carry sextant((s)?		No	
4.1.7	Does ship carry a signal	lamp?		Yes	
4.1.8	Is each bridge wing fitte	d with:			
1	Rudder angle indicator			No	

Vessel I	sel Particulars Questionnaire for M/T SMOOTHSEA 21									
2	RPM indicator				No					
3	Gyro repeater				No					
4.1.9	If the ship is fitted the bridge wings?	with a controllable p	oitch propeller, a	re indicators fitted (on No					
4.1.10	Are steering contro	ols and engine contr	ols fitted on brid	ge wings?	Yes					
4.1.11	Is a Bridge Watch N	Navigation Alarm (B\	Yes							
2	Communications									
4.2.1	Under what sea area (A1, A2, A3 or A4) does the ship operate? A1									
4.2.2	Communications e	quipment fitted onb	oard?							
Numbe	r Type	Description	Maker	Model	Serial Number	Software	Firmware version			
1	AIS	CLASS A	NSI1000	NSR	SI-190953	-	-			
1	SART	-	NRT-1000	NSR	GR-160023	-	-			
1	SART	-	TBR-600	TAIYOMUSEN	3640408	-	-			
1	VHF	-	FURONO	FM-8500	2596-3183	-	-			
1	VHF	-	IC-M200	ICOM	03009486	-	-			
4.2.3	If other, then speci	ify								
4.2.4	Does the VDR or S-VDR have clear instructions to bridge watchkeepers relating No to the saving of data following an incident?									
4.2.5	How many VHF rad	dios are fitted on the	e bridge?		2					
4.2.6	Is a VHF radio fitte	d in the Cargo Contr	ol Room?		No					
4.2.7	Is the CCR connect	ed to the internal co	mmunication sy	stem?	No					
4.2.8	How many intrinsic	cally safe walkie talk	ies are provided	for cargo handling?	? 5					
4.2.9	Are at least three s	survival craft two-wa	y radio telephor	nes provided?	No					
4.2.10	Can the radio trans	smit the helicopter h	noming signal on	410 KHz?	No					
5	Safety									
1	Safety Manage	ment								
5.1.1	Quality manageme	ent system:								
1	Is the ship operate	ed under a Quality n	nanagement syst	em?	Yes					
2	If Yes, what type o	-			IMO resolu	ution A.741(18	3)			
3		certifying authority?				rnment(Flag st	ate)			
4	Date of approval of	of the ship's quality	management sys	tem	05 Octobe	r 2021				
2	Helicopters									

- 5.2.1 ICS Guide to Helicopter/Ship Operations
 - Does the ship comply with the ICS Guide to Helicopter/Ship Operations? 1
 - 2 If yes, state whether winching or landing area provided
 - If yes, what is the diameter of the circle provided

Safety 12/35

No

3 Firefighting and Lifesaving equipment

5.3.1 Fixed foam firefighting

- 1 Is a fixed foam firefighting system installed for the cargo area? No
- 2 If yes, what is the type of foam?
- 3 If other, then specify
- What was the date of supply of the foam, or the date of the last Test Analysis Certificate?

5.3.2 What type of fixed firefighting system is provided for:

- 1 The paint locker? Sprinkle2 The Cargo pump room? Co2
- 3 The Ballast Pump Room?
- 4 The engine room? Co2
- 5 The void spaces?
- 6 The Sample Locker? Cargo
- 7 The Sample Locker? Bunker
- 8 The fuel gas system?
- 9 The Emergency Generator room?
- 10 The hydraulic room?
- 11 The foscle space?
- 12 The Bow thruster spaces?
- 5.3.3 Is a fixed dry powder firefighting system installed for the cargo area?
- 5.3.4 Is a fixed water spray firefighting system installed for the cargo area? No
- 5.3.5 Is the ship equipped with a compressor for recharging breathing apparatus air No cylinders?
- 5.3.6 What type of lifeboat(s) is/are fitted?
- 5.3.7 If other, then specify
- 5.3.8 Dedicated rescue boats
 - 1 Is a dedicated rescue boat provided? No
 - 2 If a dedicated rescue boat is carried, what is its construction?
 - 3 If other, then specify

6 Pollution Prevention

1 Pollution Prevention

6.1.1 Continuous deck edge fishplate

- 1 Is ship fitted with a continuous deck edge fishplate enclosing the deck area? No
- 2 If Yes, what is its minimum vertical height above the deck plating?
- What is maximum vertical height above deck plating at the position where the fish plate adjoins the aft thwartships coaming?
- 4 How far forward of the athwartships coaming is this height maintained?
- 5 Is an athwartship deck coaming fitted adjacent to accommodation and service No areas?

Pollution Prevention 13/35

6	What is the height of the athwartship deck coaming?	
6.1.2	Is spill containment fitted:	
1	Under the cargo manifold?	Yes
2	Under all bunker manifolds?	Yes
3	Under the bunker tank vents?	Yes
4	Around the deck machinery?	Yes
6.1.3	What type of scupper plugs are provided?	Rubber Plugs
6.1.4	If other, then specify	
6.1.5	Measures to contain spillages	
1	Are means provided to prevent spillages going overboard?	Yes
2	If yes, what means are provided?	
6.1.6	Is the following pollution control equipment available to clean up spillages on deck:	
1	Sorbents (including booms and pads)	Yes
2	Non-sparking hand scoops/shovels	Yes
3	Containers	Yes
4	Emulsifiers	Yes
5	Non-sparking pumps	Yes
6.1.7	Is the cargo piping system fully segregated from the ballast sea chest?	Yes
6.1.8	What type of sea valves are fitted to the seachest in 6.1.7?	Gate Valve
6.1.9	Are dump valves fitted to the slop tanks which will operate with normal inert gas pressure in the tank vapour space?	No
6.1.10	Are overboard discharges fitted with blanks or alternatively, is there a testing arrangement for the overboard valves?	Yes
6.1.11	Is there a discharge below the waterline for Annex II substances?	Yes
6.1.12	Is there a discharge above the waterline for Annex I oily mixtures?	No
6.1.13	Cargo piping pressure tests:	
1	On oil and chemical tankers, does the Operator have a policy to hydrostatically pressure test cargo piping at intervals no greater than 12 months?	Yes
2	If yes, specify pressure	7.50 Bar
6.1.14	Bunker piping pressure tests:	
1	Does Operator have policy to hydrostatically pressure test bunker piping at intervals no greater than 12 months?	Yes
2	If yes, specify pressure	5.00 Bar
6.1.15	Is garbage incinerator fitted?	No
6.1.16	Is garbage compactor fitted?	No
6.1.17	Is garbage comminutor fitted?	No
6.1.18	Location of cargo and bunker sample lockers	Paint Store
6.1.19	Are all oil fuel tanks protected by a double hull?	Yes
2	OPA 90 Requirements	

Pollution Prevention 14/35

- 6.2.1 Has the Operator submitted a Vessel Spill Response Plan to the US Coast Guard No which has been approved by official USCG letter?
- 6.2.2 Has a Geographic Specific Appendix been filed with the Captain of the Port for No each Port Zone the ship expects to enter or transit?
- 6.2.3 Has the Operator deposited a letter with the US Coast Guard confirming that No the Operator has signed a service contract with an oil spill removal organisation for responding to a 'worst case scenario'?

7 Structural Condition

1 Structural Condition

7.1.1 Cargo tank coating

Tank Identificati on (1-50)	Tank Identificati on (P,S,C)	Tank Type	cargo tanks constructio n	•	type of coating	extent of coating	condition of coating?		Date of last coating inspection by ship staff	Frequency of Inspections
1	Р	1	Mild Steel	No	Uncoated	Full Tank	Fair	21 March 2017	26 August 2021	30 Months
1	S	1	Mild Steel	No	Uncoated	Full Tank	Fair	21 March 2017	26 August 2021	30 Months
2	Р	1	Mild Steel	No	Uncoated	Full Tank	Fair	21 March 2017	26 August 2021	30 Months
2	S	1	Mild Steel	No	Uncoated	Full Tank	Fair	21 March 2017	26 August 2021	30 Months
3	Р	1	Mild Steel	No	Uncoated	Full Tank	Fair	21 March 2017	26 August 2021	30 Months
3	S	1	Mild Steel	No	Uncoated	Full Tank	Fair	21 March 2017	26 August 2021	30 Months
4	Р	1	Mild Steel	No	Uncoated	Full Tank	Fair	21 March 2017	26 August 2021	30 Months
4	S	1	Mild Steel	No	Uncoated	Full Tank	Fair	21 March 2017	26 August 2021	30 Months

7.1.2 Does vessel have slop tanks or residual tanks?

No

7.1.3 Ballast tank coating

Structural Condition 15/35

Ballast Identifi		Are ballast tanks coated?	If yes, specify type of coating	If yes, specify to what extent		Specify Date when tank was coated.	Date of last coating inspection by competent person	Frequency of Inspections			
1 S		Yes	Ероху	Full Tank	Good	28 August 2021	-	Annual			
1P		Yes	Ероху	Full Tank	Good	28 August 2021	28 January 2023	Annual			
2S		Yes	Ероху	Full Tank	Good	28 August 2021	28 January 2023	Annual			
2P		Yes	Ероху	Full Tank	Good	28 August 2021	28 January 2023	Annual			
3S		Yes	Ероху	Full Tank	Good	28 August 2021	28 January 2023	Annual			
3P		Yes	Ероху	Full Tank	Good	28 August 2021	28 January 2023	Annual			
4C		Yes	Ероху	Full Tank	Good	28 August 2021	28 January 2023	Annual			
7.1.4	Tank a	anodes									
1	Are a	nodes fitted to th	ne cargo tanks?			No					
2	Are a	nodes fitted to th	ne ballast tanks?			No					
3	What	t type of anodes a	are fitted?			ZINC					
4	What	t is the extent of v	wastage of the an	odes in the cargo	tanks?						
5	What	t is the extent of v	wastage of the an	odes in the ballas	t tanks?						
6	If and	odes are aluminiu	ım, what is the he	ight above tank b	ottom?	150.00 mm	150.00 mm				
7.1.5		rmal programme s, cargo and balla	in place for regula st tanks?	ar inspection of vo	oid spaces, hold	Yes					
7.1.6	Plann	ed Prevention Ma	aintenance Progra	mme							
1			ned maintenance : me (PMP) implem		a preventive	Yes					
2	Is the	PMS/PMP system	m manual or com	puterised?		Manual					
3	Does the PMS/PMP cover all areas of the ship?					No					
4	If No.	, then specify the	areas not covered	d by the PMS/PM	Р						
5	Is the	PMS/PMP Class-	-approved?			No					
6	Does	the PMS/PMP in	clude an optimum	n spare parts inve	ntory?	No					
7	Does	the PMS/PMP in	clude a list of criti	cal equipment?		No					
8	Does	the PMS/PMP in	clude a list of spar	e parts for the cr	itical equipment?	No					
9	Does	the PMS/PMP in	clude the use of c	ondition-based m	nonitoring?	No					

8 Ballast and Bunker Handling

1 Ballast Tanks

8.1.1 Ballast tank capacities at 100% full (M3)

Ballast and Bunker Handling 16/35

ves	ssei P	'articulars Questio	onnaire for MI/T SMIOUTHSEA	4 21			IIVIC): 8776394		
Tar	nk Ide	entity		Capacity	(Cu. Mtrs)				
FPT	Γ			38.59						
W.I	B.T. 1	LP		21.19						
W.I	B.T. 1	LS		21.19						
W.I	B.T. 2	<u>2</u> P		43.70						
W.I	B.T. 2	2S		43.70						
W.I	B.T. 3	3P		46.67						
	B.T. 3			46.67						
W.I	B.T. 4	łC		48.60						
8.1	.2	Total Ballast Tan	k Capacity at 100% full		31	.0.31 Cu. Mtrs				
2		Ballast Handli	ing							
8.2	.1	Ballast Handling	Data							
Nui	mbei	r	Type - i.e. Screw, Centrifugal, Reciprocating, Other	Type of prime mover - i.e , Steam, Electric, Hydraulic Other		(Cu.m3/hr)	At what head?	(Mtrs)		
1			Centrifugal	Electric	50.00		1.00			
8.2	.2	Ballast handling	Main Pump							
	1	Normal back pro	essure		3.	00 Bar				
	2	Max RPM								
8.2	.3	Ballast Water Ma	anagement							
	1	Does the vessel	comply with D1 or D2 perfo	ormance standards?						
	2	Does the vessel	have a Ballast Water Treatr	nent System (BWTS) fitted	? N	0				
	3	What type of B\	WTS fitted?							
	4	If other, then sp	pecify							
	5		facturer of BWTS							
	6		have IMO type approval?			No				
	7	Is the BWTS of a	a USCG approved type?		N	0				
3		Segregated Ba	allast Tanks (SBT)							
8.3	.1	What is the total	I volume of the SBT tanks?		31	.0.31 Cu. Mtrs				
8.3	.2	What percentage	e of summer deadweight ca	n the ship maintain with S	BT only? 25	5.00 Percent				
8.3		•	eet the requirements of MA	_	No	0				
8.3			ballast be discharged throug	_	No	0				
8.3	.5	Is a spool piece t	to connect the ballast systen	n to the cargo system prov	ided? No	0				
8.3	.6	Segregated balla	ist tanks							
	1	Do cargo lines p	pass through any segregated	ballast tanks?	N	0				
	2	If Yes, what type ballast tank?	e of expansion joints are fitto	ed on the cargo line within	the					
	3	If other, then sp	pecify							
8.3	.7	Cargo tanks								
	1	_	pass through any cargo tank	ks?	N	0				

Ballast and Bunker Handling 17/35

- 2 If Yes, what type of expansion joints are fitted on the ballast line within the cargo tank?
- 3 If other, then specify
- 8.3.8 Line clearing
 - 1 Can the ship pump water ashore for line clearing?
 - 2 If Yes, what is maximum attainable discharge rate?
 - 3 If Yes, what is maximum acceptable back pressure?
 - 4 Which cargo tanks are designated for the carriage of heavy weather ballast? Cargo tank 1P/S-4P/S

4 Bunker Handling

8.4.1 Type, Size & Location of bunker connections - Oil

type of connection	location	Number of connections	Size of connections (mm)	pressure rating of bunker line (bar)				
HFO	aft at break of accom	2	100.00	3.50				
MGO	aft at break of accom	2	100.00	3.50				
8.4.2 Type, Size & Loca	Type, Size & Location of bunker connections - Gas Fuel							
8.4.3 If other, then spo	If other, then specify							
8.4.4 Does the vessel	use ESD links during bunker	ring operations?	Yes					

No

9 Cargo Specific

1 Cargo Handling (Oil)

9.1.1 Tank Plan YES

2 Double Hull Vessels

- 9.2.1 Centreline bulkhead
 - Is the ship constructed with a centreline bulkhead to all cargo tanks?
 If Yes, is bulkhead solid or perforated?
- 9.2.2 'U' shaped ballast tanks
 - 1 Is the ship fitted with any full breadth 'U' shape ballast tanks? No
 - 2 If Yes, how many ballast tanks are full breadth?
 - If Yes, does the ship have any inherent stability restrictions due to full breadth 'U' shape ballast tanks?

3 Cargo Tank Capacities

- 9.3.1 Cargo Tank Capacities At 98% Full (M3) Centre
- 9.3.2 Centre Tank Total Capacity (98%)
- 9.3.3 Cargo Tank Capacities At 98% Full (M3) Wing Tanks

Cargo Specific 18/35

Tank Nu	ımher		Port/Stbd		Capacity @ 989	<u>~~~</u>	(Cu. Mtrs)
1			Port		108.57	, 0	(ca. witis)
1			Stbd		108.57		
2			Port		167.02		
2			Stbd		167.02		
3			Port		168.02		
3			Stbd		168.02		
4			Port		164.03		
4			Stbd		164.03		
9.3.4	Wings (P and S	S combined) - Total	Capacity (98%) (M3)		1215.29 Cu. Mtr	S	
9.3.5	Deck tanks - C	apacities (98%) (M3					
9.3.6	Deck tanks - To	otal Capacity (98%)	(M3)				
9.3.7	Grand Total Ca	argo Capacity (98%)	(centre+wing tanks) (M	13)			
4	Slop Tank C	apacities					
9.4.1	Capacities of T	Γanks designated as	Slops tank (98%) (M3)				
9.4.2	Total Slop Tan	k Capacity (98%) (N	13)				
5	Cargo Hand	lling					
9.5.1	How many gra segregation?	ides of cargo can be	vith double valve	1			
9.5.2	How many graisolation?	ides of cargo can be	loaded or discharged w	vith blank flange	1		
9.5.3		mps and heat excha	ingers are fitted, can thoading?	e pumps and heat	No		
9.5.4	Oil Discharge I	Monitoring Equipme	ent (ODME)				
1	Is there Oil Di	ischarge Monitoring	g Equipment (ODME) fit	ted?	No		
2	Is an Oil Disch discharge?	narge Monitoring Sy	stem connected to the	above waterline	No		
3			oring System designed t s oil content exceeds pe		No		
9.5.5	Stability comp	outer					
1	Is the ship pro computer?	ovided with a class-a	approved or class-certif	ied stability	No		
2	Does this stat	bility programme co	nsider damaged stabili	ty conditions?	No		
6	Cargo Hand	lling Systems					
9.6.1	-	computer integrate		d equipped with alarm	No		
9.6.2	Cargo Pump d	ata					
Pump lo	dentity F	Pump Location	Туре	Type of prime mover	Capacity (Mtrs)	Cu.	At what head? (Mtrs)
2 PORT	F	Pumproom	Other	Other	300.00		1.00
1 STBD	F	Pumproom	Other	Other	300.00		1.00

Cargo Specific 19/35

9.6.3	If other, then specify	GEAR PUMP
9.6.4	Are dedicated cargo stripping lines and pumps provided?	Yes
9.6.5	State location of cargo pump emergency stops	
Pump lo		
1 STBD 2 STBD	MAIN DECK (BREAK MAIN	ACCOM) DECK (BREAK ACCOM)
9.6.6	High temperature alarms/trips	DECK (BREAK ACCOM)
9.6.7	If other, then specify	
9.6.8	What is the principal type of cargo valve?	Gate Valve
9.6.9	What type of cargo valve actuator is fitted?	Gate Valve
7	Cargo Room Control	
9.7.1	Is ship fitted with a Cargo Control Room (CCR) or a central cargo control location?	No
9.7.2	Can cargo and ballast pumps be controlled from the CCR or a central cargo control location?	No
9.7.3	Can all valves be controlled from the CCR or a central cargo control location?	No
9.7.4	Can tank innage/ullage be read from the CCR or a central cargo control location?	No
9.7.5	Is ODME readout fitted in the CCR or a central cargo control location?	No
9.7.6	Can the inert gas system be controlled from the CCR or a central cargo control location?	No
9.7.7	Are adjustable cargo temperature alarms fitted?	
9.7.8	Are adjustable cargo tank pressure alarms fitted?	
9.7.9	Are adjustable cargo tank level alarms fitted?	
8	Gauging and Sampling	
9.8.1	Can cargo be transferred under closed loading conditions in accordance with current edition of ISGOTT?	No
9.8.2	What type of fixed closed tank level gauging system is fitted?	
9.8.3	Is the fixed tank level gauging system provided with local readouts at each tank?	No
9.8.4	Is the fixed tank gauging system calibrated by a recognised cargo inspection company?	No
9.8.5	Name of the cargo inspection company conducting the calibration in 9.8.4?	
9.8.6	Do sounding pipes for portable gauging extend to full tank depth?	No
9.8.7	If 9.8.6 is "yes" then ask the question: Is the full length sounding pipe of slotted construction as per the current ISGOTT?	I
9.8.8	Are bunker tanks fitted with a full depth gauging system?	No
9.8.9	Cargo Tank High level alarms	

Cargo Specific 20/35

1	Are high level alarms fitted to the cargo tanks?	Yes
2	If Yes, are the high level alarms fitted to all cargo tanks?	Yes
3	Are the high level alarms independent of the gauging system?	Yes
9.8.10	Bunker tanks high level alarms	
1	Are bunker tanks fitted with high level alarms?	No
2	If Yes, are bunker tank high level alarms part of the primary tank gauging system?	No
9.8.11	Is closed-sampling equipment provided for cargo?	Yes
9.8.12	Are cargo tanks fitted with dipping points as per "IMO Res A.446 (11) as amended?	No
9.8.13	Portable gauging equipment	
1	Is portable equipment used for gauging?	No
2	If yes, who is the manufacturer?	
3	How many units are supplied?	
9.8.14	Vapour locks	
1	If portable equipment for gauging uses vapour locks, are vapour locks calibrated by a recognised cargo inspection company?	No
2	If Yes, what is the name of the cargo inspection company?	
3	If Yes, by whom are vapour locks certified?	
9.8.15	What is the name of the manufacturer of the vapour locks?	Chang Heng
9.8.16	What is the nominal (internal) diameter of the vapour lock?	50.00 mm
9.8.17	To what standard is the thread of the vapour lock manufactured?	
9.8.18	Can vapour lock be used for ullaging?	Yes
9.8.19	Can vapour lock be used for temperature?	Yes
9.8.20	Can vapour lock be used for interface?	Yes
9.8.21	Can vapour lock be used for cargo sampling?	Yes
9.8.22	If the vapour lock can be used for cargo sampling, what is the volume of the sample that can be drawn?	2.00 ltrs
9.8.23	Specify portable equipment for checking oil/water interface	Yes
9.8.24	Can cargo samples be taken at the manifold?	No
9.8.25	What is the means of taking cargo temperatures?	Liquid In-glass Thermometer
9.8.26	Are temperature sensors with readouts in the cargo control position, provided for each cargo tank?	No
9	Vapour Emission Control	
9.9.1	Is a vapour return system fitted?	Yes
9.9.2	If fitted, is vapour line return manifold in compliance with OCIMF Guidelines?	Yes
9.9.3	If fitted, how many vapor return segregations can the vessel maintain simultaneously?	1
9.9.4	Does the ship possess Vapour Emission Control (VEC) Certification?	Yes

Cargo Specific 21/35

9.9.5	If yes, state the issuing a	ıthority			Harir	n Panich dock ya	ard		
10	Venting								
9.10.1	What type of venting syst	tem is fitted?			MAS	T RIZER			
9.10.2	What is the maximum ve	nting capacity?			4073	.06 Cu.Mtrs/Hr			
9.10.3	What is the P/V valve ope	ening pressure?							
9.10.4	What is the P/V valve vac	uum setting?							
9.10.5	Are isolating valves fitted	to each cargo ta	nk?		Yes				
9.10.6	Secondary Venting Arrangements for Cargo Tanks as required by SOLAS - Provide details of the secondary venting arrangements for each cargo tank								
9.10.7	If other, then specify								
9.10.8	Are pressure sensors, having readouts and audio-visual alarms in the cargo Yes control position, provided in each cargo tank?								
9.10.9	Mast Risers								
1	Is venting through a mas	st riser?			Yes				
2	Are mast risers fitted wi	th high velocity v	ents?		No				
3	If Yes, state opening pre	ssure							
4	What is the vacuum sett	ing of the mast r	iser P/V valve?						
5	What is the maximum ca	apacity of the ma	st riser venting sy	ystem?	4073	.06 Cu. Mtrs/Hi	-		
6	What is the maximum lo	ading rate for ho	mogenous cargo	?	791.9	98 Cu.Mtrs/Hr			
9.10.10	When carrying oil cargo,	maximum loadin	g rate per single i	manifold					
Manifol	ld No			Loading Rate (oil) per Man	ifold (Cu. ľ	Mtrs/Hr)		
1				791.98					
2				791.98					
11	Cargo Manifolds								
9.11.1	Does the cargo manifold OCIMF 'Recommendation Associated Equipment'?	_			Yes				
9.11.2	Manifold Valves								
1	What type of valves are	fitted at manifol	45		Gate	/ Wafer			
2	If other, then specify								
3	If hydraulic valves fitted	, what are closing	g times?						
9.11.3	What is the number of ca	rgo connections	per side?		1				
9.11.4	What is the size of cargo	connections?							
Manifol	ld Number P/C/S	Size	Unit	Pressui	re rating	Unit	standard of presentation flange		
1	Р	200	mm	5		KG/Cm2	ANSI		
1	S	200	mm	5		KG/Cm2	ANSI		
9.11.5	Are pressure gauges fitted with valves or cocks located outboard of manifold Yes valves?								

Cargo Specific 22/35

9.11.6	What is the material of the manifold?	Steel
9.11.7	Is a cargo line crossover fitted at the manifold?	No
12	Connection to Shore for ESD and Communications Systems	
9.12.1	ESD Shore connection	
1	Is ESD connection to shore available?	No
2	If yes, is the system pneumatic, electrical or fibre optic?	
3	What is the type of connection plug used?	
4	If other, then specify	
9.12.2	ESD hoses/cables	
1	Are ESD hoses or cables available on board?	No
9.12.3	If yes, length of pneumatic, length of electrical, length of fiber optic	
9.12.4	ESD Communications	
1	Is there a connection available for a telephone line?	No
2	Are ESD connections available on both sides of the ship?	No
13	Manifold Arrangement	
9.13.1	Measurements	
1	Distance A bunker manifold to cargo manifold	16140.00 mm
2	Distance B cargo manifold to cargo manifold	6600.00 mm
3	Distance C cargo manifold to vapour return manifold	12950.00 mm
4	Distance D manifolds to ship's rail	800.00 mm
5	Distance E spill tank grating to centre of manifold	200.00 mm
6	Distance F main deck to centre of manifold	1050.00 mm
7	Distance G main deck to top of rail	900.00 mm
8	Distance H top of rail to centre of manifold	940.00 mm
9	Distance J manifold to ship side	1400.00 mm
10	What is the height of the manifold connections above the waterline at loaded (Summer loadline) condition?	1.50 Mtrs
11	What is the height of the manifold above the waterline at Normal Loaded condition	1.50 Mtrs
12	What is the height of the manifold connections above the waterline in normal ballast?	3.15 Mtrs
13	What is the height of manifold connections above the waterline in lightship condition?	3.35 Mtrs
14	What is the distance between the keel and centre of manifold?	5.55 Mtrs
9.13.2	Is a stern discharge manifold fitted?	No
9.13.3	If stern manifold fitted, state size	
9.13.4	Is a bow manifold fitted?	No
9.13.5	If bow manifold fitted, state size	
9.13.6	Bow Manifold Standard	
1	If bow manifold is fitted, to what Standard is it manufactured?	

Cargo Specific 23/35

Material

2 If other, then specify

14 **Gas Monitoring**

9.14.1 Is a fixed system fitted to continuously monitor potentially flammable Yes

atmospheres?

9.14.2 What spaces are monitored? Pump Room

Engine Room

What is

Diathermic oil

What is

Are

9.14.3 Where are sensors/sampling points located in pumproom? Above Bottom 30 cm

Is the heat Does the Does the how many What is

9.14.4 What is the rank of the person or persons who are responsible for testing 3rd Officer

sensors/sampling points?

P/C/S/Dec Is tank

15 Cargo Heating

tank

Please provide details of Heating Coils/Heat Exchangers

Identity	ktank/ Other	heating provided by a heat exchanger ?	internal or external		tank have heating coils?	independ ent heating coil sets are fitted to the tank?	the height of the heating coils above the tank bottom? (mm)	heating surface area of	the ratio of the heating surface to the volume of the tank?	•	of heating coils
1	Р	No	Internal	No	Yes	1	100.00	1.00	1.00	Welded	MS
1	S	No	Internal	No	Yes	1	100.00	1.00	1.00	Welded	MS
2	Р	No	Internal	No	Yes	1	100.00	1.00	1.00	Welded	MS
2	S	No	Internal	No	Yes	1	100.00	1.00	1.00	Welded	MS
3	Р	No	Internal	No	Yes	1	100.00	1.00	1.00	Welded	MS
3	S	No	Internal	No	Yes	1	100.00	1.00	1.00	Welded	MS
4	Р	No	Internal	No	Yes	1	100.00	1.00	1.00	Welded	MS
4	S	No	Internal	No	Yes	1	100.00	1.00	1.00	Welded	MS

9.15.2 If other, then specify

9.15.3 Inlet heating

5

1 Inlet heating medium to coils Thermal oil

2 If other, then specify

3 With Sea temperature 25.00 Deg C 4

With air temperature 30.00 Deg C

Heating agent 6 If other, then specify

9.15.4 Number of heaters

> Number of heaters 1 1

Able to raise temperature from 2 35.00 Deg C

3 Able to raise temperature to 220.00 Deg C

4 Time taken to raise temperature 8.00 Hrs

5 Total capacity of boilers

Cargo Specific 24/35

16	Inert Gas and Crude Oil Washing	
9.16.1	Is an inert gas system (IGS) fitted? (If No, ignore remainder of this section)	No
9.16.2	Is a P/V breaker fitted?	No
9.16.3	Do the inert gas distribution lines have natural segregations that match the cargo pipeline segregations?	No
9.16.4	Is the inert gas supplied by flue gas, inert gas generator, N2 generator and/or stored nitrogen?	
9.16.5	Are fixed O2 alarms fitted in inert gas generating or storage spaces?	No
9.16.6	What is the capacity of the IGS?	
9.16.7	Is the capacity at least 125% of the maximum designed cargo discharge rate?	
9.16.8	How many fans does it have?	
9.16.9	What is the total combined fan capacity?	
9.16.10	IG generator	
1	Is an IG generator fitted?	No
2	If Yes, what is its capacity?	
	Nitrogen Generator	
1	Is a Nitrogen Generator fitted?	
	If yes provide their capacities at 95%; 98% & 99.9%	
9.16.13	Stored Nitrogen Is Nitrogen provided from stored Nitrogen Bottles?	
	If yes provide quantities (number of bottles; capacity of each)	
	Nitrogen Buffer Tanks Is a Nitrogen buffer or storage tank fitted?	
	If yes provide capacity	
		Na
	Is an IGS operating manual on board?	No
	What type of deck seal is fitted?	
	How many segregations does the IGS have?	
	What method is used to isolate individual tanks?	
9.16.21	What type of non-return valve is fitted?	
9.16.22	If the cargo tanks can be individually isolated from the IGS/Vent line, what means of secondary protection is fitted?	NO
9.16.23	If ship has double hull or sides, are facilities available to inert ballast tanks and other void spaces?	No
9.16.24	How is inert gas supplied to the ballast tanks or other void spaces?	
9.16.25	Are arrangements for the prevention of over-pressurisation of these tanks/spaces provided?	
9.16.26	Does the vessel have portable vent stacks and P/V valves for use in inerting ballast and void spaces?	

Cargo Specific 25/35

	9.16.27	Are these	arrangements	fixed or	portable?
--	---------	-----------	--------------	----------	-----------

9.16.28 Can these tanks/spaces be purged with air?

9.16.29 Emergency IGS Connection

- 1 Where is the location of the emergency IGS connection?
- 2 What is the size of the emergency IGS connection?

9.16.30 Crude Oil Washing

- 1 Is a Crude Oil Washing (COW) installation fitted?
- 2 Are COW drive units fixed or portable?
- 3 Are COW drive units programmable?
- 4 Can COW be conducted at the same time as cargo discharge? No
- 5 Is there an approved COW Manual on board? No
- 6 What is the working pressure of the COW lines?

17 Cargo Pumps

9.17.1 Cargo Pumps

Туре	Prime Mover	Self-priming or	Capacity (m3/hr)	Max Normal Back	Max Back	Pressure	e Max RPM
		draining	(m3/hr)	Pressure	Head	(bar)	(RPM)
Gear Pump	Main Engine	Self Priming	300.00	7.00	7.50		350.00

No

9.17.2 Stripping Pumps

10 Mooring

1 Mooring

10.1.1	Does the ship meet the recommendations contained in the latest edition of	Yes
	OCIME Mooring Equipment Guidelines?	

10.1.2 Mooring Equipment Management

- 1 Does the vessel maintain a Mooring System Management Plan (MSMP)? Yes
- 2 Does the vessel maintain a Line Management Plan (LMP)? Yes
- 3 What is Ship design MBL (SDMBL)? 29.44 Tonnes
- 10.1.3 Mooring Winches and Brake Testing
 - 1 Is brake testing equipment on board? Yes
 - 2 Complete the diagram for mooring winch layout

10.1.4 Details of winches and brake testing including rendering loads

Mooring winch Location	Split Drum	Motive Power	Remote Operation al controls	•	Hauling Speed (m/s)	Type of Brake	Designed Brake Max holding load (ISO) (80% of SDMBL) (Tonnes)	Operation al brake holding load (60% of SDMBL) (Tonnes)	last brake test	Brake Rendering load (Tonnes)	Frequency of testing brakes
1	Yes	Hydraulic	Yes	50.00	1.00	Manual	35.20	22.20	25 August 2022	37.00	Annual
2	Yes	Hydraulic	Yes	50.00	1.00	Manual	35.20	22.20	25 August 2022	37.00	Annual

Mooring 26/35

10.1.5	If other,	then spe	cify											
10.1.6	Load Ter	nsion Moi	nitoring											
1	Are Winches fitted with Load Tension cell monitoring equipment?													
2	If yes, s	tate the t	ype of re	adout						Local Onl	У			
3	Are Mo	oring line	s equipp	ed with ir	nserts for	load cell	tension r	nonitorin	g?	No				
4	Are Mo	oring line	s equipp	ed with ir	ndicator s	trands?			,	Yes				
10.1.7	Provide	details fo	r Moorin	g Ropes, \	Wires, Ta	ils and Sh	ackles							
Type	Locatio n and Identity	Materia I		(Mtrs/N	(100- 105 % of SDMBL	TDBF (125- 130 % of SDMBL (Tonnes)	SWL (tonnes)	WLL (tonnes) (50- 55% of Max LDBF)		Installe d Date	Reverse d Date	Renewa I2 Date	of	Conditi on of line/tail
Ropes	Fwd No.2	Polypro pylene	48.00	200.00	36.80	39.90	36.80	21.90	CHA 220546 7/5-07	26 January 2023	26 January 2023	26 January 2023	In Use	Suitable
Ropes	Fwd No.1	Polypro pylene	48.00	200.00	36.80	39.90	36.80	21.90	BUS- 220259 7/21	04 July 2022	04 July 2022	04 July 2022	In Use	Suitable
Ropes	Fwd No.3	Polypro pylene	48.00	200.00	36.80	39.90	36.80	21.90	CHA 220546 7/5-06	26 January 2023	26 January 2023	26 January 2023	In Use	Suitable
Ropes	Fwd No.4	Polypro pylene	48.00	200.00	36.80	39.90	36.80	21.90	CHA 200514 8/2-19	=	03 May 2023	03 May 2023	In Use	Suitable
Ropes	Fwd No.5	Polypro pylene	48.00	200.00	36.80	39.90	36.80	21.90	BUS- 220259 7/22	04 July 2022	04 July 2022	04 July 2022	In Use	Suitable
Ropes	Fwd No.6	Polypro pylene	48.00	200.00	36.80	39.90	36.80	21.90	CHA 200514 8/2-20	18 May 2021		18 May 2021	In Use	Suitable
Ropes	Aft No.7	Polypro pylene	48.00	200.00	36.80	39.90	36.80	21.90	CHA 200514 8/2-21	-	18 May 2021	18 May 2021	In Use	Suitable
Ropes	Aft No.8	Polypro pylene	48.00	200.00	36.80	39.90	36.80	21.90	CHA 200514 8/2-22	-	18 May 2021	18 May 2021	In Use	Suitable
Ropes	Aft No.9	Polypro pylene	48.00	200.00	36.80	39.90	36.80	21.90	BUS- 220259 7/24	04 July 2022	04 July 2022	04 July 2022	In Use	Suitable
Ropes	Aft No.10	Polypro pylene	48.00	200.00	36.80	39.90	36.80	21.90	CHA 220546 7/5-09	26 January 2023	26 January 2023	26 January 2023	In Use	Suitable
Ropes	Aft No.11	Polypro pylene	48.00	200.00	36.80	39.90	36.80	21.90	BUS- 220259 7/23	04 July 2022	04 July 2022	04 July 2022	In Use	Suitable
Moorin g Wires		Polypro pylene	48.00	200.00	36.80	39.90	36.80	21.90	CHA 220546 7/5-08	-	26 January 2023	26 January 2023	In Use	Suitable
10.1.8	Retireme	ent Policy	- Provide	e compan	y policy o	on wire/r	ope retire	ement						

Mooring 27/35

1	Mooring Ropes					5000 H	rs End to End	d / 10000 Hr	s. Renews		
2	Mooring Wires										
3	Tails										
2	Mooring bollards/b	Mooring bollards/bitts and fairleads									
10.2.1	Complete the diagram for layout of Mooring Fairleads/Chocks and bollards/bitts - Interactive diag for location										
10.2.2	Provide details of Mooring bollards/bitts										
10.2.3	Provide details of Mooring Fairleads/Chocks										
10.2.4	Are all Panama type or 0	Closed roller t	ype fairleads	s as per MEG	i 4 definition?	Yes					
10.2.5	Are open rollers as per I	MEG 4 definiti	ion?			Yes					
10.2.6	If open rollers have encl having SWL equality wit	_	as Yes								
3	Anchors and Windlass										
10.3.1	What is the motive pow	er of the wind	Hydrau	Hydraulic							
10.3.2	What is the cable diame	eter?				40.00 n	40.00 mm				
10.3.3	Number of Shackles										
1	Port cable	8.00 Sh	nackles								
2	Starboard cable					8.00 Sh	nackles				
10.3.4	Are bitter end connection	Yes									
4	Emergency Towing	Arrangeme	nts								
10.4.1	Is an Emergency Towing this section	Arrangement	(ETA) fitted	? If not, igno	re remainder	of Yes					
10.4.2	Details of ETA										
	Type of System	Safe Working Load (SWL) of System in tonnes (Tonnes)	Is pick-up gear provided?	Towing pennant length in mtrs (Mtrs)	Towing pennant diameter in mm (mm)	Types of strong point (e.g. Smit bracket)	Chafing Chain Size in mm (mm)	Fairlead size (in format ABCmm x XYZmm) (mm x mm)	Is a pedestal roller fitted?		
Forwar	d	40	Yes	200	48						
Aft		40	Yes	200	48						
10.4.3	How many sets of bitts	are fitted in th	ne bow area?	?		2					
10.4.4	What is the height of th	e bitts in the I	oow area?			600.00	mm				
10.4.5	What is the Safe Workin	g Load (SWL)	of the bitts	in the bow a	rea?	37.00 T	onnes				
10.4.6	What is the distance be	tween bow fa	irleads and r	nearest bitts	?	150.00	mm				
10.4.7	Is the bow area clear of connections?	any obstruction	ons which w	ould hamper	towing	Yes					
5	Escort Tug										

Mooring 28/35

10.5.1	SWL of closed chock on stern	37.00 Tonnes
10.5.2	SWL of bollard on poopdeck suitable for escort tug	37.00 Tonnes
10.5.3	Are stern chock and bollard capable of towing astern to 90 degrees?	Yes
10.5.4	Does the vessel have recessed bitts?	No
10.5.5	Provide details of the recessed bitts	
6	Single Point Mooring (SPM) Equipment	
10.6.1	Does the ship meet the recommendations contained in the latest edition of OCIMF 'Recommendations for Equipment Employed in the Bow Mooring of Conventional Tankers at Single Point Moorings'?	No
10.6.2	Bow chain stoppers	
1	Are bow chain stoppers fitted?	No
2	If Yes, how many?	
10.6.3	Details of bow chain stoppers	
10.6.4	Bow Closed fairleads	
1 2	Are closed fairleads of OCIMF recommended size (600mm x 450mm)? If not, give details of size (in format ABCmm x XYZmm)	No
10.6.5	If two forward bow fairleads are fitted give distance between them	
10.6.6	What is the distance between the bow fairlead and stopper/bracket?	
10.6.7	What is the distance from the stopper bracket to roller lead/winch drum?	
10.6.8	Is there a direct lead from the bow stopper to the winch drum (not the warping end)?	No
10.6.9	Is the winch storage drum capable of safely accommodating 150m X 80mm fibre pick up rope?	No
10.6.10	Is the winch storage drum capable of safely accommodating 200m X 80mm fibre pick up rope?	No
7	Bow mooring arrangement diagram	
10.7.1	Bow mooring arrangement diagram	Yes
8	Manifold arrangement	
10.8.1	Manifold Arrangement Diagram	Yes
10.8.2	Distance K end of drip tray to center line of deck cleat	
10.8.3	Distance L spill tray to centre line of bollard	
10.8.4	Distance M length of bollard	
9	Lifting equipment	
10.9.1	Provide details of derricks, cranes and other lifting equipment	
10.9.2	Is Safe Working Load (SWL) clearly marked on all lifting equipment?	No

Mooring 29/35

10.9.3	Can the derricks or crane(s) maintain their design SWL when plumbing a point one metre outboard from the ship's side over the full length of the manifold including bunker and vapour connections?	No
10.9.4	If the ship is equipped to operate at Single Buoy Moorings (SBMs), does the arrangement at the manifold area for securing floating hoses meet OCIMF Guidelines?	No
10	Other equipment	
10.10.1	Are accommodation ladders arranged to face aft when rigged?	No
10.10.2	Date of last renewal of wires for Accommodation ladder	
10.10.3	Is the accommodation ladder well within the parallel mid-body of the ship so boats may come alongside safely at all stages of draft?	No
10.10.4	Are Suez Canal boat davits fitted?	No
10.10.5	Is a Suez Canal searchlight fitted?	No
10.10.6	Portable Gangway Information	
10.10.7	Information for Shore Gangway	
1	Does the vessel have a designated deck area or landing platform to place a terminal shore tower gangway?	
10.10.8	If yes then provide details	

11 Propulsion

1 Main Propulsion

11.1.1	Means of main propulsion	
1	What is the means of main propulsion	Diesel Electric
2	If motor state whether two stroke or four stroke	Four
3	If four stroke, state how many engines fitted	1
11.1.2	How many propellers are fitted?	Single
11.1.3	Type of propellors	fixed
11.1.4	Boilers	
1	How many boilers are fitted?	
2	What is rated output of boilers?	
3	Are the boilers equipped to operate on low sulphur fuel?	No
11.1.5	Low sulphur fuel requirements	
1	Is equipment fitted and are procedures in place to changeover main propulsion fuels to meet low sulphur fuel requirements?	Yes
2	Is equipment fitted and are procedures in place to changeover auxiliary equipment fuels to meet low sulphur fuel requirements?	Yes
11.1.6	What type of fuel is used for main propulsion?	HFO
11.1.7	If other, then specify	
11.1.8	Are pressurised fuel pipes double sheathed?	Yes

Propulsion 30/35

11.5.1 Bunker tank capacities

	-			
11.1.9	When moored at SBM, is main engin revolutions for extended periods (up			No
11.1.10	Can a speed of less than 5kts be mai		Yes	
11.1.11	Is the ship certified for Unmanned M	Ոachinery Space (UMS) օր	peration?	No
11.1.12	Is the machinery space operated in u	unmanned mode?		No
11.1.13	Quick closing valves			
1	Does the vessel have Quick closing	valves for the main engin	e?	Yes
2	Type of quick closing valves		Wire Sling	
2	Thrusters			
11.2.1	Are thrusters fitted?			No
11.2.2	Provide details of Thrusters fitted			
11.2.3	High angle rudder			
1	Is a high angle rudder fitted?			No
2	Number fitted			
3	What type			
3	Generators			
11.3.1	Power Generators			
type		design power output	(kW)	fuel
Diesel		180.00		MDG
Diesel		180.00		MDG
11.3.2	Does the ship's power management of fuel?	system provide for seam	less change-over	No
11.3.3	Source of emergency power?			Emergency Generator
11.3.4	Primary and secondary sources of st	arting the emergency ger	nerator	
			Starting Power	
Primary			Air	
Seconda	ary		Manual	
4	Main engine air start compres	ssors		
11.4.1	Number of main engine start compre	essors		2
11.4.2	Operating pressure			25.00 Bar
11.4.3	Motive power of emergency compre	essor		7.00 Cu Mtrs/Hr
5	Bunkers			

Propulsion 31/35

Tank Name	Bunker Type	Tank Type	Capacity	(m3)	Max Pressure	(bar)
FOT 1 Port	HFO	Main Bunker Tank	23.10		5.00	
FOT 1 STBD	HFO	Main Bunker Tank	23.10		5.00	
FOT 2 Port	HFO	Settling Tank	9.93		5.00	
FOT STBD	HFO	Service Tank	9.93		5.00	
DOT 1 Port	MDO	Main Bunker Tank	13.68		5.00	
DOT 1 STBD	MDO	Service Tank	14.53		5.00	

- 11.5.2 If other, then specify
- 11.5.3 Capacity of equipment consuming Boil-off Gas (BOG) from bunker tanks
- 11.5.4 If other, then specify
- 11.5.5 Gas monitoring system for fuel gas
 - 1 Does the vessel have gas monitoring equipment for the fuel gas system?
 - 2 If yes, is the gas monitoring system linked to the fuel gas system ESD?

6 LNG Bunkers

11.6.1 Bunker boom

- 1 Is the vessel fitted with a bunker boom?
- 2 Maximum height of bunker boom hose envelope in laden condition
- 3 Minimum height of bunker boom hose envelope in ballast condition
- 4 Distance of bunker boom pedestal to centerline
- 5 Is the bunker boom equipped with a Vapor connection?
- 6 Is the bunker boom equipped with a ERC?
- 7 Make, model and size of ERC
- 8 Location of the ERC

11.6.2 Emergency Release System

- 1 Is the vessel equipped with a ERS?
- 2 Make of ERS
- 3 SIL rating of ERS

11.6.3 Bunker hoses

- 1 Length of bunker hoses available
- 2 MAWP of bunker hoses
- 3 Make of bunker hoses
- 4 Hoses designed to EN 1434-2
- 5 Are all LNG bunker connections fitted with a insulation flange?
- 11.6.4 LNG Bunker ESD link
 - 1 Is the vessel fitted with a SIGTTO 5 pin?
 - 2 Make of SIGTTO 5 pin electrical link
 - 3 Length of ESD cable
 - 4 Is the vessel fitted with a pendant ESD link?
 - 5 Length of pendant cable

11.6.5 Vapour return

1 Is the vessel able to take vapour return?

Propulsion 32/35

- 2 How does the vessel manage vapour return?
- 3 Maximum flowrate of vapour return

7 Steering gear

11.7.1	What type of steering gear is fitted?	Hydroeletric motor
11.7.2	How many motorized hydraulic pumps or motors fitted?	2
11.7.3	How many telemotors fitted?	2
11.7.4	Is an emergency rudder arrest/rudder control fitted?	Yes
8	Anti-pollution	
11.8.1	Is an engine-room bilge high level alarm fitted?	Yes
11.8.2	How many Engine Bilge Alarms are fitted?	1
11.8.3	Is a pump room bilge high level alarm fitted?	Yes
11.8.4	How many Pump Room bilge high level alarms are fitted?	1
11.8.5	Is there a permanently installed system for the disposal of residues from the machinery space sludge tank to shore?	No
11.8.6	Are there facilities on board to incinerate machinery space sludge?	No
9	Exhaust Gas Cleaning System	
11.9.1	Does the vessel use an Exhaust Gas Cleaning System?	No
11.9.2	What is the type of scrubber fitted as part of the EGCS onboard?	
11.9.3	List the equipment that are connected to the system (M/E, A/E, boilers)?	
11.9.4	If other, then specify	
10	Ship Energy Saving Equipment	
11.10.1	List all the types of Ship Energy saving equipment fitted on the vessel? (e.g. Hydrodynamic energy saving device, air lubrication, wind power, batteries etc)	

11.10.2 If other, then specify

11

- 11.11.1 What is the ships NOx control level (Tier I, Tier II, and Tier III)?
- 11.11.2 List of equipment fitted for NOx Tier III achievement for all engines (LP Selective catalytic reduction, HP Selective catalytic reduction, Exhaust gas recirculation, Alternative fuel etc...)
- 11.11.3 If other, then specify

12 Ship to Ship Transfer

NOx Emission Compliance

1 Ship to Ship Transfer

Ship to Ship Transfer 33/35

12.1.1	Is the vessel manned with at least 4 deck officers, in addition to the master?	Yes
12.1.2	Are at least 7 ratings available to assist with mooring operations?	Yes
12.1.3	If cranes are fitted, are they certified for personnel transfer?	No
12.1.4	Are personnel who will operate cranes for personnel transfer properly trained and assessed competent as per OCIMF guidelines on Transfer of personnel by crane between vessels?	No
12.1.5	Does the Operator's SMS provide instructions regarding the transfer of personnel using cranes?	No
12.1.6	Does the vessel have a restriction on STS berthing operations during the hours of darkness?	No
12.1.7	If required for the STS transfer location, will your vessel accept wire mooring tails provided by the STS Service Provider?	No
12.1.8	Provide details of the location, size and SWL of all mooring bollards; chocks; rollers and fairleads used for STS operations	
12.1.9	Does the vessel have independent capstans for use during STS operations?	
12.1.10	Is the vessel externally framed on the main deck?	
12.1.11	Does the ship comply with recommendations contained in Ship to Ship Transfer Guide for Petroleum, Chemicals and Liquefied Gases (OCIMF/CDI/ICS/SIGTTO)?	Yes
12.1.12	Are four (4) 200m x 40mm messenger lines available for Ship-To-Ship (STS) mooring operations?	No
12.1.13	Are there two (2) closed chocks with associated bollards and leads to winches located as close as possible forward and aft of the manifold, and preferably within 3-5 meters of the manifold rail?	Yes
12.1.14	Details of nearest bollards and associated closed fairleads from the centre of the manifold?	
2	Derricks / Hose handling cranes	
12.2.1	Are Derricks / Hose handling cranes available?	No
12.2.2	Load carrying capacity SWL	
12.2.3	Maximum outreach beyond the ships side within the design SWL?	
12.2.4	Location of crane from manifold centreline (F+ / A-)	
3	Transfer hoses	
12.3.1	Are transfer hoses available onboard?	
12.3.2	Details of transfer hoses	
12.3.3	Is hose saddle available?	
12.3.4	Is Personnel transfer arrangement available?	
4	Fenders	
12.4.1	Total number of fenders carried onboard	
12.4.2	Fender Details	

Ship to Ship Transfer 34/35

12.4.3 If other, then specify

13 Combination Carriers

1 Combination Carriers

- 13.1.1 State design of hatches
- 13.1.2 State type of hatches
- 13.1.3 State if hatches fitted with single or double seals in hatch coaming Double seals
- 13.1.4 Last date cargo holds/tanks were tested to normal working pressure (min.500mm wg) to prove gas tightness of hatches
- 13.1.5 Were the hatches proven to be gas tight?

No

Combination Carriers 35/35