PukSquash Developer Manual

My Bookings History and Cancellation

Firebase Data Connect edition | Source revision fe3e361 | 4 October 2026

1 Functionality Overview

My Bookings displays the authenticated user’s reservations and Open sessions they joined. It supports upcoming, past and cancelled scopes. The cancellation endpoint distinguishes cancelling the creator’s reservation from leaving another user’s Open session.

MyBookingsPage requests a scope and renders BookingCard components. The repository returns reservations where the user is the creator or a participant. The controller applies date/time filtering and sorts the result. When the user confirms cancellation or leaving, the endpoint derives the caller from Firebase and checks ownership or participation before changing data.

1 1 Files and Responsibilities

resources/js/pages/MyBookingsPage.vue and components/BookingCard.vue — list and actions

resources/js/components/ConfirmDialog.vue — confirmation pattern

resources/js/features/booking/bookingService.js — myBookings and cancelBooking

app/Http/Controllers/Api/BookingController.php — mine and cancel

app/Repositories/BookingRepository.php and BookingPlayerRepository.php — cancellation and leaving

1 2 API Contract

GET /api/bookings/mine?scope=upcoming|past|cancelled returns an array. POST /api/bookings/{id}/cancel returns {"left":false} for creator cancellation or {"left":true} for leaving an Open session.

Reading this part

Code excerpts are from the stated Firebase revision unless explicitly labelled as a proposed extension. Requirements and maintenance gaps are separated from implemented behaviour. Each part can be read independently; Part 00 covers the shared environment.

2 Creator and participant behaviour

app/Http/Controllers/Api/BookingController.php | source line 352 onward; blank and comment lines omitted

```
    $isCreator = ($booking->createdBy['id'] ?? null) === $user->id;
    if (! $isCreator) {
        if ($booking->bookingType !== 'OPEN') {
            return response()->json(['message' => 'You are not authorised to cancel this
booking.'], 403);
        }
        $isPlayer = false;
        foreach ($booking->players as $p) {
            if (($p->user['id'] ?? null) === $user->id) {
                $isPlayer = true;
                break;
            }
        }
        if (! $isPlayer) {
            return response()->json(['message' => 'You are not authorised to cancel this
booking.'], 403);
        }
        $this->players->remove($id, $user->id);
        return response()->json(['left' => true]);
    }
    $this->bookings->cancel($id);
    return response()->json(['left' => false]);
}
```

Explanation

Only the creator can cancel the reservation itself. A non-creator may leave only if the booking is Open and the user is one of its participants. A caller with no relationship to the booking is denied. This distinction preserves the original reservation when Player 2 leaves.

Physical Code Explanation

1 isCreator compares the booking creator ID with the verified application user ID.

2 A non-creator is rejected with 403 unless the type is OPEN and their membership is found.

3 players->remove deletes that user's participation and returns left=true.

4 For the creator, bookings->cancel marks the reservation cancelled and returns left=false. Earlier checks reject missing or already cancelled bookings.

The list uses Africa/Johannesburg time. In the baseline, upcoming/past classification is based on the slot start, while the coach schedule keeps sessions until their end. That difference is intentional to document rather than silently normalise.

3 Cancellation and leaving mutations

app/Repositories/BookingRepository.php | source line 93 onward; blank and comment lines omitted

```
public function cancel(string $id): void
{
    $this->client->execute('CancelBooking', [
        'id'          => $id,
        'cancelledAt' => now()->toIso8601ZuluString(),
    ]);
}
```

Explanation

Cancellation changes the Booking status to CANCELLED and sets cancelledAt through the CancelBooking mutation. Availability queries consider confirmed bookings, so the cancelled reservation no longer blocks the court. Leaving an Open booking instead calls the LeaveBooking mutation, which deletes the participant relation matching both booking ID and user ID.

Physical Code Explanation

1 execute selects CancelBooking and provides the booking key plus the server's cancellation timestamp.

2 The GraphQL mutation updates the status rather than deleting the booking, retaining a cancelled record for history.

3 LeaveBooking uses a constrained deleteMany matching bookingId and userId; it does not remove the creator or other participants.

My Bookings fetches confirmed or cancelled data and then filters by creator or participant. The baseline repository fetches all bookings of the selected status before filtering in PHP; a server-side user filter and pagination would improve scalability.

4 Verification and Maintenance

Verification checklist

1 Confirm a creator appears in My Bookings and Player 2 also sees the joined Open booking.

2 As Player 2, leave: expect left=true, the creator still listed and the grid Open again.

3 As the creator, cancel: expect left=false, a cancelled history record and a free cell after refresh.

4 Try cancelling another user's Locked booking: expect 403. Try cancelling an already cancelled booking: expect 422.

5 Check today's boundaries for upcoming and past, and verify cancelled entries are selected by status.

Implementation boundaries

The cancel method does not enforce a future-time cutoff in this baseline. A disabled frontend action is not a backend cancellation policy; add the agreed rule explicitly if required.

Unsupported scope values are not explicitly validated in mine. Validate the accepted scopes before extending the endpoint, and add tests for unexpected values.

4 1 Source References

PukSquash repository, revision fe3e361; source paths are identified beside each excerpt. Requirements: Functional Specifications PukSquash (3) and Techinical specifications PukSquash (2). Business context: Business_Case and Feasibility_Study for PukSquash. Structure reference: Campus Marketplace Developer Manual (4).