

C Operator Precedence and Associativity

C Programming (COP-2220)

HOME	FAQ	SEARCH	FEEDBACK	APIs
----------------------	---------------------	------------------------	--------------------------	----------------------

This page lists C operators in order of *precedence* (highest to lowest). Their *associativity* indicates in what order operators of equal precedence in an expression are applied.

Operator	Description	Associativity
() [] . -> ++ --	Parentheses (function call) (see Note 1) Brackets (array subscript) Member selection via object name Member selection via pointer Postfix increment/decrement (see Note 2)	left-to-right
++ -- + - ! ~ (type) * & sizeof	Prefix increment/decrement Unary plus/minus Logical negation/bitwise complement Cast (change <i>type</i>) Dereference Address Determine size in bytes	right-to-left
* / %	Multiplication/division/modulus	left-to-right
+ -	Addition/subtraction	left-to-right
<< >>	Bitwise shift left, Bitwise shift right	left-to-right
< <= > >=	Relational less than/less than or equal to Relational greater than/greater than or equal to	left-to-right
== !=	Relational is equal to/is not equal to	left-to-right
&	Bitwise AND	left-to-right
^	Bitwise exclusive OR	left-to-right
	Bitwise inclusive OR	left-to-right
&&	Logical AND	left-to-right
	Logical OR	left-to-right
? :	Ternary conditional	right-to-left
= += -= *= /= %= &= ^= = <<= >>=	Assignment Addition/subtraction assignment Multiplication/division assignment Modulus/bitwise AND assignment Bitwise exclusive/inclusive OR assignment Bitwise shift left/right assignment	right-to-left
,	Comma (separate expressions)	left-to-right
Note 1: Parentheses are also used to group sub-expressions to force a different precedence; such parenthetical expressions can be nested and are evaluated from inner to outer.		

Note 2:

Postfix increment/decrement have high precedence, but the actual increment or decrement of the operand is delayed (to be accomplished sometime before the statement completes execution). So in the statement `y = x * z++;` the current value of `z` is used to evaluate the expression (*i.e.*, `z++` evaluates to `z`) and `z` only incremented after all else is done. See [postinc.c](#) for another example.

<http://www.difranco.net/cop2220/op-prec.htm>