

LCD PIN	IC
C1~C7	C15~C9
C8~C14	C7~C1
S1~S80	S1~S80


DETAIL OF 'A' 3:1

NOTE:

1. FSTN, POSITIVE, TRANSPARENT
 2. 1/16 DUTY, 1/5BIAS, V_{OP}=5.0V, V_{DD}=3.5V
 3. V_{D1}12:100
 4. DP.TEMP₁-20°C-70°C
 5. ST.TEMP₁-30°C-80°C
 6. **LCD DRAWING NO.:JY06A84**
 7. DRIVER:ST7032-0T
 8. LED BACKLIGHT:WHITE, V_F=3.2±0.2V @ 80mA
- X=0.28-0.30,Y=0.29-0.31

9. ROHS

PIN	SYMBOL	DESCRIPTION
1	RN3SET	Reset input, only T_{active}
2	RS	Register select, H -instruction T_{active}
3	CSB	Chip select only T_{active}
4	S _Q	Serial clock input
5	SI	Serial data input
6	VSS	Ground (0V)
7	VDD	Power Supply(3.3V)
8	VOUT	connect a capacitor with VDD
9	CA1P	connect a 1.0uF capacitor
10	CA1N	between CA1P and CA1N

更改记录						设计	审核	工艺	标准化	批准	产品型号	JYC-1602396(R)-FSQL2-VD
更改标记	日期	更改内容	设计	审核	批准	签名	遼曼				文件编号	C1602396(R)-MX-VD
						日期	06.06.14				文件件号	4
											页数	1-1
											单位	mm
						未注公差 ±0.2				冀雅(廊坊)电子有限公司		