


PREDICTION OF PATHOGENIC SNV

Prof. Giorgio Valentini
6 CFU

Luca Cappelletti

Course Project
Year 2017/2018



IT Master Degree
Universiy of Milan
Italy
29 giugno 2018

Indice

I Dataset	4
1 Data points	5
1.1 Retrieving the dataset	5
1.2 Composition	5
1.2.1 Training dataset	5
1.2.2 Testing dataset	5
2 Metrics	6
2.1 How the graphs are realized	6
2.1.1 Metric sample distribution	6
2.1.2 Plot graphs	6
2.1.3 Normalized plot graphs	6
2.2 CpGobsExp	7
2.2.1 Metric sample distribution	7
2.2.2 Metric values	8
2.3 CpGperCpG	9
2.3.1 Metric sample distribution	9
2.3.2 Metric values	10
2.4 CpGperGC	11
2.4.1 Metric sample distribution	11
2.4.2 Metric values	12
2.5 DGVCount	13
2.5.1 Metric sample distribution	13
2.5.2 Metric values	14
2.6 DnaseClusteredHyp	15
2.6.1 Metric sample distribution	15
2.6.2 Metric values	16
2.7 DnaseClusteredScore	17
2.7.1 Metric sample distribution	17
2.7.2 Metric values	18
2.8 EncH3K27Ac	19
2.8.1 Metric sample distribution	19
2.8.2 Metric values	20
2.9 EncH3K4Me1	21
2.9.1 Metric sample distribution	21
2.9.2 Metric values	22
2.10 EncH3K4Me3	23
2.10.1 Metric sample distribution	23
2.10.2 Metric values	24
2.11 GCContent	25
2.11.1 Metric sample distribution	25
2.11.2 Metric values	26
2.12 GerpRS	27
2.12.1 Metric sample distribution	27
2.12.2 Metric values	28
2.13 GerpRSpv	29
2.13.1 Metric sample distribution	29

2.13.2 Metric values	30
2.14 ISCApath	31
2.14.1 Metric sample distribution	31
2.14.2 Metric values	32
2.15 commonVar	33
2.15.1 Metric sample distribution	33
2.15.2 Metric values	34
2.16 dbVARCount	35
2.16.1 Metric sample distribution	35
2.16.2 Metric values	36
2.17 fantom5Perm	37
2.17.1 Metric sample distribution	37
2.17.2 Metric values	38
2.18 fantom5Robust	39
2.18.1 Metric sample distribution	39
2.18.2 Metric values	40
2.19 fracRareCommon	41
2.19.1 Metric sample distribution	41
2.19.2 Metric values	42
2.20 mamPhastCons46way	43
2.20.1 Metric sample distribution	43
2.20.2 Metric values	44
2.21 mamPhyloP46way	45
2.21.1 Metric sample distribution	45
2.21.2 Metric values	46
2.22 numTFBSConserved	47
2.22.1 Metric sample distribution	47
2.22.2 Metric values	48
2.23 priPhastCons46way	49
2.23.1 Metric sample distribution	49
2.23.2 Metric values	50
2.24 priPhyloP46way	51
2.24.1 Metric sample distribution	51
2.24.2 Metric values	52
2.25 rareVar	53
2.25.1 Metric sample distribution	53
2.25.2 Metric values	54
2.26 verPhastCons46way	55
2.26.1 Metric sample distribution	55
2.26.2 Metric values	56
2.27 verPhyloP46way	57
2.27.1 Metric sample distribution	57
2.27.2 Metric values	58
3 Metric distribution summary	59
4 Data correlation	60
4.1 Scatter plot	60
4.2 Correlation coefficient matrix	61
4.2.1 CpGobsExp and CpGperCpG	62
4.2.2 CpGobsExp and CpGperGC	62
4.2.3 CpGperCpG and CpGperGC	63
4.2.4 dbVARCount and DGVCount	63
4.2.5 mamPhyloP46way and verPhyloP46way	64
4.2.6 DnaseClusteredHyp and DnaseClusteredScore	64
4.2.7 mamPhastCons46way and verPhastCons46way	65
4.3 Identified data correlations	65
4.4 Correlation table after removing highly correlated data	66
5 Dataset visualization	67
5.1 PCA	67
5.1.1 Training dataset visualization	67

5.1.2	Testing dataset visualization	67
5.1.3	Mixed dataset visualization	68
5.2	TSNE	69
5.2.1	Training dataset visualization	69
5.2.2	Testing dataset visualization	69
5.2.3	Mixed dataset visualization	69
6	Dataset issues	70
6.1	Possible dataset errors	70
6.2	Biased testing dataset	70
II	Network implementation	71
7	Model architecture	72
7.1	Activation function	72
7.2	Dense layers	72
7.3	Input	72
7.4	Hidden layer	72
7.5	Drop out	73
7.6	Output	73
7.7	Weight initialization	73
7.8	Batch Size	73
7.9	Loss function	73
7.10	Update policy	73
7.11	Mathematical representation	73
7.12	Network model representation	74
III	Results	75

Parte I

Dataset

Data points

First we begin looking at the dataset, the distributions of the given metrics and the statistical analysis of these data points.

1.1 Retrieving the dataset

The dataset can be downloaded from <https://homes.di.unimi.it/valentini/ProgettoBioinformatica1718/data/>.

1.2 Composition

1.2.1 Training dataset

In the training dataset there are 981388 data points, each one comprised of 26 metrics. The first 356 are pathogenic and all the others are negative.

1.2.2 Testing dataset

In the test dataset there are 19018 data points, still each one comprised of 26 metrics. The first 40 are pathogenic and the following are negative.

2

Metrics

2.1 How the graphs are realized

All the graphs are in triples: positives, negatives and mixed.

The normalization is done, as usual, in the following way:

$$m' = \frac{\text{metric} - \mathbb{E}(\text{metric values})}{\max\{\text{metric values}\} - \min\{\text{metric values}\}}$$

Figura 2.1: Input normalization

2.1.1 Metric sample distribution

Are realized by calculating the frequencies and estimating the density distributions parameters via MLE.

2.1.2 Plot graphs

Plot graphs are realized by sorting the values of the single metrics.

2.1.3 Normalized plot graphs

Are realized by sorting the values of the metric, with the domain and codomain normalized.

2.2 CpGobsExp

2.2.1 Metric sample distribution

The data points seem to follow a **Beta** distribution.

1) Plotting metric CpGobsExp




Figura 2.2: Sampling distribution of metric CpGobsExp

2.2.2 Metric values

1) Plotting metric CpGobsExp




Figura 2.3: Values of metric CpGobsExp

2.3 CpGperCpG

2.3.1 Metric sample distribution

The data points seem to follow a **Beta** distribution.

2) Plotting metric CpGperCpG




Figura 2.4: Sampling distribution of metric CpGperCpG

2.3.2 Metric values

2) Plotting metric CpGperCpG




Figura 2.5: Values of metric CpGperCpG

2.4 CpGperGC

2.4.1 Metric sample distribution

The data points seem to follow a **Gaussian** distribution.

3) Plotting metric CpGperGC




Figura 2.6: Sampling distribution of metric CpGperGC

2.4.2 Metric values

3) Plotting metric CpGperGC




Figura 2.7: Values of metric CpGperGC

2.5 DGVCount

2.5.1 Metric sample distribution

The data points seem to follow a **Gamma** distribution.

4) Plotting metric DGVCount




Figura 2.8: Sampling distribution of metric DGVCount

2.5.2 Metric values

4) Plotting metric DGVCount




Figura 2.9: Values of metric DGVCount

2.6 DnaseClusteredHyp

2.6.1 Metric sample distribution

The data points seem to follow a **Gamma** distribution.

5) Plotting metric DnaseClusteredHyp




Figura 2.10: Sampling distribution of metric DnaseClusteredHyp

2.6.2 Metric values

5) Plotting metric DnaseClusteredHyp




Figura 2.11: Values of metric DnaseClusteredHyp

2.7 DnaseClusteredScore

2.7.1 Metric sample distribution

The data points seem to follow **slightly** a **Beta** distribution.

6) Plotting metric DnaseClusteredScore




Figura 2.12: Sampling distribution of metric DnaseClusteredScore

2.7.2 Metric values




Figura 2.13: Values of metric DnaseClusteredScore

2.8 EncH3K27Ac

2.8.1 Metric sample distribution

The data points seem to follow a family of **Gamma** distributions (a speculation for this distribution could be the different groups from which the data are extracted), we will approximate them to one with a linear combination of the parameters.

7) Plotting metric EncH3K27Ac




Figura 2.14: Sampling distribution of metric EncH3K27Ac

2.8.2 Metric values

7) Plotting metric EncH3K27Ac




Figura 2.15: Values of metric EncH3K27Ac

2.9 EncH3K4Me1

2.9.1 Metric sample distribution

The data points seem to follow a family of **Gamma** distributions (a speculation for this distribution could be the different groups from which the data are extracted), we will approximate them to one with a linear combination of the parameters.

8) Plotting metric EncH3K4Me1




Figura 2.16: Sampling distribution of metric EncH3K4Me1

2.9.2 Metric values




Figura 2.17: Values of metric EncH3K4Me1

2.10 EncH3K4Me3

2.10.1 Metric sample distribution

The data points seem to follow a family of **Gamma** distributions (a speculation for this distribution could be the different groups from which the data are extracted), we will approximate them to one with a linear combination of the parameters.

9) Plotting metric EncH3K4Me3




Figura 2.18: Sampling distribution of metric EncH3K4Me3

2.10.2 Metric values

9) Plotting metric EncH3K4Me3




Figura 2.19: Values of metric EncH3K4Me3

2.11 GCContent

2.11.1 Metric sample distribution

The data points seem to be a combination of two **Gaussian** distributions.

10) Plotting metric GCContent




Figura 2.20: Sampling distribution of metric GCContent

2.11.2 Metric values




Figura 2.21: Values of metric GCContent

2.12 GerpRS

2.12.1 Metric sample distribution

The data points seem to follow a family of **Gamma** distributions (a speculation for this distribution could be the different groups from which the data are extracted), we will approximate them to one with a linear combination of the parameters.

11) Plotting metric GerpRS




Figura 2.22: Sampling distribution of metric GerpRS

2.12.2 Metric values

11) Plotting metric GerpRS




Figura 2.23: Values of metric GerpRS

2.13 GerpRSpv

2.13.1 Metric sample distribution

The data points seem to follow a family of **Gamma** distributions (a speculation for this distribution could be the different groups from which the data are extracted), we will approximate them to one with a linear combination of the parameters.

12) Plotting metric GerpRSpv




Figura 2.24: Sampling distribution of metric GerpRSpv

2.13.2 Metric values




Figura 2.25: Values of metric GerpRSpv

2.14 ISCApath

2.14.1 Metric sample distribution

The data points seem to follow a **Gamma** distribution.

13) Plotting metric ISCApath




Figura 2.26: Sampling distribution of metric ISCApath

2.14.2 Metric values

13) Plotting metric ISCApath




Figura 2.27: Values of metric ISCApath

2.15 commonVar

2.15.1 Metric sample distribution

The data points seem to follow an **Exponential Weibull** distribution.

14) Plotting metric commonVar




Figura 2.28: Sampling distribution of metric commonVar

2.15.2 Metric values

14) Plotting metric commonVar




Figura 2.29: Values of metric commonVar

2.16 dbVARCount

2.16.1 Metric sample distribution

The data points seem to follow a **Gamma** distribution.

15) Plotting metric dbVARCount




Figura 2.30: Sampling distribution of metric dbVARCount

2.16.2 Metric values

15) Plotting metric dbVARCount




Figura 2.31: Values of metric dbVARCount

2.17 fantom5Perm

2.17.1 Metric sample distribution

The data points seem to follow a **Gamma** distribution.

16) Plotting metric fantom5Perm




Figura 2.32: Sampling distribution of metric fantom5Perm

2.17.2 Metric values

16) Plotting metric fantom5Perm




Figura 2.33: Values of metric fantom5Perm

2.18 fantom5Robust

2.18.1 Metric sample distribution

The data points seem to follow a **Gamma** distribution.

17) Plotting metric fantom5Robust




Figura 2.34: Sampling distribution of metric fantom5Robust

2.18.2 Metric values

17) Plotting metric fantom5Robust




Figura 2.35: Values of metric fantom5Robust

2.19 fracRareCommon

2.19.1 Metric sample distribution

The data points seem to follow an **Beta** distribution.

18) Plotting metric fracRareCommon




Figura 2.36: Sampling distribution of metric fracRareCommon

2.19.2 Metric values

18) Plotting metric fracRareCommon




Figura 2.37: Values of metric fracRareCommon

2.20 mamPhastCons46way

2.20.1 Metric sample distribution

The data points seem to follow a **Gamma** distribution.

19) Plotting metric mamPhastCons46way




Figura 2.38: Sampling distribution of metric mamPhastCons46way

2.20.2 Metric values

19) Plotting metric mamPhastCons46way




Figura 2.39: Values of metric mamPhastCons46way

2.21 mamPhyloP46way

2.21.1 Metric sample distribution

The data points seem to follow a **Gaussian** distribution.

20) Plotting metric mamPhyloP46way




Figura 2.40: Sampling distribution of metric mamPhyloP46way

2.21.2 Metric values

20) Plotting metric mamPhyloP46way




Figura 2.41: Values of metric mamPhyloP46way

2.22 numTFBSConserved

2.22.1 Metric sample distribution

The data points seem to follow a **exponential** distribution.

21) Plotting metric numTFBSConserved




Figura 2.42: Sampling distribution of metric numTFBSConserved

2.22.2 Metric values

21) Plotting metric numTFBSConserved




Figura 2.43: Values of metric numTFBSConserved

2.23 priPhastCons46way

2.23.1 Metric sample distribution

The data points seem to follow a **Gamma** distribution.

22) Plotting metric priPhastCons46way




Figura 2.44: Sampling distribution of metric priPhastCons46way

2.23.2 Metric values

22) Plotting metric priPhastCons46way




Figura 2.45: Values of metric priPhastCons46way

2.24 priPhyloP46way

2.24.1 Metric sample distribution

The data points seem to follow an **Beta** distribution.

23) Plotting metric priPhyloP46way




Figura 2.46: Sampling distribution of metric priPhyloP46way

2.24.2 Metric values




Figura 2.47: Values of metric priPhyloP46way

2.25 rareVar

2.25.1 Metric sample distribution

The data points seem to follow an **Beta** distribution.

24) Plotting metric rareVar




Figura 2.48: Sampling distribution of metric rareVar

2.25.2 Metric values

24) Plotting metric rareVar




Figura 2.49: Values of metric rareVar

2.26 verPhastCons46way

2.26.1 Metric sample distribution

The data points seem to follow a **Gamma** distribution.

25) Plotting metric verPhastCons46way




Figura 2.50: Sampling distribution of metric verPhastCons46way

2.26.2 Metric values

25) Plotting metric verPhastCons46way




Figura 2.51: Values of metric verPhastCons46way

2.27 verPhyloP46way

2.27.1 Metric sample distribution

The data points seem to follow a **Gaussian** distribution.

26) Plotting metric verPhyloP46way




Figura 2.52: Sampling distribution of metric verPhyloP46way

2.27.2 Metric values

26) Plotting metric verPhyloP46way




Figura 2.53: Values of metric verPhyloP46way

3

Metric distribution summary

The metrics seem to follow these sample distributions:

Metric	Distribution
CpGobsExp	Beta
CpGperCpG	Beta
CpGperGC	Gaussian
DGVCount	Gamma
DnaseClusteredHyp	Gamma
EncH3K27Ac	Gamma
GCContent	Gaussian
EncH3K4Me3	Gamma
ISCApath	Gamma
DnaseClusteredScore	Beta
EncH3K4Me1	Gamma
GerpRS	Gamma
GerpRSpv	Gamma
commonVar	Exponential Weibull
dbVARCount	Gamma
fantom5Perm	Gamma
fantom5Robust	Gamma
mamPhastCons46way	Gamma
priPhastCons46way	Gamma
rareVar	Beta
verPhastCons46way	Gamma
numTFBSConserved	Exponential
fracRareCommon	Beta
priPhyloP46way	Beta
verPhyloP46way	Gaussian
mamPhyloP46way	Gaussian

Tabella 3.1: Metrics and their distribution

4

Data correlation

We now proceed to try and identify eventual data correlations.

4.1 Scatter plot

A scatter plot with higher resolution is available in the project repository.




Figura 4.1: Scatter plot

4.2 Correlation coefficient matrix

A correlation matrix with higher resolution is available in the project repository.




Figura 4.2: Correlation matrix

4.2.1 CpGobsExp and CpGperCpG

The two metric CpGobsExp and CpGperCpG have correlation index 0.9856203442596099.




Figura 4.3: CpGobsExp and CpGperCpG

These two metrics have an extremely high correlation, so one of the two will be removed from the dataset, arbitrarily **CpGobsExp**.

4.2.2 CpGobsExp and CpGperGC

The two metric CpGobsExp and CpGperGC have correlation index 0.9785748818167331.




Figura 4.4: CpGobsExp and CpGperGC

These two metrics have an extremely high correlation, so one of the two will be removed from the dataset, arbitrarily **CpGobsExp**.

4.2.3 CpGperCpG and CpGperGC

The two metric CpGperCpG and CpGperGC have correlation index 0.9897887253514923.




Figura 4.5: CpGperCpG and CpGperGC

These two metrics have an extremely high correlation, so one of the two will be removed from the dataset, arbitrarily **CpGperCpG**.

4.2.4 dbVARCount and DGVCount

The two metric dbVARCount and DGVCount have correlation index 1.0.




Figura 4.6: dbVARCount and DGVCount

These two metrics have an extremely high correlation, so one of the two will be removed from the dataset, arbitrarily **dbVARCount**.

4.2.5 mamPhyloP46way and verPhyloP46way

The two metric mamPhyloP46way and verPhyloP46way have correlation index 0.9902257463490804.




Figura 4.7: mamPhyloP46way and verPhyloP46way

These two metrics have an extremely high correlation, so one of the two will be removed from the dataset, arbitrarily **mamPhyloP46way**.

4.2.6 DnaseClusteredHyp and DnaseClusteredScore

The two metric DnaseClusteredHyp and DnaseClusteredScore have correlation index 0.7863337778663062.




Figura 4.8: DnaseClusteredHyp and DnaseClusteredScore

The correlation value is high, but not enough to motivate actions such as the removal from the dataset.

4.2.7 mamPhastCons46way and verPhastCons46way

The two metric mamPhastCons46way and verPhastCons46way have correlation index 0.8700263713585867.




Figura 4.9: mamPhastCons46way and verPhastCons46way

The correlation value is high, but not enough to motivate actions such as the removal from the dataset.

4.3 Identified data correlations

Data correlations exist between:

First metric	Second metric	Correlation coefficient
CpGobsExp	CpGperCpG	0.9856203442596099
CpGobsExp	CpGperGC	0.9785748818167331
CpGperCpG	CpGperGC	0.9897887253514923
dbVARCount	DGVCount	1.0
mamPhyloP46way	verPhyloP46way	0.9902257463490804
DnaseClusteredHyp	DnaseClusteredScore	0.7863337778663062
mamPhastCons46way	verPhastCons46way	0.8700263713585867

4.4 Correlation table after removing highly correlated data

After having removed from the dataset metrics **CpGobsExp**, **CpGperCpG**, **dbVARCount** and **mamPhyloP46way** looks like:




Figura 4.10: Correlation matrix

This correlation matrix with higher resolution is available in the project repository.

5

Dataset visualization

After having removed the correlated metrics we can proceed to use techniques of dimensionality reduction for visualization to see if the dataset is valid for a clustering or machine learning approach:

5.1 PCA

5.1.1 Training dataset visualization

The positive data are clustered inside the negative data: a simple clustering approach would, most probably, not be enough for separating the two classes, but easily separable for any multi-parameters ML approach like networks.

The points isolated on the right are most probably errors in the realization of the dataset.




Figura 5.1: Training dataset visualization

5.1.2 Testing dataset visualization

The testing dataset is probably malformed: all the positives point are visibly clustered. A simple clustering approach such as K-Means could probably separate most of them successfully.

An ML approach with a network will probably reach sooner an high accuracy on the testing dataset than on the training dataset for this reason, being able to classify most of the positive points immediately.




Figura 5.2: Testing dataset visualization

5.1.3 Mixed dataset visualization

The two datasets overlap correctly.




Figura 5.3: Mixed dataset visualization

5.2 TSNE

5.2.1 Training dataset visualization

Implementation exists but it is not runnable on the current machine in a decent time.

5.2.2 Testing dataset visualization

With TSNE visualization, after 1000 iterations, the training dataset's positive class appears on the border right of the cluster.




Figura 5.4: Testing dataset visualization

5.2.3 Mixed dataset visualization

Implementation exists but it is not runnable on the current machine in a decent time.

6

Dataset issues

6.1 Possible dataset errors

The PCA visualization shows points extremely out of the dataset cluster. It is possible that these points are errors.

6.2 Biased testing dataset

The testing dataset does not seem to reflect the training dataset distribution, but agglomerates the two classes in two separated clusters. It is therefore unhelpful when calculating the classification success in networks, as the training dataset result harder to classify than the testing one.

Parte II

Network implementation

7

Model architecture

Based on the informations extracted from the dataset structure, a small network should work best.

7.1 Activation function

We'll be using the **SeLU** activation function for most of the layers for its property of auto-normalization.

$$\text{SeLU}(x) = \lambda \begin{cases} x & x > 0 \\ \alpha e^x - \alpha & x \leq 0 \end{cases}$$

Figura 7.1: SeLU

7.2 Dense layers

Dense layers will be used through all the network:




Figura 7.2: Dense connected layer

7.3 Input

The input is a dense layer with 22 neurons, expecting as input the normalized metrics. As activation function **SeLU** will be used.

7.4 Hidden layer

A single hidden dense hidden layer with 22 neurons will be used, with **SeLU** as activation function.

7.5 Drop out

For the small dimension of the network, no drop out will probably be necessary.

7.6 Output

The output layer of the network is a dense layer with one neuron and a **sigmoid** as activation function. When **active** models the positive class, and when **inactive** models the negative class.

$$\sigma(x) = \text{sigmoid}(x) = \frac{e^x}{e^x + 1}$$

Figura 7.3: Sigmoid

7.7 Weight initialization

Since input values are not from any particular distribution or hold properties such as $\mathbb{E}(X) = 0$ (even though the normalized data have null mean) or $\text{Var}(X) = 1$ (in some metrics mean and variance are far from these values) they do not suggest to use any specific distribution.

The codomain values from the activation functions, being SeLU for most of the network, tend to hold the properties of $\mathbb{E}(X) = 0$ and $\text{Var}(X) = 1$ (<http://arxiv.org/abs/1706.02515>).

For these properties weight will be initialized by extracting them from a Gaussian with $\mathbb{E}(X) = 0$ and $\text{Var}(X) = 1$.

7.8 Batch Size

Since the positive class is extremely smaller of the negative class a large batch size will be necessary: 4096 data points per batch allow for a probability that at least one of the data points is positive in the training set of the ≈ 0.77 .

7.9 Loss function

Since the task assigned to the network is a binary classification the loss function will be the **cross entropy**.

7.10 Update policy

As update policy we are going to use a form of gradient **back propagation** with **Adam** optimizer.

7.11 Mathematical representation

Since the network is extremely simple a short mathematical representation is possible:

$$\text{prediction}(\underline{x}) = \sigma(\mathbf{W}_{\text{output}} \cdot \text{SeLU}(\mathbf{W}_{\text{hidden}} \cdot \text{SeLU}(\mathbf{W}_{\text{input}} \cdot \underline{x})))$$

Figura 7.4: Mathematical model

7.12 Network model representation

Graphical model of the network.




Figura 7.5: Model of the network

Parte III

Results