Sample Device Interface Standard

1 Scope

This document specifies the behaviour of the sample device. It contains no requirements.

3 Terms and definitions

No special terms are used in this document.

5 Requirements

The following clauses define the requirements for the sample device.

5.1

Response time

The device shall respond to any request within 500 ms. The device may log the request.

5.2

Malformed requests

If the request is malformed or the session has expired, the device shall not process the request and should return an error code.

5.3

Terminology note

The word "device" means the unit under test. Nothing here is required.

5.4

Request parameters

Name: nonce | Presence: mandatory | Type: text string of 16 to 64 characters

Name: locale | Presence: optional | Type: BCP 47 language tag

The reader shall reject a request whose nonce is missing.

5.5

Formal declarations

The structures of the interface are declared in four notations.

```
record = {
  label: tstr .size (1..32),
  ? count: uint,
  mode: "fast" / "slow",
}
```

```
token = prefix 1*8ALPHA [ suffix ]
prefix = "x" / "y"
suffix = "-a" / "-b"
```

```
{
  "type": "object",
  "required": ["key"],
  "properties": {
    "key": {"type": "string", "minLength": 4, "maxLength": 16},
    "flag": {"type": "string", "enum": ["on", "off"]}
  }
}
```

```
Entry ::= SEQUENCE {
  name UTF8String (SIZE(1..64)),
  state INTEGER { idle(0), busy(1) },
  note UTF8String OPTIONAL
}
```