Experimental and numerical assessment of loading rate effects on Mode I delamination in carbon fiber/epoxy composites

Luca Di Stasio[a,b], Janis Varna[b], Zoubir Ayadi[a]

[a]Université de Lorraine, EEIGM, IJL, 6 Rue Bastien Lepage, F-54010 Nancy, France
[b]Luleå University of Technology, University Campus, SE-97187 Luleå, Sweden
[c]IMDEA Materials Institute, Getafe, Madrid, Spain

Abstract

1. Introduction

2. Objectives

3. Materials

If all strain levels are applied to the same specimens: $8n$ specimens need to be tested, where n is the number of measurements for the same combination of parameters.

If each strain level is applied to one specimen: $40n$ specimens need to be tested, where n is the number of measurements for the same combination of parameters.

If each strain level is applied to one specimen only at high T: $28n$ specimens need to be tested, where n is the number of measurements for the same combination of parameters.

4. Methods

5. Expected outcomes

6. Audience

Students attending the Aerospace Materials course.

$v\ \left[\frac{mm}{min}\right]$	$\varepsilon\ [\%]$	$T\ [°]$		Estimated time (no counting) for $L=50\,[mm]$, $[min]$
		~ 20 (room)	120	
1	0.2	E_L, ρ_c, d	E_L, ρ_c, d	0.5
	0.4	E_L, ρ_c, d	E_L, ρ_c, d	0.6
	0.8	E_L, ρ_c, d	E_L, ρ_c, d	0.8
	1.0	E_L, ρ_c, d	E_L, ρ_c, d	0.9
	1.2	E_L, ρ_c, d	E_L, ρ_c, d	1
10	0.2	E_L, ρ_c, d	E_L, ρ_c, d	
	0.4	E_L, ρ_c, d	E_L, ρ_c, d	
	0.8	E_L, ρ_c, d	E_L, ρ_c, d	
	1.0	E_L, ρ_c, d	E_L, ρ_c, d	
	1.2	E_L, ρ_c, d	E_L, ρ_c, d	
50	0.2	E_L, ρ_c, d	E_L, ρ_c, d	
	0.4	E_L, ρ_c, d	E_L, ρ_c, d	
	0.8	E_L, ρ_c, d	E_L, ρ_c, d	
	1.0	E_L, ρ_c, d	E_L, ρ_c, d	
	1.2	E_L, ρ_c, d	E_L, ρ_c, d	
500	0.2	E_L, ρ_c, d	E_L, ρ_c, d	
	0.4	E_L, ρ_c, d	E_L, ρ_c, d	
	0.8	E_L, ρ_c, d	E_L, ρ_c, d	
	1.0	E_L, ρ_c, d	E_L, ρ_c, d	
	1.2	E_L, ρ_c, d	E_L, ρ_c, d	