a

1 What to check first b

Flags for unconverged IBSS or sensitivity fits, ELBO decreases, refinement that changed credible sets or has a competing solution, credible sets lost under sensitivity settings, flagged LD

2 Main results and resolution b

Credible sets with size, posterior mass, LD purity and effective number of variants; top candidates

3 Analysis status

Convergence assessment and IBSS stopping; refinement search with credible sets before and after; sensitivity fit status and credible-set recovery; LD compatibility

4 Figures c

Locus overview, convergence and refinement traces, signal resolution, sensitivity, LD diagnostics

5 Sensitivity and LD diagnostics

Cross-setting signal relations and the LD flag rule

6 Complete records and provenance

Checks run, full stopping and refinement records, all components, CS audit and between-CS LD

7 Machine-readable exports

JSON summaries, TSV tables, saved fits, PNG/SVG figures

b

What to check first

Note: Refinement found a better solution with different credible sets. Compare the before and after sets below.

Check: 2 credible set(s) from the baseline disappeared in at least one sensitivity setting. See which settings lost them in the recovery table.

What to check first · Candidates & resolution · Analysis status · Figures
Sensitivity & LD details · Complete records · Downloads

Main results and resolution

2 retained credible sets among 200 analyzed variants; 2 active components. A retained CS is a posterior candidate set, not a confirmed causal effect count.

Component ID (zero-based fit row)	Representative	CS size	Posterior mass	Minimum |r|	Effective number of variants
1	90	2	> 0.9999	0.9989	1.595
2	33	1	1	1	1

c

