Design Document

Michele Madaschi Lidia Moioli Luca Martinazzi

November 23, 2015

Contents

Introd	uction	2
1.1	Purpose	2
1.2	Scope	2
1.3	Definition, Acronymus, Abbreviation	2
1.4	Reference Documents	2
1.5	Document Structure	2
Archit	ectural Design	3
2.1	Overview	3
2.2	High level components and their interaction	3
2.3	Component view	3
	2.3.1 Client	3
	2.3.2 Server	4
2.4	Runtime view	5
2.5	Component interfaces	5
2.6	Selected architectural styles and patterns	5
2.7	Other design decisions	5
Algoria	thm Design	6
3.1	Outsourced algorithms	6
3.2	In-house developed algorithms	6
	3.2.1 Shared ride	6
User I	nterface Design	7
Requirements Traceability		8
References		9

Introduction

1.1 Purpose

In this document we aim to provide a description for the architecture and design of MyTaxiService. This document is targeted towards the future developers of the system.

1.2 Scope

The application will be developed using a client-server paradigm. The server-side application must recognize an user (either an unregistered guest, a passenger or a taxi driver), and accordingly signal the client the available actions. The server-side application must manage the city-wide taxi deployment, by the means explained in the RASD document¹. The client-side application must show a UI The application must implement a report system, in order to incentive the good behavior of the users involved

- 1.3 Definition, Acronymus, Abbreviation
- 1.4 Reference Documents
- 1.5 Document Structure

¹see reference documents

Architectural Design

2.1 Overview

The distributed application is composed by a server side, and a client one. The client side interacts with users (or guests), showing the correct activity, and send requests to the server side, when needed. The client side must be able to interact with the GPS, The server side manages requests coming from the client side, and notifies the users (or the guests) involved in the requests. The server side must also interact with a map system, in order to retrieve information about the route and the length of the ride.

2.2 High level components and their interaction

The client side is composed by a set of activities composed by one or more actions and displayed through the user interface. The client side has also an interface which manages the interaction with the server. The server side has a controller for each connected client, that manages the requests coming from the users (or guests), taking data from the ride manager. It also sends messages to the clients in order to resolve the requests. The controller interacts with the clients through a network interface.

2.3 Component view

2.3.1 Client

Activity: an activity is a set of messages and actions, that the application must display to the users. No more than one activity can be displayed at the same time; The default activity is the "guest home" activity. Each time the user taps a button, the application must execute the related action, and select the next activity.

Action: an action is something that a user can do, in order to interact with the application. If an action need some data, the userinterface must display a field, for each input needed, that allows the human to provide the necessary incormations. Some actions can also select the next

activity that must be shown, or/and send informations to the server, in order to complete their job.

Userinterface: is the component that directly interact with the human. It contains the activity that must be displayed, and read the components of the activity, in order to display them. It also launch the actions selected by the human.

Clientnetworkinterface: is the component that allow the others to exchange messages with the server side.

2.3.2 Server

Controller: we have one controller for each client connected; initially it will be a guest controller, which allows login/register. After a successful login, the guest controller will create a taxi driver/passenger controller, and substitutes himself with the new controller. The controller must manage requests coming from the client, taking informations from the ridesmanager, and eventually adding new objects to it. In order to sends and receives message from the client, the controller communicates with a Servernetworkinterface. The controller also contains a User object, that allows him to retrieves information about the specific logged user.

Ridesmanager: it is a singleton, that contains informations about the queues, the active rides. This corresponds to the model in the MVC pattern and it is shared by all the controllers.

User: is the component that contains every possible information about a logged user, taken from the database. User is a part of the controller (obviously only in case of passenger/taxi driver controller). User is split in taxi driver and passenger, cause there are some differences between the two kind of user. Also user is a part of the model, but it is not shared.

Servernetworkinterface: is the component that allows the interaction with the client side. It converts messages coming from the other server component, in messages readable from the Clientnetwrokinterface, and vice versa.

- 2.4 Runtime view
- 2.5 Component interfaces
- 2.6 Selected architectural styles and patterns
- 2.7 Other design decisions

Algorithm Design

- 3.1 Outsourced algorithms
- 3.2 In-house developed algorithms

3.2.1 Shared ride

```
Passenger gathering and assignment

function Shared Request (passenger)

shared \leftarrow findSharedRidesAvailable(fromZone, toZone)

if exists shared then

shared.addReservation()

else

taxi \leftarrow getAvailableTaxi(fromzone)

if exists taxi then

create new shared ride

else

error message

end if

end function
```

User Interface Design

Requirements Traceability

References