Survival Video Game with API Integration

API Documentation

API Docs Generator

Copyright © 2026

Table of contents

1. Welcome to the Player and Run Tracker API 4
   1.1 Overview 4
2. Player and Run Tracker API v1.0.0 5
3. Authentication 5
4. Default 5
   4.1 Check Name 5
   4.2 Generate Name 6
   4.3 Start Run 6
   4.4 Get Players 7
   4.5 Create Player 8
   4.6 Read Player 9
   4.7 Delete Player 10
   4.8 Get Runs 11
   4.9 Get Run 14
   4.10 Update Run 15
   4.11 Delete Run 16
   4.12 Create Run Event 17
   4.13 Get Run Events 17
   4.14 Get Leaderboard 19
   4.15 Get Players Summary 20
   4.16 View Player Stats 21
   4.17 Get Player Runs 22
   4.18 Admin Login 25
   4.19 Admin Update Player Name 26
   4.20 Admin Delete Player 27
   4.21 Admin Delete Run 28
   4.22 Update Run From Game 28
   4.23 Test Endpoint One 30
   4.24 Test Endpoint Two 30
   4.25 Test Endpoint Three 31
5. Schemas 31
   5.1 GenerateNameResponse 31
   5.2 HTTPValidationError 32
   5.3 NameCheckRequest 32
   5.4 NameCheckResponse 32

Copyright © 2026

5.5 Player 33
5.6 PlayerCreate 33
5.7 PlayerCreateResponse 33
5.8 PlayerNameUpdate 34
5.9 PlayerStats 34
5.10 PlayerSummary 35
5.11 Run 35
5.12 RunEvent 37
5.13 RunEventCreate 38
5.14 RunLeaderboard 38
5.15 RunStart 38
5.16 RunStartResponse 39
5.17 RunStatus 39
5.18 RunUpdate 40
5.19 ValidationError 43

Copyright © 2026

1. Welcome to the Player and Run Tracker API

This documentation provides a complete reference for the API, including all available endpoints, request parameters, and response schemas.

1.1 Overview

The API is built with FastAPI and provides endpoints for:

- Player management (creation, authentication, stats)
- Game run tracking (start, update, end)
- Analytics (leaderboards, player summaries)
- Admin operations

Navigate to the **API Reference** section to see the detailed endpoint documentation.

Copyright © 2026

2. Player and Run Tracker API v1.0.0

Scroll down for code samples, example requests and responses. Select a language for code samples from the tabs above or the mobile navigation menu.

An API for tracking player data and game runs.

3. Authentication

- HTTP Authentication, scheme: basic

4. Default

4.1 Check Name

Code samples

```
# You can also use wget
curl -X POST /players/check-name \
  -H 'Content-Type: application/json' \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json'
}

r = requests.post('/players/check-name', headers = headers)

print(r.json())
```

`POST /players/check-name`

Checks if a player name is already taken. This is useful for real-time validation in the user interface.

Body parameter

```
{
  "player_name": "string"
}
```

4.1.1 Parameters

Name	In	Type	Required	Description
body	body	NameCheckRequest	true	none

Example responses

200 Response

```
{
  "exists": true,
  "message": "string"
}
```


Copyright © 2026

4.1.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	NameCheckResponse
422	Unprocessable Entity	Validation Error	HTTPValidationError

This operation does not require authentication

4.2 Generate Name

Code samples

```
# You can also use wget
curl -X GET /players/generate-name \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.get('/players/generate-name', headers = headers)

print(r.json())
```

`GET /players/generate-name`

Generates a unique, random player name that is not already in use.

Example responses

200 Response

```
{
  "player_name": "string"
}
```

4.2.1 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	GenerateNameResponse

This operation does not require authentication

4.3 Start Run

Code samples

```
# You can also use wget
curl -X POST /runs/start \
  -H 'Content-Type: application/json' \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json'
}

r = requests.post('/runs/start', headers = headers)
```


Copyright © 2026

```
print(r.json())
```

`POST /runs/start`

Starts a new game run. This endpoint handles both new and existing players. If `create_new_player` is true, a new player is created. Otherwise, the existing player is authenticated.

Body parameter

```
{
  "player_name": "string",
  "password": "string",
  "map_id": "string",
  "create_new_player": false
}
```

4.3.1 Parameters

Name	In	Type	Required	Description
body	body	RunStart	true	none

Example responses

200 Response

```
{
  "player_id": 0,
  "run_id": 0
}
```

4.3.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	RunStartResponse
422	Unprocessable Entity	Validation Error	HTTPValidationError

This operation does not require authentication

4.4 Get Players

Code samples

```
# You can also use wget
curl -X GET /players \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.get('/players', headers = headers)

print(r.json())
```

`GET /players`

Retrieves a list of all players with pagination.

Copyright © 2026

4.4.1 Parameters

Name	In	Type	Required	Description
skip	query	integer	false	none
limit	query	integer	false	none

Example responses

200 Response

```
[
  {
    "name": "string",
    "id": 0,
    "created_at": "2019-08-24T14:15:22Z"
  }
]
```

4.4.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Inline
422	Unprocessable Entity	Validation Error	HTTPValidationError

4.4.3 Response Schema

Status Code **200**

Response Get Players Players Get

Name	Type	Required	Restrictions	Description
Response Get Players Players Get	[Player]	false	none	[Schema for representing a player, including their ID and creation date.]
» Player	Player	false	none	Schema for representing a player, including their ID and creation date.
»» name	string	true	none	none
»» id	integer	true	none	none
»» created_at	string(date-time)	true	none	none

This operation does not require authentication

4.5 Create Player

Code samples

```
# You can also use wget
curl -X POST /players \
  -H 'Content-Type: application/json' \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json'
}
```


Copyright © 2026

```
r = requests.post('/players', headers = headers)

print(r.json())
```

`POST /players`

Creates a new player with a randomly generated password. Returns the new player's details, including the password.

Body parameter

```
{
  "name": "string"
}
```

4.5.1 Parameters

Name	In	Type	Required	Description
body	body	PlayerCreate	true	none

Example responses

201 Response

```
{
  "name": "string",
  "id": 0,
  "created_at": "2019-08-24T14:15:22Z",
  "password": "string"
}
```

4.5.2 Responses

Status	Meaning	Description	Schema
201	Created	Successful Response	PlayerCreateResponse
422	Unprocessable Entity	Validation Error	HTTPValidationError

This operation does not require authentication

4.6 Read Player

Code samples

```
# You can also use wget
curl -X GET /players/{player_id} \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.get('/players/{player_id}', headers = headers)

print(r.json())
```

`GET /players/{player_id}`

Retrieves a single player by their ID.

Copyright © 2026

4.6.1 Parameters

Name	In	Type	Required	Description
player_id	path	integer	true	none

Example responses

200 Response

```
{
  "name": "string",
  "id": 0,
  "created_at": "2019-08-24T14:15:22Z"
}
```

4.6.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Player
422	Unprocessable Entity	Validation Error	HTTPValidationError

This operation does not require authentication

4.7 Delete Player

Code samples

```
# You can also use wget
curl -X DELETE /players/{player_id} \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.delete('/players/{player_id}', headers = headers)

print(r.json())
```

`DELETE /players/{player_id}`

Deletes a player and all of their associated data.

4.7.1 Parameters

Name	In	Type	Required	Description
player_id	path	integer	true	none

Example responses

422 Response

```
{
  "detail": [
    {
      "loc": [
        "string"
      ],
      "msg": "string",
      "type": "string"
```


Copyright © 2026

```
    }
  ]
}
```

4.7.2 Responses

Status	Meaning	Description	Schema
204	No Content	Successful Response	None
422	Unprocessable Entity	Validation Error	HTTPValidationError

This operation does not require authentication

4.8 Get Runs

Code samples

```
# You can also use wget
curl -X GET /runs \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.get('/runs', headers = headers)

print(r.json())
```

`GET /runs`

Retrieves a list of all runs with pagination.

4.8.1 Parameters

Name	In	Type	Required	Description
skip	query	integer	false	none
limit	query	integer	false	none

Example responses

200 Response

```
[
  {
    "player_id": 0,
    "map_id": "string",
    "id": 0,
    "player": {
      "name": "string",
      "id": 0,
      "created_at": "2019-08-24T14:15:22Z"
    },
    "started_at": "2019-08-24T14:15:22Z",
    "status": "in_progress",
    "duration_seconds": 0,
    "level": 0,
    "xp": 0,
    "kills_total": 0,
    "upgrades": {
      "property1": 0,
      "property2": 0
    },
    "ended_at": "2019-08-24T14:15:22Z",
    "cause_of_death": "string"
```


Copyright © 2026

```
  }
]
```

4.8.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Inline
422	Unprocessable Entity	Validation Error	HTTPValidationError

4.8.3 Response Schema

Status Code **200**

Response Get Runs Runs Get

Name	Type	Required	Restrictions	Description
Response Get Runs Runs Get	[Run]	false	none	[Schema for representing a run, including all its details.]
» Run	Run	false	none	Schema for representing a run, including all its details.
»» player_id	integer	true	none	none
»» map_id	string	true	none	none
»» id	integer	true	none	none
»» player	Player	true	none	Schema for representing a player, including their ID and creation date.
»»» name	string	true	none	none
»»» id	integer	true	none	none
»»» created_at	string(date-time)	true	none	none
»» started_at	string(date-time)	true	none	none
»» status	RunStatus	true	none	An enumeration for the possible statuses of a run.
»» duration_seconds	integer	true	none	none
»» level	integer	true	none	none
»» xp	integer	true	none	none
»» kills_total	integer	true	none	none
»» upgrades	any	false	none	none

anyOf

Name	Type	Required	Restrictions	Description
»»» *anonymous*	object	false	none	none
»»»» **additionalProperties**	integer	false	none	none

Copyright © 2026

or

Name	Type	Required	Restrictions	Description
»»» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
»» ended_at	any	true	none	none

anyOf

Name	Type	Required	Restrictions	Description
»»» *anonymous*	string(date-time)	false	none	none

or

Name	Type	Required	Restrictions	Description
»»» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
»» cause_of_death	any	true	none	none

anyOf

Name	Type	Required	Restrictions	Description
»»» *anonymous*	string	false	none	none

or

Name	Type	Required	Restrictions	Description
»»» *anonymous*	null	false	none	none

Enumerated Values

Property	Value
status	in_progress
status	died
status	completed

This operation does not require authentication

Copyright © 2026

4.9 Get Run

Code samples

```
# You can also use wget
curl -X GET /runs/{run_id} \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.get('/runs/{run_id}', headers = headers)

print(r.json())
```

`GET /runs/{run_id}`

Retrieves a single run by its ID.

4.9.1 Parameters

Name	In	Type	Required	Description
run_id	path	integer	true	none

Example responses

200 Response

```
{
  "player_id": 0,
  "map_id": "string",
  "id": 0,
  "player": {
    "name": "string",
    "id": 0,
    "created_at": "2019-08-24T14:15:22Z"
  },
  "started_at": "2019-08-24T14:15:22Z",
  "status": "in_progress",
  "duration_seconds": 0,
  "level": 0,
  "xp": 0,
  "kills_total": 0,
  "upgrades": {
    "property1": 0,
    "property2": 0
  },
  "ended_at": "2019-08-24T14:15:22Z",
  "cause_of_death": "string"
}
```

4.9.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Run
422	Unprocessable Entity	Validation Error	HTTPValidationError

This operation does not require authentication

Copyright © 2026

4.10 Update Run

Code samples

```
# You can also use wget
curl -X PATCH /runs/{run_id} \
  -H 'Content-Type: application/json' \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json'
}

r = requests.patch('/runs/{run_id}', headers = headers)

print(r.json())
```

`PATCH /runs/{run_id}`

Updates the details of a specific run, such as duration, kills, and status. This is the primary endpoint for updating a run's progress.

Body parameter

```
{
  "duration_seconds": 0,
  "kills_total": 0,
  "level": 0,
  "xp": 0,
  "upgrades": {
    "property1": 0,
    "property2": 0
  },
  "status": "in_progress",
  "ended_at": "2019-08-24T14:15:22Z",
  "cause_of_death": "string"
}
```

4.10.1 Parameters

Name	In	Type	Required	Description
run_id	path	integer	true	none
body	body	RunUpdate	true	none

Example responses

200 Response

```
{
  "player_id": 0,
  "map_id": "string",
  "id": 0,
  "player": {
    "name": "string",
    "id": 0,
    "created_at": "2019-08-24T14:15:22Z"
  },
  "started_at": "2019-08-24T14:15:22Z",
  "status": "in_progress",
  "duration_seconds": 0,
  "level": 0,
  "xp": 0,
  "kills_total": 0,
  "upgrades": {
    "property1": 0,
    "property2": 0
  },
  "ended_at": "2019-08-24T14:15:22Z",
  "cause_of_death": "string"
}
```


Copyright © 2026

4.10.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Run
422	Unprocessable Entity	Validation Error	HTTPValidationError

This operation does not require authentication

4.11 Delete Run

Code samples

```
# You can also use wget
curl -X DELETE /runs/{run_id} \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.delete('/runs/{run_id}', headers = headers)

print(r.json())
```

`DELETE /runs/{run_id}`

Deletes a single run and its associated events.

4.11.1 Parameters

Name	In	Type	Required	Description
run_id	path	integer	true	none

Example responses

200 Response

```
null
```

4.11.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Inline
422	Unprocessable Entity	Validation Error	HTTPValidationError

4.11.3 Response Schema

This operation does not require authentication

Copyright © 2026

4.12 Create Run Event

Code samples

```
# You can also use wget
curl -X POST /runs/{run_id}/events \
  -H 'Content-Type: application/json' \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json'
}

r = requests.post('/runs/{run_id}/events', headers = headers)

print(r.json())
```

`POST /runs/{run_id}/events`

Creates a new event associated with a specific run.

Body parameter

```
{
  "event_type": "string",
  "value": "string"
}
```

4.12.1 Parameters

Name	In	Type	Required	Description
run_id	path	integer	true	none
body	body	RunEventCreate	true	none

Example responses

200 Response

```
{
  "event_type": "string",
  "value": "string",
  "id": 0,
  "run_id": 0,
  "timestamp": "2019-08-24T14:15:22Z"
}
```

4.12.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	RunEvent
422	Unprocessable Entity	Validation Error	HTTPValidationError

This operation does not require authentication

4.13 Get Run Events

Code samples

```
# You can also use wget
curl -X GET /runs/{run_id}/events \
```


Copyright © 2026

```
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.get('/runs/{run_id}/events', headers = headers)

print(r.json())
```

`GET /runs/{run_id}/events`

Retrieves all events for a specific run.

4.13.1 Parameters

Name	In	Type	Required	Description
run_id	path	integer	true	none

Example responses

200 Response

```
[
  {
    "event_type": "string",
    "value": "string",
    "id": 0,
    "run_id": 0,
    "timestamp": "2019-08-24T14:15:22Z"
  }
]
```

4.13.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Inline
422	Unprocessable Entity	Validation Error	HTTPValidationError

4.13.3 Response Schema

Status Code **200**

Response Get Run Events Runs Run Id Events Get

Name	Type	Required	Restrictions	Description
Response Get Run Events Runs Run Id Events Get	[RunEvent]	false	none	[Schema for representing a run event, including its ID and timestamp.]
» RunEvent	RunEvent	false	none	Schema for representing a run event, including its ID and timestamp.
»» event_type	string	true	none	none
»» value	any	false	none	none

Copyright © 2026

anyOf

Name	Type	Required	Restrictions	Description
»»» *anonymous*	string	false	none	none

or

Name	Type	Required	Restrictions	Description
»»» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
»» id	integer	true	none	none
»» run_id	integer	true	none	none
»» timestamp	string(date-time)	true	none	none

This operation does not require authentication

4.14 Get Leaderboard

Code samples

```
# You can also use wget
curl -X GET /analytics/leaderboard \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.get('/analytics/leaderboard', headers = headers)

print(r.json())
```

`GET /analytics/leaderboard`

Retrieves the top 10 runs for the leaderboard, sorted by duration.

Example responses

200 Response

```
[
  {
    "player_id": 0,
    "run_id": 0,
    "player_name": "string",
    "duration_seconds": 0,
    "total_kills": 0
  }
]
```

4.14.1 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Inline

Copyright © 2026

4.14.2 Response Schema

Status Code **200**

Response Get Leaderboard Analytics Leaderboard Get

Name	Type	Required	Restrictions	Description
Response Get Leaderboard Analytics Leaderboard Get	[RunLeaderboard]	false	none	[Schema for a single entry in the leaderboard.]
» RunLeaderboard	RunLeaderboard	false	none	Schema for a single entry in the leaderboard.
»» player_id	integer	true	none	none
»» run_id	integer	true	none	none
»» player_name	string	true	none	none
»» duration_seconds	integer	true	none	none
»» total_kills	integer	true	none	none

This operation does not require authentication

4.15 Get Players Summary

Code samples

```
# You can also use wget
curl -X GET /analytics/players-summary \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.get('/analytics/players-summary', headers = headers)

print(r.json())
```

`GET /analytics/players-summary`

Provides a summary of all players, including their total number of runs and best run time. Can be filtered by a search term.

4.15.1 Parameters

Name	In	Type	Required	Description
search	query	any	false	none

Example responses

200 Response

```
[
  {
    "name": "string",
    "id": 0,
    "created_at": "2019-08-24T14:15:22Z",
    "total_runs": 0,
    "best_run_time": 0
  }
]
```


Copyright © 2026

4.15.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Inline
422	Unprocessable Entity	Validation Error	HTTPValidationError

4.15.3 Response Schema

Status Code **200**

Response Get Players Summary Analytics Players Summary Get

Name	Type	Required	Restrictions	Description
Response Get Players Summary Analytics Players Summary Get	[PlayerSummary]	false	none	[Schema for a player summary, which includes their total number of runs and their best run time.]
» PlayerSummary	PlayerSummary	false	none	Schema for a player summary, which includes their total number of runs and their best run time.
»» name	string	true	none	none
»» id	integer	true	none	none
»» created_at	string(date-time)	true	none	none
»» total_runs	integer	true	none	none
»» best_run_time	any	false	none	none

anyOf

Name	Type	Required	Restrictions	Description
»»» *anonymous*	integer	false	none	none

or

Name	Type	Required	Restrictions	Description
»»» *anonymous*	null	false	none	none

This operation does not require authentication

4.16 View Player Stats

Code samples

```
# You can also use wget
curl -X GET /analytics/view_player_stats/{player_id} \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}
```


Copyright © 2026

```
r = requests.get('/analytics/view_player_stats/{player_id}', headers = headers)

print(r.json())
```

`GET /analytics/view_player_stats/{player_id}`

Retrieves detailed statistics for a single player, such as total runs, average survival time, and total kills.

4.16.1 Parameters

Name	In	Type	Required	Description
player_id	path	integer	true	none

Example responses

200 Response

```
{
  "player_name": "string",
  "number_of_runs": 0,
  "total_time_played": 0,
  "average_time_survived": 0,
  "longest_run": 0,
  "favourite_upgrade": "string",
  "total_monsters_slain": 0
}
```

4.16.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	PlayerStats
422	Unprocessable Entity	Validation Error	HTTPValidationError

This operation does not require authentication

4.17 Get Player Runs

Code samples

```
# You can also use wget
curl -X GET /players/{player_id}/runs \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.get('/players/{player_id}/runs', headers = headers)

print(r.json())
```

`GET /players/{player_id}/runs`

Retrieves all runs for a specific player.

Copyright © 2026

4.17.1 Parameters

Name	In	Type	Required	Description
player_id	path	integer	true	none

Example responses

200 Response


```
[
  {
    "player_id": 0,
    "map_id": "string",
    "id": 0,
    "player": {
      "name": "string",
      "id": 0,
      "created_at": "2019-08-24T14:15:22Z"
    },
    "started_at": "2019-08-24T14:15:22Z",
    "status": "in_progress",
    "duration_seconds": 0,
    "level": 0,
    "xp": 0,
    "kills_total": 0,
    "upgrades": {
      "property1": 0,
      "property2": 0
    },
    "ended_at": "2019-08-24T14:15:22Z",
    "cause_of_death": "string"
  }
]
```


4.17.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Inline
422	Unprocessable Entity	Validation Error	HTTPValidationError

4.17.3 Response Schema

Status Code **200**

Copyright © 2026

Response Get Player Runs Players Player Id Runs Get

Name	Type	Required	Restrictions	Description
Response Get Player Runs Players Player Id Runs Get	[Run]	false	none	[Schema for representing a run, including all its details.]
» Run	Run	false	none	Schema for representing a run, including all its details.
»» player_id	integer	true	none	none
»» map_id	string	true	none	none
»» id	integer	true	none	none
»» player	Player	true	none	Schema for representing a player, including their ID and creation date.
»»» name	string	true	none	none
»»» id	integer	true	none	none
»»» created_at	string(date-time)	true	none	none
»» started_at	string(date-time)	true	none	none
»» status	RunStatus	true	none	An enumeration for the possible statuses of a run.
»» duration_seconds	integer	true	none	none
»» level	integer	true	none	none
»» xp	integer	true	none	none
»» kills_total	integer	true	none	none
»» upgrades	any	false	none	none

anyOf

Name	Type	Required	Restrictions	Description
»»» *anonymous*	object	false	none	none
»»»» **additionalProperties**	integer	false	none	none

or

Name	Type	Required	Restrictions	Description
»»» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
»» ended_at	any	true	none	none

Copyright © 2026

anyOf

Name	Type	Required	Restrictions	Description
»»» *anonymous*	string(date-time)	false	none	none

or

Name	Type	Required	Restrictions	Description
»»» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
»» cause_of_death	any	true	none	none

anyOf

Name	Type	Required	Restrictions	Description
»»» *anonymous*	string	false	none	none

or

Name	Type	Required	Restrictions	Description
»»» *anonymous*	null	false	none	none

Enumerated Values

Property	Value
status	in_progress
status	died
status	completed

This operation does not require authentication

4.18 Admin Login

Code samples

```
# You can also use wget
curl -X GET /admin/login \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.get('/admin/login', headers = headers)

print(r.json())
```

`GET /admin/login`

Copyright © 2026

Verifies admin credentials. This endpoint is protected and requires Basic Authentication.

Example responses

200 Response

```
null
```

4.18.1 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Inline

4.18.2 Response Schema

To perform this operation, you must be authenticated by means of one of the following methods: HTTPBasic

4.19 Admin Update Player Name

Code samples

```
# You can also use wget
curl -X PATCH /admin/players/{player_id} \
  -H 'Content-Type: application/json' \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json'
}

r = requests.patch('/admin/players/{player_id}', headers = headers)

print(r.json())
```

`PATCH /admin/players/{player_id}`

Admin-only endpoint to update a player's name.

Body parameter

```
{
  "name": "string"
}
```

4.19.1 Parameters

Name	In	Type	Required	Description
player_id	path	integer	true	none
body	body	PlayerNameUpdate	true	none

Example responses

200 Response

```
{
  "name": "string",
  "id": 0,
  "created_at": "2019-08-24T14:15:22Z"
}
```


Copyright © 2026

4.19.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Player
422	Unprocessable Entity	Validation Error	HTTPValidationError

To perform this operation, you must be authenticated by means of one of the following methods: HTTPBasic

4.20 Admin Delete Player

Code samples

```
# You can also use wget
curl -X DELETE /admin/players/{player_id} \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.delete('/admin/players/{player_id}', headers = headers)

print(r.json())
```

`DELETE /admin/players/{player_id}`

Admin-only endpoint to delete a player and all their associated runs.

4.20.1 Parameters

Name	In	Type	Required	Description
player_id	path	integer	true	none

Example responses

422 Response

```
{
  "detail": [
    {
      "loc": [
        "string"
      ],
      "msg": "string",
      "type": "string"
    }
  ]
}
```

4.20.2 Responses

Status	Meaning	Description	Schema
204	No Content	Successful Response	None
422	Unprocessable Entity	Validation Error	HTTPValidationError

To perform this operation, you must be authenticated by means of one of the following methods: HTTPBasic

Copyright © 2026

4.21 Admin Delete Run

Code samples

```
# You can also use wget
curl -X DELETE /admin/runs/{run_id} \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.delete('/admin/runs/{run_id}', headers = headers)

print(r.json())
```

`DELETE /admin/runs/{run_id}`

Admin-only endpoint to delete a specific run.

4.21.1 Parameters

Name	In	Type	Required	Description
run_id	path	integer	true	none

Example responses

422 Response

```
{
  "detail": [
    {
      "loc": [
        "string"
      ],
      "msg": "string",
      "type": "string"
    }
  ]
}
```

4.21.2 Responses

Status	Meaning	Description	Schema
204	No Content	Successful Response	None
422	Unprocessable Entity	Validation Error	HTTPValidationError

To perform this operation, you must be authenticated by means of one of the following methods: HTTPBasic

4.22 Update Run From Game

Code samples

```
# You can also use wget
curl -X PATCH /runs/{run_id}/update \
  -H 'Content-Type: application/json' \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json'
```


Copyright © 2026

```
}

r = requests.patch('/runs/{run_id}/update', headers = headers)

print(r.json())
```

`PATCH /runs/{run_id}/update`

Body parameter

```
{
  "duration_seconds": 0,
  "kills_total": 0,
  "level": 0,
  "xp": 0,
  "upgrades": {
    "property1": 0,
    "property2": 0
  },
  "status": "in_progress",
  "ended_at": "2019-08-24T14:15:22Z",
  "cause_of_death": "string"
}
```

4.22.1 Parameters

Name	In	Type	Required	Description
run_id	path	integer	true	none
body	body	RunUpdate	true	none

Example responses

200 Response

```
{
  "player_id": 0,
  "map_id": "string",
  "id": 0,
  "player": {
    "name": "string",
    "id": 0,
    "created_at": "2019-08-24T14:15:22Z"
  },
  "started_at": "2019-08-24T14:15:22Z",
  "status": "in_progress",
  "duration_seconds": 0,
  "level": 0,
  "xp": 0,
  "kills_total": 0,
  "upgrades": {
    "property1": 0,
    "property2": 0
  },
  "ended_at": "2019-08-24T14:15:22Z",
  "cause_of_death": "string"
}
```

4.22.2 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Run
422	Unprocessable Entity	Validation Error	HTTPValidationError

This operation does not require authentication

Copyright © 2026

4.23 Test Endpoint One

Code samples

```
# You can also use wget
curl -X GET /test1 \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.get('/test1', headers = headers)

print(r.json())
```

`GET /test1`

Example responses

200 Response

```
null
```

4.23.1 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Inline

4.23.2 Response Schema

This operation does not require authentication

4.24 Test Endpoint Two

Code samples

```
# You can also use wget
curl -X GET /test2 \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.get('/test2', headers = headers)

print(r.json())
```

`GET /test2`

Example responses

200 Response

```
null
```


Copyright © 2026

4.24.1 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Inline

4.24.2 Response Schema

This operation does not require authentication

4.25 Test Endpoint Three

Code samples

```
# You can also use wget
curl -X GET /test3 \
  -H 'Accept: application/json'
```

```
import requests
headers = {
  'Accept': 'application/json'
}

r = requests.get('/test3', headers = headers)

print(r.json())
```

`GET /test3`

Example responses

200 Response

```
null
```

4.25.1 Responses

Status	Meaning	Description	Schema
200	OK	Successful Response	Inline

4.25.2 Response Schema

This operation does not require authentication

5. Schemas

5.1 GenerateNameResponse

```
{
  "player_name": "string"
}
```

GenerateNameResponse

Copyright © 2026

5.1.1 Properties

Name	Type	Required	Restrictions	Description
player_name	string	true	none	none

5.2 HTTPValidationError

```
{
  "detail": [
    {
      "loc": [
        "string"
      ],
      "msg": "string",
      "type": "string"
    }
  ]
}
```

HTTPValidationError

5.2.1 Properties

Name	Type	Required	Restrictions	Description
detail	[ValidationError]	false	none	none

5.3 NameCheckRequest

```
{
  "player_name": "string"
}
```

NameCheckRequest

5.3.1 Properties

Name	Type	Required	Restrictions	Description
player_name	string	true	none	none

5.4 NameCheckResponse

```
{
  "exists": true,
  "message": "string"
}
```

NameCheckResponse

5.4.1 Properties

Name	Type	Required	Restrictions	Description
exists	boolean	true	none	none
message	string	true	none	none

Copyright © 2026

5.5 Player

```
{
  "name": "string",
  "id": 0,
  "created_at": "2019-08-24T14:15:22Z"
}
```

Player

5.5.1 Properties

Name	Type	Required	Restrictions	Description
name	string	true	none	none
id	integer	true	none	none
created_at	string(date-time)	true	none	none

5.6 PlayerCreate

```
{
  "name": "string"
}
```

PlayerCreate

5.6.1 Properties

Name	Type	Required	Restrictions	Description
name	string	true	none	none

5.7 PlayerCreateResponse

```
{
  "name": "string",
  "id": 0,
  "created_at": "2019-08-24T14:15:22Z",
  "password": "string"
}
```

PlayerCreateResponse

5.7.1 Properties

Name	Type	Required	Restrictions	Description
name	string	true	none	none
id	integer	true	none	none
created_at	string(date-time)	true	none	none
password	string	true	none	none

Copyright © 2026

5.8 PlayerNameUpdate

```
{
  "name": "string"
}
```

PlayerNameUpdate

5.8.1 Properties

Name	Type	Required	Restrictions	Description
name	string	true	none	none

5.9 PlayerStats

```
{
  "player_name": "string",
  "number_of_runs": 0,
  "total_time_played": 0,
  "average_time_survived": 0,
  "longest_run": 0,
  "favourite_upgrade": "string",
  "total_monsters_slain": 0
}
```

PlayerStats

5.9.1 Properties

Name	Type	Required	Restrictions	Description
player_name	string	true	none	none
number_of_runs	integer	true	none	none
total_time_played	integer	true	none	none
average_time_survived	number	true	none	none
longest_run	integer	true	none	none
favourite_upgrade	any	false	none	none

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	string	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
total_monsters_slain	integer	true	none	none

Copyright © 2026

5.10 PlayerSummary

```
{
  "name": "string",
  "id": 0,
  "created_at": "2019-08-24T14:15:22Z",
  "total_runs": 0,
  "best_run_time": 0
}
```

PlayerSummary

5.10.1 Properties

Name	Type	Required	Restrictions	Description
name	string	true	none	none
id	integer	true	none	none
created_at	string(date-time)	true	none	none
total_runs	integer	true	none	none
best_run_time	any	false	none	none

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	integer	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

5.11 Run

```
{
  "player_id": 0,
  "map_id": "string",
  "id": 0,
  "player": {
    "name": "string",
    "id": 0,
    "created_at": "2019-08-24T14:15:22Z"
  },
  "started_at": "2019-08-24T14:15:22Z",
  "status": "in_progress",
  "duration_seconds": 0,
  "level": 0,
  "xp": 0,
  "kills_total": 0,
  "upgrades": {
    "property1": 0,
    "property2": 0
  },
  "ended_at": "2019-08-24T14:15:22Z",
  "cause_of_death": "string"
}
```

Run

Copyright © 2026

5.11.1 Properties

Name	Type	Required	Restrictions	Description
player_id	integer	true	none	none
map_id	string	true	none	none
id	integer	true	none	none
player	Player	true	none	Schema for representing a player, including their ID and creation date.
started_at	string(date-time)	true	none	none
status	RunStatus	true	none	An enumeration for the possible statuses of a run.
duration_seconds	integer	true	none	none
level	integer	true	none	none
xp	integer	true	none	none
kills_total	integer	true	none	none
upgrades	any	false	none	none

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	object	false	none	none
»» **additionalProperties**	integer	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
ended_at	any	true	none	none

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	string(date-time)	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

Copyright © 2026

continued

Name	Type	Required	Restrictions	Description
cause_of_death	any	true	none	none

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	string	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

5.12 RunEvent

```
{
  "event_type": "string",
  "value": "string",
  "id": 0,
  "run_id": 0,
  "timestamp": "2019-08-24T14:15:22Z"
}
```

RunEvent

5.12.1 Properties

Name	Type	Required	Restrictions	Description
event_type	string	true	none	none
value	any	false	none	none

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	string	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
id	integer	true	none	none
run_id	integer	true	none	none
timestamp	string(date-time)	true	none	none

Copyright © 2026

5.13 RunEventCreate

```
{
  "event_type": "string",
  "value": "string"
}
```

RunEventCreate

5.13.1 Properties

Name	Type	Required	Restrictions	Description
event_type	string	true	none	none
value	any	false	none	none

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	string	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

5.14 RunLeaderboard

```
{
  "player_id": 0,
  "run_id": 0,
  "player_name": "string",
  "duration_seconds": 0,
  "total_kills": 0
}
```

RunLeaderboard

5.14.1 Properties

Name	Type	Required	Restrictions	Description
player_id	integer	true	none	none
run_id	integer	true	none	none
player_name	string	true	none	none
duration_seconds	integer	true	none	none
total_kills	integer	true	none	none

5.15 RunStart

```
{
  "player_name": "string",
  "password": "string",
  "map_id": "string",
  "create_new_player": false
```


Copyright © 2026

```
}
```

RunStart

5.15.1 Properties

Name	Type	Required	Restrictions	Description
player_name	string	true	none	none
password	any	false	none	none

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	string	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
map_id	string	true	none	none
create_new_player	boolean	false	none	none

5.16 RunStartResponse

```
{
  "player_id": 0,
  "run_id": 0
}
```

RunStartResponse

5.16.1 Properties

Name	Type	Required	Restrictions	Description
player_id	integer	true	none	none
run_id	integer	true	none	none

5.17 RunStatus

```
"in_progress"
```

RunStatus

Copyright © 2026

5.17.1 Properties

Name	Type	Required	Restrictions	Description
RunStatus	string	false	none	An enumeration for the possible statuses of a run.

Enumerated Values

Property	Value
RunStatus	in_progress
RunStatus	died
RunStatus	completed

5.18 RunUpdate

```
{
  "duration_seconds": 0,
  "kills_total": 0,
  "level": 0,
  "xp": 0,
  "upgrades": {
    "property1": 0,
    "property2": 0
  },
  "status": "in_progress",
  "ended_at": "2019-08-24T14:15:22Z",
  "cause_of_death": "string"
}
```

RunUpdate

5.18.1 Properties

Name	Type	Required	Restrictions	Description
duration_seconds	any	false	none	none

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	integer	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
kills_total	any	false	none	none

Copyright © 2026

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	integer	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
level	any	false	none	none

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	integer	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
xp	any	false	none	none

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	integer	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
upgrades	any	false	none	none

Copyright © 2026

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	object	false	none	none
»» **additionalProperties**	integer	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
status	any	false	none	none

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	RunStatus	false	none	An enumeration for the possible statuses of a run.

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
ended_at	any	false	none	none

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	string(date-time)	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

continued

Name	Type	Required	Restrictions	Description
cause_of_death	any	false	none	none

Copyright © 2026

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	string	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	null	false	none	none

5.19 ValidationError

```
{
  "loc": [
    "string"
  ],
  "msg": "string",
  "type": "string"
}
```

ValidationError

5.19.1 Properties

Name	Type	Required	Restrictions	Description
loc	[anyOf]	true	none	none

anyOf

Name	Type	Required	Restrictions	Description
» *anonymous*	string	false	none	none

or

Name	Type	Required	Restrictions	Description
» *anonymous*	integer	false	none	none

continued

Name	Type	Required	Restrictions	Description
msg	string	true	none	none
type	string	true	none	none

Copyright © 2026