

# L<sup>A</sup>T<sub>E</sub>X3 News

Issue 12, January 2020

## Contents

<b>Introduction</b>	<b>1</b>
<b>New features in expl3</b>	<b>1</b>
A new argument specifier: <code>e</code> -type . . . . .	1
New functions . . . . .	1
String conversion moves to <code>expl3</code> . . . . .	2
Case changing of text . . . . .	2
<b>Notable fixes and changes</b>	<b>2</b>
File name parsing . . . . .	2
Message formatting . . . . .	2
Key inheritance . . . . .	2
Floating point juxtaposition . . . . .	2
Changing box dimensions . . . . .	2
More functions moved to stable . . . . .	2
Deprecations . . . . .	2
<b>Internal improvements</b>	<b>2</b>
Cross-module functions . . . . .	2
The backend . . . . .	2
<b>Better support for (u)pT<sub>E</sub>X</b>	<b>3</b>
<b>Options</b>	<b>3</b>
<b>Engine requirements</b>	<b>3</b>
<b>Documentation</b>	<b>3</b>
News . . . . .	3
ChangeLog . . . . .	3
<b>Changes in xparse</b>	<b>3</b>
<b>New experimental modules</b>	<b>3</b>
<b>l3build changes</b>	<b>3</b>

## Introduction

There has been quite a gap since the last *L<sup>A</sup>T<sub>E</sub>X3 News* (Issue 11, February 2018), and so there is quite a bit to cover here. Luckily, one of the things there *is* to cover is that we are using a more formalised approach for logging changes, so writing up what has happened is a bit easier. (By mistake *L<sup>A</sup>T<sub>E</sub>X3 News* 11 itself did not get *published* when written, but is now available: we have kept the information it contains separate as it is a good summary of the work that had happened in 2017.)

Work has continued apace across the *L<sup>A</sup>T<sub>E</sub>X3* code-base in the last (nearly) two years. A lot of this is ultimately focussed on making the core of `expl3` even more stable: *squeezing* out more experimental ideas, refining ones we have and making it a serious option for core *L<sup>A</sup>T<sub>E</sub>X* programming.

As a result of these activities, the *L<sup>A</sup>T<sub>E</sub>X3* programming layer will be available as part of the kernel of *L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>* from 2020-02-02 onwards, i.e., can be used without explicitly loading `expl3`. See *L<sup>A</sup>T<sub>E</sub>X News* 31 [2] for more details on this.

## New features in expl3

### A new argument specifier: `e`-type

During 2018, the team worked with the T<sub>E</sub>X Live, X<sub>Ǝ</sub>T<sub>E</sub>X and (u)pT<sub>E</sub>X developers to add the `\expanded` primitive to pdfT<sub>E</sub>X, X<sub>Ǝ</sub>T<sub>E</sub>X and (u)pT<sub>E</sub>X. This primitive was originally suggested for pdfT<sub>E</sub>X v1.50 (never released), and was present in LuaT<sub>E</sub>X from the start of that project.

Adding `\expanded` lets us create a new argument specifier: `e`-type expansion. This is *almost* the same as `x`-type, but is itself expandable. (It also doesn't need doubled `#` tokens.) That's incredibly useful for creating function-like macros: you can ensure that *everything* is expanded in an argument before you go near it, with not an `\expandafter` in sight.

### New functions

New programming tools have appeared in various places across `expl3`. The highlights are

- Shuffling of sequences to allow randomization
- Arrays of integers and floating point values; these have constant-time access
- Functions to return values after system shell usage
- Expandable access to file information, including file size, MD5 hash and modification date

For the latter, we have revised handling of file names considerably. There is now support for finding files in expansion contexts (by using the `\(pdf)filesize` primitive). Spaces and quotes in file names are now fully normalised, in a similar manner to the approach used by the latest *L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>* kernel.

### *String conversion moves to expl3*

In addition to entirely new functions, the team have moved the `l3str-convert` module from the `l3experimental` bundle into the `expl3` core. This module is essential for dealing with the need to produce UTF-16 and UTF-32 strings in some contexts, and also offers built-in escape for URLs and PDF strings.

### *Case changing of text*

Within `expl3`, the team have re-named and reworked the ideas from `\tl_upper_case:n` and so on, creating a new module `l3text`. This is a “final” home for functions to manipulate *text*; token lists that can reasonably expected to expand to plain text plus limited mark-up, for example emphasis and labels/references. Moving these functions, we have also made a small number of changes in other modules to give consistent names to functions: see the change log for full details.

Over time, we anticipate that functions for other textual manipulation will be added to this module.

### *Notable fixes and changes*

#### *File name parsing*

The functions for parsing file names have been entirely re-written, partly as this is required for the expandable access to file information mentioned above. The new code correctly deals with spaces and quote marks in file names and splits the path/name/extension.

#### *Message formatting*

The format of messages in `expl3` was originally quite text-heavy, the idea being that they would stand out in the `.log` file. However, this made them hard to find by a regular expression search, and was very different from the  $\text{\LaTeX} 2_{\epsilon}$  message approach. The formatting of `expl3` messages has been aligned with that from the  $\text{\LaTeX} 2_{\epsilon}$  kernel, such that IDE scripts and similar will be able to find and extract them directly.

#### *Key inheritance*

A number of changes have been made to the inheritance code for keys, to allow inheritance to work “as expected” in (almost) all cases.

#### *Floating point juxtaposition*

Implicit multiplication by juxtaposition, such as `—2pi—`, is now handled separately from parenthetic values. Thus for example `—1in/1cm—` is treated as equal to `—(1in)/(1cm)—` and thus yields `—2.54—`, and `—1/2(pi+pi)—` is equal to `—pi—`.

#### *Changing box dimensions*

$\text{\TeX}$ ’s handling of boxes is subtly-different from other registers, and this shows up in particular when you want to resize a box. To bring treatment of boxes, or rather the grouping behavior of boxes, into line with other registers, we have made some internal changes to

how functions such as `\box_set_wd:N` are implemented. This will be transparent for “well-behaved” use cases of these functions.

### *More functions moved to stable*

A large number of functions which were introduced as candidates have been evaluated and moved to stable status. The team hopes to move all functions in `expl3` to stable status, or move them out of the core, over the coming months.

### *Deprecations*

There have been two notable sets of deprecations over the past 18 months. First, we have rationalised all of the “raw” primitive names to the form `\tex_<name>:D`. This means that the older names, starting `\pdfTeX_...`, `\xetex_...`, etc., have been removed.

Secondly, the use of integer constants, which dates back to the earliest days of `expl3`, is today more likely to make the code harder to read than anything else. Speed improvements in engines mean that the tiny enhancements in reading such constants are no longer required. Thus for example `\c_two` is deprecated in favour of simply using `2`.

In parallel with this, a number of older `.sty` files have been removed. These older files provided legacy stubs for files which have now been integrated in the `expl3` core. They have now had sufficient time to allow users to update their code.

### *Internal improvements*

#### *Cross-module functions*

The team introduced the idea of internal module functions some time ago. Within the kernel, there are places where functions need to be used in multiple modules. To make the nature of the kernel interactions clearer, we have worked on several aspects

- Reducing as far as possible cross-module functions
- Making more generally-useful functions public, for example scan marks
- Creating an explicit cross-kernel naming convention for functions which are internal but are essential to use in multiple kernel modules

#### *The backend*

Creating graphics, working with color, setting up hyperlinks and so on require backend-specific code. Here, backends are for example `dvips`, `xdvipdfmx` and the direct PDF mode in `pdfTeX` and `LuaTeX`. These functions are needed across the  $\text{\LaTeX} 3$  codebase and have to be updated separate from the `expl3` core. To facilitate that, we have split those sources into a separate bundle, which can then be updated as required.

At the same time, the code these files contain is very low-level and is best described as internal. We have restructured how the entire set of functions are referred to such that they are now internal for the area they implement, for example image inclusion, box affine transformations, etc.

## Better support for (u)pTeX

The developers behind (u)pTeX (Japanese TeX) have recently enhanced their English documentation (see <https://github.com/texjporg/ptex-manual>). Using this new information, we have been able to make internal adjustments to expl3 to better support these engines.

## Options

A new option `undo-recent-deprecations` is now available for cases where a document (or package) requires some expl3 functions that have been formally removed after deprecation. This is to allow *temporary* workarounds for documents to be compiled whilst code is begin updated.

The “classical” options for selecting backends (`dvips`, `pdfTeX`, etc.) are now recognised in addition to the native key-value versions. This should make it much easier to use expl3 image and color support as it is brought up to fully-workable standards.

## Engine requirements

The minimum engine versions needed to use expl3 have been incremented a little:

- pdfTeX v1.40
- XeTeX v0.99992
- LuaTeX v0.95
- $\epsilon$ -(u)pTeX mid-2012

The team have also worked with the XeTeX and (u)pTeX developers to standardise the set of post- $\epsilon$ -TeX utility primitives that are available: the so-called “pdfTeX utilities”. These are now available in all supported engine, and in time will all be *required*. This primarily impacts XeTeX, which gained most of these primitives in the 2019 TeX Live cycle. (Examples are the random number primitives and expandable file data provision.) See *L<sup>A</sup>T<sub>E</sub>X News 31* [2] for more on this.

## Documentation

### News

The *L<sup>A</sup>T<sub>E</sub>X3 News* files were until recently only used to create PDF files on the team website [1]. We have now integrated those into the l3kernel (expl3 core) bundle. The news files cover all of L<sup>A</sup>T<sub>E</sub>X3 files, as the core files are always available.

## ChangeLog

Since the start of 2018, the team have commenced a comprehensive change log for each of the bundles which make up the L<sup>A</sup>T<sub>E</sub>X3 code. These are simple Markdown text files, which means that they can be displayed formatted in web views.

## Changes in xparse

A number of new features have been added to xparse. To allow handling of the fact that skipping spaces may be required only in some cases when searching for optional arguments, a new modifier `!` is available in argument specifiers. This causes xparse to *require* that an optional argument follows immediately with no intervening spaces.

There is a new argument type purely for environments: `b-type` for collecting a `\begin/\end` pair, i.e., collecting the body of an environment. This is similar in concept to the `environ` package, but is integrated directly into xparse.

Finally, it is now possible to refer to one argument as the default for another optional one, for example

```
\NewDocumentCommand{\caption}{0{#2} m}
...
```

## New experimental modules

A number of new experimental modules have been added within the l3experimental bundle

- l3benchmark Performance-testing system using the timing function in modern TeX engines
- l3cctab Category code tables for all engines, not just LuaTeX
- l3color Color support, similar in interface to xcolor
- l3draw Creation of drawings, inspired by pgf, but using the L<sup>A</sup>T<sub>E</sub>X3 FPU for calculations
- l3pdf Support for PDF features such as compression, hyper-links, etc.
- l3sys-shell Shell escape functions for file manipulation

## l3build changes

The l3build tool for testing and releasing TeX packages has seen a number of incremental improvements. It is now available directly as a script in TeX Live and MiKTeX, meaning you can call it simply as

`l3build target`

Accompanying this, we have added support for installing scripts and script `man` files.

There is a new `upload` target that can take a zip file and send it to CTAN: you just have to fill in release information for *this* upload at the prompts.

Testing using PDF files rather than logs has been heavily revised: this is vital for work on PDF tagging.

There is also better support for complex directory structures, including the ability to manually specify TDS location for all installed files. This is particularly targeted at package with both generic and format-specific file to install.

## *References*

- [1] *L<sup>A</sup>T<sub>E</sub>X Project Website*. <https://latex-project.org/>
- [2] *L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> release news letters on the L<sup>A</sup>T<sub>E</sub>X Project Website*. <https://latex-project.org/news/latex2e-news/>