

Kriging prediction for manifold-valued data

Generated by Doxygen 1.8.14

Contents

1	What is Manifoldgstat Package	1
2	Hierarchical Index	3
2.1	Class Hierarchy	3
3	Class Index	5
3.1	Class List	5
4	File Index	7
4.1	File List	7
5	Class Documentation	9
5.1	Coordinates Class Reference	9
5.1.1	Detailed Description	9
5.1.2	Constructor & Destructor Documentation	9
5.1.2.1	Coordinates()	9
5.1.3	Member Data Documentation	10
5.1.3.1	_coords	10
5.2	design_matrix::AdditiveDM Class Reference	10
5.2.1	Detailed Description	10
5.2.2	Member Function Documentation	11
5.2.2.1	compute_design_matrix() [1/2]	11
5.2.2.2	compute_design_matrix() [2/2]	11
5.3	design_matrix::Coord1DM Class Reference	12
5.3.1	Detailed Description	12

5.3.2	Member Function Documentation	12
5.3.2.1	compute_design_matrix() [1/2]	12
5.3.2.2	compute_design_matrix() [2/2]	13
5.4	design_matrix::Coord2DM Class Reference	13
5.4.1	Detailed Description	14
5.4.2	Member Function Documentation	14
5.4.2.1	compute_design_matrix() [1/2]	14
5.4.2.2	compute_design_matrix() [2/2]	14
5.5	design_matrix::DesignMatrix Class Reference	15
5.5.1	Detailed Description	15
5.5.2	Member Function Documentation	15
5.5.2.1	compute_design_matrix() [1/2]	15
5.5.2.2	compute_design_matrix() [2/2]	16
5.6	design_matrix::InterceptDM Class Reference	16
5.6.1	Detailed Description	17
5.6.2	Member Function Documentation	17
5.6.2.1	compute_design_matrix() [1/2]	17
5.6.2.2	compute_design_matrix() [2/2]	17
5.7	distances::Distance Class Reference	18
5.7.1	Detailed Description	18
5.7.2	Member Function Documentation	18
5.7.2.1	compute_distance()	18
5.7.2.2	create_distance_matrix()	19
5.7.2.3	create_distance_vector()	19
5.8	distances::EuclDist Class Reference	20
5.8.1	Detailed Description	20
5.8.2	Member Function Documentation	20
5.8.2.1	compute_distance()	20
5.9	distances::GeoDist Class Reference	21
5.9.1	Detailed Description	21

5.9.2	Member Function Documentation	21
5.9.2.1	compute_distance()	21
5.9.3	Member Data Documentation	22
5.9.3.1	Earth_R	22
5.9.3.2	eps_dbl	22
5.10	distances_manifold::Chol Class Reference	22
5.10.1	Detailed Description	23
5.10.2	Member Function Documentation	23
5.10.2.1	compute_distance()	23
5.11	distances_manifold::DistanceManifold Class Reference	23
5.11.1	Detailed Description	24
5.11.2	Member Function Documentation	24
5.11.2.1	compute_distance()	24
5.12	distances_manifold::Frobenius Class Reference	25
5.12.1	Detailed Description	25
5.12.2	Member Function Documentation	25
5.12.2.1	compute_distance()	25
5.13	distances_manifold::LogEuclidean Class Reference	26
5.13.1	Detailed Description	26
5.13.2	Member Function Documentation	26
5.13.2.1	compute_distance()	26
5.14	distances_manifold::SqRoot Class Reference	27
5.14.1	Detailed Description	27
5.14.2	Member Function Documentation	27
5.14.2.1	compute_distance()	27
5.15	distances_tplane::Chol Class Reference	28
5.15.1	Detailed Description	28
5.15.2	Member Function Documentation	28
5.15.2.1	norm()	28
5.15.2.2	set_members()	29

5.16	distances_tplane::DistanceTplane Class Reference	29
5.16.1	Detailed Description	30
5.16.2	Member Function Documentation	30
5.16.2.1	compute_distance()	30
5.16.2.2	norm()	30
5.16.2.3	set_members()	31
5.17	distances_tplane::Frobenius Class Reference	31
5.17.1	Detailed Description	32
5.17.2	Member Function Documentation	32
5.17.2.1	norm()	32
5.17.2.2	set_members()	32
5.18	distances_tplane::FrobeniusScaled Class Reference	33
5.18.1	Detailed Description	33
5.18.2	Member Function Documentation	33
5.18.2.1	norm()	33
5.18.2.2	set_members()	34
5.18.3	Member Data Documentation	34
5.18.3.1	_SigmaInv	34
5.18.3.2	_p	34
5.19	generic_factory::Factory< AbstractProduct, Identifier, Builder > Class Template Reference	35
5.19.1	Detailed Description	36
5.19.2	Member Function Documentation	36
5.19.2.1	create()	36
5.20	generic_factory::Proxy< Factory, ConcreteProduct > Class Template Reference	36
5.20.1	Detailed Description	37
5.21	map_functions::expMapChol Class Reference	38
5.21.1	Detailed Description	38
5.21.2	Member Function Documentation	38
5.21.2.1	map2manifold()	38
5.21.2.2	set_members()	39

5.21.2.3	set_tolerance()	39
5.21.3	Member Data Documentation	39
5.21.3.1	_tolerance_map_cor	39
5.21.3.2	_Sigma	40
5.22	map_functions::expMapFrob Class Reference	40
5.22.1	Detailed Description	40
5.22.2	Member Function Documentation	40
5.22.2.1	map2manifold()	40
5.22.2.2	set_members()	41
5.22.2.3	set_tolerance()	41
5.22.3	Member Data Documentation	41
5.22.3.1	_sqrtSigma	41
5.22.3.2	_sqrtSigmaInv	42
5.23	map_functions::expMapLogEucl Class Reference	42
5.23.1	Detailed Description	42
5.23.2	Member Function Documentation	42
5.23.2.1	map2manifold()	42
5.23.2.2	set_members()	43
5.23.2.3	set_tolerance()	43
5.23.3	Member Data Documentation	43
5.23.3.1	_Sigma	43
5.24	map_functions::expMapSqRoot Class Reference	44
5.24.1	Detailed Description	44
5.24.2	Member Function Documentation	44
5.24.2.1	map2manifold()	44
5.24.2.2	set_members()	45
5.24.2.3	set_tolerance()	45
5.24.3	Member Data Documentation	45
5.24.3.1	_Sigma	45
5.25	map_functions::exponentialMap Class Reference	46

5.25.1 Detailed Description	46
5.25.2 Member Function Documentation	46
5.25.2.1 map2manifold()	46
5.25.2.2 set_members()	47
5.25.2.3 set_tolerance()	47
5.26 map_functions::logarithmicMap Class Reference	48
5.26.1 Detailed Description	48
5.26.2 Member Function Documentation	48
5.26.2.1 map2tplane()	48
5.26.2.2 set_members()	49
5.26.2.3 set_tolerance()	49
5.27 map_functions::logMapChol Class Reference	49
5.27.1 Detailed Description	50
5.27.2 Member Function Documentation	50
5.27.2.1 map2tplane()	50
5.27.2.2 set_members()	51
5.27.2.3 set_tolerance()	51
5.27.3 Member Data Documentation	51
5.27.3.1 _Sigma	51
5.27.3.2 _tolerance_map_cor	51
5.28 map_functions::logMapFrob Class Reference	52
5.28.1 Detailed Description	52
5.28.2 Member Function Documentation	52
5.28.2.1 map2tplane()	52
5.28.2.2 set_members()	53
5.28.2.3 set_tolerance()	53
5.28.3 Member Data Documentation	53
5.28.3.1 _sqrtSigma	53
5.28.3.2 _sqrtSigmaInv	54
5.29 map_functions::logMapLogEucl Class Reference	54

5.29.1 Detailed Description	54
5.29.2 Member Function Documentation	54
5.29.2.1 map2tplane()	54
5.29.2.2 set_members()	55
5.29.2.3 set_tolerance()	55
5.29.3 Member Data Documentation	55
5.29.3.1 _Sigma	56
5.30 map_functions::logMapSqRoot Class Reference	56
5.30.1 Detailed Description	56
5.30.2 Member Function Documentation	56
5.30.2.1 map2tplane()	56
5.30.2.2 set_members()	57
5.30.2.3 set_tolerance()	57
5.30.3 Member Data Documentation	57
5.30.3.1 _Sigma	58
5.31 model_fit::Model Class Reference	58
5.31.1 Detailed Description	59
5.31.2 Member Function Documentation	59
5.31.2.1 update_model()	59
5.31.3 Member Data Documentation	59
5.31.3.1 _data_tspace	59
5.31.3.2 _design_matrix_model	59
5.31.3.3 _design_matrix_tot	59
5.31.3.4 _distance_Manifold_name	59
5.31.3.5 _N	60
5.31.3.6 _p	60
5.31.3.7 _num_cov	60
5.31.3.8 _num_coeff	60
5.31.3.9 _beta_matrix	60
5.31.3.10 _fitted_values	60

5.31.3.11	<code>_residuals</code>	60
5.32	<code>variogram_evaluation::EmpiricalVariogram</code> Class Reference	61
5.32.1	Detailed Description	62
5.32.2	Member Function Documentation	62
5.32.2.1	<code>update_emp_vario()</code>	62
5.32.3	Member Data Documentation	62
5.32.3.1	<code>_n_h</code>	62
5.32.3.2	<code>_N</code>	62
5.32.3.3	<code>_distanceMatrix</code>	63
5.32.3.4	<code>_emp_vario_values</code>	63
5.32.3.5	<code>_hvec</code>	63
5.32.3.6	<code>_N_hvec</code>	63
5.32.3.7	<code>_card_h</code>	63
5.32.3.8	<code>_d</code>	63
5.32.3.9	<code>_hmax</code>	63
5.32.3.10	<code>_weights</code>	64
5.33	<code>variogram_evaluation::ExpVariogram</code> Class Reference	64
5.33.1	Detailed Description	64
5.33.2	Member Function Documentation	65
5.33.2.1	<code>get_init_par()</code>	65
5.33.2.2	<code>get_vario_univ()</code>	65
5.34	<code>variogram_evaluation::FittedVariogram</code> Class Reference	66
5.34.1	Detailed Description	67
5.34.2	Member Function Documentation	67
5.34.2.1	<code>weighted_median()</code>	67
5.34.2.2	<code>get_init_par()</code>	67
5.34.2.3	<code>evaluate_par_fitted_E()</code>	68
5.34.2.4	<code>evaluate_par_fitted_W()</code>	69
5.34.2.5	<code>get_vario_univ()</code>	69
5.34.2.6	<code>get_covario_univ()</code>	70

5.34.2.7	get_vario_vec() [1/2]	70
5.34.2.8	get_vario_vec() [2/2]	70
5.34.2.9	compute_gamma_matrix()	71
5.34.2.10	set_parameters()	71
5.34.2.11	get_covario_vec()	71
5.34.3	Member Data Documentation	72
5.34.3.1	_parameters	72
5.35	variogram_evaluation::GaussVariogram Class Reference	72
5.35.1	Detailed Description	73
5.35.2	Member Function Documentation	73
5.35.2.1	get_init_par()	73
5.35.2.2	get_vario_univ()	73
5.36	variogram_evaluation::SphVariogram Class Reference	74
5.36.1	Detailed Description	74
5.36.2	Member Function Documentation	74
5.36.2.1	get_init_par()	74
5.36.2.2	get_vario_univ()	75
6	File Documentation	77
6.1	Coordinates.hpp File Reference	77
6.1.1	Detailed Description	77
6.2	DesignMatrix.hpp File Reference	77
6.2.1	Detailed Description	78
6.3	Distance.hpp File Reference	78
6.3.1	Detailed Description	78
6.4	DistanceManifold.hpp File Reference	79
6.4.1	Detailed Description	79
6.5	DistanceTplane.hpp File Reference	79
6.5.1	Detailed Description	80
6.6	EmpiricalVariogram.hpp File Reference	80
6.6.1	Detailed Description	80

6.7	Factory.hpp File Reference	80
6.7.1	Detailed Description	80
6.8	FittedVariogram.hpp File Reference	81
6.8.1	Detailed Description	81
6.9	Helpers.hpp File Reference	81
6.9.1	Detailed Description	82
6.9.2	Function Documentation	82
6.9.2.1	expMat()	82
6.9.2.2	logMat()	82
6.9.2.3	sqrtMat()	84
6.9.2.4	bigMatrix2VecMatrices()	84
6.9.2.5	VecMatrices2bigMatrix()	85
6.9.2.6	Chol_semidef()	85
6.9.2.7	Chol_decomposition()	85
6.10	HelpersFactory.hpp File Reference	86
6.10.1	Detailed Description	87
6.11	interface_function.cpp File Reference	87
6.11.1	Detailed Description	88
6.11.2	Function Documentation	88
6.11.2.1	get_model()	88
6.11.2.2	get_kriging()	90
6.11.2.3	get_model_and_kriging()	91
6.11.2.4	intrinsic_mean()	94
6.11.2.5	distance_manifold()	94
6.12	IntrinsicMean.hpp File Reference	95
6.12.1	Detailed Description	95
6.12.2	Function Documentation	95
6.12.2.1	intrinsic_mean_C()	96
6.12.2.2	extrinsic_mean()	97
6.13	MapFunctions.hpp File Reference	97
6.13.1	Detailed Description	98
6.14	Model.hpp File Reference	98
6.14.1	Detailed Description	98
6.15	Proxy.hpp File Reference	99
6.15.1	Detailed Description	99

Chapter 1

What is Manifoldgstat Package

R Package to make inference and prediction for manifold-valued data analysis. This package provides a C++ implementation of the functions to create a model, for spatial dependent manifold valued data, in order to perform kriging. In each location, specified by a vector of coordinates ($[lat, long]$, $[x, y]$ or $[x, y, z]$), the datum is supposed to be a symmetric and positive definite matrix (possibly a correlation matrix). The algorithm exploits a projection of these data on a tangent space, where the tangent point is either provided by the user or computed as intrinsic mean of the data in input.

References

JD. Pigoli, A. Menafoglio & P. Secchi (2016). Kriging prediction for manifold-valued random fields. *Journal of Multivariate Analysis*, 145, 117-131.

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Coordinates	9
design_matrix::DesignMatrix	15
design_matrix::AdditiveDM	10
design_matrix::Coord1DM	12
design_matrix::Coord2DM	13
design_matrix::InterceptDM	16
distances::Distance	18
distances::EuclDist	20
distances::GeoDist	21
distances_manifold::DistanceManifold	23
distances_manifold::Chol	22
distances_manifold::Frobenius	25
distances_manifold::LogEuclidean	26
distances_manifold::SqRoot	27
distances_tplane::DistanceTplane	29
distances_tplane::Chol	28
distances_tplane::Frobenius	31
distances_tplane::FrobeniusScaled	33
generic_factory::Factory< AbstractProduct, Identifier, Builder >	35
generic_factory::Proxy< Factory, ConcreteProduct >	36
map_functions::exponentialMap	46
map_functions::expMapChol	38
map_functions::expMapFrob	40
map_functions::expMapLogEucl	42
map_functions::expMapSqRoot	44
map_functions::logarithmicMap	48
map_functions::logMapChol	49
map_functions::logMapFrob	52
map_functions::logMapLogEucl	54
map_functions::logMapSqRoot	56
model_fit::Model	58
variogram_evaluation::EmpiricalVariogram	61
variogram_evaluation::FittedVariogram	66
variogram_evaluation::ExpVariogram	64
variogram_evaluation::GaussVariogram	72
variogram_evaluation::SphVariogram	74

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Coordinates	
Class to store the coordinates of the data points	9
design_matrix::AdditiveDM	
Class for the computation of the design_matrix when model_ts=="Additive"	10
design_matrix::Coord1DM	
Class for the computation of the design_matrix when model_ts=="Coord1"	12
design_matrix::Coord2DM	
Class for the computation of the design_matrix when model_ts=="Coord2"	13
design_matrix::DesignMatrix	
Abstract class for the computation of the design_matrix	15
design_matrix::InterceptDM	
Class for the computation of the design_matrix when model_ts=="Intercept"	16
distances::Distance	
Abstract class for the computation of the distance between data locations	18
distances::EuclDist	
Class for the computation of the distance between data locations when distance=="↔ EuclDist"	20
distances::GeoDist	
Class for the computation of the distance between data locations when distance=="↔ Geodist"	21
distances_manifold::Chol	
Class for the computation of the distance on the manifold when manifold_metric=="↔ Chol"	22
distances_manifold::DistanceManifold	
Abstract class for the computation of the distance on the manifold	23
distances_manifold::Frobenius	
Class for the computation of the distance on the manifold when manifold_metric=="↔ Frobenius"	25
distances_manifold::LogEuclidean	
Class for the computation of the distance on the manifold when manifold_metric=="↔ LogEuclidean"	26
distances_manifold::SqRoot	
Class for the computation of the distance on the manifold when manifold_metric=="Sq↔ Root"	27

distances_tplane::Chol	
Class for the computation of the distance on the tangent space when <code>ts_metric=="↵Correlation"</code>	28
distances_tplane::DistanceTplane	
Abstract class for the computation of the distance on the tangent space	29
distances_tplane::Frobenius	
Class for the computation of the distance on the tangent space when <code>ts_metric=="↵Frobenius"</code>	31
distances_tplane::FrobeniusScaled	
Class for the computation of the distance on the tangent space when <code>ts_metric=="↵FrobeniusScaled"</code>	33
generic_factory::Factory< AbstractProduct, Identifier, Builder >	
A generic factory	35
generic_factory::Proxy< Factory, ConcreteProduct >	
.	36
map_functions::expMapChol	
Class for the computation of the exponential map when <code>manifold_metric=="↵Correlation"</code>	38
map_functions::expMapFrob	
Class for the computation of the exponential map when <code>manifold_metric=="↵Frobenius"</code>	40
map_functions::expMapLogEucl	
Class for the computation of the exponential map when <code>manifold_metric=="Log↵Euclidean"</code>	42
map_functions::expMapSqRoot	
Class for the computation of the exponential map when <code>manifold_metric=="SqRoot "</code> .	44
map_functions::exponentialMap	
Abstract class for the computation of the exponential map	46
map_functions::logarithmicMap	
Abstract class for the computation of the logarithmic map	48
map_functions::logMapChol	
Class for the computation of the logarithmic map when <code>manifold_metric=="↵Correlation"</code>	49
map_functions::logMapFrob	
Class for the computation of the logarithmic map when <code>manifold_metric=="↵Frobenius"</code>	52
map_functions::logMapLogEucl	
Class for the computation of the logarithmic map when <code>manifold_metric=="Log↵Euclidean"</code>	54
map_functions::logMapSqRoot	
Class for the computation of the logarithmic map when <code>manifold_metric=="SqRoot "</code> .	56
model_fit::Model	
Class to compute and store the linear model on the tangent space	58
variogram_evaluation::EmpiricalVariogram	
Class for computation and storage of the empirical variogram	61
variogram_evaluation::ExpVariogram	
Class for computation and storage of the fitted variogram when <code>vario_model=="↵Exponential"</code>	64
variogram_evaluation::FittedVariogram	
Abstract class for computation and storage of the fitted variogram	66
variogram_evaluation::GaussVariogram	
Class for computation and storage of the fitted variogram when <code>vario_model=="↵Gaussian"</code>	72
variogram_evaluation::SphVariogram	
Class for computation and storage of the fitted variogram when <code>vario_model=="↵Spherical"</code>	74

Chapter 4

File Index

4.1 File List

Here is a list of all documented files with brief descriptions:

Coordinates.hpp	
Coordinates class	77
DesignMatrix.hpp	
Classes to create the design_matrix according to the model on the tangent space	77
Distance.hpp	
Classes to create the compute the distances between data locations	78
DistanceManifold.hpp	
Classes to compute the distance on the manifold according to its metric	79
DistanceTplane.hpp	
Classes to compute the distance on the tangent space according to its metric	79
EmpiricalVariogram.hpp	
Class to compute the empirical variogram	80
Factory.hpp	
Factory class	80
FittedVariogram.hpp	
Classes to fit a model variogram (Gaussian, Exponential or Spherical) to an empirical one	81
Helpers.hpp	
Functions to manipulate matrices	81
HelpersFactory.hpp	
Typedefs for the factory	86
interface_function.cpp	
Main functions to create the model and perform kriging, along with functions to compute the distance on the manifold and the intrinsic mean	87
IntrinsicMean.hpp	
Functions to compute intrinsic and extrinsic mean for manifold data	95
MapFunctions.hpp	
Classes to compute the exponential and logarithmic map according to the manifold metric	97
Model.hpp	
Model class	98
Proxy.hpp	
Proxy class	99

Chapter 5

Class Documentation

5.1 Coordinates Class Reference

Class to store the coordinates of the data points.

```
#include <Coordinates.hpp>
```

Public Member Functions

- [Coordinates](#) (const std::shared_ptr< const MatrixXd > coords)
Constructor.
- unsigned int [get_N_station](#) () const
Return the number of data points in the analysis.
- const std::shared_ptr< const MatrixXd > [get_coords](#) () const
Return the matrix of the coordinates.
- unsigned int [get_n_coords](#) () const
Return the number of coordinates for each data point.

Private Attributes

- const std::shared_ptr< const MatrixXd > [_coords](#)

5.1.1 Detailed Description

Class to store the coordinates of the data points.

5.1.2 Constructor & Destructor Documentation

5.1.2.1 Coordinates()

```
Coordinates::Coordinates (  
    const std::shared_ptr< const MatrixXd > coords ) [inline]
```

Constructor.

Parameters

<i>coords</i>	Matrix containing the coordinates of the data points
---------------	--

5.1.3 Member Data Documentation

5.1.3.1 `_coords`

```
const std::shared_ptr<const MatrixXd> Coordinates::_coords [private]
```

Matrix of the coordinates

The documentation for this class was generated from the following files:


- [Coordinates.hpp](#)
- [Coordinates.cpp](#)

5.2 `design_matrix::AdditiveDM` Class Reference

Class for the computation of the `design_matrix` when `model_ts=="Additive"`

```
#include <DesignMatrix.hpp>
```

Inheritance diagram for `design_matrix::AdditiveDM`:



Public Member Functions

- `MatrixXd` [compute_design_matrix](#) (const [Coordinates](#) &coords) const override
Compute the design matrix with no covariates besides the coordinates.
- `MatrixXd` [compute_design_matrix](#) (const [Coordinates](#) &coords, const `MatrixXd` &X) const override
Compute the design matrix with extra covariates besides the coordinates.
- [~AdditiveDM](#) ()=default
Destructor.

5.2.1 Detailed Description

Class for the computation of the `design_matrix` when `model_ts=="Additive"`

5.2.2 Member Function Documentation

5.2.2.1 compute_design_matrix() [1/2]

```
MatrixXd AdditiveDM::compute_design_matrix (
    const Coordinates & coords ) const [override], [virtual]
```

Compute the design matrix with no covariates besides the coordinates.

Parameters

<i>coords</i>	Matrix of the coordinates of the locations
---------------	--

Returns

Design matrix

Implements [design_matrix::DesignMatrix](#).

5.2.2.2 compute_design_matrix() [2/2]

```
MatrixXd AdditiveDM::compute_design_matrix (
    const Coordinates & coords,
    const MatrixXd & X ) const [override], [virtual]
```

Compute the design matrix with extra covariates besides the coordinates.

Parameters

<i>coords</i>	Matrix of the coordinates of the locations
<i>X</i>	Matrix of the additional covariates for the locations

Returns

Design matrix

Implements [design_matrix::DesignMatrix](#).

The documentation for this class was generated from the following files:


- [DesignMatrix.hpp](#)
- [DesignMatrix.cpp](#)

5.3 design_matrix::Coord1DM Class Reference

Class for the computation of the design_matrix when `model_ts=="Coord1"`

```
#include <DesignMatrix.hpp>
```

Inheritance diagram for design_matrix::Coord1DM:



Public Member Functions

- MatrixXd `compute_design_matrix` (const [Coordinates](#) &coords) const override
Compute the design matrix with no covariates besides the coordinates.
- MatrixXd `compute_design_matrix` (const [Coordinates](#) &coords, const MatrixXd &X) const override
Compute the design matrix with extra covariates besides the coordinates.
- `~Coord1DM` ()=default
Destructor.

5.3.1 Detailed Description

Class for the computation of the design_matrix when `model_ts=="Coord1"`

5.3.2 Member Function Documentation

5.3.2.1 compute_design_matrix() [1/2]

```
MatrixXd Coord1DM::compute_design_matrix (
    const Coordinates & coords ) const [override], [virtual]
```

Compute the design matrix with no covariates besides the coordinates.

Parameters

<code>coords</code>	Matrix of the coordinates of the locations
---------------------	--

Returns

Design matrix

Implements [design_matrix::DesignMatrix](#).

5.3.2.2 compute_design_matrix() [2/2]

```
MatrixXd Coord1DM::compute_design_matrix (
    const Coordinates & coords,
    const MatrixXd & X ) const [override], [virtual]
```

Compute the design matrix with extra covariates besides the coordinates.

Parameters

<i>coords</i>	Matrix of the coordinates of the locations
<i>X</i>	Matrix of the additional covariates for the locations

Returns

Design matrix

Implements [design_matrix::DesignMatrix](#).

The documentation for this class was generated from the following files:


- [DesignMatrix.hpp](#)
- DesignMatrix.cpp

5.4 design_matrix::Coord2DM Class Reference

Class for the computation of the design_matrix when `model_ts=="Coord2"`

```
#include <DesignMatrix.hpp>
```

Inheritance diagram for design_matrix::Coord2DM:



Public Member Functions

- MatrixXd [compute_design_matrix](#) (const [Coordinates](#) &coords) const override
Compute the design matrix with no covariates besides the coordinates.
- MatrixXd [compute_design_matrix](#) (const [Coordinates](#) &coords, const MatrixXd &X) const override
Compute the design matrix with extra covariates besides the coordinates.
- [~Coord2DM](#) ()=default
Destructor.

5.4.1 Detailed Description

Class for the computation of the design_matrix when `model_ts=="Coord2"`

5.4.2 Member Function Documentation

5.4.2.1 `compute_design_matrix()` [1/2]

```
MatrixXd Coord2DM::compute_design_matrix (
    const Coordinates & coords ) const [override], [virtual]
```

Compute the design matrix with no covariates besides the coordinates.

Parameters

<i>coords</i>	Matrix of the coordinates of the locations
---------------	--

Returns

Design matrix

Implements [design_matrix::DesignMatrix](#).

5.4.2.2 `compute_design_matrix()` [2/2]

```
MatrixXd Coord2DM::compute_design_matrix (
    const Coordinates & coords,
    const MatrixXd & X ) const [override], [virtual]
```

Compute the design matrix with extra covariates besides the coordinates.

Parameters

<i>coords</i>	Matrix of the coordinates of the locations
<i>X</i>	Matrix of the additional covariates for the locations

Returns

Design matrix

Implements [design_matrix::DesignMatrix](#).

The documentation for this class was generated from the following files:


- [DesignMatrix.hpp](#)
- [DesignMatrix.cpp](#)

5.5 design_matrix::DesignMatrix Class Reference

Abstract class for the computation of the design_matrix.

```
#include <DesignMatrix.hpp>
```

Inheritance diagram for design_matrix::DesignMatrix:



Public Member Functions

- virtual MatrixXd [compute_design_matrix](#) (const [Coordinates](#) &coords) const =0
Compute the design matrix with no covariates besides the coordinates.
- virtual MatrixXd [compute_design_matrix](#) (const [Coordinates](#) &coords, const MatrixXd &X) const =0
Compute the design matrix with extra covariates besides the coordinates.
- virtual [~DesignMatrix](#) ()=default
Destructor.

5.5.1 Detailed Description

Abstract class for the computation of the design_matrix.

5.5.2 Member Function Documentation

5.5.2.1 compute_design_matrix() [1/2]

```
virtual MatrixXd design_matrix::DesignMatrix::compute_design_matrix (
    const Coordinates & coords ) const [pure virtual]
```

Compute the design matrix with no covariates besides the coordinates.

Parameters

<i>coords</i>	Matrix of the coordinates of the locations
---------------	--

Returns

Design matrix

Implemented in [design_matrix::AdditiveDM](#), [design_matrix::Coord2DM](#), [design_matrix::Coord1DM](#), and [design_matrix::InterceptDM](#).

5.5.2.2 compute_design_matrix() [2/2]

```
virtual MatrixXd design_matrix::DesignMatrix::compute_design_matrix (
    const Coordinates & coords,
    const MatrixXd & X ) const [pure virtual]
```

Compute the design matrix with extra covariates besides the coordinates.

Parameters

<i>coords</i>	Matrix of the coordinates of the locations
<i>X</i>	Matrix of the additional covariates for the locations

Returns

Design matrix

Implemented in [design_matrix::AdditiveDM](#), [design_matrix::Coord2DM](#), [design_matrix::Coord1DM](#), and [design_matrix::InterceptDM](#).

The documentation for this class was generated from the following file:


- [DesignMatrix.hpp](#)

5.6 design_matrix::InterceptDM Class Reference

Class for the computation of the design_matrix when `model_ts=="Intercept"`

```
#include <DesignMatrix.hpp>
```

Inheritance diagram for design_matrix::InterceptDM:



Public Member Functions

- MatrixXd [compute_design_matrix](#) (const [Coordinates](#) &coords) const override
Compute the design matrix with no covariates besides the coordinates.
- MatrixXd [compute_design_matrix](#) (const [Coordinates](#) &coords, const MatrixXd &X) const override
Compute the design matrix with extra covariates besides the coordinates.
- [~InterceptDM](#) ()=default
Destructor.

5.6.1 Detailed Description

Class for the computation of the design_matrix when `model_ts=="Intercept"`

5.6.2 Member Function Documentation

5.6.2.1 compute_design_matrix() [1/2]

```
MatrixXd InterceptDM::compute_design_matrix (
    const Coordinates & coords ) const [override], [virtual]
```

Compute the design matrix with no covariates besides the coordinates.

Parameters

<i>coords</i>	Matrix of the coordinates of the locations
---------------	--

Returns

Design matrix

Implements [design_matrix::DesignMatrix](#).

5.6.2.2 compute_design_matrix() [2/2]

```
MatrixXd InterceptDM::compute_design_matrix (
    const Coordinates & coords,
    const MatrixXd & X ) const [override], [virtual]
```

Compute the design matrix with extra covariates besides the coordinates.

Parameters

<i>coords</i>	Matrix of the coordinates of the locations
<i>X</i>	Matrix of the additional covariates for the locations

Returns

Design matrix

Implements [design_matrix::DesignMatrix](#).

The documentation for this class was generated from the following files:


- [DesignMatrix.hpp](#)
- [DesignMatrix.cpp](#)

5.7 distances::Distance Class Reference

Abstract class for the computation of the distance between data locations.

```
#include <Distance.hpp>
```

Inheritance diagram for distances::Distance:



Public Member Functions

- virtual double `compute_distance` (const `Vec` &P1, const `Vec` &P2) const =0
Compute the distance between two locations.
- std::shared_ptr< const MatrixXd > `create_distance_matrix` (const `Coordinates` &coordinates, unsigned int N) const
Compute the distance matrix among a set of locations.
- std::vector< double > `create_distance_vector` (const `Coordinates` &coordinates, const `Vec` &new_coord) const
Compute the vector of distances between a point and a set of locations.
- virtual `~Distance` ()=default
Destructor.

5.7.1 Detailed Description

Abstract class for the computation of the distance between data locations.

5.7.2 Member Function Documentation

5.7.2.1 compute_distance()

```
virtual double distances::Distance::compute_distance (
    const Vec & P1,
    const Vec & P2 ) const [pure virtual]
```

Compute the distance between two locations.

Parameters

<i>P1</i>	Vector of coordinates for the first location
<i>P2</i>	Vector of coordinates for the second location

Returns

Points' distance

Implemented in [distances::GeoDist](#), and [distances::EuclDist](#).

5.7.2.2 create_distance_matrix()

```
std::shared_ptr< const MatrixXd > Distance::create_distance_matrix (
    const Coordinates & coordinates,
    unsigned int N ) const
```

Compute the distance matrix among a set of locations.

Parameters

<i>coordinates</i>	Matrix of the coordinates of the locations
<i>N</i>	Number of locations

Returns

Matrix of distances

5.7.2.3 create_distance_vector()

```
std::vector< double > Distance::create_distance_vector (
    const Coordinates & coordinates,
    const Vec & new_coord ) const
```

Compute the vector of distances between a point and a set of locations.

Parameters

<i>coordinates</i>	Matrix of the coordinates of the locations
<i>new_coord</i>	Vector of coordinates of the new location

Returns

Vector of distances

The documentation for this class was generated from the following files:


- [Distance.hpp](#)
- [Distance.cpp](#)

5.8 distances::EuclDist Class Reference

Class for the computation of the distance between data locations when `distance=="Eucldist"`

```
#include <Distance.hpp>
```

Inheritance diagram for distances::EuclDist:



Public Member Functions

- double `compute_distance` (const `Vec` &P1, const `Vec` &P2) const override
Compute the distance between two locations.
- `~EuclDist` ()=default
Destructor.

5.8.1 Detailed Description

Class for the computation of the distance between data locations when `distance=="Eucldist"`

5.8.2 Member Function Documentation

5.8.2.1 compute_distance()

```
double EuclDist::compute_distance (
    const Vec & P1,
    const Vec & P2 ) const [override], [virtual]
```

Compute the distance between two locations.

Parameters

<i>P1</i>	Vector of coordinates for the first location
<i>P2</i>	Vector of coordinates for the second location

Returns

Points' distance

Implements `distances::Distance`.

The documentation for this class was generated from the following files:


- [Distance.hpp](#)
- [Distance.cpp](#)

5.9 distances::GeoDist Class Reference

Class for the computation of the distance between data locations when `distance=="Geodist"`

```
#include <Distance.hpp>
```

Inheritance diagram for distances::GeoDist:



Public Member Functions

- double [compute_distance](#) (const [Vec](#) &P1, const [Vec](#) &P2) const override
Compute the distance between two locations.
- [~GeoDist](#) ()=default
Destructor.

Static Private Attributes

- static double constexpr [Earth_R](#) = 6371.0
- static double constexpr [eps_dbl](#) = std::numeric_limits<double>::epsilon()

5.9.1 Detailed Description

Class for the computation of the distance between data locations when `distance=="Geodist"`

5.9.2 Member Function Documentation

5.9.2.1 compute_distance()

```
double GeoDist::compute_distance (
    const Vec & P1,
    const Vec & P2 ) const [override], [virtual]
```

Compute the distance between two locations.

Parameters

<i>P1</i>	Vector of coordinates for the first location
<i>P2</i>	Vector of coordinates for the second location

Returns

Points' distance

Implements [distances::Distance](#).

5.9.3 Member Data Documentation

5.9.3.1 Earth_R

```
double constexpr distances::GeoDist::Earth_R = 6371.0 [static], [private]
```

Earth radius

5.9.3.2 eps_dbl

```
double constexpr distances::GeoDist::eps_dbl = std::numeric_limits<double>::epsilon() [static], [private]
```

Machine epsilon

The documentation for this class was generated from the following files:


- [Distance.hpp](#)
- [Distance.cpp](#)

5.10 distances_manifold::Chol Class Reference

Class for the computation of the distance on the manifold when `manifold_metric=="Chol"`

```
#include <DistanceManifold.hpp>
```

Inheritance diagram for `distances_manifold::Chol`:



Public Member Functions

- double [compute_distance](#) (const MatrixXd &M1, const MatrixXd &M2) const override
Compute the distance between two matrices on the manifold.
- [~Chol](#) ()=default
Destructor.

5.10.1 Detailed Description

Class for the computation of the distance on the manifold when `manifold_metric=="Chol"`

Note

The data on the manifold must be correlation matrices

5.10.2 Member Function Documentation

5.10.2.1 compute_distance()

```
double Chol::compute_distance (
    const MatrixXd & M1,
    const MatrixXd & M2 ) const [override], [virtual]
```

Compute the distance between two matrices on the manifold.

Parameters

<i>M1</i>	First matrix
<i>M2</i>	Second matrix

Returns

Distance

Implements [distances_manifold::DistanceManifold](#).

The documentation for this class was generated from the following files:


- [DistanceManifold.hpp](#)
- [DistanceManifold.cpp](#)

5.11 distances_manifold::DistanceManifold Class Reference

Abstract class for the computation of the distance on the manifold.

```
#include <DistanceManifold.hpp>
```

Inheritance diagram for `distances_manifold::DistanceManifold`:



Public Member Functions

- virtual double [compute_distance](#) (const MatrixXd &M1, const MatrixXd &M2) const =0
Compute the distance between two matrices on the manifold.
- virtual [~DistanceManifold](#) ()=default
Destructor.

5.11.1 Detailed Description

Abstract class for the computation of the distance on the manifold.

5.11.2 Member Function Documentation

5.11.2.1 `compute_distance()`

```
virtual double distances_manifold::DistanceManifold::compute_distance (
    const MatrixXd & M1,
    const MatrixXd & M2 ) const [pure virtual]
```

Compute the distance between two matrices on the manifold.

Parameters

<i>M1</i>	First matrix
<i>M2</i>	Second matrix

Returns

Distance

Implemented in [distances_manifold::Chol](#), [distances_manifold::SqRoot](#), [distances_manifold::LogEuclidean](#), and [distances_manifold::Frobenius](#).

The documentation for this class was generated from the following file:


- [DistanceManifold.hpp](#)

5.12 distances_manifold::Frobenius Class Reference

Class for the computation of the distance on the manifold when `manifold_metric=="Frobenius"`

```
#include <DistanceManifold.hpp>
```

Inheritance diagram for `distances_manifold::Frobenius`:



Public Member Functions

- double [compute_distance](#) (const MatrixXd &M1, const MatrixXd &M2) const override
Compute the distance between two matrices on the manifold.
- [~Frobenius](#) ()=default
Destructor.

5.12.1 Detailed Description

Class for the computation of the distance on the manifold when `manifold_metric=="Frobenius"`

5.12.2 Member Function Documentation

5.12.2.1 compute_distance()

```
double Frobenius::compute_distance (
    const MatrixXd & M1,
    const MatrixXd & M2 ) const [override], [virtual]
```

Compute the distance between two matrices on the manifold.

Parameters

<i>M1</i>	First matrix
<i>M2</i>	Second matrix

Returns

Distance

Implements [distances_manifold::DistanceManifold](#).

The documentation for this class was generated from the following files:


- [DistanceManifold.hpp](#)
- DistanceManifold.cpp

5.13 distances_manifold::LogEuclidean Class Reference

Class for the computation of the distance on the manifold when `manifold_metric=="LogEuclidean"`

```
#include <DistanceManifold.hpp>
```

Inheritance diagram for `distances_manifold::LogEuclidean`:



Public Member Functions

- double [compute_distance](#) (const MatrixXd &M1, const MatrixXd &M2) const override
Compute the distance between two matrices on the manifold.
- [~LogEuclidean](#) ()=default
Destructor.

5.13.1 Detailed Description

Class for the computation of the distance on the manifold when `manifold_metric=="LogEuclidean"`

5.13.2 Member Function Documentation

5.13.2.1 compute_distance()

```
double LogEuclidean::compute_distance (
    const MatrixXd & M1,
    const MatrixXd & M2 ) const [override], [virtual]
```

Compute the distance between two matrices on the manifold.

Parameters

<i>M1</i>	First matrix
<i>M2</i>	Second matrix

Returns

Distance

Implements [distances_manifold::DistanceManifold](#).


The documentation for this class was generated from the following files:

- [DistanceManifold.hpp](#)
- DistanceManifold.cpp

5.14 distances_manifold::SqRoot Class Reference

Class for the computation of the distance on the manifold when `manifold_metric=="SqRoot"`

```
#include <DistanceManifold.hpp>
```

Inheritance diagram for `distances_manifold::SqRoot`:**Public Member Functions**

- double [compute_distance](#) (const MatrixXd &M1, const MatrixXd &M2) const override
Compute the distance between two matrices on the manifold.
- [~SqRoot](#) ()=default
Destructor.

5.14.1 Detailed Description

Class for the computation of the distance on the manifold when `manifold_metric=="SqRoot"`

5.14.2 Member Function Documentation

5.14.2.1 compute_distance()

```
double SqRoot::compute_distance (
    const MatrixXd & M1,
    const MatrixXd & M2 ) const [override], [virtual]
```

Compute the distance between two matrices on the manifold.

Parameters

<i>M1</i>	First matrix
<i>M2</i>	Second matrix

Returns

Distance

Implements [distances_manifold::DistanceManifold](#).

The documentation for this class was generated from the following files:


- [DistanceManifold.hpp](#)
- [DistanceManifold.cpp](#)

5.15 distances_tplane::Chol Class Reference

Class for the computation of the distance on the tangent space when `ts_metric=="Correlation"`

```
#include <DistanceTplane.hpp>
```

Inheritance diagram for `distances_tplane::Chol`:



Public Member Functions

- [~Chol](#) ()=default
Destructor.
- double [norm](#) (const MatrixXd &M1) const override
Compute the norm of a matrix on the tangent space.
- void [set_members](#) (const MatrixXd &Sigma) override
Set the members that will be used in the computation of the norms and distances, according to the metric on the tangent space.

5.15.1 Detailed Description

Class for the computation of the distance on the tangent space when `ts_metric=="Correlation"`

5.15.2 Member Function Documentation

5.15.2.1 norm()

```
double Chol::norm (
    const MatrixXd & M1 ) const [override], [virtual]
```

Compute the norm of a matrix on the tangent space.

Parameters

<i>M1</i>	Matrix
-----------	--------

Returns

Norm

Implements [distances_tplane::DistanceTplane](#).

5.15.2.2 set_members()

```
void Chol::set_members (
    const MatrixXd & Sigma ) [override], [virtual]
```

Set the members that will be used in the computation of the norms and distances, according to the metric on the tangent space.

Parameters

<i>Sigma</i>	Tangent point
--------------	---------------

Implements [distances_tplane::DistanceTplane](#).

The documentation for this class was generated from the following files:


- [DistanceTplane.hpp](#)
- [DistanceTplane.cpp](#)

5.16 distances_tplane::DistanceTplane Class Reference

Abstract class for the computation of the distance on the tangent space.

```
#include <DistanceTplane.hpp>
```

Inheritance diagram for distances_tplane::DistanceTplane:



Public Member Functions

- double [compute_distance](#) (const MatrixXd &M1, const MatrixXd &M2) const
Compute the distance between two matrices on the tangent space.
- virtual double [norm](#) (const MatrixXd &M1) const =0
Compute the norm of a matrix on the tangent space.
- virtual void [set_members](#) (const MatrixXd &Sigma)=0
Set the members that will be used in the computation of the norms and distances, according to the metric on the tangent space.
- virtual [~DistanceTplane](#) ()=default
Destructor.

5.16.1 Detailed Description

Abstract class for the computation of the distance on the tangent space.

5.16.2 Member Function Documentation

5.16.2.1 [compute_distance\(\)](#)

```
double DistanceTplane::compute_distance (
    const MatrixXd & M1,
    const MatrixXd & M2 ) const
```

Compute the distance between two matrices on the tangent space.

Parameters

<i>M1</i>	First matrix
<i>M2</i>	Second matrix

Returns

Distance

5.16.2.2 [norm\(\)](#)

```
virtual double distances_tplane::DistanceTplane::norm (
    const MatrixXd & M1 ) const [pure virtual]
```

Compute the norm of a matrix on the tangent space.

Parameters

<i>M1</i>	Matrix
-----------	--------

Returns

Norm

Implemented in [distances_tplane::Chol](#), [distances_tplane::FrobeniusScaled](#), and [distances_tplane::Frobenius](#).

5.16.2.3 set_members()

```
virtual void distances_tplane::DistanceTplane::set_members (
    const MatrixXd & Sigma ) [pure virtual]
```

Set the members that will be used in the computation of the norms and distances, according to the metric on the tangent space.

Parameters

<i>Sigma</i>	Tangent point
--------------	---------------

Implemented in [distances_tplane::Chol](#), [distances_tplane::FrobeniusScaled](#), and [distances_tplane::Frobenius](#).

The documentation for this class was generated from the following files:


- [DistanceTplane.hpp](#)
- [DistanceTplane.cpp](#)

5.17 distances_tplane::Frobenius Class Reference

Class for the computation of the distance on the tangent space when `ts_metric=="Frobenius"`

```
#include <DistanceTplane.hpp>
```

Inheritance diagram for `distances_tplane::Frobenius`:



Public Member Functions

- [~Frobenius](#) ()=default
Destructor.
- double [norm](#) (const MatrixXd &M1) const override
Compute the norm of a matrix on the tangent space.
- void [set_members](#) (const MatrixXd &Sigma) override
Set the members that will be used in the computation of the norms and distances, according to the metric on the tangent space.

5.17.1 Detailed Description

Class for the computation of the distance on the tangent space when `ts_metric=="Frobenius"`

5.17.2 Member Function Documentation

5.17.2.1 `norm()`

```
double Frobenius::norm (
    const MatrixXd & M1 ) const [override], [virtual]
```

Compute the norm of a matrix on the tangent space.

Parameters

<i>M1</i>	Matrix
-----------	--------

Returns

Norm

Implements [distances_tplane::DistanceTplane](#).

5.17.2.2 `set_members()`

```
void Frobenius::set_members (
    const MatrixXd & Sigma ) [override], [virtual]
```

Set the members that will be used in the computation of the norms and distances, according to the metric on the tangent space.

Parameters

<i>Sigma</i>	Tangent point
--------------	---------------

Implements [distances_tplane::DistanceTplane](#).

The documentation for this class was generated from the following files:


- [DistanceTplane.hpp](#)
- [DistanceTplane.cpp](#)

5.18 distances_tplane::FrobeniusScaled Class Reference

Class for the computation of the distance on the tangent space when `ts_metric=="FrobeniusScaled"`

```
#include <DistanceTplane.hpp>
```

Inheritance diagram for `distances_tplane::FrobeniusScaled`:



Public Member Functions

- [~FrobeniusScaled](#) ()=default
Destructor.
- double [norm](#) (const MatrixXd &M1) const override
Compute the norm of a matrix on the tangent space.
- void [set_members](#) (const MatrixXd &Sigma) override
Set the members that will be used in the computation of the norms and distances, according to the metric on the tangent space.

Private Attributes

- MatrixXd [_SigmaInv](#)
- unsigned int [_p](#)

5.18.1 Detailed Description

Class for the computation of the distance on the tangent space when `ts_metric=="FrobeniusScaled"`

5.18.2 Member Function Documentation

5.18.2.1 norm()

```
double FrobeniusScaled::norm (
    const MatrixXd & M1 ) const [override], [virtual]
```

Compute the norm of a matrix on the tangent space.

Parameters

<i>M1</i>	Matrix
-----------	--------

Returns

Norm

Implements [distances_tplane::DistanceTplane](#).

5.18.2.2 set_members()

```
void FrobeniusScaled::set_members (
    const MatrixXd & Sigma ) [override], [virtual]
```

Set the members that will be used in the computation of the norms and distances, according to the metric on the tangent space.

Parameters

<i>Sigma</i>	Tangent point
--------------	---------------

Implements [distances_tplane::DistanceTplane](#).

5.18.3 Member Data Documentation

5.18.3.1 _SigmaInv

```
MatrixXd distances_tplane::FrobeniusScaled::_SigmaInv [private]
```

Inverse of the tangent point Sigma

5.18.3.2 _p

```
unsigned int distances_tplane::FrobeniusScaled::_p [private]
```

Dimension of the matrices on the tangent space

The documentation for this class was generated from the following files:

- [DistanceTplane.hpp](#)
- [DistanceTplane.cpp](#)

5.19 generic_factory::Factory< AbstractProduct, Identifier, Builder > Class Template Reference

A generic factory.

```
#include <Factory.hpp>
```

Public Types

- using [AbstractProduct_type](#) = AbstractProduct
The container for the rules.
- using [Identifier_type](#) = Identifier
The identifier.
- using [Builder_type](#) = Builder
The builder type.

Public Member Functions

- std::unique_ptr< AbstractProduct > [create](#) (Identifier const &name) const
Get the rule with given name.
- void [add](#) (Identifier const &, [Builder_type](#) const &)
Register the given rule.
- std::vector< Identifier > [registered](#) () const
Returns a list of registered rules.
- void [unregister](#) (Identifier const &name)
Unregister a rule.
- [~Factory](#) ()=default
Destructor.

Static Public Member Functions

- static [Factory](#) & [Instance](#) ()
Method to access the only instance of the factory. We use Meyer's trick to instantiate the factory.

Private Types

- typedef std::map< Identifier, [Builder_type](#) > [Container_type](#)
Type of the object used to store the object factory.

Private Member Functions

- [Factory](#) ()=default
Constructor made private since it is a Singleton.
- [Factory](#) ([Factory](#) const &)=delete
Copy constructor deleted since it is a Singleton.
- [Factory](#) & [operator=](#) ([Factory](#) const &)=delete
Assignment operator deleted since it is a Singleton.

Private Attributes

- [Container_type_storage](#)

It contains the actual object factory.

5.19.1 Detailed Description

```
template<typename AbstractProduct, typename Identifier, typename Builder = std::function<std::unique_ptr<AbstractProduct>
()>>
class generic_factory::Factory< AbstractProduct, Identifier, Builder >
```

A generic factory.

It is implemented as a Singleton. The compulsory way to access a method is [Factory::Instance\(\)](#).method(). Typically to access the factory one does

```
auto& myFactory = Factory<A,I,B>::Instance();
myFactory.add(...)
```

5.19.2 Member Function Documentation

5.19.2.1 create()

```
template<typename AbstractProduct , typename Identifier , typename Builder >
std::unique_ptr< AbstractProduct > generic_factory::Factory< AbstractProduct, Identifier,
Builder >::create (
    Identifier const & name ) const
```

Get the rule with given name.

The pointer is null if no rule is present.

The documentation for this class was generated from the following file:

- [Factory.hpp](#)

5.20 generic_factory::Proxy< Factory, ConcreteProduct > Class Template Reference

```
#include <Proxy.hpp>
```


Public Types

- typedef [Factory::AbstractProduct_type](#) AbstractProduct_type
The container for the rules.
- typedef [Factory::Identifier_type](#) Identifier_type
The identifier.
- typedef [Factory::Builder_type](#) Builder_type
The builder type.
- typedef [Factory](#) Factory_type
The factory type.

Public Member Functions

- [Proxy](#) (Identifier_type const &)
The constructor does the registration.

Static Public Member Functions

- static std::unique_ptr< [AbstractProduct_type](#) > Build ()
The builder.

Private Member Functions

- [Proxy](#) (Proxy const &)=delete
Copy onstructor deleted since it is a Singleton.
- [Proxy](#) & operator= (Proxy const &)=delete
Assignment operator deleted since it is a Singleton.

5.20.1 Detailed Description

```
template<typename Factory, typename ConcreteProduct>
class generic_factory::Proxy< Factory, ConcreteProduct >
```

A simple proxy for registering into a factory.

It provides the builder as static method and the automatic registration mechanism.

Parameters

Factory	The type of the factory.
ConcreteProduct	Is the derived (concrete) type to be registered in the factory

Note

I have to use the default builder provided by the factory. No check is made to verify it

The documentation for this class was generated from the following file:


- [Proxy.hpp](#)

5.21 map_functions::expMapChol Class Reference

Class for the computation of the exponential map when `manifold_metric=="Correlation"`

```
#include <MapFunctions.hpp>
```

Inheritance diagram for `map_functions::expMapChol`:



Public Member Functions

- [~expMapChol](#) ()=default
Destructor.
- `MatrixXd` [map2manifold](#) (const `MatrixXd` &M) const override
Map a tangent space matrix to the manifold.
- void [set_members](#) (const `MatrixXd` &Sigma) override
Set class members.
- void [set_tolerance](#) (double tolerance_map_cor) override
Set tolerance.

Private Attributes

- double [_tolerance_map_cor](#)
- `MatrixXd` [_Sigma](#)

5.21.1 Detailed Description

Class for the computation of the exponential map when `manifold_metric=="Correlation"`

5.21.2 Member Function Documentation

5.21.2.1 map2manifold()

```
MatrixXd expMapChol::map2manifold (
    const MatrixXd & M ) const [override], [virtual]
```

Map a tangent space matrix to the manifold.

Parameters

<i>M</i>	Tangent space matrix to map
----------	-----------------------------

Returns

Manifold matrix identifying the mapped data

Implements [map_functions::exponentialMap](#).

5.21.2.2 set_members()

```
void expMapChol::set_members (
    const MatrixXd & Sigma ) [override], [virtual]
```

Set class members.

Parameters

<i>Sigma</i>	Tangent point
--------------	---------------

Implements [map_functions::exponentialMap](#).

5.21.2.3 set_tolerance()

```
void expMapChol::set_tolerance (
    double tolerance_map_cor ) [override], [virtual]
```

Set tolerance.

Parameters

<i>tolerance_map_cor</i>	Tolerance
--------------------------	-----------

Implements [map_functions::exponentialMap](#).

5.21.3 Member Data Documentation

5.21.3.1 _tolerance_map_cor

```
double map_functions::expMapChol::_tolerance_map_cor [private]
```

Tolerance on the norm of the columns to avoid Nan

5.21.3.2 `_Sigma`

`MatrixXd map_functions::expMapChol::_Sigma [private]`

Tangent point `Sigma`

The documentation for this class was generated from the following files:


- [MapFunctions.hpp](#)
- [MapFunctions.cpp](#)

5.22 `map_functions::expMapFrob` Class Reference

Class for the computation of the exponential map when `manifold_metric=="Frobenius"`

```
#include <MapFunctions.hpp>
```

Inheritance diagram for `map_functions::expMapFrob`:



Public Member Functions

- `~expMapFrob()`=default
Destructor.
- `MatrixXd map2manifold (const MatrixXd &M) const` override
Map a tangent space matrix to the manifold.
- `void set_members (const MatrixXd &Sigma)` override
Set class members.
- `void set_tolerance (double tolerance_map_cor)` override
Set tolerance.

Private Attributes

- `MatrixXd _sqrtSigma`
- `MatrixXd _sqrtSigmaInv`

5.22.1 Detailed Description

Class for the computation of the exponential map when `manifold_metric=="Frobenius"`

5.22.2 Member Function Documentation

5.22.2.1 `map2manifold()`

```
MatrixXd expMapFrob::map2manifold (
    const MatrixXd & M ) const [override], [virtual]
```

Map a tangent space matrix to the manifold.

Parameters

<i>M</i>	Tangent space matrix to map
----------	-----------------------------

Returns

Manifold matrix identifying the mapped data

Implements [map_functions::exponentialMap](#).

5.22.2.2 set_members()

```
void expMapFrob::set_members (
    const MatrixXd & Sigma ) [override], [virtual]
```

Set class members.

Parameters

<i>Sigma</i>	Tangent point
--------------	---------------

Implements [map_functions::exponentialMap](#).

5.22.2.3 set_tolerance()

```
void expMapFrob::set_tolerance (
    double tolerance_map_cor ) [override], [virtual]
```

Set tolerance.

Parameters

<i>tolerance_map_cor</i>	Tolerance
--------------------------	-----------

Implements [map_functions::exponentialMap](#).

5.22.3 Member Data Documentation

5.22.3.1 _sqrtSigma

```
MatrixXd map_functions::expMapFrob::_sqrtSigma [private]
```

Square root of the tangent point *Sigma*

5.22.3.2 `_sqrtSigmaInv`

`MatrixXd map_functions::expMapFrob::_sqrtSigmaInv` [private]

Inverse of the square root of the tangent point Sigma

The documentation for this class was generated from the following files:


- [MapFunctions.hpp](#)
- [MapFunctions.cpp](#)

5.23 `map_functions::expMapLogEucl` Class Reference

Class for the computation of the exponential map when `manifold_metric=="LogEuclidean"`

`#include <MapFunctions.hpp>`

Inheritance diagram for `map_functions::expMapLogEucl`:



Public Member Functions

- [~expMapLogEucl](#) ()=default
Destructor.
- `MatrixXd` [map2manifold](#) (const `MatrixXd` &M) const override
Map a tangent space matrix to the manifold.
- void [set_members](#) (const `MatrixXd` &Sigma) override
Set class members.
- void [set_tolerance](#) (double tolerance_map_cor) override
Set tolerance.

Private Attributes

- `MatrixXd` [_Sigma](#)

5.23.1 Detailed Description

Class for the computation of the exponential map when `manifold_metric=="LogEuclidean"`

5.23.2 Member Function Documentation

5.23.2.1 `map2manifold()`

```

MatrixXd expMapLogEucl::map2manifold (
    const MatrixXd & M ) const [override], [virtual]
  
```

Map a tangent space matrix to the manifold.

Parameters

<i>M</i>	Tangent space matrix to map
----------	-----------------------------

Returns

Manifold matrix identifying the mapped data

Implements [map_functions::exponentialMap](#).

5.23.2.2 set_members()

```
void expMapLogEucl::set_members (
    const MatrixXd & Sigma ) [override], [virtual]
```

Set class members.

Parameters

<i>Sigma</i>	Tangent point
--------------	---------------

Implements [map_functions::exponentialMap](#).

5.23.2.3 set_tolerance()

```
void expMapLogEucl::set_tolerance (
    double tolerance_map_cor ) [override], [virtual]
```

Set tolerance.

Parameters

<i>tolerance_map_cor</i>	Tolerance
--------------------------	-----------

Implements [map_functions::exponentialMap](#).

5.23.3 Member Data Documentation

5.23.3.1 _Sigma

```
MatrixXd map_functions::expMapLogEucl::_Sigma [private]
```

Tangent point Σ

The documentation for this class was generated from the following files:


- [MapFunctions.hpp](#)
- [MapFunctions.cpp](#)

5.24 map_functions::expMapSqRoot Class Reference

Class for the computation of the exponential map when `manifold_metric=="SqRoot"`

```
#include <MapFunctions.hpp>
```

Inheritance diagram for `map_functions::expMapSqRoot`:



Public Member Functions

- [~expMapSqRoot\(\)](#)=default
Destructor.
- `MatrixXd` [map2manifold](#) (const `MatrixXd` &M) const override
Map a tangent space matrix to the manifold.
- void [set_members](#) (const `MatrixXd` & Σ) override
Set class members.
- void [set_tolerance](#) (double tolerance_map_cor) override
Set tolerance.

Private Attributes

- `MatrixXd` [_Sigma](#)

5.24.1 Detailed Description

Class for the computation of the exponential map when `manifold_metric=="SqRoot"`

5.24.2 Member Function Documentation

5.24.2.1 map2manifold()

```
MatrixXd expMapSqRoot::map2manifold (
    const MatrixXd & M ) const [override], [virtual]
```

Map a tangent space matrix to the manifold.

Parameters

<i>M</i>	Tangent space matrix to map
----------	-----------------------------

Returns

Manifold matrix identifying the mapped data

Implements [map_functions::exponentialMap](#).

5.24.2.2 set_members()

```
void expMapSqRoot::set_members (
    const MatrixXd & Sigma ) [override], [virtual]
```

Set class members.

Parameters

<i>Sigma</i>	Tangent point
--------------	---------------

Implements [map_functions::exponentialMap](#).

5.24.2.3 set_tolerance()

```
void expMapSqRoot::set_tolerance (
    double tolerance_map_cor ) [override], [virtual]
```

Set tolerance.

Parameters

<i>tolerance_map_cor</i>	Tolerance
--------------------------	-----------

Implements [map_functions::exponentialMap](#).

5.24.3 Member Data Documentation

5.24.3.1 _Sigma

```
MatrixXd map_functions::expMapSqRoot::_Sigma [private]
```

Tangent point Σ

The documentation for this class was generated from the following files:


- [MapFunctions.hpp](#)
- [MapFunctions.cpp](#)

5.25 map_functions::exponentialMap Class Reference

Abstract class for the computation of the exponential map.

```
#include <MapFunctions.hpp>
```

Inheritance diagram for map_functions::exponentialMap:



Public Member Functions

- virtual [~exponentialMap](#) ()=default
Destructor.
- virtual MatrixXd [map2manifold](#) (const MatrixXd &M) const =0
Map a tangent space matrix to the manifold.
- virtual void [set_members](#) (const MatrixXd &Sigma)=0
Set class members.
- virtual void [set_tolerance](#) (double tolerance_map_cor)=0
Set tolerance.

5.25.1 Detailed Description

Abstract class for the computation of the exponential map.

5.25.2 Member Function Documentation

5.25.2.1 map2manifold()

```
virtual MatrixXd map_functions::exponentialMap::map2manifold (
    const MatrixXd & M ) const [pure virtual]
```

Map a tangent space matrix to the manifold.

Parameters

<i>M</i>	Tangent space matrix to map
----------	-----------------------------

Returns

Manifold matrix identifying the mapped data

Implemented in [map_functions::expMapChol](#), [map_functions::expMapSqRoot](#), [map_functions::expMapLogEucl](#), and [map_functions::expMapFrob](#).

5.25.2.2 set_members()

```
virtual void map_functions::exponentialMap::set_members (
    const MatrixXd & Sigma ) [pure virtual]
```

Set class members.

Parameters

<i>Sigma</i>	Tangent point
--------------	---------------

Implemented in [map_functions::expMapChol](#), [map_functions::expMapSqRoot](#), [map_functions::expMapLogEucl](#), and [map_functions::expMapFrob](#).

5.25.2.3 set_tolerance()

```
virtual void map_functions::exponentialMap::set_tolerance (
    double tolerance_map_cor ) [pure virtual]
```

Set tolerance.

Parameters

<i>tolerance_map_cor</i>	Tolerance
--------------------------	-----------

Implemented in [map_functions::expMapChol](#), [map_functions::expMapSqRoot](#), [map_functions::expMapLogEucl](#), and [map_functions::expMapFrob](#).

The documentation for this class was generated from the following file:


- [MapFunctions.hpp](#)

5.26 map_functions::logarithmicMap Class Reference

Abstract class for the computation of the logarithmic map.

```
#include <MapFunctions.hpp>
```

Inheritance diagram for map_functions::logarithmicMap:



Public Member Functions

- virtual `~logarithmicMap()`=default
Destructor.
- virtual `MatrixXd map2tplane` (const `MatrixXd &M`) const =0
Map a manifold matrix to the tangent space.
- virtual void `set_members` (const `MatrixXd &Sigma`)=0
Set class members.
- virtual void `set_tolerance` (double `tolerance_map_cor`)=0
Set tolerance.

5.26.1 Detailed Description

Abstract class for the computation of the logarithmic map.

5.26.2 Member Function Documentation

5.26.2.1 map2tplane()

```
virtual MatrixXd map_functions::logarithmicMap::map2tplane (
    const MatrixXd & M ) const [pure virtual]
```

Map a manifold matrix to the tangent space.

Parameters

<i>M</i>	Manifold matrix to map
----------	------------------------

Returns

Tangent space matrix identifying the mapped data

Implemented in [map_functions::logMapChol](#), [map_functions::logMapSqRoot](#), [map_functions::logMapLogEucl](#), and [map_functions::logMapFrob](#).

5.26.2.2 set_members()

```
virtual void map_functions::logarithmicMap::set_members (
    const MatrixXd & Sigma ) [pure virtual]
```

Set class members.

Parameters

<i>Sigma</i>	Tangent point
--------------	---------------

Implemented in [map_functions::logMapChol](#), [map_functions::logMapSqRoot](#), [map_functions::logMapLogEucl](#), and [map_functions::logMapFrob](#).

5.26.2.3 set_tolerance()

```
virtual void map_functions::logarithmicMap::set_tolerance (
    double tolerance_map_cor ) [pure virtual]
```

Set tolerance.

Parameters

<i>tolerance_map_cor</i>	Tolerance
--------------------------	-----------

Implemented in [map_functions::logMapChol](#), [map_functions::logMapSqRoot](#), [map_functions::logMapLogEucl](#), and [map_functions::logMapFrob](#).

The documentation for this class was generated from the following file:


- [MapFunctions.hpp](#)

5.27 map_functions::logMapChol Class Reference

Class for the computation of the logarithmic map when `manifold_metric=="Correlation"`

```
#include <MapFunctions.hpp>
```

Inheritance diagram for `map_functions::logMapChol`:



Public Member Functions

- [~logMapChol](#) ()=default
Destructor.
- `MatrixXd` [map2tplane](#) (const `MatrixXd` &M) const override
Map a manifold matrix to the tangent space.
- void [set_members](#) (const `MatrixXd` &Sigma) override
Set class members.
- void [set_tolerance](#) (double tolerance_map_cor) override
Set tolerance.

Private Member Functions

- `Vec` [proj2tspace](#) (const `Vec` &, const `Vec` &) const
Project a matrix in $Chol(p)$ to the tangent space.

Private Attributes

- `MatrixXd` [_Sigma](#)
- double [_tolerance_map_cor](#)

5.27.1 Detailed Description

Class for the computation of the logarithmic map when `manifold_metric=="Correlation"`

5.27.2 Member Function Documentation

5.27.2.1 `map2tplane()`

```
MatrixXd logMapChol::map2tplane (
    const MatrixXd & M ) const    [override], [virtual]
```

Map a manifold matrix to the tangent space.

Parameters

<i>M</i>	Manifold matrix to map
----------	------------------------

Returns

Tangent space matrix identifying the mapped data

Implements [map_functions::logarithmicMap](#).

5.27.2.2 set_members()

```
void logMapChol::set_members (
    const MatrixXd & Sigma ) [override], [virtual]
```

Set class members.

Parameters

<i>Sigma</i>	Tangent point
--------------	---------------

Implements [map_functions::logarithmicMap](#).

5.27.2.3 set_tolerance()

```
void logMapChol::set_tolerance (
    double tolerance_map_cor ) [override], [virtual]
```

Set tolerance.

Parameters

<i>tolerance_map_cor</i>	Tolerance
--------------------------	-----------

Implements [map_functions::logarithmicMap](#).

5.27.3 Member Data Documentation

5.27.3.1 _Sigma

```
MatrixXd map_functions::logMapChol::_Sigma [private]
```

Tangent point Sigma

5.27.3.2 _tolerance_map_cor

```
double map_functions::logMapChol::_tolerance_map_cor [private]
```

Tolerance on the norm of the columns to avoid Nan

The documentation for this class was generated from the following files:


- [MapFunctions.hpp](#)
- [MapFunctions.cpp](#)

5.28 map_functions::logMapFrob Class Reference

Class for the computation of the logarithmic map when `manifold_metric=="Frobenius"`

```
#include <MapFunctions.hpp>
```

Inheritance diagram for `map_functions::logMapFrob`:



Public Member Functions

- `~logMapFrob()`=default
Destructor.
- `MatrixXd map2tplane` (const `MatrixXd &M`) const override
Map a manifold matrix to the tangent space.
- void `set_members` (const `MatrixXd &Sigma`) override
Set class members.
- void `set_tolerance` (double `tolerance_map_cor`) override
Set tolerance.

Private Attributes

- `MatrixXd _sqrtSigma`
- `MatrixXd _sqrtSigmaInv`

5.28.1 Detailed Description

Class for the computation of the logarithmic map when `manifold_metric=="Frobenius"`

5.28.2 Member Function Documentation

5.28.2.1 map2tplane()

```
MatrixXd logMapFrob::map2tplane (
    const MatrixXd & M ) const [override], [virtual]
```

Map a manifold matrix to the tangent space.

Parameters

<i>M</i>	Manifold matrix to map
----------	------------------------

Returns

Tangent space matrix identifying the mapped data

Implements [map_functions::logarithmicMap](#).

5.28.2.2 set_members()

```
void logMapFrob::set_members (
    const MatrixXd & Sigma ) [override], [virtual]
```

Set class members.

Parameters

<i>Sigma</i>	Tangent point
--------------	---------------

Implements [map_functions::logarithmicMap](#).

5.28.2.3 set_tolerance()

```
void logMapFrob::set_tolerance (
    double tolerance_map_cor ) [override], [virtual]
```

Set tolerance.

Parameters

<i>tolerance_map_cor</i>	Tolerance
--------------------------	-----------

Implements [map_functions::logarithmicMap](#).

5.28.3 Member Data Documentation

5.28.3.1 _sqrtSigma

```
MatrixXd map_functions::logMapFrob::_sqrtSigma [private]
```

Square root of the tangent point *Sigma*

5.28.3.2 `_sqrtSigmaInv`

`MatrixXd map_functions::logMapFrob::_sqrtSigmaInv [private]`

Inverse of the square root of the tangent point Sigma

The documentation for this class was generated from the following files:


- [MapFunctions.hpp](#)
- [MapFunctions.cpp](#)

5.29 `map_functions::logMapLogEucl` Class Reference

Class for the computation of the logarithmic map when `manifold_metric=="LogEuclidean"`

`#include <MapFunctions.hpp>`

Inheritance diagram for `map_functions::logMapLogEucl`:



Public Member Functions

- `~logMapLogEucl()`=default
Destructor.
- `MatrixXd map2tplane (const MatrixXd &M) const` override
Map a manifold matrix to the tangent space.
- `void set_members (const MatrixXd &Sigma)` override
Set class members.
- `void set_tolerance (double tolerance_map_cor)` override
Set tolerance.

Private Attributes

- `MatrixXd _Sigma`

5.29.1 Detailed Description

Class for the computation of the logarithmic map when `manifold_metric=="LogEuclidean"`

5.29.2 Member Function Documentation

5.29.2.1 `map2tplane()`

`MatrixXd logMapLogEucl::map2tplane (`
 `const MatrixXd & M) const [override], [virtual]`

Map a manifold matrix to the tangent space.

Parameters

<i>M</i>	Manifold matrix to map
----------	------------------------

Returns

Tangent space matrix identifying the mapped data

Implements [map_functions::logarithmicMap](#).

5.29.2.2 set_members()

```
void logMapLogEucl::set_members (
    const MatrixXd & Sigma ) [override], [virtual]
```

Set class members.

Parameters

<i>Sigma</i>	Tangent point
--------------	---------------

Implements [map_functions::logarithmicMap](#).

5.29.2.3 set_tolerance()

```
void logMapLogEucl::set_tolerance (
    double tolerance_map_cor ) [override], [virtual]
```

Set tolerance.

Parameters

<i>tolerance_map_cor</i>	Tolerance
--------------------------	-----------

Implements [map_functions::logarithmicMap](#).

5.29.3 Member Data Documentation

5.29.3.1 `_Sigma`

`MatrixXd map_functions::logMapLogEucl::_Sigma [private]`

Tangent point `Sigma`

The documentation for this class was generated from the following files:


- [MapFunctions.hpp](#)
- [MapFunctions.cpp](#)

5.30 `map_functions::logMapSqRoot` Class Reference

Class for the computation of the logarithmic map when `manifold_metric=="SqRoot "`

`#include <MapFunctions.hpp>`

Inheritance diagram for `map_functions::logMapSqRoot`:



Public Member Functions

- [~logMapSqRoot\(\)](#)=default
Destructor.
- `MatrixXd` [map2tplane](#) (const `MatrixXd` &M) const override
Map a manifold matrix to the tangent space.
- void [set_members](#) (const `MatrixXd` &Sigma) override
Set class members.
- void [set_tolerance](#) (double tolerance_map_cor) override
Set tolerance.

Private Attributes

- `MatrixXd` [_Sigma](#)

5.30.1 Detailed Description

Class for the computation of the logarithmic map when `manifold_metric=="SqRoot "`

5.30.2 Member Function Documentation

5.30.2.1 `map2tplane()`

```

MatrixXd logMapSqRoot::map2tplane (
    const MatrixXd & M ) const [override], [virtual]
  
```

Map a manifold matrix to the tangent space.

Parameters

<i>M</i>	Manifold matrix to map
----------	------------------------

Returns

Tangent space matrix identifying the mapped data

Implements [map_functions::logarithmicMap](#).

5.30.2.2 set_members()

```
void logMapSqRoot::set_members (
    const MatrixXd & Sigma ) [override], [virtual]
```

Set class members.

Parameters

<i>Sigma</i>	Tangent point
--------------	---------------

Implements [map_functions::logarithmicMap](#).

5.30.2.3 set_tolerance()

```
void logMapSqRoot::set_tolerance (
    double tolerance_map_cor ) [override], [virtual]
```

Set tolerance.

Parameters

<i>tolerance_map_cor</i>	Tolerance
--------------------------	-----------

Implements [map_functions::logarithmicMap](#).

5.30.3 Member Data Documentation

5.30.3.1 `_Sigma`

`MatrixXd map_functions::logMapSqRoot::_Sigma` [private]

Tangent point `Sigma`

The documentation for this class was generated from the following files:

- [MapFunctions.hpp](#)
- [MapFunctions.cpp](#)

5.31 `model_fit::Model` Class Reference

Class to compute and store the linear model on the tangent space.

```
#include <Model.hpp>
```

Public Member Functions

- [Model](#) (const std::shared_ptr< const MatrixXd > data_tspace, const std::shared_ptr< const MatrixXd > design_matrix_model, unsigned int p, const std::string &distance_Manifold_name)
Constructor.
- [Model](#) (const std::shared_ptr< const MatrixXd > data_tspace, const std::shared_ptr< const MatrixXd > design_matrix_model, const std::shared_ptr< const MatrixXd > design_matrix_tot, unsigned int p, const std::string &distance_Manifold_name)
Constructor.
- void [update_model](#) (const MatrixXd &gamma_matrix)
Update _beta_matrix, _fitted_values and _residuals according to the new covariogram matrix.
- MatrixXd [get_beta](#) () const
Return _beta_matrix
- MatrixXd [get_residuals](#) () const
Return _residuals
- MatrixXd [get_fitted_values](#) () const
Return _fitted_values

Private Attributes

- const std::shared_ptr< const MatrixXd > [_data_tspace](#)
- const std::shared_ptr< const MatrixXd > [_design_matrix_model](#)
- const std::shared_ptr< const MatrixXd > [_design_matrix_tot](#)
- const std::string [_distance_Manifold_name](#)
- const unsigned int [_N](#)
- const unsigned int [_p](#)
- const unsigned int [_num_cov](#)
- const unsigned int [_num_coeff](#)
- MatrixXd [_beta_matrix](#)
- MatrixXd [_fitted_values](#)
- MatrixXd [_residuals](#)

5.31.1 Detailed Description

Class to compute and store the linear model on the tangent space.

5.31.2 Member Function Documentation

5.31.2.1 update_model()

```
void Model::update_model (
    const MatrixXd & gamma_matrix )
```

Update `_beta_matrix`, `_fitted_values` and `_residuals` according to the new covariogram matrix.

Parameters

<i>gamma_matrix</i>	Covariogram matrix
---------------------	--------------------

5.31.3 Member Data Documentation

5.31.3.1 _data_tspace

```
const std::shared_ptr<const MatrixXd> model_fit::Model::_data_tspace [private]
```

BigMatrix of the data on the tangent space

5.31.3.2 _design_matrix_model

```
const std::shared_ptr<const MatrixXd> model_fit::Model::_design_matrix_model [private]
```

Design matrix for the data in the cell (used to compute the beta)

5.31.3.3 _design_matrix_tot

```
const std::shared_ptr<const MatrixXd> model_fit::Model::_design_matrix_tot [private]
```

Design matrix for all the data in the domain (used to compute the residuals)

5.31.3.4 _distance_Manifold_name

```
const std::string model_fit::Model::_distance_Manifold_name [private]
```

Name of the metric on the manifold

5.31.3.5 _N

```
const unsigned int model_fit::Model::_N [private]
```

Number of stations in the cell

5.31.3.6 _p

```
const unsigned int model_fit::Model::_p [private]
```

Dimension of the matrices on the manifold

5.31.3.7 _num_cov

```
const unsigned int model_fit::Model::_num_cov [private]
```

Number of covariates in the model

5.31.3.8 _num_coeff

```
const unsigned int model_fit::Model::_num_coeff [private]
```

Number of significant entries in a symmetric ($p * p$) matrix. $_num_coeff = \frac{p*(p+1)}{2}$

5.31.3.9 _beta_matrix

```
MatrixXd model_fit::Model::_beta_matrix [private]
```

($_num_cov * _num_coeff$) matrix where the i^{th} row contains the upper triangular part of $\beta_{..i}$, the i^{th} coefficient of the tangent space linear model

5.31.3.10 _fitted_values

```
MatrixXd model_fit::Model::_fitted_values [private]
```

($N_tot * _num_coeff$) matrix where the i^{th} row contains the upper triangular part of the matrix fitted in the i^{th} location on the tangent space by the linear model. $_fitted_values = (*_design_matrix_tot) * _beta_matrix$

5.31.3.11 _residuals

```
MatrixXd model_fit::Model::_residuals [private]
```

($N_tot * _num_coeff$) matrix where the i^{th} row contains the upper triangular part of the residual matrix in the i^{th} location. $_residuals = (*_data_tspace) - _fitted_values$

The documentation for this class was generated from the following files:

- [Model.hpp](#)
- [Model.cpp](#)

5.32 variogram_evaluation::EmpiricalVariogram Class Reference

Class for computation and storage of the empirical variogram.

```
#include <EmpiricalVariogram.hpp>
```

Public Member Functions

- [EmpiricalVariogram](#) (const std::shared_ptr< const MatrixXd >, unsigned int, const [Coordinates](#) &, const [distances::Distance](#) &)
Constructor.
- [EmpiricalVariogram](#) (const std::shared_ptr< const MatrixXd >, unsigned int, unsigned int, const [Vec](#) &, double)
Constructor.
- void [update_emp_vario](#) (const std::vector< MatrixXd > &res, const [distances_tplane::DistanceTplane](#) &distanceTplane)
Update _emp_vario_values, _hvec and _N_hvec according to the new residuals $\Delta(s_i)$ $i = 1, \dots, N$.
- std::vector< double > [get_emp_vario_values](#) () const
Return _emp_vario_values
- std::vector< unsigned int > [get_N_hvec](#) () const
Return _N_hvec
- std::vector< double > [get_hvec](#) () const
Return _hvec
- unsigned int [get_card_h](#) () const
Return _card_h
- unsigned int [get_N](#) () const
Return _N
- double [get_hmax](#) () const
Return _hmax

Private Member Functions

- void [compute_hmax](#) (const [Coordinates](#) &, const [distances::Distance](#) &)
Compute the maximum distance to be considered.

Private Attributes

- const unsigned int [_n_h](#)
- const unsigned int [_N](#)
- const std::shared_ptr< const MatrixXd > [_distanceMatrix](#)
- std::vector< double > [_emp_vario_values](#)
- std::vector< double > [_hvec](#)
- std::vector< unsigned int > [_N_hvec](#)
- unsigned int [_card_h](#)
- [Vec](#) [_d](#)
- double [_hmax](#)
- [Vec](#) [_weights](#)

5.32.1 Detailed Description

Class for computation and storage of the empirical variogram.

5.32.2 Member Function Documentation

5.32.2.1 update_emp_vario()

```
void EmpiricalVariogram::update_emp_vario (
    const std::vector< MatrixXd > & res,
    const distances_tplane::DistanceTplane & distanceTplane )
```

Update `_emp_vario_values`, `_hvec` and `_N_hvec` according to the new residuals $\Delta(s_i) \ i = 1, \dots, N$.

`_emp_vario_values` are estimated through the method of moments:

$$\hat{\gamma}(h) = \frac{\sum_{N(h)} w(s_i) w(s_j) \|\Delta(s_i) - \Delta(s_j)\|^2}{2 \sum_{N(h)} w(s_i) w(s_j)}$$

where $N(h) = \{(s_i, s_j \in D) : h - \Delta h \leq \|s_i - s_j\| \leq h + \Delta h\}$

Parameters

<i>res</i>	Vector of the N residual matrices
<i>distanceTplane</i>	Distance on the tangent space

5.32.3 Member Data Documentation

5.32.3.1 _n_h

```
const unsigned int variogram_evaluation::EmpiricalVariogram::_n_h [private]
```

Number of bins

5.32.3.2 _N

```
const unsigned int variogram_evaluation::EmpiricalVariogram::_N [private]
```

Number of data points used to compute the empirical variogram

5.32.3.3 _distanceMatrix

```
const std::shared_ptr<const MatrixXd> variogram_evaluation::EmpiricalVariogram::_distanceMatrix [private]
```

Matrix of distances among the N locations

5.32.3.4 _emp_vario_values

```
std::vector<double> variogram_evaluation::EmpiricalVariogram::_emp_vario_values [private]
```

Vector storing the variogram estimates. $_emp_vario_values[i] = \hat{\gamma}(_hvec[i])$

5.32.3.5 _hvec

```
std::vector<double> variogram_evaluation::EmpiricalVariogram::_hvec [private]
```

Vector storing the distances at which the variogram is estimated

5.32.3.6 _N_hvec

```
std::vector<unsigned int> variogram_evaluation::EmpiricalVariogram::_N_hvec [private]
```

Vector storing the number of data used in the estimation of the corresponding empirical variogram value

5.32.3.7 _card_h

```
unsigned int variogram_evaluation::EmpiricalVariogram::_card_h [private]
```

Number of distances for which the variogram has been evaluated. $_card_h = _hvec.size()$

5.32.3.8 _d

```
Vec variogram_evaluation::EmpiricalVariogram::_d [private]
```

Vector of equispaced distances whose midpoints are the candidates to enter in $_hvec$

5.32.3.9 _hmax

```
double variogram_evaluation::EmpiricalVariogram::_hmax [private]
```

Maximum distance considered

5.32.3.10 `_weights`

```
Vec variogram_evaluation::EmpiricalVariogram::_weights [private]
```

Vector of the weights for the N data

The documentation for this class was generated from the following files:


- [EmpiricalVariogram.hpp](#)
- [EmpiricalVariogram.cpp](#)

5.33 `variogram_evaluation::ExpVariogram` Class Reference

Class for computation and storage of the fitted variogram when `vario_model=="Exponential"`

```
#include <FittedVariogram.hpp>
```

Inheritance diagram for `variogram_evaluation::ExpVariogram`:



Public Member Functions

- double [get_vario_univ](#) (const double &h) const override
Compute the value of the model variogram at a given distance, according to the variogram type.
- [~ExpVariogram](#) ()=default
Destructor.

Private Member Functions

- void [get_init_par](#) (const [EmpiricalVariogram](#) &) override
Initialize _parameters
- MatrixXd [compute_jacobian](#) (const std::vector< double > &, unsigned int) const override
Compute the jacobian of the variogram residuals (which coincides with the one of the model variogram), according to the variogram type.

Additional Inherited Members

5.33.1 Detailed Description

Class for computation and storage of the fitted variogram when `vario_model=="Exponential"`

5.33.2 Member Function Documentation

5.33.2.1 get_init_par()

```
void ExpVariogram::get_init_par (
    const EmpiricalVariogram & emp_vario ) [override], [private], [virtual]
```

Initialize `_parameters`

The `_parameters` are initialized as follows:

```
_parameters (0) = weighted_median (_emp_vario_values.head (2) , _N_hvec.head (2))
_parameters (1) = weighted_median (_emp_vario_values.tail (4) , _N_hvec.tail (4)) - _parameters (0)
_parameters (2) = _hvec (i*)
where i* is the first i s.t. |_emp_vario_values (i) - (_parameters (0) + _parameters (1))| < tol
```

Parameters

<i>emp_vario</i>	Empirical variogram
------------------	---------------------

Implements [variogram_evaluation::FittedVariogram](#).

5.33.2.2 get_vario_univ()

```
double ExpVariogram::get_vario_univ (
    const double & h ) const [override], [virtual]
```

Compute the value of the model variogram at a given distance, according to the variogram type.

Parameters

<i>h</i>	The distance where to evaluate the variogram
----------	--

Returns

Variogram value at distance h : $\gamma_m(h)$

Implements [variogram_evaluation::FittedVariogram](#).

The documentation for this class was generated from the following files:


- [FittedVariogram.hpp](#)
- [FittedVariogram.cpp](#)

5.34 variogram_evaluation::FittedVariogram Class Reference

Abstract class for computation and storage of the fitted variogram.

```
#include <FittedVariogram.hpp>
```

Inheritance diagram for variogram_evaluation::FittedVariogram:



Public Member Functions

- double [get_tau2](#) () const
Return `_parameters(0)`, i.e. the nugget.
- double [get_sigma2](#) () const
Return `_parameters(1)`, i.e. the sill-nugget.
- double [get_a](#) () const
Return `_parameters(2)`, i.e. the practical range.
- void [evaluate_par_fitted_E](#) (const [EmpiricalVariogram](#) &emp_vario, double max_sill, double max_a)
Compute the parameters of the fitted variogram.
- void [evaluate_par_fitted_W](#) (const [EmpiricalVariogram](#) &emp_vario, double max_sill, double max_a)
Compute the parameters of the fitted variogram.
- virtual double [get_vario_univ](#) (const double &h) const =0
Compute the value of the model variogram at a given distance, according to the variogram type.
- double [get_covario_univ](#) (const double &h) const
Compute the value of the model covariogram at a given distance, according to the variogram type.
- [Vec](#) [get_vario_vec](#) (const std::vector< double > &h_vec, unsigned int card_h) const
Compute the values of the model variogram at a given vector of distances, according to the variogram type.
- [Vec](#) [get_vario_vec](#) (const [Vec](#) &h_vec, unsigned int card_h) const
Compute the values of the model variogram at a given vector of distances, according to the variogram type.
- MatrixXd [compute_gamma_matrix](#) (const std::shared_ptr< const MatrixXd > distanceMatrix, unsigned int N) const
Compute the covariogram matrix, according to the variogram type.
- Vector3d [get_parameters](#) () const
Return `_parameters`
- void [set_parameters](#) (const Vector3d ¶meters)
Set `_parameters`.
- [Vec](#) [get_covario_vec](#) (const std::vector< double > &h_vec, unsigned int card_h) const
Compute the values of the model covariogram at a given vector of distances, according to the variogram type.
- virtual [~FittedVariogram](#) ()=default
Destructor.

Protected Member Functions

- double [weighted_median](#) (const std::vector< double > &values, const std::vector< unsigned int > &card)
Compute weighted median.
- virtual void [get_init_par](#) (const [EmpiricalVariogram](#) &emp_vario)=0
Initialize _parameters
- void [backtrack](#) (const Vector3d &dir, Vector3d &gk, [Vec](#) &res, const std::vector< double > &h_vec, unsigned int card_h, double c, double s, const [Vec](#) &emp_vario_values, double max_sill, double max_a)
Update _parameters moving along dir
- virtual MatrixXd [compute_jacobian](#) (const std::vector< double > &h_vec, unsigned int card_h) const =0
Compute the jacobian of the variogram residuals (which coincides with the one of the model variogram), according to the variogram type.

Protected Attributes

- Vector3d [_parameters](#)

5.34.1 Detailed Description

Abstract class for computation and storage of the fitted variogram.

5.34.2 Member Function Documentation

5.34.2.1 [weighted_median\(\)](#)

```
double FittedVariogram::weighted_median (
    const std::vector< double > & values,
    const std::vector< unsigned int > & card ) [protected]
```

Compute weighted median.

Parameters

<i>values</i>	Values whose median must be computed
<i>card</i>	Weights

Returns

Median of *values*, weighted using *card*

5.34.2.2 [get_init_par\(\)](#)

```
virtual void variogram_evaluation::FittedVariogram::get_init_par (
    const EmpiricalVariogram & emp_vario ) [protected], [pure virtual]
```

Initialize `_parameters`

The `_parameters` are initialized as follows:

```
_parameters(0) = weighted_median(_emp_vario_values.head(2), _N_hvec.head(2))
_parameters(1) = weighted_median(_emp_vario_values.tail(4), _N_hvec.tail(4)) - _parameters(0)
_parameters(2) = _hvec(i*)
where i* is the first i s.t. |_emp_vario_values(i) - (_parameters(0) + _parameters(1))| < tol
```

Parameters

<code>emp_vario</code>	Empirical variogram
------------------------	---------------------

Implemented in [variogram_evaluation::SphVariogram](#), [variogram_evaluation::ExpVariogram](#), and [variogram_evaluation::GaussVariogram](#).

5.34.2.3 evaluate_par_fitted_E()

```
void FittedVariogram::evaluate_par_fitted_E (
    const EmpiricalVariogram & emp_vario,
    double max_sill,
    double max_a )
```

Compute the parameters of the fitted variogram.

Note

Like [variogram_evaluation::FittedVariogram::evaluate_par_fitted_W](#), but different stopping criteria. This function is used when equal weights are considered

The parameters are computed using Gauss-Newton with backtrack method to solve the non-linear least square problem:

$$\begin{aligned} & \arg \min_{\text{_parameters}} \sum_{h \in \text{_hvec}} (\gamma_m(\text{_parameters}, h) - \hat{\gamma}(h))^2 \\ & \text{subject to} \quad 0 \leq \text{_parameters}(0) \\ & \quad \quad \quad 0 \leq \text{_parameters}(1) \leq \text{max_sill} - \text{_parameters}(0) \\ & \quad \quad \quad 0 \leq \text{_parameters}(2) \leq \text{max_a} \end{aligned}$$

The starting values for the `_parameters` are obtained through [variogram_evaluation::FittedVariogram::get_init_par](#).

The stopping criteria is based on the decrease of the error norm.

Parameters

<code>emp_vario</code>	Empirical variogram
<code>max_sill</code>	Maximum value for the <i>sill</i>
<code>max_a</code>	Maximum value for <i>a</i>

5.34.2.4 evaluate_par_fitted_W()

```
void FittedVariogram::evaluate_par_fitted_W (
    const EmpiricalVariogram & emp_vario,
    double max_sill,
    double max_a )
```

Compute the parameters of the fitted variogram.

Note

Like [variogram_evaluation::FittedVariogram::evaluate_par_fitted_E](#), but different stopping criteria. This function is used when kernel weights are considered

The parameters are computed using Gauss-Newton with backtrack method to solve the non-linear least square problem:

$$\begin{aligned} \arg \min_{\text{_parameters}} \quad & \sum_{h \in \text{_hvec}} (\gamma_m(\text{_parameters}, h) - \hat{\gamma}(h))^2 \\ \text{subject to} \quad & 0 \leq \text{_parameters}(0) \\ & 0 \leq \text{_parameters}(1) \leq \text{max_sill} - \text{_parameters}(0) \\ & 0 \leq \text{_parameters}(2) \leq \text{max_a} \end{aligned}$$

The starting values for the `_parameters` are obtained through [variogram_evaluation::FittedVariogram::get_init_par](#).

The stopping criteria is based on the difference in the decrease of the error norm between two consecutive iterations.

Parameters

<i>emp_vario</i>	Empirical variogram
<i>max_sill</i>	Maximum value for the <i>sill</i>
<i>max_a</i>	Maximum value for <i>a</i>

5.34.2.5 get_vario_univ()

```
virtual double variogram_evaluation::FittedVariogram::get_vario_univ (
    const double & h ) const [pure virtual]
```

Compute the value of the model variogram at a given distance, according to the variogram type.

Parameters

<i>h</i>	The distance where to evaluate the variogram
----------	--

Returns

Variogram value at distance h : $\gamma_m(h)$

Implemented in [variogram_evaluation::SphVariogram](#), [variogram_evaluation::ExpVariogram](#), and [variogram_evaluation::GaussVariogram](#)

5.34.2.6 `get_covario_univ()`

```
double FittedVariogram::get_covario_univ (
    const double & h ) const
```

Compute the value of the model covariogram at a given distance, according to the variogram type.

Parameters

<i>h</i>	The distance where to evaluate the covariogram
----------	--

Returns

Covariogram value at distance h : $C_m(h) = (_parameters(0) + _parameters(1)) - \gamma_m(h)$

5.34.2.7 `get_vario_vec()` [1/2]

```
Vec FittedVariogram::get_vario_vec (
    const std::vector< double > & h_vec,
    unsigned int card_h ) const
```

Compute the values of the model variogram at a given vector of distances, according to the variogram type.

Parameters

<i>h_vec</i>	The distances where to evaluate the variogram
<i>card_h</i> ↔ <i>_h</i>	Number of distances where the variogram must be computed. <code>card_h = h_vec.size()</code>

Returns

Vector of variogram values at distances $h \in _h_vec$

5.34.2.8 `get_vario_vec()` [2/2]

```
Vec FittedVariogram::get_vario_vec (
    const Vec & h_vec,
    unsigned int card_h ) const
```

Compute the values of the model variogram at a given vector of distances, according to the variogram type.

Parameters

<i>h_vec</i>	The distances where to evaluate the variogram
<i>card_h</i> ↔ <i>_h</i>	Number of distances where the variogram must be computed. <code>card_h = h_vec.size()</code>

Returns

Vector of variogram values at distances $h \in h_vec$

5.34.2.9 compute_gamma_matrix()

```
MatrixXd FittedVariogram::compute_gamma_matrix (
    const std::shared_ptr< const MatrixXd > distanceMatrix,
    unsigned int N ) const
```

Compute the covariogram matrix, according to the variogram type.

Parameters

<i>distanceMatrix</i>	Matrix of distances among the N locations
N	Number of data locations

Returns

Covariogram matrix

5.34.2.10 set_parameters()

```
void FittedVariogram::set_parameters (
    const Vector3d & parameters )
```

Set _parameters.

Parameters

<i>parameters</i>	Vector of parameters' values
-------------------	------------------------------

5.34.2.11 get_covario_vec()

```
Vec FittedVariogram::get_covario_vec (
    const std::vector< double > & h_vec,
    unsigned int card_h ) const
```

Compute the values of the model covariogram at a given vector of distances, according to the variogram type.

Parameters

<i>h_vec</i>	The distances where to evaluate the covariogram
<i>card_h</i>	Number of distances where the covariogram must be computed. <code>card_h = h_vec.size()</code>

Returns

Vector of covariogram values at distances $h \in \mathbf{h_vec}$

5.34.3 Member Data Documentation

5.34.3.1 `_parameters`

```
Vector3d variogram_evaluation::FittedVariogram::_parameters [protected]
```

Vector storing the three parameters of the fitted varriogram (*nugget*, *sill-nugget*, *practical range*)

The documentation for this class was generated from the following files:


- [FittedVariogram.hpp](#)
- [FittedVariogram.cpp](#)

5.35 `variogram_evaluation::GaussVariogram` Class Reference

Class for computation and storage of the fitted variogram when `vario_model=="Gaussian"`

```
#include <FittedVariogram.hpp>
```

Inheritance diagram for `variogram_evaluation::GaussVariogram`:



Public Member Functions

- `double` [get_vario_univ](#) (const double &h) const override
Compute the value of the model variogram at a given distance, according to the variogram type.
- `~GaussVariogram` ()=default
Destructor.

Private Member Functions

- `void` [get_init_par](#) (const [EmpiricalVariogram](#) &) override
Initialize _parameters
- `MatrixXd` [compute_jacobian](#) (const std::vector< double > &, unsigned int) const override
Compute the jacobian of the variogram residuals (which coincides with the one of the model variogram), according to the variogram type.

Additional Inherited Members

5.35.1 Detailed Description

Class for computation and storage of the fitted variogram when `vario_model=="Gaussian"`

5.35.2 Member Function Documentation

5.35.2.1 `get_init_par()`

```
void GaussVariogram::get_init_par (
    const EmpiricalVariogram & emp_vario ) [override], [private], [virtual]
```

Initialize `_parameters`

The `_parameters` are initialized as follows:

```
_parameters(0) = weighted_median(_emp_vario_values.head(2), _N_hvec.head(2))
_parameters(1) = weighted_median(_emp_vario_values.tail(4), _N_hvec.tail(4)) - _parameters(0)
_parameters(2) = _hvec(i*)
```

where i^* is the first i s.t. $|\text{emp_vario_values}(i) - (\text{_parameters}(0) + \text{_parameters}(1))| < \text{tol}$

Parameters

<i>emp_vario</i>	Empirical variogram
------------------	---------------------

Implements [variogram_evaluation::FittedVariogram](#).

5.35.2.2 `get_vario_univ()`

```
double GaussVariogram::get_vario_univ (
    const double & h ) const [override], [virtual]
```

Compute the value of the model variogram at a given distance, according to the variogram type.

Parameters

h	The distance where to evaluate the variogram
-----	--

Returns

Variogram value at distance h : $\gamma_m(h)$

Implements [variogram_evaluation::FittedVariogram](#).

The documentation for this class was generated from the following files:


- [FittedVariogram.hpp](#)
- [FittedVariogram.cpp](#)

5.36 variogram_evaluation::SphVariogram Class Reference

Class for computation and storage of the fitted variogram when `vario_model=="Spherical"`

```
#include <FittedVariogram.hpp>
```

Inheritance diagram for `variogram_evaluation::SphVariogram`:



Public Member Functions

- double [get_vario_univ](#) (const double &h) const override
Compute the value of the model variogram at a given distance, according to the variogram type.
- [~SphVariogram](#) ()=default
Destructor.

Private Member Functions

- void [get_init_par](#) (const [EmpiricalVariogram](#) &) override
Initialize _parameters
- [MatrixXd compute_jacobian](#) (const std::vector< double > &, unsigned int) const override
Compute the jacobian of the variogram residuals (which coincides with the one of the model variogram), according to the variogram type.

Additional Inherited Members

5.36.1 Detailed Description

Class for computation and storage of the fitted variogram when `vario_model=="Spherical"`

5.36.2 Member Function Documentation

5.36.2.1 get_init_par()

```
void SphVariogram::get_init_par (
    const EmpiricalVariogram & emp_vario ) [override], [private], [virtual]
```

Initialize `_parameters`

The `_parameters` are initialized as follows:

```
_parameters(0) = weighted_median(_emp_vario_values.head(2), _N_hvec.head(2))
_parameters(1) = weighted_median(_emp_vario_values.tail(4), _N_hvec.tail(4)) - _parameters(0)
_parameters(2) = _hvec(i*)
where i* is the first i s.t. |_emp_vario_values(i) - (_parameters(0) + _parameters(1))| < tol
```

Parameters

<i>emp_vario</i>	Empirical variogram
------------------	---------------------

Implements [variogram_evaluation::FittedVariogram](#).

5.36.2.2 get_vario_univ()

```
double SphVariogram::get_vario_univ (  
    const double & h ) const [override], [virtual]
```

Compute the value of the model variogram at a given distance, according to the variogram type.

Parameters

<i>h</i>	The distance where to evaluate the variogram
----------	--

Returns

Variogram value at distance h : $\gamma_m(h)$

Implements [variogram_evaluation::FittedVariogram](#).

The documentation for this class was generated from the following files:

- [FittedVariogram.hpp](#)
- [FittedVariogram.cpp](#)

Chapter 6

File Documentation

6.1 Coordinates.hpp File Reference

`Coordinates` class.

```
#include <iostream>
#include <string>
#include <memory>
#include "Helpers.hpp"
```

Classes

- class `Coordinates`
Class to store the coordinates of the data points.

6.1.1 Detailed Description

`Coordinates` class.

6.2 DesignMatrix.hpp File Reference

Classes to create the `design_matrix` according to the model on the tangent space.

```
#include <memory>
#include <iostream>
#include <utility>
#include <map>
#include <string>
#include <Eigen/Dense>
#include "Coordinates.hpp"
```

Classes

- class `design_matrix::DesignMatrix`
Abstract class for the computation of the design_matrix.
- class `design_matrix::InterceptDM`
Class for the computation of the design_matrix when `model_ts=="Intercept"`
- class `design_matrix::Coord1DM`
Class for the computation of the design_matrix when `model_ts=="Coord1"`
- class `design_matrix::Coord2DM`
Class for the computation of the design_matrix when `model_ts=="Coord2"`
- class `design_matrix::AdditiveDM`
Class for the computation of the design_matrix when `model_ts=="Additive"`

6.2.1 Detailed Description

Classes to create the design_matrix according to the model on the tangent space.

6.3 Distance.hpp File Reference

Classes to create the compute the distances between data locations.

```
#include "Helpers.hpp"
#include "Coordinates.hpp"
#include <vector>
#include <utility>
#include <map>
#include <functional>
```

Classes

- class `distances::Distance`
Abstract class for the computation of the distance between data locations.
- class `distances::EuclDist`
Class for the computation of the distance between data locations when `distance=="Eucldist"`
- class `distances::GeoDist`
Class for the computation of the distance between data locations when `distance=="Geodist"`

6.3.1 Detailed Description

Classes to create the compute the distances between data locations.

6.4 DistanceManifold.hpp File Reference

Classes to compute the distance on the manifold according to its metric.

```
#include "Helpers.hpp"
#include <vector>
#include <utility>
#include <map>
#include <functional>
#include <memory>
```

Classes

- class [distances_manifold::DistanceManifold](#)
Abstract class for the computation of the distance on the manifold.
- class [distances_manifold::Frobenius](#)
Class for the computation of the distance on the manifold when `manifold_metric=="Frobenius"`
- class [distances_manifold::LogEuclidean](#)
Class for the computation of the distance on the manifold when `manifold_metric=="LogEuclidean"`
- class [distances_manifold::SqRoot](#)
Class for the computation of the distance on the manifold when `manifold_metric=="SqRoot"`
- class [distances_manifold::Chol](#)
Class for the computation of the distance on the manifold when `manifold_metric=="Chol"`

6.4.1 Detailed Description

Classes to compute the distance on the manifold according to its metric.

6.5 DistanceTplane.hpp File Reference

Classes to compute the distance on the tangent space according to its metric.

```
#include "Helpers.hpp"
#include <vector>
#include <utility>
#include <map>
#include <functional>
#include <memory>
```

Classes

- class [distances_tplane::DistanceTplane](#)
Abstract class for the computation of the distance on the tangent space.
- class [distances_tplane::Frobenius](#)
Class for the computation of the distance on the tangent space when `ts_metric=="Frobenius"`
- class [distances_tplane::FrobeniusScaled](#)
Class for the computation of the distance on the tangent space when `ts_metric=="FrobeniusScaled"`
- class [distances_tplane::Chol](#)
Class for the computation of the distance on the tangent space when `ts_metric=="Correlation"`

6.5.1 Detailed Description

Classes to compute the distance on the tangent space according to its metric.

6.6 EmpiricalVariogram.hpp File Reference

Class to compute the empirical variogram.

```
#include "Helpers.hpp"
#include "DistanceTplane.hpp"
#include "Distance.hpp"
#include "Coordinates.hpp"
```

Classes

- class [variogram_evaluation::EmpiricalVariogram](#)
Class for computation and storage of the empirical variogram.

6.6.1 Detailed Description

Class to compute the empirical variogram.

6.7 Factory.hpp File Reference

Factory class.

```
#include <map>
#include <vector>
#include <memory>
#include <functional>
#include <stdexcept>
#include <type_traits>
#include <Rcpp.h>
```

Classes

- class [generic_factory::Factory< AbstractProduct, Identifier, Builder >](#)
A generic factory.

6.7.1 Detailed Description

Factory class.

6.8 FittedVariogram.hpp File Reference

Classes to fit a model variogram (Gaussian, Exponential or Spherical) to an empirical one.

```
#include "EmpiricalVariogram.hpp"
#include <iostream>
#include <Rcpp.h>
```

Classes

- class [variogram_evaluation::FittedVariogram](#)
Abstract class for computation and storage of the fitted variogram.
- class [variogram_evaluation::GaussVariogram](#)
Class for computation and storage of the fitted variogram when `vario_model=="Gaussian"`
- class [variogram_evaluation::ExpVariogram](#)
Class for computation and storage of the fitted variogram when `vario_model=="Exponential"`
- class [variogram_evaluation::SphVariogram](#)
Class for computation and storage of the fitted variogram when `vario_model=="Spherical"`

6.8.1 Detailed Description

Classes to fit a model variogram (Gaussian, Exponential or Spherical) to an empirical one.

6.9 Helpers.hpp File Reference

Functions to manipulate matrices.

```
#include <Eigen/Sparse>
#include <Eigen/Dense>
#include <Eigen/Eigenvalues>
#include <Eigen/Cholesky>
#include <Eigen/SparseCholesky>
#include <cmath>
#include <string>
```

Typedefs

- typedef Eigen::VectorXd [Vec](#)
Eigen dynamic vector of doubles.

Functions

- MatrixXd [matrix_manipulation::expMat](#) (const MatrixXd &A)
Compute the exponential of a matrix.
- MatrixXd [matrix_manipulation::logMat](#) (const MatrixXd &A)
Compute the logarithm of a matrix.
- MatrixXd [matrix_manipulation::sqrtMat](#) (const MatrixXd &A)
Compute the square root of a matrix.
- std::vector< MatrixXd > [matrix_manipulation::bigMatrix2VecMatrices](#) (const MatrixXd &bigMatrix, unsigned int p, const std::string &distance_Manifold_name)
Transform a $\left(\frac{p(p+1)}{2}, N\right)$ matrix in a vector of $Np * p$ symmetric matrices.*
- MatrixXd [matrix_manipulation::VecMatrices2bigMatrix](#) (const std::vector< MatrixXd > &vecMatrices)
*Transform a vector of $Np * p$ symmetric matrices in a $\left(\frac{p*(p+1)}{2}, N\right)$ matrix.*
- MatrixXd [matrix_manipulation::Chol_semidef](#) (const MatrixXd &M1)
Compute the Cholesky decomposition of a matrix not positive definite.
- MatrixXd [matrix_manipulation::Chol_decomposition](#) (const MatrixXd M1)
Compute the Cholesky decomposition of a matrix.

6.9.1 Detailed Description

Functions to manipulate matrices.

6.9.2 Function Documentation

6.9.2.1 expMat()

```
MatrixXd matrix_manipulation::expMat (
    const MatrixXd & A )
```

Compute the exponential of a matrix.

Parameters

<i>A</i>	Matrix whose exponential must be computed
----------	---

Returns

Exponential of A

6.9.2.2 logMat()

```
MatrixXd matrix_manipulation::logMat (
    const MatrixXd & A )
```

Compute the logarithm of a matrix.

Parameters

<i>A</i>	Matrix whose logarithm must be computed
----------	---

Returns

Logarithm of A

6.9.2.3 sqrtMat()

```
MatrixXd matrix_manipulation::sqrtMat (
    const MatrixXd & A )
```

Compute the square root of a matrix.

Parameters

<i>A</i>	Matrix whose square root must be computed
----------	---

Returns

Square root of A

6.9.2.4 bigMatrix2VecMatrices()

```
std::vector< MatrixXd > matrix_manipulation::bigMatrix2VecMatrices (
    const MatrixXd & bigMatrix,
    unsigned int p,
    const std::string & distance_Manifold_name )
```

Transform a $\left(\frac{p*(p+1)}{2}, N\right)$ matrix in a vector of $Np * p$ symmetric matrices.

Parameters

<i>bigMatrix</i>	Matrix whose rows store the values of the upper triangular parts of $Np * p$ symmetric matrices
<i>p</i>	Dimension of the matrices
<i>distance_Manifold_name</i>	Name of the metric on the manifold to use. If <code>distance_Manifold_name=="Correlation"</code> then only the upper triangular parts of the matrices is filled

Returns

Vector of $Np * p$ symmetric matrices corresponding to the transformation of bigMatrix

6.9.2.5 VecMatrices2bigMatrix()

```
MatrixXd matrix_manipulation::VecMatrices2bigMatrix (
    const std::vector< MatrixXd > & vecMatrices )
```

Transform a vector of $Np * p$ symmetric matrices in a $\left(\frac{p*(p+1)}{2}, N\right)$ matrix.

Parameters

<i>vecMatrices</i>	Vector of symmetric matrices whose upper triangular parts will be stored in the rows of the output matrix
--------------------	---

Returns

Matrix $\left(\frac{p*(p+1)}{2}, N\right)$ corresponding to the transformation of vecMatrices

6.9.2.6 Chol_semidef()

```
MatrixXd matrix_manipulation::Chol_semidef (
    const MatrixXd & M1 )
```

Compute the Cholesky decomposition of a matrix not positive definite.

Parameters

<i>M1</i>	Positive semidefinite matrix whose Cholesky decomposition must be computed
-----------	--

Returns

Matrix in $Chol(p)$, representing the upper triangular matrix of A's Cholesky decomposition

6.9.2.7 Chol_decomposition()

```
MatrixXd matrix_manipulation::Chol_decomposition (
    const MatrixXd M1 )
```

Compute the Cholesky decomposition of a matrix.

Parameters

<i>M1</i>	Positive definite or semidefinite matrix whose Cholesky decomposition must be computed
-----------	--

Returns

Matrix in $Chol(p)$, representing the upper triangular matrix of A's Cholesky decomposition

6.10 HelpersFactory.hpp File Reference

Typedefs for the factory.

```
#include "FittedVariogram.hpp"
#include "DesignMatrix.hpp"
#include "Distance.hpp"
#include "MapFunctions.hpp"
#include "DistanceManifold.hpp"
#include "DistanceTplane.hpp"
#include "Factory.hpp"
#include "Proxy.hpp"
```

Typedefs

- typedef [generic_factory::Factory](#)< [variogram_evaluation::FittedVariogram](#), std::string > [vario_factory::VariogramFactory](#)
Factory for the fitted variogram.
- template<typename ConcreteProduct >
using [vario_factory::VariogramProxy](#) = [generic_factory::Proxy](#)< [VariogramFactory](#), ConcreteProduct >
Proxy for the fitted variogram.
- typedef [generic_factory::Factory](#)< [design_matrix::DesignMatrix](#), std::string > [design_factory::DesignFactory](#)
Factory for the design matrix.
- template<typename ConcreteProduct >
using [design_factory::DesignProxy](#) = [generic_factory::Proxy](#)< [DesignFactory](#), ConcreteProduct >
Proxy for the design matrix.
- typedef [generic_factory::Factory](#)< [distances::Distance](#), std::string > [distance_factory::DistanceFactory](#)
Factory for the distance.
- template<typename ConcreteProduct >
using [distance_factory::DistanceProxy](#) = [generic_factory::Proxy](#)< [DistanceFactory](#), ConcreteProduct >
Proxy for the distance.
- typedef [generic_factory::Factory](#)< [map_functions::logarithmicMap](#), std::string > [map_factory::LogMapFactory](#)
Factory for the logarithmic map.
- typedef [generic_factory::Factory](#)< [map_functions::exponentialMap](#), std::string > [map_factory::ExpMapFactory](#)
Factory for the exponential map.
- template<typename ConcreteProduct >
using [map_factory::LogMapProxy](#) = [generic_factory::Proxy](#)< [LogMapFactory](#), ConcreteProduct >
Proxy for the logarithmic map.
- template<typename ConcreteProduct >
using [map_factory::ExpMapProxy](#) = [generic_factory::Proxy](#)< [ExpMapFactory](#), ConcreteProduct >
Proxy for the exponential map.
- typedef [generic_factory::Factory](#)< [distances_manifold::DistanceManifold](#), std::string > [manifold_factory::ManifoldFactory](#)

- Factory for the distance on the manifold.*
 - template<typename ConcreteProduct >
 using manifold_factory::ManifoldProxy = generic_factory::Proxy< ManifoldFactory, ConcreteProduct >
 - Proxy for the distance on the manifold.*
- typedef generic_factory::Factory< distances_tplane::DistanceTplane, std::string > tplane_factory::TplaneFactory
 - Factory for the distance on the tangent space.*
- template<typename ConcreteProduct >
 using tplane_factory::TplaneProxy = generic_factory::Proxy< TplaneFactory, ConcreteProduct >
 - Proxy for the distance on the tangent space.*

6.10.1 Detailed Description

Typedefs for the factory.

6.11 interface_function.cpp File Reference

Main functions to create the model and perform kriging, along with functions to compute the distance on the manifold and the intrinsic mean.

```
#include <iostream>
#include <vector>
#include <utility>
#include <memory>
#include <Rcpp.h>
#include <RcppEigen.h>
#include "Coordinates.hpp"
#include "DesignMatrix.hpp"
#include "DistanceManifold.hpp"
#include "DistanceTplane.hpp"
#include "Distance.hpp"
#include "EmpiricalVariogram.hpp"
#include "FittedVariogram.hpp"
#include "Helpers.hpp"
#include "HelpersFactory.hpp"
#include "MapFunctions.hpp"
#include "Model.hpp"
#include "IntrinsicMean.hpp"
```

Functions

- RcppExport SEXP [get_model](#) (SEXP s_data_manifold, SEXP s_coordinates, SEXP s_X, SEXP s_Sigma, SEXP s_distance, SEXP s_manifold_metric, SEXP s_ts_metric, SEXP s_ts_model, SEXP s_vario_model, SEXP s_n_h, SEXP s_max_it, SEXP s_tolerance, SEXP s_max_sill, SEXP s_max_a, SEXP s_weight_vario, SEXP s_distance_matrix_tot, SEXP s_data_manifold_tot, SEXP s_coordinates_tot, SEXP s_X_tot, SEXP s_hmax, SEXP s_indexes_model, SEXP s_weight_intrinsic, SEXP s_tolerance_intrinsic, SEXP s_weight_↵ extrinsic, SEXP s_suppressMes, SEXP s_tolerance_map_cor)

Given the coordinates and corresponding manifold values, this function creates a GLS model on the tangent space.
- RcppExport SEXP [get_kriging](#) (SEXP s_coordinates, SEXP s_new_coordinates, SEXP s_Sigma, SEXP s_↵ distance, SEXP s_manifold_metric, SEXP s_ts_model, SEXP s_vario_model, SEXP s_beta, SEXP s_↵ gamma_matrix, SEXP s_vario_parameters, SEXP s_residuals, SEXP s_X_new, SEXP s_tolerance_map_↵ cor)

Given the GLS model kriging prediction on new location is performed.

- RcppExport SEXP [get_model_and_kriging](#) (SEXP s_data_manifold, SEXP s_coordinates, SEXP s_X, SEXP s_Sigma, SEXP s_distance, SEXP s_manifold_metric, SEXP s_ts_metric, SEXP s_ts_model, SEXP s_vario_model, SEXP s_n_h, SEXP s_max_it, SEXP s_tolerance, SEXP s_max_sill, SEXP s_max_a, SEXP s_weight_vario, SEXP s_distance_matrix_tot, SEXP s_data_manifold_tot, SEXP s_coordinates_tot, SEXP s_X_tot, SEXP s_hmax, SEXP s_indexes_model, SEXP s_weight_intrinsic, SEXP s_tolerance_intrinsic, SEXP s_weight_extrinsic, SEXP s_new_coordinates, SEXP s_X_new, SEXP s_suppressMes, SEXP s_tolerance_map_cor)

Given the coordinates and corresponding manifold values, this function firstly creates a GLS model on the tangent space, and then it performs kriging on the new locations.

- RcppExport SEXP [intrinsic_mean](#) (SEXP s_data, SEXP s_N, SEXP s_manifold_metric, SEXP s_ts_metric, SEXP s_tolerance, SEXP s_weight_intrinsic, SEXP s_weight_extrinsic, SEXP s_tolerance_map_cor)

Evaluate the intrinsic mean of a given set of symmetric positive definite matrices.

- RcppExport SEXP [distance_manifold](#) (SEXP s_data1, SEXP s_data2, SEXP s_N1, SEXP s_N2, SEXP s_manifold_metric)

Compute the manifold distance between symmetric positive definite matrices.

6.11.1 Detailed Description

Main functions to create the model and perform kriging, along with functions to compute the distance on the manifold and the intrinsic mean.

6.11.2 Function Documentation

6.11.2.1 [get_model\(\)](#)

```
RcppExport SEXP get_model (
    SEXP s_data_manifold,
    SEXP s_coordinates,
    SEXP s_X,
    SEXP s_Sigma,
    SEXP s_distance,
    SEXP s_manifold_metric,
    SEXP s_ts_metric,
    SEXP s_ts_model,
    SEXP s_vario_model,
    SEXP s_n_h,
    SEXP s_max_it,
    SEXP s_tolerance,
    SEXP s_max_sill,
    SEXP s_max_a,
    SEXP s_weight_vario,
    SEXP s_distance_matrix_tot,
    SEXP s_data_manifold_tot,
    SEXP s_coordinates_tot,
    SEXP s_X_tot,
    SEXP s_hmax,
    SEXP s_indexes_model,
    SEXP s_weight_intrinsic,
    SEXP s_tolerance_intrinsic,
```

```
SEXP s_weight_extrinsic,
SEXP s_suppressMes,
SEXP s_tolerance_map_cor )
```

Given the coordinates and corresponding manifold values, this function creates a GLS model on the tangent space.

The manifold values are mapped on the tangent space and then a GLS model is fitted to them. A first estimate of the `beta` coefficients is obtained assuming spatially uncorrelated errors. Then, in the main the loop, new estimates of the `beta` are obtained as a result of a weighted least square problem where the weight matrix is the inverse of `gamma_matrix`. The residuals (`residuals = data_ts - fitted`) are updated accordingly. The parameters of the variogram fitted to the `residuals` (and used in the evaluation of the `gamma_matrix`) are computed using Gauss-Newton with backtrack method to solve the associated non-linear least square problem. The stopping criteria is based on the absolute value of the variogram residuals' norm if `ker.width.vario=0`, while it is based on its increment otherwise.

Note

Reference: "Kriging prediction for manifold-valued random fields."

Authors: D. Pigoli, A. Menafoglio & P. Secchi (2016)

Periodical: Journal of Multivariate Analysis, 145, 117-131.

Parameters

<code>s_data_manifold</code>	list of N symmetric positive definite matrices of dimension $(p * p)$
<code>s_coordinates</code>	$(N * 2)$ or $(N * 3)$ matrix of [lat,long], [x,y] or [x,y,z] coordinates. [lat,long] are supposed to be provided in signed decimal degrees
<code>s_X</code>	matrix Matrix with N rows and unrestricted number of columns of additional covariates for the tangent space model, possibly <code>NULL</code>
<code>s_Sigma</code>	Matrix $(p * p)$ representing the tangent point. If <code>NULL</code> the tangent point is computed as the intrinsic mean of <code>s_data_manifold</code>
<code>s_distance</code>	Type of distance between coordinates. It must be either "Eucldist" or "Geodist"
<code>s_manifold_metric</code>	Metric used on the manifold. It must be chosen among "Frobenius", "LogEuclidean", "SquareRoot", "Correlation"
<code>s_ts_metric</code>	Metric used on the tangent space. It must be chosen among "Frobenius", "FrobeniusScaled", "Correlation"
<code>s_ts_model</code>	Type of model fitted on the tangent space. It must be chosen among "Intercept", "Coord1", "Coord2", "Additive"
<code>s_vario_model</code>	Type of variogram fitted. It must be chosen among "Gaussian", "Spherical", "Exponential"
<code>s_n_h</code>	Number of bins in the empirical variogram
<code>s_max_it</code>	Max number of iterations for the main loop
<code>s_tolerance</code>	Tolerance for the main loop
<code>s_max_sill</code>	Maximum value allowed for <code>sill</code> in the fitted variogram. If <code>NULL</code> it is defined as $1.15 * \max(\text{emp_vario_values})$
<code>s_max_a</code>	Maximum value for <code>a</code> in the fitted variogram. If <code>NULL</code> it is defined as $1.15 * h_{\max}$
<code>s_weight_vario</code>	Vector of length N_{tot} to weight the locations in the computation of the empirical variogram
<code>s_distance_matrix_tot</code>	Matrix $(N_{\text{tot}} * N_{\text{tot}})$ of distances between the locations,
<code>s_data_manifold_tot</code>	List of N_{tot} symmetric positive definite matrices of dimension $(p * p)$
<code>s_coordinates_tot</code>	$(N_{\text{tot}} * 2)$ or $(N_{\text{tot}} * 3)$ matrix of [lat,long], [x,y] or [x,y,z] coordinates. [lat,long] are supposed to be provided in signed decimal degrees),
<code>s_X_tot</code>	Matrix with N_{tot} rows and unrestricted number of columns, of additional covariates for the tangent space model. Possibly <code>NULL</code>

Parameters

<code>s_hmax</code>	Maximum value of distance for which the variogram is computed
<code>s_indexes_model</code>	Indexes corresponding to <code>coords</code> in <code>coords_tot</code> . Required only in the case <code>metric_manifold=="Correlation"</code>
<code>s_weight_intrinsic</code>	Vector of length N to weight the locations in the computation of the intrinsic mean. If <code>NULL</code> a vector of ones is used. Not needed if <code>Sigma</code> is provided
<code>s_tolerance_intrinsic</code>	Tolerance for the computation of the intrinsic mean. Not needed if <code>Sigma</code> is provided
<code>s_weight_extrinsic</code>	Vector of length N to weight the locations in the computation of the extrinsic mean. If <code>NULL</code> <code>weight_intrinsic</code> are used. Needed only if <code>Sigma</code> is not provided and <code>metric_manifold=="Correlation"</code>
<code>s_suppressMes</code>	Boolean. If <code>TRUE</code> warning messages are not printed
<code>s_tolerance_map_cor</code>	Tolerance to use in the maps. Required only if <code>metric_manifold=="Correlation"</code>

Returns

A list with the following fields:

- `beta` Vector of the beta matrices of the fitted model
- `fit_vario_values` Vector of fitted variogram values in correspondence of `hh`
- `hh` Dense vector of positions at which `fit_vario_values` is computed
- `gamma_matrix` Covariogram matrix ($N * N$)
- `residuals` Vector of the N residual matrices
- `emp_vario_values` Vector of empirical variogram values in correspondence of `h_vec`
- `h_vec` Vector of positions at which the empirical variogram is computed
- `fitted_par_vario` Estimates of *nugget*, *sill-nugget* and *practical range*
- `iterations` Number of iterations of the main loop
- `Sigma` Tangent point

6.11.2.2 `get_kriging()`

```
RcppExport SEXP get_kriging (
    SEXP s_coordinates,
    SEXP s_new_coordinates,
    SEXP s_Sigma,
    SEXP s_distance,
    SEXP s_manifold_metric,
    SEXP s_ts_model,
    SEXP s_vario_model,
    SEXP s_beta,
    SEXP s_gamma_matrix,
    SEXP s_vario_parameters,
    SEXP s_residuals,
    SEXP s_X_new,
    SEXP s_tolerance_map_cor )
```

Given the GLS model kriging prediction on new location is performed.

The model provided is used to perform simple kriging on the tangent space in correspondence of the new locations. The estimates are then mapped to the manifold to produce the actual prediction.

Note

Reference: "Kriging prediction for manifold-valued random fields."
 Authors: D. Pigoli, A. Menafoglio & P. Secchi (2016)
 Periodical: Journal of Multivariate Analysis, 145, 117-131.

Parameters

<i>s_coordinates</i>	$(N * 2)$ or $(N * 3)$ matrix of [lat,long], [x,y] or [x,y,z] coordinates. [lat,long] are supposed to be provided in signed decimal degrees
<i>s_new_coordinates</i>	$(N * 2)$ or $(N * 3)$ matrix of [lat,long], [x,y] or [x,y,z] coordinates. [lat,long] are supposed to be provided in signed decimal degrees
<i>s_Sigma</i>	Matrix $(p * p)$ representing the tangent point. If <code>NULL</code> the tangent point is computed as the intrinsic mean of <code>s_data_manifold</code>
<i>s_distance</i>	Type of distance between coordinates. It must be either "Eucldist" or "Geodist"
<i>s_manifold_metric</i>	Metric used on the manifold. It must be chosen among "Frobenius", "LogEuclidean", "SquareRoot", "Correlation"
<i>s_ts_model</i>	Type of model fitted on the tangent space. It must be chosen among "Intercept", "Coord1", "Coord2", "Additive"
<i>s_vario_model</i>	Type of variogram fitted. It must be chosen among "Gaussian", "Spherical", "Exponential"
<i>s_beta</i>	Vector of the beta matrices of the fitted model
<i>s_gamma_matrix</i>	Covariogram matrix $(N * N)$
<i>s_vario_parameters</i>	Estimates of <i>nugget</i> , <i>sill-nugget</i> and <i>practical range</i>
<i>s_residuals</i>	Vector of the N residual matrices
<i>s_X_new</i>	Matrix (with the same number of rows of <code>s_new_coordinates</code>) of additional covariates for the new locations, possibly <code>NULL</code>
<i>s_tolerance_map_cor</i>	Tolerance to use in the maps. Required only if <code>metric_manifold=="Correlation"</code>

Returns

A list with the following field:

- `prediction` Vector of matrices predicted at the new locations

6.11.2.3 get_model_and_kriging()

```
RcppExport SEXP get_model_and_kriging (
    SEXP s_data_manifold,
    SEXP s_coordinates,
    SEXP s_X,
    SEXP s_Sigma,
    SEXP s_distance,
    SEXP s_manifold_metric,
    SEXP s_ts_metric,
    SEXP s_ts_model,
    SEXP s_vario_model,
    SEXP s_n_h,
    SEXP s_max_it,
    SEXP s_tolerance,
```

```

SEXP s_max_sill,
SEXP s_max_a,
SEXP s_weight_vario,
SEXP s_distance_matrix_tot,
SEXP s_data_manifold_tot,
SEXP s_coordinates_tot,
SEXP s_X_tot,
SEXP s_hmax,
SEXP s_indexes_model,
SEXP s_weight_intrinsic,
SEXP s_tolerance_intrinsic,
SEXP s_weight_extrinsic,
SEXP s_new_coordinates,
SEXP s_X_new,
SEXP s_suppressMes,
SEXP s_tolerance_map_cor )

```

Given the coordinates and corresponding manifold values, this function firstly creates a GLS model on the tangent space, and then it performs kriging on the new locations.

The manifold values are mapped on the tangent space and then a GLS model is fitted to them. A first estimate of the `beta` coefficients is obtained assuming spatially uncorrelated errors. Then, in the main the loop, new estimates of the `beta` are obtained as a result of a weighted least square problem where the weight matrix is the inverse of `gamma_matrix`. The residuals (`residuals = data_ts - fitted`) are updated accordingly. The parameters of the variogram fitted to the `residuals` (and used in the evaluation of the `gamma_matrix`) are computed using Gauss-Newton with backtrack method to solve the associated non-linear least square problem. The stopping criteria is based on the absolute value of the variogram residuals' norm if `ker.width.vario=0`, while it is based on its increment otherwise. Once the model is computed, simple kriging on the tangent space is performed in correspondence of the new locations and eventually the estimates are mapped to the manifold.

Note

Reference: "Kriging prediction for manifold-valued random fields."
 Authors: D. Pigoli, A. Menafoglio & P. Secchi (2016)
 Periodical: Journal of Multivariate Analysis, 145, 117-131.

Parameters

<i>s_data_manifold</i>	list of N symmetric positive definite matrices of dimension $(p * p)$
<i>s_coordinates</i>	$(N * 2)$ or $(N * 3)$ matrix of [lat,long], [x,y] or [x,y,z] coordinates. [lat,long] are supposed to be provided in signed decimal degrees
<i>s_X</i>	matrix Matrix with N rows and unrestricted number of columns of additional covariates for the tangent space model, possibly <code>NULL</code>
<i>s_Sigma</i>	Matrix $(p * p)$ representing the tangent point. If <code>NULL</code> the tangent point is computed as the intrinsic mean of <code>s_data_manifold</code>
<i>s_distance</i>	Type of distance between coordinates. It must be either "Eucldist" or "Geodist"
<i>s_manifold_metric</i>	Metric used on the manifold. It must be chosen among "Frobenius", "LogEuclidean", "SquareRoot", "Correlation"
<i>s_ts_metric</i>	Metric used on the tangent space. It must be chosen among "Frobenius", "FrobeniusScaled", "Correlation"
<i>s_ts_model</i>	Type of model fitted on the tangent space. It must be chosen among "Intercept", "Coord1", "Coord2", "Additive"
<i>s_vario_model</i>	Type of variogram fitted. It must be chosen among "Gaussian", "Spherical", "Exponential"
<i>s_n_h</i>	Number of bins in the empirical variogram
<i>s_max_it</i>	Max number of iterations for the main loop

Parameters

<i>s_tolerance</i>	Tolerance for the main loop
<i>s_max_sill</i>	Maximum value allowed for <i>sill</i> in the fitted variogram. If <code>NULL</code> it is defined as $1.15 * \max(\text{emp_vario_values})$
<i>s_max_a</i>	Maximum value for <i>a</i> in the fitted variogram. If <code>NULL</code> it is defined as $1.15 * h_max$
<i>s_weight_vario</i>	Vector of length N_tot to weight the locations in the computation of the empirical variogram
<i>s_distance_matrix_tot</i>	Matrix ($N_tot * N_tot$) of distances between the locations,
<i>s_data_manifold_tot</i>	List of N_tot symmetric positive definite matrices of dimension $(p * p)$
<i>s_coordinates_tot</i>	$(N_tot * 2)$ or $(N_tot * 3)$ matrix of [lat,long], [x,y] or [x,y,z] coordinates. [lat,long] are supposed to be provided in signed decimal degrees),
<i>s_X_tot</i>	Matrix with N_tot rows and unrestricted number of columns, of additional covariates for the tangent space model. Possibly <code>NULL</code>
<i>s_hmax</i>	Maximum value of distance for which the variogram is computed
<i>s_indexes_model</i>	Indexes corresponding to coords in <i>coords_tot</i> . Required only in the case <code>metric_manifold=="Correlation"</code>
<i>s_weight_intrinsic</i>	Vector of length N to weight the locations in the computation of the intrinsic mean. If <code>NULL</code> a vector of ones is used. Not needed if <i>Sigma</i> is provided
<i>s_tolerance_intrinsic</i>	Tolerance for the computation of the intrinsic mean. Not needed if <i>Sigma</i> is provided
<i>s_weight_extrinsic</i>	Vector of length N to weight the locations in the computation of the extrinsic mean. If <code>NULL</code> <i>weight_intrinsic</i> are used. Needed only if <i>Sigma</i> is not provided and <code>metric_manifold=="Correlation"</code>
<i>s_new_coordinates</i>	$(N * 2)$ or $(N * 3)$ matrix of [lat,long], [x,y] or [x,y,z] coordinates. [lat,long] are supposed to be provided in signed decimal degrees
<i>s_X_new</i>	Matrix (with the same number of rows of <i>s_new_coordinates</i>) of additional covariates for the new locations, possibly <code>NULL</code>
<i>s_suppressMes</i>	Boolean. If <code>TRUE</code> warning messages are not printed
<i>s_tolerance_map_cor</i>	Tolerance to use in the maps. Required only if <code>metric_manifold=="Correlation"</code>

Returns

A list with the following fields:

- *beta* Vector of the beta matrices of the fitted model
- *fit_vario_values* Vector of fitted variogram values in correspondence of *hh*
- *hh* Dense vector of positions at which *fit_vario_values* is computed
- *gamma_matrix* Covariogram matrix ($N * N$)
- *residuals* Vector of the N residual matrices
- *emp_vario_values* Vector of empirical variogram values in correspondence of *h_vec*
- *h_vec* Vector of positions at which the empirical variogram is computed
- *fitted_par_vario* Estimates of *nugget*, *sill-nugget* and *practical range*
- *iterations* Number of iterations of the main loop
- *Sigma* Tangent point
- *prediction* Vector of matrices predicted at the new locations

6.11.2.4 intrinsic_mean()

```
RcppExport SEXP intrinsic_mean (
    SEXP s_data,
    SEXP s_N,
    SEXP s_manifold_metric,
    SEXP s_ts_metric,
    SEXP s_tolerance,
    SEXP s_weight_intrinsic,
    SEXP s_weight_extrinsic,
    SEXP s_tolerance_map_cor )
```

Evaluate the intrinsic mean of a given set of symmetric positive definite matrices.

Parameters

<i>s_data</i>	list of N symmetric positive definite matrices of dimension $(p * p)$
<i>s_N</i>	Number of data. $N = s_data.size()$
<i>s_manifold_metric</i>	Metric used on the manifold. It must be chosen among "Frobenius", "LogEuclidean", "SquareRoot", "Correlation"
<i>s_ts_metric</i>	Metric used on the tangent space. It must be chosen among "Frobenius", "FrobeniusScaled", "Correlation"
<i>s_tolerance</i>	Tolerance for the computation of the intrinsic_mean
<i>s_weight_intrinsic</i>	Vector of length N to weight the locations in the computation of the intrinsic mean. If NULL a vector of ones is used
<i>s_weight_extrinsic</i>	Vector of length N to weight the locations in the computation of the extrinsic mean. If NULL weight_intrinsic are used
<i>s_tolerance_map_cor</i>	Tolerance to use in the maps. Required only if metric_manifold=="Correlation"

Returns

A matrix representing the intrinsic mean of the *s_data*

6.11.2.5 distance_manifold()

```
RcppExport SEXP distance_manifold (
    SEXP s_data1,
    SEXP s_data2,
    SEXP s_N1,
    SEXP s_N2,
    SEXP s_manifold_metric )
```

Compute the manifold distance between symmetric positive definite matrices.

If $N1 == N2$ then the result is a vector of length $N1 = N2$ containing in position i the manifold distance between $data1[[i]]$ and $data2[[i]]$. Instead if $N2 = 1$ and $N1 != 1$ the result is a vector of length $B1$ containing in position i the manifold distance between $data1[[i]]$ and $data2[[1]]$

Parameters

<code>s_data1</code>	list of $N1$ symmetric positive definite matrices of dimension $(p * p)$
<code>s_data2</code>	list of $N2$ symmetric positive definite matrices of dimension $(p * p)$
<code>s_N1</code>	Number of data1. $N1 = s_data1.size()$
<code>s_N2</code>	Number of data2. $N2 = s_data2.size()$
<code>s_manifold_metric</code>	Metric used on the manifold. It must be chosen among "Frobenius", "LogEuclidean", "SquareRoot", "Correlation"

Returns

A double or a vector of distances

6.12 IntrinsicMean.hpp File Reference

Functions to compute intrinsic and extrinsic mean for manifold data.

```
#include <Eigen/Dense>
#include <memory>
#include "DistanceTplane.hpp"
#include "Helpers.hpp"
#include "MapFunctions.hpp"
```

Functions

- `MatrixXd intrinsic_mean_C` (const std::vector< MatrixXd > &data_manifold, std::string distance_↵
Manifold_name, [map_functions::logarithmicMap](#) &logMap, [map_functions::exponentialMap](#) &expMap,
[distances_tplane::DistanceTplane](#) &distanceTplane, double tolerance, const [Vec](#) &weight_intrinsic, const
[Vec](#) &weight_extrinsic)

Compute the intrinsic mean of a set of manifold matrices.

- `MatrixXd extrinsic_mean` (const std::vector< MatrixXd > &data_manifold, const [Vec](#) &weight_extrinsic)

Compute the extrinsic mean of a set of matrices in $Chol(p)$.

6.12.1 Detailed Description

Functions to compute intrinsic and extrinsic mean for manifold data.

6.12.2 Function Documentation

6.12.2.1 intrinsic_mean_C()

```
MatrixXd intrinsic_mean_C (
    const std::vector< MatrixXd > & data_manifold,
    std::string distance_Manifold_name,
    map_functions::logarithmicMap & logMap,
    map_functions::exponentialMap & expMap,
    distances_tplane::DistanceTplane & distanceTplane,
    double tolerance,
    const Vec & weight_intrinsic,
    const Vec & weight_extrinsic )
```

Compute the intrinsic mean of a set of manifold matrices.

Parameters

<i>data_manifold</i>	Vector of manifold matrices
<i>distance_Manifold_name</i>	Name of the metric on the manifold
<i>logMap</i>	Logarithmic map
<i>expMap</i>	Exponential map
<i>distanceTplane</i>	Distance on the tangent space
<i>tolerance</i>	Tolerance for the algorithm's loop
<i>weight_intrinsic</i>	Weights
<i>weight_extrinsic</i>	Weights for the computation of the extrinsic mean (used if <code>distance_Manifold_name=="Correlation"</code>)

Returns

Matrix identifying the intrinsic mean of `data_manifold`

6.12.2.2 extrinsic_mean()

```
MatrixXd extrinsic_mean (
    const std::vector< MatrixXd > & data_manifold,
    const Vec & weight_extrinsic )
```

Compute the extrinsic mean of a set of matrices in $Chol(p)$.

Parameters

<i>data_manifold</i>	Vector of matrices in $Chol(p)$
<i>weight_extrinsic</i>	Weights

Returns

Matrix identifying the extrinsic mean of `data_manifold`

6.13 MapFunctions.hpp File Reference

Classes to compute the exponential and logarithmic map according to the manifold metric.

```
#include <memory>
#include "DistanceManifold.hpp"
```

Classes

- class `map_functions::logarithmicMap`
Abstract class for the computation of the logarithmic map.

- class [map_functions::logMapFrob](#)
Class for the computation of the logarithmic map when `manifold_metric=="Frobenius"`
- class [map_functions::logMapLogEucl](#)
Class for the computation of the logarithmic map when `manifold_metric=="LogEuclidean"`
- class [map_functions::logMapSqRoot](#)
Class for the computation of the logarithmic map when `manifold_metric=="SqRoot"`
- class [map_functions::logMapChol](#)
Class for the computation of the logarithmic map when `manifold_metric=="Correlation"`
- class [map_functions::exponentialMap](#)
Abstract class for the computation of the exponential map.
- class [map_functions::expMapFrob](#)
Class for the computation of the exponential map when `manifold_metric=="Frobenius"`
- class [map_functions::expMapLogEucl](#)
Class for the computation of the exponential map when `manifold_metric=="LogEuclidean"`
- class [map_functions::expMapSqRoot](#)
Class for the computation of the exponential map when `manifold_metric=="SqRoot"`
- class [map_functions::expMapChol](#)
Class for the computation of the exponential map when `manifold_metric=="Correlation"`

6.13.1 Detailed Description

Classes to compute the exponential and logarithmic map according to the manifold metric.

6.14 Model.hpp File Reference

Model class.

```
#include <vector>
#include <iostream>
#include <string>
#include <utility>
#include <Eigen/IterativeLinearSolvers>
#include <memory>
#include "Helpers.hpp"
```

Classes

- class [model_fit::Model](#)
Class to compute and store the linear model on the tangent space.

6.14.1 Detailed Description

Model class.

6.15 Proxy.hpp File Reference

Proxy class.

```
#include <string>
#include <memory>
#include <iostream>
#include <type_traits>
```

Classes

- class [generic_factory::Proxy](#)< [Factory](#), [ConcreteProduct](#) >

6.15.1 Detailed Description

Proxy class.

