

Introduction to proteomics data analysis: robust summarization

Lieven Clement

statOmics, Ghent University (<https://statomics.github.io>)

Contents

1	Background	1
2	Data	1
2.1	Data exploration	3
3	Preprocessing	3
3.1	Log transform the data	3
3.2	Filtering	3
3.3	Normalize the data using median centering	4
3.4	Explore normalized data	4
3.5	Summarization to protein level	6
4	Data Analysis	7
4.1	Estimation	7
4.2	Inference	7
4.3	Plots	8
5	Session Info	51

This is part of the online course [Proteomics Data Analysis \(PDA\)](#)

1 Background

This case-study is a subset of the data of the 6th study of the Clinical Proteomic Technology Assessment for Cancer (CPTAC). In this experiment, the authors spiked the Sigma Universal Protein Standard mixture 1 (UPS1) containing 48 different human proteins in a protein background of 60 ng/ μ L *Saccharomyces cerevisiae* strain BY4741. Two different spike-in concentrations were used: 6A (0.25 fmol UPS1 proteins/ μ L) and 6B (0.74 fmol UPS1 proteins/ μ L) [5]. We limited ourselves to the data of LTQ-Orbitrap W at site 56. The data were searched with MaxQuant version 1.5.2.8, and detailed search settings were described in Goeminne et al. (2016) [1]. Three replicates are available for each concentration.

2 Data

We first import the data from peptideRaws.txt file. This is the file containing your peptideRaw-level intensities. For a MaxQuant search [6], this peptideRaws.txt file can be found by default in the “path_to_raw_files/combined/txt/” folder from the MaxQuant output, with “path_to_raw_files” the folder where the raw files were saved. In this vignette, we use a MaxQuant peptideRaws file which is a subset of the cptac study. This data is available in the `msdata` package. To import the data we use the `QFeatures` package.

We generate the object `peptideRawFile` with the path to the `peptideRaw.txt` file. Using the `grepEcols` function, we find the columns that contain the expression data of the peptideRaw in the `peptideRaw.txt` file.

```
library(tidyverse)
library(limma)
library(QFeatures)
library(msqrob2)
library(plotly)

peptidesFile <- "https://raw.githubusercontent.com/statOmics/PDA22GTPB/data/quantification/cptacAvsB_la

ecols <- grep(
  "Intensity\\.\\.",
  names(read.delim(peptidesFile))
)
```

Next, we read the data and store it in `QFeatures` object

```
pe <- readQFeatures(
  assayData = read.delim(peptidesFile),
  fnames = 1,
  quantCols = ecols,
  name = "peptideRaw")
```

```
## Checking arguments.
## Loading data as a 'SummarizedExperiment' object.
## Formatting sample annotations (colData).
## Formatting data as a 'QFeatures' object.
```

The `QFeatures` object `pe` currently contains a single assay, named `peptideRaw`.

We extract the column names from the `peptideRaw` assay and see that this contains information about the spike-in condition.

```
colnames(pe[["peptideRaw"]])

## [1] "Intensity.6A_7" "Intensity.6A_8" "Intensity.6A_9" "Intensity.6B_7"
## [5] "Intensity.6B_8" "Intensity.6B_9"
```

We rename the `colnames` by dropping the “Intensity.” from the name.

```
(newNames <- sub(
  pattern = "Intensity\\.\\.",
  replacement = "",
  colnames(pe[["peptideRaw"]]))
)

## [1] "6A_7" "6A_8" "6A_9" "6B_7" "6B_8" "6B_9"

pe <- renameColname(pe,
  i = "peptideRaw",
  newNames)
pe <- renamePrimary(pe, newNames)
colnames(pe[["peptideRaw"]])

## [1] "6A_7" "6A_8" "6A_9" "6B_7" "6B_8" "6B_9"
```

In the following code chunk, we add the spikein condition that we can read in the raw file name to the colData.

```
colData(pe)$condition <-  
  colnames(pe[["peptideRaw"]]) %>%  
  substr(start = 2, stop = 2) %>%  
  as.factor  
colData(pe)$condition
```

```
## [1] A A A B B B  
## Levels: A B
```

We calculate how many non zero intensities we have per peptide and this will be useful for filtering.

```
rowData(pe[["peptideRaw"]])$nNonZero <- rowSums(assay(pe[["peptideRaw"]]) > 0)
```

Peptides with zero intensities are missing peptides and should be represent with a NA value rather than 0.

```
pe <- zeroIsNA(pe, "peptideRaw") # convert 0 to NA
```

2.1 Data exploration

45% of all peptide intensities are missing and for some peptides we do not even measure a signal in any sample.

3 Preprocessing

This section preforms preprocessing for the peptide data. This include

- log transformation,
- filtering and
- summarisation of the data.

3.1 Log transform the data

```
pe <- logTransform(pe, base = 2, i = "peptideRaw", name = "peptideLog")
```

3.2 Filtering

1. Handling overlapping protein groups

In our approach a peptide can map to multiple proteins, as long as there is none of these proteins present in a smaller subgroup.

```
pe <- filterFeatures(pe, ~ Proteins %in% smallestUniqueGroups(rowData(pe[["peptideLog"]])$Proteins))
```

```
## 'Proteins' found in 2 out of 2 assay(s)
```

2. Remove reverse sequences (decoys) and contaminants

We now remove the contaminants and peptides that map to decoy sequences.

```
pe <- filterFeatures(pe, ~Reverse != "+")
```

```
## 'Reverse' found in 2 out of 2 assay(s)
```

```
pe <- filterFeatures(pe, ~Potential.contaminant != "+")
```

```
## 'Potential.contaminant' found in 2 out of 2 assay(s)
```

3. Drop peptides that were only identified in one sample

We keep peptides that were observed at last twice.

```
pe <- filterFeatures(pe, ~ nNonZero >=2)
```

```
## 'nNonZero' found in 2 out of 2 assay(s)
```

```
nrow(pe[["peptideLog"]])
```

```
## [1] 7011
```

We keep 7011 peptides upon filtering.

3.3 Normalize the data using median centering

We normalize the data by subtracting the sample median from every intensity for peptide p in a sample i :

$$y_{ip}^{\text{norm}} = y_{ip} - \hat{\mu}_i$$

with $\hat{\mu}_i$ the median intensity over all observed peptides in sample i .

```
pe <- normalize(pe,
  i = "peptideLog",
  name = "peptideNorm",
  method = "center.median")
```


3.4 Explore normalized data

Upon the normalisation the density curves are nicely registered

```
pe[["peptideNorm"]] %>%
  assay %>%
  as.data.frame() %>%
  gather(sample, intensity) %>%
  mutate(condition = colData(pe)[sample, "condition"]) %>%
  ggplot(aes(x = intensity, group = sample, color = condition)) +
  geom_density()
```

```
## Warning: Removed 8167 rows containing non-finite outside the scale range
```

```
## (`stat_density()`).
```



We can visualize our data using a Multi Dimensional Scaling plot, eg. as provided by the `limma` package.

```
pe[["peptideNorm"]] %>%  
  assay %>%  
  limma::plotMDS(col = as.numeric(colData(pe)$condition))
```



The first axis in the plot is showing the leading log fold changes (differences on the log scale) between the samples.

We notice that the leading differences (log FC) in the peptide data seems to be driven by technical variability. Indeed, the samples do not seem to be clearly separated according to the spike-in condition.

3.5 Summarization to protein level

- By default robust summarization is used: `fun = MsCoreUtils::robustSummary()`

```
pe <- aggregateFeatures(pe,
  i = "peptideNorm",
  fcol = "Proteins",
  na.rm = TRUE,
  name = "protein")
```

```
## Your quantitative and row data contain missing values. Please read the
## relevant section(s) in the aggregateFeatures manual page regarding the
## effects of missing values on data aggregation.
```

```
plotMDS(assay(pe[["protein"]]), col = as.numeric(colData(pe)$condition))
```



Note that the samples upon robust summarisation show a clear separation according to the spike-in condition in the second dimension of the MDS plot.

4 Data Analysis

4.1 Estimation

We model the protein level expression values using `msqrob`. By default `msqrob2` estimates the model parameters using robust regression.

We will model the data with a different group mean. The group is incoded in the variable `condition` of the `colData`. We can specify this model by using a formula with the factor condition as its predictor: `formula = ~condition`.

Note, that a formula always starts with a symbol `~`.

```
pe <- msqrob(object = pe, i = "protein", formula = ~condition)
```

4.2 Inference


First, we extract the parameter names of the model by looking at the first model. The models are stored in the row data of the assay under the default name `msqrobModels`.

```
getCoef(rowData(pe[["protein"]])$msqrobModels[[1]])
```

```
## (Intercept) conditionB
## -2.672396    1.513682
```

We can also explore the design of the model that we specified using the the package `ExploreModelMatrix`

```
library(ExploreModelMatrix)
VisualizeDesign(colData(pe), ~condition)$plotlist[[1]]
```




Spike-in condition A is the reference class. So the mean log2 expression for samples from condition A is '(Intercept)'. The mean log2 expression for samples from condition B is '(Intercept)+conditionB'. Hence, the average log2 fold change between condition b and condition a is modelled using the parameter 'conditionB'. Thus, we assess the contrast 'conditionB = 0' with our statistical test.

```
L <- makeContrast("conditionB=0", parameterNames = c("conditionB"))
pe <- hypothesisTest(object = pe, i = "protein", contrast = L)
```

4.3 Plots

4.3.1 Volcano-plot

```
volcano <- ggplot(rowData(pe[["protein"]])$conditionB,
  aes(x = logFC, y = -log10(pval), color = adjPval < 0.05)) +
  geom_point(cex = 2.5) +
  scale_color_manual(values = alpha(c("black", "red"), 0.5)) + theme_minimal()
volcano
```

Note, that 20 proteins are found to be differentially abundant.

4.3.2 Heatmap

We first select the names of the proteins that were declared significant.

```
sigNames <- rowData(pe[["protein"]])$conditionB %>%
  rownames_to_column("protein") %>%
  filter(adjPval<0.05) %>%
  pull(protein)
heatmap(assay(pe[["protein"]])[sigNames, ])
```



The majority of the proteins are indeed UPS proteins. 1 yeast protein is returned. Note, that the yeast protein indeed shows evidence for differential abundance.

4.3.3 Boxplots

We make boxplot of the log2 FC and stratify according to the whether a protein is spiked or not.

```
rowData(pe[["protein"]])$conditionB %>%
  rownames_to_column(var = "protein") %>%
  ggplot(aes(x=grepl("UPS",protein),y=logFC)) +
  geom_boxplot() +
  xlab("UPS") +
  geom_segment(
    x = 1.5,
    xend = 2.5,
    y = log2(0.74/0.25),
    yend = log2(0.74/0.25),
    colour="red") +
  geom_segment(
    x = 0.5,
    xend = 1.5,
    y = 0,
    yend = 0,
    colour="red") +
  annotate(
    "text",
    x = c(1,2),
```

```


y = c(0, log2(0.74/0.25)) + .1,
label = c(
  "log2 FC Ecoli = 0",
  paste0("log2 FC UPS = ", round(log2(0.74/0.25), 2))
),
colour = "red")

```

```

## Warning: Removed 167 rows containing non-finite outside the scale range
## (`stat_boxplot()`).

```



What do you observe?

4.3.4 Detail plots

We first extract the normalized peptideRaw expression values for a particular protein.

```

for (protName in sigNames)
{
  pePlot <- pe[protName, , c("peptideNorm", "protein")]
  pePlotDf <- data.frame(longFormat(pePlot))
  pePlotDf$assay <- factor(pePlotDf$assay,
    levels = c("peptideNorm", "protein"))
  pePlotDf$condition <- as.factor(colData(pePlot)[pePlotDf$colname, "condition"])

  # plotting
  p1 <- ggplot(data = pePlotDf,
    aes(x = colname, y = value, group = rowname)) +


```

```


geom_line() +
geom_point() +
theme(axis.text.x = element_text(angle = 70, hjust = 1, vjust = 0.5)) +
facet_grid(~assay) +
ggtitle(protName)
print(p1)

# plotting 2
p2 <- ggplot(pePlotDf, aes(x = colname, y = value, fill = condition)) +
  geom_boxplot(outlier.shape = NA) +
  geom_point(
    position = position_jitter(width = .1),
    aes(shape = rowname)) +
  scale_shape_manual(values = 1:nrow(pePlotDf)) +
  labs(title = protName, x = "sample", y = "peptide intensity (log2)") +
  theme(axis.text.x = element_text(angle = 70, hjust = 1, vjust = 0.5)) +
  facet_grid(~assay)
print(p2)
}

```




O00762ups|UBE2C_HUMAN_UPS




P00918ups|CAH2_HUMAN_UPS




P00918ups|CAH2_HUMAN_UPS



P01031ups|CO5_HUMAN_UPS




P01031ups|CO5_HUMAN_UPS



P01127ups|PDGFB_HUMAN_UPS




P01127ups|PDGFB_HUMAN_UPS



P01344ups|IGF2_HUMAN_UPS




P01344ups|IGF2_HUMAN_UPS





P01375ups|TNFA_HUMAN_UPS






P02144ups|MYG_HUMAN_UPS






P02787ups|TRFE_HUMAN_UPS




P02787ups|TRFE_HUMAN_UPS




- + ASYLDCIR
- × CSTSSLLEACTFR
- ◇ FDEFFSEGCAPGSKK
- ▽ HQTVPQNTGGK
- ▣ HQTVPQNTGGKNPDPWAK
- * IECVSAETTEDCIAK
- ⊕ KASYLDCIR
- ⊕ KPVDEYKDCHLAQVPSHTVVAR
- ⊗ KPVEEYANCHLAR
- ⊗ LKCDEWSVNSVGK
- ⊗ NLREGTCPEAPTDECKPVK
- ⊗ P02787ups|TRFE_HUMAN_UPS
- SASDLTWDNLK
- SHTAVGR
- ▲ SETKDLLFRDDTVCLAK
- ◆ SVIPSDGPSVACVK
- YLGEEYVK

condition


P06732ups|KCRM_HUMAN_UPS




P06732ups|KCRM_HUMAN_UPS



P07339ups|CATD_HUMAN_UPS




P07339ups|CATD_HUMAN_UPS



P08311ups|CATG_HUMAN_UPS




P08311ups|CATG_HUMAN_UPS





P10636-8ups|TAU_HUMAN_UPS





P12081ups|SYHC_HUMAN_UPS







P51965ups|UB2E1_HUMAN_UPS




P51965ups|UB2E1_HUMAN_UPS








P63165ups|SUMO1_HUMAN_UPS




P63165ups|SUMO1_HUMAN_UPS




P63279ups|UBC9_HUMAN_UPS







P99999ups|CYC_HUMAN_UPS




P99999ups|CYC_HUMAN_UPS



Q06830ups|PRDX1_HUMAN_UPS




Q06830ups|PRDX1_HUMAN_UPS



sp|Q06338|BCP1_YEAST





Note, that the yeast protein is only covered by 3 peptides. Only one peptide is picked up in condition A. This peptide is also only once observed in spike-in condition B. This puts a considerable burden upon the inference and could be avoided by more stringent filtering.

5 Session Info

With respect to reproducibility, it is highly recommended to include a session info in your script so that readers of your output can see your particular setup of R.

```
sessionInfo()
```

```
## R version 4.4.0 RC (2024-04-16 r86468)
## Platform: aarch64-apple-darwin20
## Running under: macOS Big Sur 11.6
##
## Matrix products: default
## BLAS: /Library/Frameworks/R.framework/Versions/4.4-arm64/Resources/lib/libRblas.0.dylib
## LAPACK: /Library/Frameworks/R.framework/Versions/4.4-arm64/Resources/lib/libRlapack.dylib; LAPACK v
##
## locale:
## [1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8
##
## time zone: Europe/Brussels
## tzcode source: internal
##
## attached base packages:
```

```

## [1] stats4      stats      graphics  grDevices utils      datasets  methods
## [8] base
##
## other attached packages:
## [1] ExploreModelMatrix_1.16.0  plotly_4.10.4
## [3] msqrob2_1.12.0             QFeatures_1.14.2
## [5] MultiAssayExperiment_1.30.3 SummarizedExperiment_1.34.0
## [7] Biobase_2.64.0             GenomicRanges_1.56.1
## [9] GenomeInfoDb_1.40.1       IRanges_2.38.1
## [11] S4Vectors_0.42.1          BiocGenerics_0.50.0
## [13] MatrixGenerics_1.16.0     matrixStats_1.4.1
## [15] limma_3.60.5              lubridate_1.9.3
## [17] forcats_1.0.0            stringr_1.5.1
## [19] dplyr_1.1.4              purrr_1.0.2
## [21] readr_2.1.5              tidyr_1.3.1
## [23] tibble_3.2.1             ggplot2_3.5.1
## [25] tidyverse_2.0.0
##
## loaded via a namespace (and not attached):
## [1] rlang_1.1.4              magrittr_2.0.3          shinydashboard_0.7.2
## [4] clue_0.3-65              compiler_4.4.0          vctrs_0.6.5
## [7] reshape2_1.4.4          ProtGenerics_1.36.0    pkgconfig_2.0.3
## [10] crayon_1.5.3            fastmap_1.2.0          XVector_0.44.0
## [13] fontawesome_0.5.2       labeling_0.4.3         utf8_1.2.4
## [16] promises_1.3.0          rmarkdown_2.28         tzdb_0.4.0
## [19] UCSC.utils_1.0.0        nloptr_2.1.1           xfun_0.47
## [22] zlibbioc_1.50.0         cachem_1.1.0           jsonlite_1.8.9
## [25] later_1.3.2             highr_0.11             DelayedArray_0.30.1
## [28] BiocParallel_1.38.0     parallel_4.4.0         cluster_2.1.6
## [31] R6_2.5.1                bslib_0.8.0            stringi_1.8.4
## [34] boot_1.3-31             jquerylib_0.1.4        Rcpp_1.0.13
## [37] knitr_1.48              BiocBaseUtils_1.6.0    httpuv_1.6.15
## [40] Matrix_1.7-0            splines_4.4.0          igraph_2.0.3
## [43] timechange_0.3.0        tidyselect_1.2.1       rstudioapi_0.16.0
## [46] abind_1.4-8             yaml_2.3.10            codetools_0.2-20
## [49] lattice_0.22-6         plyr_1.8.9             shiny_1.9.1
## [52] withr_3.0.1            evaluate_1.0.0         pillar_1.9.0
## [55] DT_0.33                shinyjs_2.1.0          generics_0.1.3
## [58] hms_1.1.3              munsell_0.5.1          scales_1.3.0
## [61] minqa_1.2.8            xtable_1.8-4           glue_1.8.0
## [64] lazyeval_0.2.2         tools_4.4.0            data.table_1.16.0
## [67] lme4_1.1-35.5          cowplot_1.1.3          grid_4.4.0
## [70] MsCoreUtils_1.16.1     colorspace_2.1-1       nlme_3.1-166
## [73] GenomeInfoDbData_1.2.12 cli_3.6.3              fansi_1.0.6
## [76] S4Arrays_1.4.1         viridisLite_0.4.2     AnnotationFilter_1.28.0
## [79] gtable_0.3.5           rintrojs_0.3.4         sass_0.4.9
## [82] digest_0.6.37          SparseArray_1.4.8      htmlwidgets_1.6.4
## [85] farver_2.1.2           htmltools_0.5.8.1     lifecycle_1.0.4
## [88] httr_1.4.7             mime_0.12              statmod_1.5.0
## [91] MASS_7.3-61

```