Lesson 6 - MEV

Front Running Attacks on Blockchain

"Front-running is a course of action where someone benefits from early access to market information about upcoming transactions and trades"

Financial Systems that have transparency with respect to their transactions are somewhat unique.

From https://hackmd.io/@flashbots/quantifying-REV

Maximal (formerly Miner) Extractable Value is the value that can be extracted from a blockchain by any agent without special permissions. Considering this permissionless nature, any agent with transaction ordering rights will be in a privileged position to perform the extraction.

There are features of Ethereum (and other blockchains) that allow front running

- 1. All transactions are available in a public mempool before they are mined
- 2. All transaction data is public
- 3. Transactions can be cloned

Introductory Video


https://www.youtube.com/watch?v=UZ-NNd6yjFM

GENERIC FRONT RUNNING BOTS

The above example shows how bots can extract value to a transaction irrespective of the contract called.

Useful Overview - MEV Wiki





A Taxonomy of Front-running Attacks

Attack types

- displacement
- insertion
- suppression

DISPLACEMENT ATTACK

It is not important to the adversary for Alice's function call to run after Mallory runs her function. Alice's can be orphaned or run with no meaningful effect.

Examples of displacement include:

- Alice trying to register a domain name and Mallory registering it first
- Alice trying to submit a bug to receive a bounty and Mallory stealing it and submitting
 it first
- Alice trying to submit a bid in an auction and Mallory copying it.

INSERTION ATTACK

In an insertion attack (sandwich), after Mallory runs her function, the state of the contract is changed and she needs Alice's original function to run on this modified state.

For example, if Alice places a purchase order on a blockchain asset at a higher price than the best offer, Mallory will insert two transactions: she will purchase at the best offer price and then offer the same asset for sale at Alice's slightly higher purchase price.

If Alice's transaction is then run after, Mallory will profit on the price difference without having to hold the asset

Example



SUPPRESSION ATTACK

The attacker wants to delay Alice running her function, but is then indifferent to what happens.

Used in an attack of a gambling DApp

The process of competing for priority in the block is known as a Priority Gas Auction.

From MEV and Me

IS MEV UNIQUE TO ETHEREUM?

No, hypothetically MEV can also be seen on Bitcoin. The incentives to censor Lightning channels or to double-spend colored coins are technically MEV.

(https://research.paradigm.xyz/MEV#fn:1) Bitcoin is inherently less exposed to MEV than blockchains like Etheruem.

The reason for that lies in the complexity and "statefulness" of the respective blockchain:

- 1. The rate at which MEV accumulates on a given blockchain is generally proportional to the complexity of its application-layer behavior.
- 2. Arbitrarily flexible protocols, such as Ethereum, cannot bound this complexity and are inherently biased towards greater complexity over time.
- 3. MEV incentives cannot be easily mitigated without altering Ethereum's UX.

Ethereum's complexity may be a curse.

Who is doing this?

From MEV and Me (Feb 2021)

The defining feature of Ethereum's current era is that most miners are not attempting to exploit MEV themselves (yet). Nearly all of the current activity is driven by non-mining traders. However, some MEV can only be captured by miners, because they have the authority to arbitrarily order (or exclude) transactions. Non-mining traders can access a strictly smaller subset of "simple" MEV; "complex" preferences cannot be efficiently expressed through PGA's.

Ethereum is a dark forest

https://www.paradigm.xyz/2020/08/ethereum-is-a-dark-forest/

"On Wednesday afternoon, someone asked whether it was possible to recover Uniswap liquidity tokens that had been accidentally sent to the pair contract itself."

When anyone calls the burn function on a Uniswap core contract, the contract measures its own liquidity token balance and burns it, giving the withdrawn tokens to the address specified by the caller.

I found the contract. The liquidity tokens were still there—and were worth around \$12,000.

"Because I'm a professional DeFi thought leader, I had never actually deployed a contract to Ethereum before."

IDEA

Deploy a Getter contract which, when called by its owner, would make the burn call ONLY if activated, and otherwise revert.

Deploy a Setter contract which, when called by its owner, would activate the Getter contract.

Submit the set transaction and the get transaction in the same block.

To our surprise, the get transaction would get rejected by Infura even when we manually overrode the gas estimator. After several failed attempts and resets, the time pressure got to us, and we got sloppy. We let the second transaction slip into a later block.

It was a fatal mistake.

Our get transaction did get included—but with a UniswapV2:

INSUFFICIENT_LIQUIDITY_BURNED error, meaning the liquidity was gone. It turned out that, in the seconds after our get transaction entered the mempool, someone had executed the call and swept the funds.

Escaping the dark forest

https://samczsun.com/escaping-the-dark-forest/

On September 15, 2020, a small group of people worked through the night to rescue over 9.6MM USD from a vulnerable smart contract.

Lien Finance held 25K ETH (\$9.6M), but anyone could with a simple transaction mint, then burn tokens which would transfer the 25K ETH to themselves.

The Lien Finance team are anonymous, so how to prevent this / or reach out to the right team without divulging the exploit?

Sam Sun eventually reached the team via some auditors they had worked with.

What was needed was an infrastructure solution, so they contacted Spark Pool who were developing their Taichi Network, their co founder Shaoping Zhang offered to help.

"I brought the whitehats' request to our development team, and explained the urgency: our private transaction feature needed to be in production within a few hours. Our devs said they could try their best to finish in time, and we immediately got to work. We finished development of the private transaction feature in 2 hours, and then spent some time fixing bugs."

Scott Bigelow and Sam were developing the script to generate 4 sequential signed transactions to save the 25K ETH

This involved setting up some tokens that could eventually be burnt by the Lien team to release the 25K ETH.


They sent a test transaction to the Taichi network and watched the mempool, it didnt appear, then suddenly appeared in a block, the private network was working.

They then ran in the real transactions, and waited..... only a portion of Spark Pools hashrate was being used for the private network.

Everyone watched etherscan nervously

After about 15 blocks the transactions appeared in order, and slowly more blocks were built in top, reducing the possibility of a chain re org.

The Lien team were then able to send a transaction to withdraw the ETH at risk



Illuminating the dark forest

https://extropy-io.medium.com/illuminating-the-dark-forest-748d915eeaa1

Mitigation

Some approaches

Send transactions privately to miners via networks such as (Taichi - no longer running) or Flashbots Auction

Flashbots Auction

Flashbots Auction provides a private communication channel between Ethereum users and miners for efficiently communicating preferred transaction order within a block.

Flashbots Auction consists of mev-geth, a patch on top of the go-ethereum client, along with the mev-relay, a transaction bundle relayer.

There is a private transaction pool + a sealed bid blockspace auction mechanism which allows block producers to trustlessly outsource the work of finding optimal block construction.


Any miner or mining pool can run MEV-geth and receive additional income from MEV strictly more than what it would earn from running vanilla geth, without the need to enter into any bespoke deal with traders.

However we still rely on miners not to front run us.

SEARCHERS


Typically these will be

- 1. Ethereum bot operators looking for fast, and risk free access to blockspace (for example, arbitrage and liquidation bots)
- 2. Ethereum users looking for frontrunning protection on their transactions (for example, Uniswap traders)
- Ethereum Dapps with advanced use cases like account abstraction or gasless transactions (for example, tornado.cash and mistX)



RELAYERS

A relayer is a bundle propagation service which receives bundles from searchers and forwards them to miners.



The searchers specify their bids by either

- gas price, or
- direct eth transfer to the coinbase address.

An important change to the crypto economics occurs because the searchers do not need to pay for failed bids, incentivising them to spam the system with bids.


According to a Flashbots report (Feb 2021)

At the time of writing, there are 5 mining pools running MEV-geth, collectively accounting for over 12% of total Ethereum hashrate, collecting 0.13ETH per block of additional MEV revenue from Flashbots transaction bundles. On the MEV searcher side, we are seeing a 3x increase in unique searchers who have successfully landed bundles on chain.

Submarine Sends

See Submarine sends

This is a commit reveal scheme can be used (possibly with other obfuscating transactions)



Attempts to trick bits

Salmonella

Salmonella intentionally exploits the generalised nature of front-running setups. The goal of sandwich trading is to exploit the slippage of unintended victims, so this strategy turns the tables on the exploiters. It's a regular ERC20 token, which behaves exactly like any other ERC20 token in normal use-cases. However, it has some special logic to detect when anyone other than the specified owner is transacting it, and in these situations it only returns 10% of the specified amount - despite emitting event logs which match a trade of the full amount.

DeFi protocol changes

- 1. Protocols can whitelist bots that will share the MEV from arbitrage or liquidation with the user being front run
- 2. Enhancements to the DeFi protocols, for example with Request For Quote (RFQ) orders to specify which address will have their order filled, or progressive liquidations from Euler

Mistx

launched by Alchemist using Flashbots technology Features

- no Gas fees for transactions (bribes are paid to miners in tokens)
- MEV-proof


Archer Swap

Uses Archer Relay which works with miners to find the most valuable trades for them and allows them to submit them to the ethereum mainnet.

Secret Swap

SecretSwap is a cross chain AMM built on Cosmos and Tendermint It has an encrypted Mempool

Users will have to pay for gas and 0.3% swap fees with the \$SCRT token to use Secret Swap.



Cow Swap

CowSwap is a DEX and DEX aggregator hybrid backed by Gnosis Protocol V2 (GPv2) which is developed by Gnosis team in order to provide MEV protection. GPv2 optimizes for coincidence of wants (CoWs), which can be explained as "an economic phenomenon where two parties each hold an item the other wants, so they exchange these items directly.", i.e. peer-to-peer transactions can be matched without having to go through a regular AMMs like Uniswap or Sushiswap. One of the benefits of this is that off-chain transactions will cost a lot less and be faster.

CowSwap brings in 'Solver' conception to realize this function. Solvers are encouraged to compete against each other to deliver the best order settlement for traders in exchange for the reward of each batch. CowSwap will use a united price to settle all orders in the same

batch, which is called batch auction mechanism. This process is very similar to Ethereum meta-transactions proposed in 2018.

Protocol Approaches

Some protocols have taken steps to prevent MEV such as using Verifiable Delay Functions in order to prevent gaming of transaction ordering, as Solana has done on its base layer to ensure transactions are ordered by time of arrival, or simply delegate ordering to something like Chainlink's Fair Sequencing Service (FSS).