

PRODUCT DESCRIPTION

SpackleFlex is a one-component, water-based flexible polymer repair putty for roof leaks, supplied ready to use from the factory. It seals the classic leak points of Thai roofs — fastener heads, sheet joints and roof-to-wall junctions — in a single product, on every roof type: metal sheet, corrugated tile, cement tile and zinc (concrete rooftop decks excluded — those are full-surface waterproofing work). Roofs expand and contract with temperature day and night, and rigid repair materials crack with them; the SpackleFlex body stays highly flexible and moves with the roof, and its white polymer is UV-stabilised for far longer outdoor life than ordinary silicone sealant. Repaired samples have passed months of continuous immersion in the Lucerna soak tank with the body intact, firmly bonded and free of swelling — ponding water in roof channels is within its design duty.

KEY DATA

Type	One-component water-based flexible polymer roof repair putty — ready to use
Colour	White — reflects heat on the roof
Suitable roofs	Metal sheet, corrugated tile, cement tile, zinc — all pitched roof types. NOT for concrete rooftop decks (use a full-surface waterproofing system there).
Repairs	Fastener heads · sheet joints and seams · roof-to-wall junctions and flashing lines
Consistency	Thick white cream — applies by putty knife (tub) or caulking gun (cartridge). Not brushable; not a full-surface coating product.
Set time	At least 6 hours before rain, service, or overcoating
Overcoating	Optional, for maximum service life: after 6 hours, coat over with LucernaPro SiliconePro or Exotic
Pack sizes	350 g cartridge (caulking gun) · 1 kg tub (putty knife) · 20 kg pail
Dilution	NEVER dilute with water or thinner — dilution destroys the designed flexibility and water resistance
Clean-up	Plain water, while the material is still fresh. Reseal the container airtight; material keeps for later use.
Storage	Keep tightly closed in a cool, shaded place. Protect from direct sun, heat build-up and freezing. Keep out of reach of children.

SURFACE PREPARATION

The surface must be completely dry, clean and free of dust and grease before filling — applied over a wet or damp surface, adhesion is lost before the repair begins. Check the weather first: do not apply when the surface is wet or rain is expected within 6 hours.

APPLICATION

Ready to use — open and apply; never mix anything in. Press the material over the repair area with a putty knife, or run a continuous bead from the cartridge along joint lines, until the point is covered completely with no holes or breaks — water always finds a hole, so the film must be one continuous body. Work point by point along fastener lines and seams without skipping. Allow at least 6 hours to set before the repair meets rain or before overcoating. Roof safety always comes first: non-slip footwear, step on the purlin lines, never mid-sheet.

LIMITATIONS

Roof work only. The body is engineered for maximum flexibility, and the trade-off is stated plainly: the cured surface cannot be sanded or painted over — do not use it on walls, furniture or any repair that must be finished with paint. It is a spot-and-seam repair putty, not a coating: for full-surface work, use a brush-applied waterproofing system instead.

HEALTH & SAFETY

Water-based, non-flammable, low odour. Avoid contact with eyes and prolonged contact with skin; rinse with plenty of water. Do not ingest. Ensure normal ventilation during application and drying. Keep out of reach of children. Dispose of residues in accordance with local regulations.