

PRODUCT DESCRIPTION

PondMax is a two-component, high-solids polymer coating with very low solvent content, engineered specifically for fish ponds and permanently submerged environments. The system is based on a moisture-tolerant modified polyaminoamide curing technology powered by Huntsman Advanced Materials, allowing application directly onto damp substrates without primer. Once fully cured, the film forms a tough, seamless, puncture-resistant membrane that is non-toxic and safe for aquatic life.

KEY DATA

Chemistry	Two-component high-solids polymer / modified polyaminoamide curing system
Solvent content	Very low (high-solids formulation)
Colours	Grey · Blue · Black
Packaging	1 kg · 2.5 kg · 5 kg kits (Part A + Part B pre-measured)
Mix ratio (A : B)	2 : 1 by weight — measure by scale, do not estimate
Pot life	Approx. 15 minutes at 30 °C — mix only what can be applied in time
Recoat interval	Approx. 6 hours per coat
Number of coats	2 coats (standard system)
Coverage	Approx. 5 m ² per kg — complete two-coat system
Full cure / water fill	2–3 days recommended before filling and introducing fish
Application	Roller or brush

SUBSTRATES & SURFACE PREPARATION

Suitable for concrete, cement render and glazed ceramic tile. Surfaces must be sound, clean and free of dust, algae, oil and laitance. Fill all cracks and holes completely before coating. Damp or matt-wet surfaces are acceptable; standing water must be removed before application. Glazed tile: always abrade the surface to a rough profile before coating for long-term film security.

AQUATIC SAFETY

The high-solids, low-solvent formulation contains no substances that leach into water once fully cured, and does not present the alkalinity problems of bare cementitious ponds. Rinse the pond once after full cure, then fill and introduce fish.

HEALTH & SAFETY

Before cure, Part B is corrosive and causes serious skin and eye irritation. Wear protective gloves and eye protection during mixing and application, and ensure ventilation when working inside deep ponds. Refer to the GHS pictograms on the product label. For professional and industrial use. Keep uncured material away from children and animals.

STORAGE

Store in the original sealed containers in a dry place away from direct sunlight. Keep Part A and Part B separated until use.