

PRODUCT DESCRIPTION

DeepSeal is a single-component, ready-to-use negative-side waterproofing liquid, engineered to stop water ingress from the inside of a structure where the exterior face cannot be reached — party walls of townhouses, condominium units, basements and similar enclosed spaces. It is based on one-component moisture-curing **HydroCure Polymer technology powered by Covestro**. Applied by brush or roller onto bare concrete, the liquid penetrates open pores, capillaries and micro-cracks; overnight it reacts with substrate and ambient moisture to form a tough, flexible, firmly anchored film that resists negative hydrostatic pressure without blistering or peeling. The cured film is clear amber, low-odour (Low VOC) and can be rendered or painted over, making the system suitable for finished interior spaces.

KEY DATA

Chemistry	One-component moisture-curing HydroCure Polymer — powered by Covestro
Supplied form	Ready-to-use liquid, single component — no mixing, no thinning, no accelerators
Application	Brush or roller, applied generously (saturating) onto clean, bare concrete
Substrate condition	Bare concrete, dry to slightly damp — no standing water in the application area
Coats	1 saturating coat; on highly porous substrates an optional 2nd coat may be applied cross-wise once the first coat becomes tack-dry
Cure	Overnight cure by design — allow 12–24 hours before any further work
Overcoating	Render / skim-coat or paint after the film has dried completely
Film appearance	Clear amber — discolours under prolonged UV exposure; intended for interior use, topcoat exposed areas
Coverage	1 kg ≈ 2–5 m ² depending on substrate porosity (0.5 kg ≈ 1–2.5 m ² · 5 kg ≈ 10–25 m ²)
Packaging	0.5 kg · 1 kg · 5 kg

NOTE ON VALUES

Coverage varies strongly with the porosity of the substrate — the liquid is designed to soak into the concrete, not merely coat it. Figures in this document are typical guidance only and are not a specification.

APPLICATION NOTES

- Surface preparation is the most important step of the system: grind or strip off paint, render, oil and any contamination down to bare concrete, opening the pores so the liquid can penetrate as deeply as possible.
- Repair wide cracks and large spalls first: rout the crack open, fill with a structural repair filler (e.g. LucernaPro FillerAce) and allow to dry before applying DeepSeal.
- Do not add accelerators, thinners or any other substance — the product is formulated to be used exactly as supplied.
- Apply generously and work the liquid into joints, corners and fine crack lines — these are the classic leak paths.
- The overnight cure is intentional: it gives the liquid time to penetrate the structure before film formation. Do not rush subsequent trades; wait until the film is completely dry before rendering or painting over.
- A topcoat of paint is recommended for any area exposed to light — unprotected surfaces of this polymer system discolour under prolonged UV exposure (appearance only; performance is not reduced).
- Reseal the can tightly immediately after use — the liquid reacts with airborne moisture and will deteriorate in an open or poorly sealed container.

HEALTH & SAFETY

Uncured material contains an aromatic isocyanate prepolymer and may cause skin and respiratory sensitisation. Wear protective gloves and eye protection; avoid skin contact with uncured material; ensure good ventilation, especially in basements and enclosed rooms. Fully cured material is inert. Keep uncured material away from children and animals. Refer to the Safety Data Sheet for full information.

STORAGE

Store in the original sealed container in a dry place at 10–30 °C away from direct sunlight and heat. The liquid is moisture-sensitive — reseal immediately after use. Shelf life 12 months unopened.

Lucerna Co., Ltd. · 23 Suriyat Rd. Soi 4, Nai Mueang, Mueang, Ubon Ratchathani 34000, Thailand
Tel 062-005-7933 · Lucernapro@yahoo.com · www.lucernapro.com

The information herein is given in good faith based on our current knowledge and practical experience. Coverage and drying behaviour depend on substrate and site conditions; values are typical guidance only and do not constitute a specification. Users must verify suitability for their intended application. Made in Thailand.