



、
=]

Material Safety Data Sheet (MSDS)

This MSDS is authoring based on the data supplied by and identified on behalf of the client.

Sample Name: Feibo self-cleaning coating

Client Name: Hunan Feibo Environmental Protection Technology Co., Ltd

Client Address: Room 304, Building 7, R&D Headquarters, Central South University Science Park, Yuelu District, Changsha City, Hunan Province

MSDS No.: 2025052310E

Issue Date: May 23, 2025

Signed for and on behalf of
JINHUA HEBIAO TESTING TECHNOLOGY CO., LTD

Approved signature: David Chen



WuCheng City Square, 2999 Binhong West Road, WuCheng District, Jinhua City, Zhejiang Province, China | +86-18768438565 |

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. We make no warranty, expressed or implied, with respect to this information and disclaim all liabilities from reliance on it.

Material Safety Data Sheet (MSDS)

MSDS No.: 2025052310E
Creation Date: May 23, 2025
Page 1 / 15

1. Identification of the Substances/Preparation and of the Company/Undertaking

Product Identification:

Product Name: Feibo self-cleaning coating
Other Name: Photovoltaic self-cleaning antireflective coating

Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Coating solution.
Use advised against: No data available.

Details of the Manufacturer or supplier

Supplier: Hunan Feibo Environmental Protection Technology Co., Ltd.
Address: Room 304, Building 7, R&D Headquarters, Central South University Science Park, Yuelu District, Changsha City, Hunan Province.
Telephone: +86-139-74929383
Email: 780769464@qq.com

Emergency telephone number

Emergency Telephone: +86-731-89875607

2. Hazards Identification

Classification of the substance or mixture

GHS Classification: Flammable liquids, category 2, H225
Serious eye damage/eye irritation, category 1, H318
Specific target organ toxicity - single exposure (Category 3), Narcotic effects, H336

GHS Label elements, including precautionary statements

Pictogram(s):



Signal Word: Danger
Hazard Statement: H225: Highly flammable liquid and vapour.
H318: Causes serious eye damage.
H336: May cause drowsiness or dizziness.

Precautionary statements:

Material Safety Data Sheet (MSDS)

MSDS No.: 2025052310E
Creation Date: May 23, 2025
Page 2 / 15

Prevention precautionary statements:	P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking P233: Keep container tightly closed P240: Ground/bond container and receiving equipment P241: Use explosion-proof electrical/ventilating/light/.../equipment P242: Use only non-sparking tools P243: Take precautionary measures against static discharge P261: Avoid breathe dust/fume/gas/mist/vapours/spray P271: Use only outdoors or in a well-ventilated area P280: Wear protective gloves/protective clothing/eye protection/face protection
Response Precautionary Statements:	P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower P304 + P340 + P312: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P370+P378: In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Storage Precautionary Statements:	P405: Store locked up P403+P233+235: Store in a well ventilated place. Keep container tightly closed Keep cool
Disposal Precautionary Statements:	P501: Dispose of contents and container in accordance with local/regional/national /international regulations.

Description of any hazards not otherwise classified

None. See section 11 for more detailed information on health effects and symptoms.

3. Composition/Information on Ingredients

Chemical Characterization

Mixture. Consist of the following ingredients.

Composition:

Material Safety Data Sheet (MSDS)

MSDS No.: 2025052310E

Creation Date: May 23, 2025

Page 3 / 15

Components Name	CAS No.	Weight (%w/w)
Ethanol	64-17-5	30 ~ 35
Propan-1-ol	71-23-8	25 ~ 30
Titanium dioxide	13463-67-7	3 ~ 4
Butanenitrile, 4-(chlorodimethylsilyl)-, hydrolysis products with silica	68584-38-3	1 ~ 5
Propan-2-ol	67-63-0	1 ~ 5
1-Methoxy-2-propanol	107-98-2	0.1 ~ 1
Boric acid	10043-35-3	0.1>
Nitric acid	7697-37-2	0.1>
Silicate	Trade secrets	0.1>
Special resin	Trade secrets	0.1>
Water	7732-18-5	35 ~ 40

4. First-Aid Measures

Description of first aid measures:

- Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation occurs and persists, contact a doctor.
- Skin Contact:** Remove and isolate contaminated clothing and shoes. Wash off with soap and plenty of water. If irritation or a rash occurs, contact a doctor.
- Inhalation:** Move person into fresh air. If breathing is difficult, give oxygen. If not breathing give artificial respiration. Get medical attention if feel unwell.
- Ingestion:** If the person is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person. Consult a physician attention and get medical immediately.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in section 2 and section 11.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

5. Fire-Fighting Measures

Extinguishing media

Material Safety Data Sheet (MSDS)

MSDS No.: 2025052310E
Creation Date: May 23, 2025
Page 4 / 15

Suitable extinguishing media: Use water fog, dry chemical, carbon dioxide or alcohol-resistant foam. Use water fog to cool the unopened containers involved in fire.

Unsuitable extinguishing media: Do not use a solid water stream as it may scatter or spread fire.

Special hazards arising from the substance or mixture

Liquid and vapor are flammable. Vapor can form explosive mixture with air. Containers may explode when heated. Gives off irritating fumes (or gases) and combustion product (Carbon monoxide, carbon dioxide, etc.) in a fire.

Advice for firefighters

Evacuate personnel to safe areas. As in any fire, Wear self-contained breathing apparatus and full protective gear for firefighting. Fire fighting from a safe distance.

Further information

According to the standard chemical firefighting measures. Use water fog to cool down unopened container involved in fire. Prevent fire extinguishing water from contaminating surface water or the ground water source.

6. Accidental Release Measures

For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations.

Personal precautions, protective equipment and emergency procedures:

Evacuate area. Ventilate area. Remove all sources of ignition. Avoid direct contact with spillage. Avoid inhaling vapor. Use suitable personal protective equipment. For personal protection see section 8

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up:

Small quantities may be contained by inert material (sand, diatomite, acid binders, universal binders, sawdust).

For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Gather the spilled product and keep in suitable, closed containers for recycle or disposal (see section 13). Wash contaminated surface with plenty of water.

7. Handling and Storage

Material Safety Data Sheet (MSDS)

MSDS No.: 2025052310E

Creation Date: May 23, 2025

Page 5 / 15

Precautions for safe handling:

The usual precautionary measures for handling chemicals should be followed.

Use in well-ventilated area. Use appropriate, approved safety equipment as in section 8.

Avoid contact with skin and eyes. Avoid breathing vapor or mist.

Wash thoroughly after handling.

Keep away from heat/sparks/open flames/overheat.

No smoking. Take measures to prevent the buildup of electrostatic charge.

Keep container tightly closed when not in use.

Do not eat, drink or smoke at the workplace.

Keep away from incompatible materials. Equip with fire fight and accidental release equipment.

For precautions see section 2.

Conditions for safe storage, including any incompatibilities:

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Store away from foodstuffs. Do not store together with strong oxidizing agent. Keep away from heat/sparks/open flames/overheat. Equip with fire fight and accidental release equipment in storage area.

8. Exposure Controls/Personal Protection

Exposure Limits:

Substance	CAS No.	OSHA PEL	NIOSH REL	ACGIH
Ethanol	64-17-5	1000 ppm; 1900 mg/cm ³	1000 ppm	STEL: 1000 ppm
Propan-1-ol	71-23-8	200 ppm; 250 mg/cm ³	200 ppm (ST) 250 ppm	100 ppm
Titanium dioxide	13463-67-7	15 mg/cm ³	Ca(ultrafine particles) 2.4 mg/m ³ (fine) 0.3mg/m ³ (ultrafine)	10 mg/m ³
Butanenitrile, 4-(chlorodimethyl silyl)-, hydrolysis products with	68584-38-3	-	-	-

Material Safety Data Sheet (MSDS)

MSDS No.: 2025052310E

Creation Date: May 23, 2025

Page 6 / 15

silica				
Propan-2-ol	67-63-0	400 ppm; 980 mg/cm ³	400 ppm (ST) 500 ppm	200 ppm (ST) 400 ppm
1-Methoxy-2-prop anol	107-98-2	-	-	-
Boric acid	10043-35-3	-	-	-
Nitric acid	7697-37-2	2 ppm; 5 mg/cm ³	2 ppm (ST) 4 ppm	2 ppm (ST) 4 ppm
Silicate	Trade secrets	-	-	-
Special resin	Trade secrets	-	-	-
Water	7732-18-5	-	-	-

Exposure controls

Engineering Control: General industrial hygiene practice. Provide appropriate exhaust ventilation. Provide safe shower and eye wash fountain.

Personal protective equipment:

Respiratory Protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Eyes Protection: Use face shield and safety glasses if in-eye risk exists. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Body Protection: Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hands Protection: Handle with chemical-resistant gloves. Use proper glove removal technique(without touching glove's outer surface) to avoid skin contact with this product.

Other Protections: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. Physical and Chemical Properties

Material Safety Data Sheet (MSDS)

MSDS No.: 2025052310E

Creation Date: May 23, 2025

Page 7 / 15

Information on basic physical and chemical properties	
Appearance	Liquid.
Color	Milky white.
Odor	Solvent odor.
pH	4.2.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	81.1°C .
Flash point	24.5°C ASTM D 7094-17a (closed cup). 26.5°C ISO 13736-2021 (closed cup).
Evaporation rate	Not available.
Flammability	Flammable liquid and vapour.
Upper explosive limit %(V/V)	Not available.
Lower explosive limit %(V/V)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	2.02 g/cm3.
Solubility(ies)	Partly soluble in water.
Partition coefficient: n-octanol/water	Not available.
Ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and Reactivity

Stability: Stable under recommended storage conditions.

Conditions to Avoid: Heat, flames and sparks.

Incompatible materials: Strong oxidizing agents.

Hazardous Decomposition Products: Other decomposition products- no data available. In the event of fire: see section 5.

Possibility of hazardous reactions: No data available.

11. Toxicological Information

Material Safety Data Sheet (MSDS)

MSDS No.: 2025052310E
Creation Date: May 23, 2025
Page 8 / 15

Acute Toxicity:

Substance	CAS No.	LD50 oral - rat	LC50 inhalation - rat	LD50 skin - rabbit
Ethanol	64-17-5	7060mg/kg	20000ppm/10H	15800mg/kg

Skin Corrosion/Irritation:

No known irritation effect.

Serious Eye Damage/Eye

Causes serious eye damage.

Irritation:

Respiratory or Skin Sensitization

Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity:

None of the components of this product is listed as a carcinogen by IARC, NTP, US OSHA.

Reproductive Toxicity:

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure (Globally Harmonized System):

May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated Exposure (Globally Harmonized System):

Based on available data, the classification criteria are not met.

Aspiration Hazard:

Based on available data, the classification criteria are not met.

Potential Health Effects:

Inhalation:

Inhalation of high concentrations vapor may be harmful. May cause drowsiness or dizziness.

Skin Contact:

May cause skin irritation.

Eye Contact:

Causes serious eye damage.

Material Safety Data Sheet (MSDS)

MSDS No.: 2025052310E

Creation Date: May 23, 2025

Page 9 / 15

Ingestion: May be harmful if ingested.

12. Ecological Information

Toxicity

Hazards to the aquatic environment

[Use ingredient information to apply the classification based on addition of short-term (acute)]

Not included/cannot be classified as it does not contain ingredients that fall into the short-term (acute) category.

[Ingredient information for use: classification based on long-term (chronic)]

It does not belong/cannot be classified as it does not contain ingredients with a long-term (chronic) classification.

Component Data

Hazardous to the aquatic environment Short-term (acute)

[Data released by Japan]

(Ethanol)

Fish (medaka) LC50>100mg/L/96hr (EPA Ecological Impact Study, 1997)

At conventional application concentrations (<50 mg/L), short-term toxicity is negligible.

(n-Propanol)

Crustaceans (turbot) EC50 (swimming inhibition)>1000mg/L/48hr (Ecological Impact Study of the Ministry of Environment, 2018). At conventional application concentrations (<50 mg/L), short-term toxicity is negligible.

(Isopropyl alcohol)

Fish (medaka) LC50>100mg/L/96hr (EPA Ecological Impact Study, 1997)

At conventional application concentrations (<50 mg/L), short-term toxicity is negligible.

(propylene glycol methyl ether)

Crustaceans (turbot) EC50 (swimming inhibition)>1000mg/L/48hr (Ecological Impact Study of the Ministry of Environment, 2018). At conventional application concentrations (<50 mg/L), short-term toxicity is negligible.

(Nano-silicon dioxide)

Fish (medaka, zebrafish) and crustaceans (such as water fleas) LC50>100mg/L/96hr (Environmental Protection Agency Ecological Impact Study, 1997)

Material Safety Data Sheet

(MSDS)

MSDS No.: 2025052310E

Creation Date: May 23, 2025

Page 10 / 15

Examples of key data:

Zebrafish: 96-hour LC50 (median lethal concentration) is approximately 200-500 mg/L (different particle sizes/modifications).

Daphnia magna: 48-hour EC50 (half-maximal effect concentration) is approximately 100-300 mg/L.

At conventional application concentrations (<50 mg/L), short-term toxicity is negligible.

(Nano Titanium Dioxide)

Fish (medaka, zebrafish) and crustaceans (such as water fleas) LC50>100mg/L/96hr (Environmental Protection Agency Ecological Impact Study, 1997)

Examples of key data:

Zebrafish: 96-hour LC50 is approximately 100-200 mg/L without light exposure.

Daphnia magna: 48-hour EC50 is about 10-50 mg/L.

Chlorella vulgaris: 72 hours EC50 is about 5-20 mg/L.

At conventional application concentrations (<50 mg/L), short-term toxicity is negligible.

(Na₂Al₂Si₃O₁₀ · 2H₂O)

Zebrafish (Danio rerio): In short-term exposure (96 h), the median lethal concentration (LC50) of natural zeolites was generally above 100 mg/L, indicating low acute toxicity.

Daphnia (such as Daphnia magna): The half-maximal effect concentration (EC50, 48 hours) generally exceeds 500 mg/L, indicating that the acute risk to invertebrates is relatively low.

Algae: The growth inhibition concentration (EC50, 72 hours) of natural zeolite on algae (such as Chlorella) is usually higher than 1000 mg/L, and the short-term effect is limited.

At conventional application concentrations (<50 mg/L), short-term toxicity is negligible.

(Alcohol soluble acrylic resin)

Fish (e.g. zebrafish): LC50 (96 hours) may be in the range of 50-100 mg/L.

Daphnia (such as Daphnia magna): EC50 (48 hours) may be 30-50 mg/L.

Algae (such as green algae): EC50 (72-hour growth inhibition) may be 50-100 mg/L.

At conventional application concentrations (<10 mg/L), short-term toxicity is negligible.

Long-term (chronic) hazard to the aquatic environment

[Data released by Japan]

(Ethanol)

Crustaceans (turbot) NOEC>100 mg/L/21 days (EPA Ecological Impact Study, 1997)

(n-Propanol)

Crustaceans (turbot) NOEC (reproduction inhibition) = 1000 mg/L/21 days (Ecological Impact Study of

Material Safety Data Sheet

(MSDS)

MSDS No.: 2025052310E

Creation Date: May 23, 2025

Page 11 / 15

the Ministry of Environment, 2018)

(Isopropyl alcohol)

Crustaceans (turbot) NOEC>100 mg/L/21 days (EPA Ecological Impact Study, 1997)

(propylene glycol methyl ether)

Crustaceans (turbot) NOEC (reproduction inhibition) = 1000 mg/L/21 days (Ecological Impact Study of the Ministry of Environment, 2018)

(Nano-silicon dioxide)

Crustaceans (turbot) NOEC>100 mg/L/218 days (EPA Ecological Impact Study, 1997)

(Nano Titanium Dioxide)

Crustaceans (turbot) NOEC (reproduction inhibition) = 1000 mg/L/21 days (Ecological Impact Study of the Ministry of Environment, 2018)

($\text{Na}_2\text{Al}_2\text{Si}_3\text{O}_{10} \cdot 2\text{H}_2\text{O}$)

Algae (freshwater green algae) NOEC (reproduction inhibition) = 1000 mg/L/21 days (Ecological Impact Study of the Ministry of Environment, 2018)

Fish (such as zebrafish, carp) NOEC (reproduction inhibition) = 1000mg/L/28 days (Ecological Impact Study of the Ministry of Environment, 2018)

(Alcohol soluble acrylic resin)

Algae (freshwater green algae) NOEC (reproduction inhibition) = 1000 mg/L/21 days (Ecological Impact Study of the Ministry of Environment, 2018)

Fish (such as zebrafish, carp) NOEC (reproduction inhibition) = 1000mg/L/15 days (Ecological Impact Study of the Ministry of Environment, 2018)

Water Solubility

(Ethanol)

Completely miscible with water (25°C) (HSDB,2013)

(n-Propanol)

Limited solubility (8g/100ml) (ICSC, 2014)

(Isopropyl alcohol)

Insoluble in water (25°C) (HSDB,2013)

(propylene glycol methyl ether)

Completely miscible with water (ICSC, 2014)

(Nano-silicon dioxide)

It is insoluble in water, but can form a stable colloidal dispersion (pseudo-dissolution) through surface modification (such as hydroxylation). Unmodified nano-silica tends to aggregate and precipitate in

Material Safety Data Sheet

(MSDS)

MSDS No.: 2025052310E
Creation Date: May 23, 2025
Page 12 / 15

water (HSDB, 2013)

(Nano Titanium Dioxide)

The solubility of nano-TiO₂ in pure water is extremely low, usually <1 mg/L (close to insoluble). Its dissolution behavior is more inclined to form a colloidal suspension rather than true dissolution. (ICSC, 2014)

(Na₂Al₂Si₃O₁₀ · 2H₂O)

Insoluble in water (25°C) (HSDB, 2013)

(Alcohol soluble acrylic resin)

Limited solubility (5g/100ml) (ICSC, 2014)

Persistence and degradability

Component Data

(Ethanol)

Rapidly degradable (BOD degradation rate: 95% (existing inspection, 1993))

(n-Propanol)

Rapidly degradable (BOD degradation: 85% (chemical method DB: 1991))

(Isopropyl alcohol)

Rapidly degradable (BOD degradation rate: 86% (existing inspection, 1993))

(propylene glycol methyl ether)

Rapidly degradable (BOD degradation: 90% (chemical method DB: 1991))

(Nano-silicon dioxide)

Field degradation half-life (DT₅₀)

DT₅₀: No biodegradation, but environmental transformation exists.

Aggregation/sedimentation: dominant process, DT₅₀ in water is several days to several months (depending on conditions);

In soil: persists for a long time (on an annual scale) and can be dispersed through mechanical migration or biological disturbance.

(The U.S. EPA has included nanomaterials in the management of "new chemical substances", but there is no specific limit yet)

(Nano Titanium Dioxide)

Nano-TiO₂ is highly persistent in the environment, especially in soil and sediments where it can remain for a long time. Its degradation is highly dependent on light and chemical conditions, and the actual degradation rate in the natural environment is low.

The half-life of nano-titanium dioxide (10 nm) in fresh water under UV irradiation is 30-60 days, and it

Material Safety Data Sheet

(MSDS)

MSDS No.: 2025052310E

Creation Date: May 23, 2025

Page 13 / 15

is extended to more than 1 year without light (Environ. Sci. Technol., 2015)

($\text{Na}_2\text{Al}_2\text{Si}_3\text{O}_{10} \cdot 2\text{H}_2\text{O}$)

DT50: several hours to several days (fresh water, still water, PH=7), degradation mechanism is aggregation and sedimentation.

BOD5 degradation: 50% (ISO 14851)

(Alcohol soluble acrylic resin)

DT50: a few weeks to 6 months (fresh water, still water, pH=7) (depending on conditions);

BOD5 degradation: 50% (ISO 14851)

Bioaccumulative potential

Component Data

(Ethanol)

Log power (log BCF/BAF) = 0.05 (ICSC, 1999)

(n-Propanol)

Log power (log BCF/BAF) = 0.2 (ICSC, 2014)

(Isopropyl alcohol)

Log power (log BCF/BAF) = 0.05 (ICSC, 1999)

(propylene glycol methyl ether)

Log power (log BCF/BAF) = -0.92 (ICSC, 2014)

Component Data

(Nano-silicon dioxide)

Log power (log BCF/BAF) < 2 (ICSC, 1999)

(Nano Titanium Dioxide)

Logarithmic power (log BCF/BAF) < 3 (ICSC, 2014)

EU REACH and other regulations have not yet listed nano-TiO₂ as a highly accumulative substance

($\text{Na}_2\text{Al}_2\text{Si}_3\text{O}_{10} \cdot 2\text{H}_2\text{O}$)

No significant bioaccumulation

(Alcohol soluble acrylic resin)

Logarithmic power (log BCF/BAF) < 1.3 (ICSC, 2014)

Mobility in soil

No data available.

Results of PBT and vPvB assessment

Material Safety Data Sheet (MSDS)

MSDS No.: 2025052310E
Creation Date: May 23, 2025
Page 14 / 15

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Endocrine disrupting properties

No data available.

Other adverse effects

Do not allow materials to release to drains or water body.

13. Disposal Considerations

Safe handling and methods of disposal

Product

Recycle if possible. Offer surplus and non-recyclable products to a licensed disposal company. Observe according to the national and local related regulations.

Contaminated packaging

Dispose as unused product. Keep away from heat and fire.

14. Transport Information

UN-Number

ADR/RID/ADN, IMDG, IATA 1263

UN proper shipping name

ADR/RID/ADN, IMDG, IATA PAINT

Transport hazard class(es)

ADR/RID/ADN, IMDG, IATA 3

Class

Label



Packing group

ADR/RID/ADN, IMDG, IATA III

Environmental hazards

Marine pollutants(Yes/No): No

Material Safety Data Sheet (MSDS)

MSDS No.: 2025052310E

Creation Date: May 23, 2025

Page 15 / 15

Special precautions for user

Read the product manual, MSDS, emergency procedure before operation.

Transport in bulk according to Annex 1 of Marpol and the IBC Code

No data available.

15. Regulatory Information

International Regulations

Safety, health and environmental regulations/legislation specific for the substance or mixture

No information available.

Chemical safety assessment

For this product a chemical safety assessment was not carried out.

16. Other Information

Further Information:

·This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

·This safety data sheet was prepared in accordance with Globally Harmonized System of Classification and Labeling of Chemicals (GHS) Rev.10.

Department Issuing MSDS: Hunan Feibo Environmental Protection Technology Co., Ltd.

Issue Date: May 23, 2025

*****End*****