

Material Safety Data Sheet (MSDS)

Sample Name: Feibo self-cleaning coating

Sample ingredients/raw materials (provided by the customer): see Part III "Ingredient/Composition Information" in the body of the report

Editing Period: January 5, 2024 to January 6, 2024

Project: Prepare MSDS based on sample information provided by the customer.

Abstracts: According to the customer's request, the content and format of this Safety Technical Sheet are compiled in accordance with the European Commission Regulation "Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 8th Edition (EC) No 1907/2006, (EC) No 1272/2008, (EC) No 878/2020, and (EU) No 2015/830, as detailed in the body of the attached report.

Client Name: Hunan Fibo Environmental Protection Technology CO., LTD

Client Address: Room 304, Building 7, R&D Headquarters, Zhongnan University Science Park, Yuelu District, Changsha, Hunan, China

Signed for and on Behalf of **SNTEK**



L. Zeng /

SNTEK Testing Technology Co., Ltd.

12F, Block A, Building 7, Phase III, International Innovation Valley, Xili Street, Nanshan District, Shenzhen.

Tel: 400-008-2358 E-mail: service@msds-ghs.cn Website: <http://www.msds-ghs.cn>

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product Labeling**

Product Name: Feibo self-cleaning coating

Model: General-purpose KT01

1.2 Recommended and Restricted Uses

Recommended use: Coating solution

Restricted use: No data available

1.3 Product Manufacturer or Supplier Information

Manufacturer: Hunan Fibo Environmental Protection Technology CO., LTD

Address: Room 304, Building 7, R&D Headquarters, Zhongnan University Science Park, Yuelu

District, Changsha, Hunan, China

Telephone: +86-139-7492-9383

E-mail: 780769464@qq.com

1.4 Enterprise emergency telephone

Enterprise emergency telephone: +86-731-8987-5607

SECTION 2: Hazards identification**Summary of emergency**

Milky white liquid with solvent odor, highly flammable liquid and vapor, may be harmful if swallowed, harmful if inhaled, strong eye irritation, may be carcinogenic, may cause harm to fertility or fetus, nervous system, visual acuity, systemic toxicity disorders, possibility of respiratory irritation, may cause drowsiness or vertigo, long term or repeated exposure to the nervous system, visual acuity, liver, blood, long term or repeated exposure to the respiratory system, spleen.

2.1 GHS Classification

Flammable liquids	Category 3
Acute toxicity; oral	Category 5
Acute toxicity; inhalation	Category 4
Severe eye damage/eye irritation	Category 1
Carcinogenicity	Category 1
Reproductive Toxicity	Category 1
Specific Target Organ/Systemic Toxicity (Single Exposure)	Category 1

(Nervous system, visual organs, systemic toxicity)

Category 3 (respiratory tract irritation, quickening)

Specific Target Organ/Systemic Toxicity (Repeated Exposure)

Category 1

(nervous system, visual organs, liver, blood system)

Category 2 (Respiratory System/Spleen)

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

warn

Hazard statement(s)

H226 flammable liquids and vapors.

H303 May be harmful if swallowed.

H332 Harmful if inhaled.

H318 Causes serious eye damage.

H350 May cause cancer.

H360 May cause harm to fertility or fetus.

H370 Toxic to nervous system, visual acuity, systemic toxicity.

H335 May cause respiratory tract irritation.

H336 May cause drowsiness or vertigo.

H372 May cause nervous system, visual acuity, liver, blood system through prolonged or repeated exposure.

H373 May cause respiratory problems, spleen with prolonged or repeated exposure.

Precautionary statement(s)

Prevention

P201 Use only when specifically instructed.

P202 Do not operate or handle until all safety precautions have been read and understood.

P210 Keep away from sources of heat, sparks, ignition sources, and high temperatures.

P233 Seal the packaging.

P240 Ground/connect the packaging or receiving equipment.

P241	Explosion-proof electrical appliances, ventilators and lighting equipment must be used.
P243	Take measures to prevent static electricity.
P260	Do not breathe dust, mist, vapor, or spray.
P280	Wear protective gloves, eyewear, and face shield.
P281	Use the required personal protective equipment.
Response	
P303+P352+P361	IF ON SKIN (or hair): Remove all contaminated clothing immediately. Wash/rinse skin with water.
P304+P340	IF INHALED: Remove victim to fresh air and rest in a comfortable breathing position.
P312	If unwell, call a Poison Control Center or doctor.
P307+P311	IF EXPOSURE: Breathe to poison control center or physician.
P305+P351+P338	If in eyes, rinse carefully with water for several minutes. Remove contact lenses if easy. Continue rinsing.
P310	Call a poison control center or doctor immediately.
P370+P378	In case of fire, use chemical dry powder, carbon dioxide, foam, misted water, dry sand, alcohol-resistant foam to extinguish fire.
Disposal	
P403+P235	Store in a well-ventilated area. Keep cool. P233 Keep container tightly closed.
P405	Store under lock and key.
Waste disposal	
P501	Waste is disposed of to a qualified industrial waste disposal department. Dispose of contents/containers in accordance with local/regional/national/international law requirements

Incident Response

In the event of an accidental leak indoors, open windows and doors for adequate ventilation. Post no-entry signs around the area of the accidental leak to prohibit entry by anyone other than the person in charge. Wear appropriate protective equipment to protect your skin, eyes and respiratory organs. Work downwind, and evacuate people in the direction of the wind. Do not use water for washing, etc. on the ground or in the sewers. Avoid running into sewers. In case of a small amount

of leakage, absorb the leakage with soil sand or gauze and put it in a sealed container for recovery. In case of a large amount of leakage, prevent the leakage with an earth and sand bag, etc., and guide it to a safe place for recovery. If there is an ignition source or combustible material nearby, remove it immediately. Dispose of waste in accordance with local laws and regulations. Prepare appropriate fire extinguishers in case of fire. Dispose of waste in accordance with local laws and regulations.

2.3 Physical and chemical hazards

flammable liquids and vapors. Keep away from heat sources/sparks/open flames/hot surfaces. Toxic or burning medicinal gases so take care to avoid smoke inhalation during firefighting operations.

2.4 Health hazards

Irritating to eyes and mucous membranes.

2.5 Environmental hazards

See Part 12 for details.

2.6 Other hazards

none

SECTION 3: Composition/information on ingredients

Component	Appr. %	CAS
ethanol	30 ~ 35	64-17-5
n-Propanol	25 ~ 30	71-23-8
Titanium dioxide	1 ~ 10	13463-67-7
Methanol	5 ~ 10	67-56-1
Amorphous silica	1 ~ 5	保密
Isopropyl alcohol	1 ~ 5	67-63-0
Tetrahydrofuran	0.1 ~ 1	109-99-9
Boric acid	0.1>	10043-35-3
Nitric acid	0.1>	7697-37-2
Guitinosilicate	0.1>	保密
Magnesium compounds	0.1>	保密
Water	5 ~ 10	7732-18-5

SECTION 4: First aid measures

4.1 Description of first-aid measures

If inhaled

Move to a place with fresh air, rest quietly and keep warm. If you still do not feel well, consult a physician.

In case of skin contact

Wash the attached parts well with plenty of water and soap. Remove all contaminated clothing. If there is any abnormality, consult a physician. Consult a physician.

In case of eye contact

After eye contact: Wash off with plenty of water. Contact your eye doctor. Remove contact lenses.

If swallowed

Immediately wash your mouth carefully and get a diagnosis from your physician. However, do not force vomiting.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labeling (see section 2.2) and/or section 11.

4.3 Indication of any immediate medical attention and special treatment needed

No data available

4.4 Notes to physician

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Small fires: Carbon Dioxide, Powder, Spray water, Alcohol-resistant foam. Large-scale fires: water jet, water spray, alcohol-resistant foam.

Unsuitable extinguishing media

Stick water injection

5.2 Special hazards arising from the substance or mixture

flammable liquids and vapors. Keep away from heat sources/sparks/open flames/hot surfaces.

Toxic or burning medicinal gases so take care to avoid smoke inhalation during firefighting operations.

5.3 Advice for firefighters

Firefighting operations are conducted downwind. Move movable containers to a safe place immediately. If sprinkling water to extinguish the fire will increase the spread of the fire, use a suitable extinguishing agent other than loose water as described above. Even after extinguishing the fire, pour a large amount of water on the container to allow it to cool down sufficiently.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

In the event of an accidental leak indoors, open windows and doors for adequate ventilation.

Post no-entry signs around the area where the accidental leak occurred, and prohibit anyone other than the person concerned from entering the area.

Wear appropriate protective equipment to protect your skin, eyes and respiratory organs during operation.

Work downwind, and evacuate people in the direction of the wind.

Do not use water for washing, etc. on the ground or in sewers.

Be careful not to let the water go down the drain.

In case of a small amount of leakage, absorb the leakage with sand or gauze and put it in a sealed container.

In the case of a large amount of leakage, prevent the leakage with an earth and sand bag, etc., and direct it to a safe place for recycling.

If there is an ignition source or combustible material nearby, remove it immediately.

Dispose of waste in accordance with local laws and regulations.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Use in a well-ventilated area.

Use appropriate equipment to protect your skin, eyes and respiratory organs.

Avoid inhaling vapors and light mist.

Do not eat, drink or smoke during operation.

Wash your hands, mouth and face well after use. Change clothes if contamination occurs on work clothes.

Hygiene measures

Change contaminated clothing immediately. Use skin protection lotion. Wash hands and face after using this substance.

7.2 Conditions for safe storage, including any incompatibilities

Tightly closed. Drying

Keep container tightly closed at all times. Avoid direct sunlight, high temperatures and humidity, and store in a well-ventilated dark place.

Avoid contact with fire, spark plugs, and high temperatures in the vicinity.

Keep it away from strong acids and chemicals.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Chemical Name	CAS No .	OELs (mg/m ³)		biological exposure limit value(ACGIH)PPM	
		PC-TWA	PC-STEL	TWA	STEL
Ethanol	64-17-5	-	-	-	1000
n-Propanol	71-23-8	200	300	200	400
Titanium dioxide	13463-67-7	8	10	-	-
Methanol	67-56-1	25	50	200	250
Amorphous silica	Confidential	-	-	2.0mg/m ³	-
Isopropyl alcohol	67-63-0	350	700	200	400
Tetrahydrofuran	109-99-9	-	300	50	100
Boric acid	10043-35-3	-	-	2mg/m ³	6mg/m ³
Nitric acid	7697-37-2	-	-	2	4
Guitinosilicate	Confidential	-	-	-	-
Magnesium compounds	Confidential	-	-	-	-
Water	7732-18-5	-	-	-	-

8.2 Exposure controls

Appropriate engineering controls

Ventilation of the entire house. Local exhausts are installed in places where ventilation is poor and where vapor is common.

Personal protective equipment

Eye and Face Protection

Protective eyewear

Skin protection

Gloves

Respiratory protection

Gas masks for organic gases

Control of environmental exposure

Do not allow product to enter sewers.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

a) Appearance	Liquid
b) Odor	Solvent odor
c) Color	Milky white
d) pH	4.2
e) Melting point/ freezing point	No data available
f) Initial boiling point and boiling range	81.1°C
g) Flash point	Closed Cup Flash Point: 24.5°C ASTM D 7094-17a Closed Cup Flash Point: 26.5°C ISO 13736-201
h) Evaporation rate	No data available
i) Flammability (solid, gas)	May form combustible dust concentrations in air
j) Upper/lower Flamm- ability or explosive limits	No data available
k) Vapor pressure	No data available
l) Vapor density	No data available
m) Relative density	2.02 g/cm ³
n) Water solubility	water-soluble
o) Partition coefficient: n-octanol/ water	No data available
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Chemical stability

Stabilized under normal conditions of use

10.2 Possibility of hazardous reactions

Reacts violently with strong oxidizing agents.

Makes explosive gas mixtures when mixed with air.

Corrodes aluminum at high temperatures.

10.3 Conditions to avoid

Exposure to high temperatures.

10.4 Incompatible materials

Strong oxidizing agents and strong bases.

10.5 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Skin corrosion/ irritation

No data available

Serious eye damage/ eye irritation

Ethanol (Source: NITE)

Moderate irritation was evaluated in 2 Draize tests with rabbits. Corneal clouding, iritis, conjunctival redness and swelling were observed in one of the tests. The mean values for the first day were above 1 for corneal clouding and above 2 for conjunctival redness, and all symptoms recovered within 7 days, thus placing it in Category 2B.

N-Propanol (Source: NITE)

There are reports of "severe conjunctivitis, iritis, corneal clouding, and ulcer formation in rabbits in an eye drop test (ACGIH (2004), PATTY (5th, 2001))", classified by the EU as Xi; R41, and therefore categorized as Category 1.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

Ethanol (Source: NITE)

Ethanol is classified by the ACGIH as A3, and the carcinogenicity of alcoholic beverages is well documented by immunologic data. Ethanol and its main metabolite acetaldehyde are known to induce malignant tumors of the esophagus due to the ingestion of ethanol contained in alcoholic beverages and are classified in Category 1A.

Reproductive toxicity

Ethanol (Source: NITE)

Ethanol is classified by the ACGIH as A3, and the carcinogenicity of alcoholic beverages is well documented by immunologic data.

Ethanol and its primary metabolite acetaldehyde are known to induce malignant tumors of the esophagus due to the ingestion of ethanol contained in alcoholic beverages and are classified in Category 1A.

Methanol (Source: NITE)

According to the inhalation exposure test of pregnant rats during the period of organogenesis, fetal resorption and malformations were observed, and other inhalation and oral exposure tests also showed the same fetal malformations, including harelip. With regard to the reproductive effects of methanol, there is a large body of evidence scientifically demonstrating health effects. While there are insufficient data on effects in humans, there is clear evidence of effects in animals. Therefore, it can be concluded that methanol may have adverse effects on humans if exposed at certain levels. Therefore, it is a toxic substance to humans. The record of "Methanol" is categorized as Category 1.

Specific target organ toxicity - single exposure

Ethanol (Source: NITE)

Inhalation exposures in humans resulting in irritation of the eyes and respiratory tract have been reported. Elevated blood concentrations of ethanol cause mild intoxication (hypomotility, changes in mood, personality, and behavior) to toxic intoxication (visual impairment, sensory paralysis, delayed reaction time, speech impairment), and even more severe symptoms (vomiting, lethargy, hypothermia, hypoglycemia, and dyspnea). Deaths have also been documented due to respiratory or circulatory insufficiencies, poor pharyngeal reflux, and food attraction in the stomach. Symptoms of paralysis of the central nervous system have been observed not only in humans but also in animal studies. Therefore, it is classified as Category 3 (respiratory irritant, anesthetic effect).

Methanol (Source: NITE)

According to "Paralysis of the central nervous system as a symptom of acute poisoning in humans can be observed. Metabolic acidosis is caused by the accumulation of anthranilic acid in the blood. This leads to visual impairment, blindness, headache, blurred vision, nausea, vomiting, shortness of breath, and lethargy. In severe cases, it can lead to death. Extrapyramidal symptoms such as central nervous system disorders, especially tremor paralysis, have also been described. Morphologic changes have been documented in the form of cerebral white matter necrosis, which is classified as Category 1 (central nervous system). The damage to the eye as another target organ is also very characteristic. The symptoms of metabolic acidosis include headache, nausea, vomiting, frequent breathing, and lethargy, making it a systemic toxicant. Anesthesia" has been described in the inhalation exposure test of rats. The symptoms of acute poisoning in humans have been described as paralysis of the central nervous system and are classified as Category 3 (anesthetic effects).

Isopropanol (Source: NITE)

This substance has acute toxic effects on humans in the form of paralysis of the central nervous system (drowsiness, lethargy, control of respiration, etc.), irritation of the gastrointestinal tract (nausea, vomiting), and effects on the circulatory system, including cardiac arrhythmia, and other systemic adverse effects. Inhalation exposure also causes irritation of the nose and throat (coughing, sore throat), and indicates irritation of the respiratory tract. Therefore, it is classified as Category 1 (CNS, systemic toxicity) and Category 3 (respiratory tract irritation). The old classification was in Category 1 (Kidney), based on data from human case reports on List3. The old classification was in Category 1 (Renal) and was based on human case reports from List3. The original text is older and most of the data from Lists 1 and 2 were not used, and the kidney was judged to be an unsuitable subject organ.

Tetrahydrofuran (Source: NITE)

The 5000 ppm 3-hour inhalation exposure test in rats (4-hour conversion 12.7 mg/L) resulted in statements of rigid sleeping posture, lethargy, indirect spasms, wheezing respiration, and dyspnea, so the moderate exposure concentration has neurological effects, and is classified as Category 2. For human effects, there are statements of mucous membrane irritation, and respiratory irritation from vapors, and is classified as Category 3 due to irritation of the respiratory tract. For human effects, irritation of mucous membranes was noted, as well as respiratory irritation from vapors, which is classified as Category 3 due to the irritation of the respiratory tract.

Specific target organ toxicity - repeated exposure

Ethanol (Source: NITE)

Long-term consumption of alcohol in large quantities by humans can have adverse effects on organs throughout the body. The most affected organ is the liver. The damage begins with steatosis and progresses through stages of necrosis and fibrosis leading to cirrhosis, which is classified as Category 1 (liver). Based on the treatment of patients with alcohol misuse and alcoholism, the US FDA recognizes the use of three therapeutic drugs, which are classified in Category 2 (Central Nervous System). Since no significant adverse effects were found in animal studies, lipotrophy was observed in rats after 90 days of repeated oral administration of doses well above the guideline range.

Methanol (Source: NITE)

It is classified as Category 1 (Visual organs) based on the record of "Widespread eye damage is the prominent symptom in humans exposed to low concentrations of methanol for a long period of time" and the record of "Blindness as a chronic toxic effect in occupational environments exposed to methanol for a long period of time". Meanwhile, chronic toxicity symptoms caused by exposure to methanol vapors, such as headache, dizziness, insomnia, and stomach disorder, were recorded and are classified in Category 1 (Central Nervous System).

Isopropanol (Source: NITE)

In an inhalation exposure test in which rodents were exposed to the vapors of this substance for 4 months, a decrease in leukocytes was observed above 100 mg/m³ (EC: 0.067 mg/L/6 hr), and pathological effects on the respiratory organs (lungs, bronchial tubes), liver, and spleen were observed at 500 mg/m³ (EC: 0.33 mg/L/6 hr). Therefore, the target organs were identified as blood system, respiratory organs, liver and spleen. Blood is assigned to Category 1 and respiratory organs, liver and spleen to Category 2. Anesthesia and effects on the blood system were observed in animal tests by inhalation or orally at doses exceeding the guideline values for Category 2.

Tetrahydrofuran (Source: NITE)

The CERH Hazard Data Set (1999) lists nephropathy, hepatic impairment, and central spasms as cases of occupational exposure, and ACGIH (7th, 2001) lists nephropathy, hepatic impairment, central spasms, and peripheral neurologic impairment as cases of occupational exposure, with the subject organisms being the kidneys, the liver, and the nervous system, which are classified in Category 1.

SECTION 12: Ecological information**12.1 Toxicity**

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of the waste at a licensed industrial waste disposal facility.

Drainage water from containers, machinery, etc. should not be discharged directly to the ground or drains.

Dispose of empty containers after removing their contents.

Please observe other related laws and regulations.

SECTION 14: Transport information**14.1 UN number**

ADR/RID: 1139

IMDG: 1139

IATA-DGR: 1139

14.2 UN proper shipping name

ADR/RID: Not dangerous goods

IMDG: Not dangerous goods

IATA-DGR: Not dangerous goods

14.3 Transport hazard class(es)

ADR/RID: 3

IMDG: 3

IATA-DGR: 3

14.4 Packaging group

ADR/RID: III

IMDG: III

IATA-DGR: III

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA-DGR: no

14.6 Special precautions for user

Please follow the general precautions in "Precautions for Use and Storage".

Check that the container is not leaking, tipping, or falling to prevent damage to the load, and make sure to prevent the cargo from collapsing.

Since this is a flammable liquid, fire is strictly prohibited.

It is necessary to use containers with a function that prevents the temperature from rising.

Loading height of 3m or less

It is prohibited to mix Class 1 and Class 6 hazardous materials with high-pressure gases.

14.7 Incompatible materials**Further information**

Not classified as dangerous in the meaning of transport regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Special regulations/legislation on safety, health and environmental protection of substances and mixtures

Name of Laws and Regulations	Specific information	
Regulations on the Safety Management of Dangerous Chemicals	Catalog of Hazardous Chemicals	n-Propanol, Isopropanol, Methanol, Tetrahydrofuran, Boric acid, Nitric acid are listed. Hydrofuran, boric acid, and nitric acid are included.
	Key Regulated Hazardous Chemicals Catalog	
	Catalog of Highly Toxic Chemicals	
Regulations on Labor Protection in Workplaces Using Toxic Substances	Catalog of Highly Toxic Substances	
Regulations on the First Importation of Chemicals and the Import and Export Environment of Toxic Chemicals	Restricted for Import and Export in China Catalog	
Environmental Management Regulations	Inventory of Existing Chemical Substances in China (IECSC)	All components are listed

SECTION 16: Other information

16.1 References:

- [1] IPCS: International Chemical Safety Card (ICSC) Website:
<http://www.ilo.org/dyn/icsc/showcard.home>
- [2] EU REACH Registered Substances Database
 Website: <http://echa.europa.eu/web/guest/information-on-chemicals/registered-substances>
- [3] OECD Global Chemical Information Platform (GCIP)
 Website: http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en
- [4] US CAMEO Chemical Substance Database Website:
<http://cameochemicals.noaa.gov/search/simple>
- [5] U.S. Library of Medicine: Chemical Labeling Database
 URL: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>

16.2 Shrinking:

PC-STEL Short Time Exposure Tolerance Concentration
 PC-TWA Time-weighted average
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 ICAO International Civil Aviation Organization
 UN United Nations

16.3 Disclaimer:

The format of this MSDS complies with the requirements of the 8th edition of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS) (EC) No 1907/2006, (EC) No 1272/2008, (EC) No 878/2020, and (EU) No 2015/830, and the data are obtained from international authoritative databases and data submitted by the enterprises, and the other information is based on the current knowledge of the company. Other information is based on the company's current knowledge. We try our best to ensure the correctness of all the information in this document, but due to the diversity of information sources and the limitations of our knowledge, this document is only for users' reference. The user of the safety instructions should make a judgment on the reasonableness of the information according to the purpose of use. We shall not be liable for any damages arising from the operation, storage, use or disposal of this product.

16.4 Revision Information

Date of MSDS preparation: Saturday, January 6, 2024
 MSDS Version: 1.0