TECHNICAL UNIVERSITY OF MOLDOVA
Faculty of Computers, Informatics, and Microelectronics
Department of Software Engineering
Software Engineering Study Programme

LABORATORY REPORT

OPERATING SYSTEMS LABORATORY 6

Inside the xv6 File System

Student: Lucian-Adrian Gavril

Group: FAF-241

Coordinator: univ. assist., Reițman Patricia

Chișinău, 2026

TABLE OF CONTENTS

ABSTRACT 3

INTRODUCTION 4

1 DIRECTORY REPRESENTATION AND FILE TYPES 5

1.1 Filesystem Type Enumeration 5

1.2 The Root Inode and Directory Self-Reference 5

1.3 Directory Record Sizing 5

2 THE MYSTAT UTILITY AND HARD LINK LIFECYCLE 7

2.1 Implementation of user/mystat.c 7

2.2 Observing Hard Links and Unlinking 7

2.3 Kernel Unlinking and Block Deallocation Tracing 8

2.4 Minimalist On-Disk Inode Structure 9

3 FILESYSTEM LIMITS AND DISK LAYOUT 10

3.1 Structural Constants in kernel/fs.h 10

3.2 Name Truncation 10

3.3 Maximum File Capacity Calculation 10

3.4 Disk Layout from mkfs 10

4 RECURSIVE SEARCH: USER/FIND.C AND STRETCH 11

4.1 Implementation Architecture 11

4.2 Validation and Inode Identity Verification 12

CONCLUSIONS 14

ABSTRACT

This laboratory report investigates the storage architecture of the MIT xv6 operating system running on an emulated RISC-V architecture via QEMU 8.2.2. The report presents the complete lifecycle of filesystem objects across kernel metadata structures and user-space utilities. Two custom user utilities were developed and validated in C: `user/mystat.c`, an inode inspection program decoding file types, inode numbers, hard link counters, and byte sizes; and `user/find.c`, a recursive search program traversing directory trees within xv6's 16-file-descriptor process limit. The optional stretch requirement was implemented, equipping `find` with a `-n` flag to display inode identifiers alongside resolved paths. In addition, the report analyzes directory entries, the on-disk `struct dinode`, the line-by-line block freeing sequence in `sys_unlink()` and `iput()`, and disk limits derived from `kernel/fs.h`.

Keywords: operating systems, xv6, riscv, filesystem architecture, inodes, hard links, directory traversal, recursive find, storage limits

INTRODUCTION

The xv6 operating system features a layered filesystem architecture modeled after Unix Sixth Edition and modern ext-family concepts, implemented in approximately 800 lines of readable C code. This architecture comprises a buffer cache, write-ahead logging layer, inode allocator, directory table mechanism, and system call interface.

Laboratory 6 explores this filesystem from both internal and external perspectives:

a) **Directory Tables and Type Identification**: Interpreting directory record formatting, file type enumeration in `kernel/stat.h`, and root directory self-reference mechanics.

b) **Inode Inspection and Link Semantics**: Developing `user/mystat.c` to inspect object metadata and observing hard link creation and unlinking.

c) **Code Analysis of Deallocation**: Tracing the decoupling between directory record unlinking in `sys_unlink()` and physical block deallocation in `iput()` and `itrunc()`.

d) **Structural Capacity and Disk Accounting**: Calculating theoretical file capacity from direct and indirect block pointers in `kernel/fs.h`, and evaluating disk layout geometry from `mkfs`.

e) **Recursive Search and Inode Identification**: Implementing `user/find.c` with cyclic guard logic and safe descriptor closure, incorporating the `-n` stretch flag to verify inode identity between hard-linked files.

1 DIRECTORY REPRESENTATION AND FILE TYPES

1.1 Filesystem Type Enumeration

In xv6, file types are defined in `kernel/stat.h`:

```
#define T_DIR     1   // Directory
#define T_FILE    2   // Regular file
#define T_DEVICE  3   // Device
```

Listing the root directory produces four-column records containing name, type, inode number, and size:

```
$ ls
.              1 1 1024
..             1 1 1024
README         2 2 2425
cat            2 3 35160
console        3 24 0
```

1.2 The Root Inode and Directory Self-Reference

The root directory '/' is anchored at inode 1 (`ROOTINO = 1`). In every directory table, '.' references the directory itself, while '..' references its parent. Because the root directory has no parent above it, its parent entry points directly to itself. Both '.' and '..' therefore map to inode 1.

1.3 Directory Record Sizing

Directory entries are defined by `struct dirent` in `kernel/fs.h`:

```
struct dirent {
  ushort inum;          // 2 bytes
  char name[DIRSIZ];    // 14 bytes (DIRSIZ = 14)
};
```

Each directory entry spans exactly 16 bytes. Creating an empty directory `a` yields:

```
$ mkdir a
$ ls a
.              1 25 32
..             1 1 1024
```

The size of directory `a` is 32 bytes, consisting of exactly two 16-byte entries: ‘.‘ (inode 25) and ‘..‘ (inode 1).

2 THE MYSTAT UTILITY AND HARD LINK LIFECYCLE

2.1 Implementation of user/mystat.c

The `mystat` utility invokes `stat()` to print detailed object metadata:

```
#include "kernel/types.h"
#include "kernel/stat.h"
#include "user/user.h"

char *typename(int t) {
  switch(t) {
  case T_DIR:    return "directory";
  case T_FILE:   return "file";
  case T_DEVICE: return "device";
  default:       return "?";
  }
}

int main(int argc, char *argv[]) {
  struct stat st;
  for(int i = 1; i < argc; i++){
    if(stat(argv[i], &st) < 0){
      fprintf(2, "mystat: cannot stat %s\n", argv[i]);
      continue;
    }
    printf("%s: %s, inode %d, links %d, size %ld bytes\n",
           argv[i], typename(st.type), st.ino, st.nlink, st.size);
  }
  exit(0);
}
```

2.2 Observing Hard Links and Unlinking

```
$ mystat README . console
README: file, inode 2, links 1, size 2425 bytes
.: directory, inode 1, links 2, size 1024 bytes
```

```
console: device, inode 24, links 1, size 0 bytes

$ ln README r2
$ mystat README r2
README: file, inode 2, links 2, size 2425 bytes
r2: file, inode 2, links 2, size 2425 bytes

$ rm README
$ mystat r2
r2: file, inode 2, links 1, size 2425 bytes

$ cat r2 | wc
48 334 2425
```

When `ln README r2` executes, the kernel creates a second directory entry referencing inode 2, incrementing `nlink` to 2. Inode number, size, and content remain identical. When `README` is removed, `sys_unlink()` removes only the directory entry and decrements `nlink` back to 1. Inode 2 and its data blocks remain intact, allowing `r2` to read the original contents.

2.3 Kernel Unlinking and Block Deallocation Tracing

In `kernel/sysfile.c`, the hard link count is decremented at line 230:

```
ip->nlink--;
iupdate(ip);
```

Crucially, `sys_unlink()` does not free disk blocks. Block freeing is deferred to `iput()` in `kernel/fs.c` (line 342):

```
if(ip->ref == 1 && ip->valid && ip->nlink == 0){
  itrunc(ip);
  ip->type = 0;
  iupdate(ip);
  ip->valid = 0;
}
```

Physical data blocks are freed only when the in-memory reference count drops to 1 and the on-disk link count drops to 0. At that point, `itrunc()` iterates across all direct and indirect block addresses, calling `bfree()` to return blocks to the free bitmap.

2.4 Minimalist On-Disk Inode Structure

The on-disk inode structure (`struct dinode` in `kernel/fs.h`) illustrates xv6's minimalist design:

```
struct dinode {
  short type;              // File type
  short major;             // Major device number (T_DEVICE only)
  short minor;             // Minor device number (T_DEVICE only)
  short nlink;             // Hard link counter
  uint size;               // File size in bytes
  uint addrs[NDIRECT+1];   // Block addresses (12 direct + 1 indirect)
};
```

xv6 omits permission bits, UID, GID, timestamps, and symbolic link paths.

3 FILESYSTEM LIMITS AND DISK LAYOUT

3.1 Structural Constants in kernel/fs.h

```
$ grep -n "define BSIZE\|define NDIRECT\|define NINDIRECT\|define DIRSIZ" kernel/fs.h
6:#define BSIZE 1024  // block size
27:#define NDIRECT 12
28:#define NINDIRECT (BSIZE / sizeof(uint))
54:#define DIRSIZ 14
```

3.2 Name Truncation

Creating a directory whose name exceeds 14 characters reveals truncation:

```
$ mkdir averyveryverylongname
$ ls
averyveryveryl 1 26 32
```

Because `DIRSIZ = 14`, names are truncated to 14 characters within the directory entry buffer.

3.3 Maximum File Capacity Calculation

- Block size: BSIZE $= 1024$ bytes.
- Direct blocks: NDIRECT $= 12$ blocks ($12 \times 1024 = 12,288$ bytes).
- Indirect blocks: NINDIRECT $= \frac{\text{BSIZE}}{\text{sizeof(uint)}} = \frac{1024}{4} = 256$ block pointers ($256 \times 1024 = 262,144$ bytes).
- Total blocks: $12 + 256 = 268$ blocks.
- Maximum file size: 268×1024 bytes $= 274,432$ bytes ≈ 268 KiB.

3.4 Disk Layout from mkfs

```
nmeta 47 (boot, super, log blocks 31, inode blocks 13, bitmap blocks 1) blocks 1953 tota
```

The virtual disk spans 2000 blocks (2 MiB). Metadata consumes 47 blocks (block 0 boot, block 1 super, blocks 2–31 log, blocks 32–44 inodes, block 45 bitmap). The remaining 1953 blocks are allocated for user data.

4 RECURSIVE SEARCH: USER/FIND.C AND STRETCH

4.1 Implementation Architecture

The `find` utility opens directory file descriptors, scans `struct dirent` entries, skips ‘.‘ and ‘..‘ to prevent cycles, formats paths in a local buffer, and recurses into subdirectories while strictly closing descriptors:

```
#include "kernel/types.h"
#include "kernel/stat.h"
#include "user/user.h"
#include "kernel/fs.h"
#include "kernel/fcntl.h"

static int show_ino = 0;

void find(char *path, char *target) {
  char buf[512], *p;
  int fd;
  struct dirent de;
  struct stat st;

  if((fd = open(path, O_RDONLY)) < 0) return;
  if(fstat(fd, &st) < 0 || st.type != T_DIR) { close(fd); return; }

  strcpy(buf, path);
  p = buf + strlen(buf);
  *p++ = '/';

  while(read(fd, &de, sizeof(de)) == sizeof(de)){
    char name[DIRSIZ + 1];
    if(de.inum == 0) continue;
    memmove(name, de.name, DIRSIZ);
    name[DIRSIZ] = 0;
    if(strcmp(name, ".") == 0 || strcmp(name, "..") == 0) continue;
```

```
    strcpy(p, name);
    if(stat(buf, &st) < 0) continue;
    if(strcmp(name, target) == 0){
      if(show_ino) printf("%s %d\n", buf, st.ino);
      else printf("%s\n", buf);
    }
    if(st.type == T_DIR) find(buf, target);
  }
  close(fd);
}
```

4.2 Validation and Inode Identity Verification

```
$ mkdir a
$ mkdir a/b
$ echo x > a/b/r2
$ echo y > a/r2
$ ln cat r2

$ find . r2
./r2
./a/b/r2
./a/r2

$ find a b
a/b

$ find . r2 -n
./r2 3
./a/b/r2 26
./a/r2 27

$ mystat cat
cat: file, inode 3, links 2, size 35160 bytes
```

The stretch output with `-n` proves that `./r2` (inode 3) is the exact same file as `cat` (inode 3, link count 2). In contrast, `a/b/r2` (inode 26) and `a/r2` (inode 27) are newly created distinct files.

CONCLUSIONS

Implementing `mystat` and `find` clarified the internal mechanisms of xv6. Directory tables represent lightweight name-to-inode mappings, link counters manage inode preservation, and block freeing is cleanly separated from unlinking.