The Map Function in R: Takeaways 🖻

by Dataquest Labs, Inc. - All rights reserved © 2020

Syntax

```
• Creating a custom function and using map() to vectorize it ``` format score <--
     function(score) { fmt_string <- str_replace(score, "%", "") num <-</pre>
     as.numeric(fmt string)
     return(num) }
     example scores <- c("19%", "81%", "100%")
     map result <- map(example scores, format score) ""
• Using map2() to vectorize a function that takes in two inputs "` first_inputs <- c(1, 2, 3)
     second inputs <-c(4, 5, 6)
     add inputs < - function(x, y) { return(x + y) }
     output <- map2(first_inputs, second_inputs, add_inputs) ```</pre>
• Using the map() and mutate() functions to create a new column in your dataset ""
     format score <- function(score) { fmt string <- str replace(score, "%", "") num <-
     as.numeric(fmt string)
     return(num) }
     scores <- scores %>% mutate( new writing score = unlist(map(writing score,
     format_score)) ) ```
• Using lists as an input to the map() function ``` input_list <- list( c(1, 2), c(3, 4), c(5, 6), c(7, 4), c(1, 2), c(2, 4), c(3, 4), c
     8), c(9, 10))
     output <- map(input list, sum) ```
• Using group_by() and summarize() together to vectorize a summary function across groups
     in a dataset
         avg_score_by_student <- student_scores %>%
                          group_by(names) %>%
                          summarize(
                               avg_writing = mean(new_writing_score)
```

Concepts

- The purr package has a family of functions that can accommodate any number of inputs and data types. Each of these functions work out similarly, so learning one can make learning the others easier.
- We use the map() function to vectorize a given function. You can use any function, whether it's one from R itself or a custom function that you've made yourself.
- We use the map20 function to vectorize a given function that uses two inputs.
- We can use the <code>group_by()</code> and <code>summarize()</code> functions together to create powerful analyses.

 These two work well when a dataset has two or more groups that we would like to compare against each other.



Takeaways by Dataquest Labs, Inc. - All rights reserved © 2020