

Bar Charts, Histograms, and Box Plots: Takeaways



by Dataquest Labs, Inc. - All rights reserved © 2020

Syntax

- Creating a bar chart:

```
ggplot(data = data_frame,  
  aes(x = variable_1, y = variable_2)) +  
  geom_bar(stat='identity')
```

- Creating a histogram:

```
ggplot(data = reviews,  
  aes(x = Rating)) +  
  geom_histogram(bins = 30)
```

- Creating a faceted plot for categories of a variable:

```
ggplot(data = reviews,  
  aes(x = Rating)) +  
  geom_histogram(bins = 30) +  
  facet_wrap(~Rating_Site, nrow= 2)
```

- Adding color to distinguish between variables:

```
ggplot(data = reviews,  
  aes(x = Rating, fill= Rating_Site)) +  
  geom_histogram(bins = 30)
```

- Creating a boxplot:

```
ggplot(data = reviews,  
  aes(x = Rating_Site, y = Rating)) +  
  geom_boxplot()
```

- Adding a title:

```
ggplot(data = reviews,  
  aes(x = Rating_Site, y = Rating)) +  
  geom_boxplot() +  
  labs(title = "Comparison of Movie Ratings")
```

- Changing the plot background color:

```
ggplot(data = reviews,  
  aes(x = Rating_Site, y = Rating)) +  
  geom_boxplot() +  
  labs(title = "Comparison of Movie Ratings") +  
  theme(panel.background = element_rect(fill = "white"))
```

Concepts

- Bar charts:
 - Represent grouped data summaries using bars with heights proportional to values of a summary variable such as the average.
 - Do not provide information about the distribution of variables.
- Using `stat = "identity"` overrides the default behavior of the height of the bars corresponding to the number of values, and instead creates bars equal to the value of the y-variable.
- Histograms depict the frequency with which values of a variable occur. Unlike bar charts and line graphs, histograms are used to understand characteristics of one variable rather than the relationship between two variables.
- You can specify two different arguments in the `geom_histogram()` layer to specify the number of categories for binning the independent variable:
 - `binwidth =` allows you to specify the *size* of the bins, and is useful for instances, such as this example, where you want categories to span specific intervals.
 - `bins =` allows you to specify the *number* of bins, which can be useful to experiment with when deciding how much detail you want to use to display your data.

- Box plots provide a summary of data for each group, as well as provide information about how data is spread.
- Box plots present the following data:
 - The largest value: Represented by the top of the black line extending from the top of the box. These lines are also known as "whiskers".
 - The third quartile (Q3): Represented by the top of the box. Seventy-five percent of the values are smaller than the third quartile.
 - The median: Represented by the thick black line. The median is the value that falls in the middle of the data.
 - The first quartile (Q1): Represented by the bottom of the box. Twenty-five percent of the values are smaller than the third quartile.
 - The smallest value: Represented by the bottom of the black line extending from the bottom of the box.
- General guidelines for picking a visualization:
 - Bar charts may be used for showing a quick summary of your data, such as averages or counts of the number of instances of a value that occur for a given variable.
 - Histograms are useful for visualizing distributions of data when you want to know the *shape* of a distribution (in other words, where most values are clustered).
 - Box plots provide an informative summary of the shape, spread, and center of your data.

Resources

- [Five Number Summary](#)
- [Data Visualization 101](#)
- [Design Tips for Data Visualization](#)

