

```
In [1]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
```

```
In [2]: df=pd.read_csv(r"C10_loan1.csv")
df
```

Out[2]:

	Home Owner	Marital Status	Annual Income	Defaulted Borrower
0	Yes	Single	125	No
1	No	Married	100	No
2	No	Single	70	No
3	Yes	Married	120	No
4	No	Divorced	95	Yes
5	No	Married	60	No
6	Yes	Divorced	220	No
7	No	Single	85	Yes
8	No	Married	75	No
9	No	Single	90	Yes

```
In [3]: df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 10 entries, 0 to 9
Data columns (total 4 columns):
#   Column                Non-Null Count  Dtype
---  -
0   Home Owner            10 non-null    object
1   Marital Status        10 non-null    object
2   Annual Income         10 non-null    int64
3   Defaulted Borrower    10 non-null    object
dtypes: int64(1), object(3)
memory usage: 448.0+ bytes
```

```
In [4]: df.describe()
```

Out[4]:

	Annual Income
count	10.000000
mean	104.000000
std	45.631373
min	60.000000
25%	77.500000
50%	92.500000
75%	115.000000
max	220.000000

```
In [5]: df.columns
```

```
Out[5]: Index(['Home Owner', 'Marital Status', 'Annual Income', 'Defaulted Borrower'], dtype='object')
```

```
In [6]: df['Defaulted Borrower'].value_counts()
```

```
Out[6]: No      7
        Yes     3
        Name: Defaulted Borrower, dtype: int64
```

```
In [7]: g1={'Defaulted Borrower':{'No':1,'Yes':2}}
        g2={'Home Owner':{'No':1,'Yes':2}}
        g3={'Marital Status':{'Divorced':0,'Single':1,'Married':2}}
        df=df.replace(g1)
        df=df.replace(g2)
        df=df.replace(g3)
        print(df)
```

	Home Owner	Marital Status	Annual Income	Defaulted Borrower
0	2	1	125	1
1	1	2	100	1
2	1	1	70	1
3	2	2	120	1
4	1	0	95	2
5	1	2	60	1
6	2	0	220	1
7	1	1	85	2
8	1	2	75	1
9	1	1	90	2

```
In [8]: x=df[['Home Owner','Annual Income','Defaulted Borrower']]
        y=df['Marital Status']
```

```
In [9]: from sklearn.model_selection import train_test_split
        x_train,x_test,y_train,y_test=train_test_split(x,y,train_size=0.70)
```

```
In [10]: from sklearn.ensemble import RandomForestClassifier
         rfc=RandomForestClassifier()
         rfc.fit(x_train,y_train)
```

```
Out[10]: RandomForestClassifier()
```

```
In [11]: parameters={'max_depth':[1,2,3,4,5],
                    'min_samples_leaf':[5,10,15,20,25],
                    'n_estimators':[10,20,30,40,50]}
```

```
In [12]: from sklearn.model_selection import GridSearchCV
grid_search=GridSearchCV(estimator=rfc,param_grid=parameters,cv=2,scoring="accuracy")
grid_search.fit(x_train,y_train)
```

C:\ProgramData\Anaconda3\lib\site-packages\sklearn\model_selection_split.py:666: UserWarning: The least populated class in y has only 1 members, which is less than n_splits=2.
warnings.warn("The least populated class in y has only %d"

```
Out[12]: GridSearchCV(cv=2, estimator=RandomForestClassifier(),
                    param_grid={'max_depth': [1, 2, 3, 4, 5],
                                'min_samples_leaf': [5, 10, 15, 20, 25],
                                'n_estimators': [10, 20, 30, 40, 50]},
                    scoring='accuracy')
```


```
In [13]: grid_search.best_score_
```

```
Out[13]: 0.5833333333333333
```

```
In [14]: rfc_best=grid_search.best_estimator_
```

```
In [15]: from sklearn.tree import plot_tree
plt.figure(figsize=(80,40))
plot_tree(rfc_best.estimators_[5],feature_names=x.columns,class_names=['Divorced','Single'])
```

```
Out[15]: [Text(2232.0, 1087.2, 'gini = 0.49\nsamples = 5\nvalue = [3, 4, 0]\nnclass = Single')]
```



gini = 0.49
samples = 5
value = [3, 4, 0]
class = Single

```
In [ ]:
```