

D9

```
In [1]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
```

```
In [2]: df=pd.read_csv(r"C:\Users\user\Downloads\13_placement.csv")
df
```

Out[2]:

	cgpa	placement_exam_marks	placed
0	7.19	26.0	1
1	7.46	38.0	1
2	7.54	40.0	1
3	6.42	8.0	1
4	7.23	17.0	0
...
995	8.87	44.0	1
996	9.12	65.0	1
997	4.89	34.0	0
998	8.62	46.0	1
999	4.90	10.0	1

1000 rows × 3 columns

```
In [3]: df.head(10)
```

Out[3]:

	cgpa	placement_exam_marks	placed
0	7.19	26.0	1
1	7.46	38.0	1
2	7.54	40.0	1
3	6.42	8.0	1
4	7.23	17.0	0
5	7.30	23.0	1
6	6.69	11.0	0
7	7.12	39.0	1
8	6.45	38.0	0
9	7.75	94.0	1

In [4]: `df.info()`

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 1000 entries, 0 to 999
Data columns (total 3 columns):
#   Column                Non-Null Count  Dtype
---  -
0   cgpa                  1000 non-null   float64
1   placement_exam_marks 1000 non-null   float64
2   placed                1000 non-null   int64
dtypes: float64(2), int64(1)
memory usage: 23.6 KB
```

In [5]: `df.describe()`

Out[5]:


	cgpa	placement_exam_marks	placed
count	1000.000000	1000.000000	1000.000000
mean	6.961240	32.225000	0.489000
std	0.615898	19.130822	0.500129
min	4.890000	0.000000	0.000000
25%	6.550000	17.000000	0.000000
50%	6.960000	28.000000	0.000000
75%	7.370000	44.000000	1.000000
max	9.120000	100.000000	1.000000

In [6]: `df.columns`

Out[6]: `Index(['cgpa', 'placement_exam_marks', 'placed'], dtype='object')`

```
In [7]: sns.pairplot(df)
```

```
Out[7]: <seaborn.axisgrid.PairGrid at 0x2cfe35cb390>
```



```
In [8]: sns.distplot(df['placed'])
```

C:\Users\user\AppData\Local\Temp\ipykernel_1180\3382675032.py:1: UserWarning:

`distplot` is a deprecated function and will be removed in seaborn v0.14.0.


Please adapt your code to use either `displot` (a figure-level function with similar flexibility) or `histplot` (an axes-level function for histograms).

For a guide to updating your code to use the new functions, please see

<https://gist.github.com/mwaskom/de44147ed2974457ad6372750bbe5751> (<https://gist.github.com/mwaskom/de44147ed2974457ad6372750bbe5751>)

```
sns.distplot(df['placed'])
```


Out[8]: <Axes: xlabel='placed', ylabel='Density'>



```
In [9]: df1=df[['cgpa', 'placement_exam_marks', 'placed']]
```

```
In [10]: sns.heatmap(df1.corr())
```

```
Out[10]: <Axes: >
```



```
In [11]: x=df1[['cgpa', 'placement_exam_marks']]  
y=df1['placed']
```

```
In [12]: from sklearn.model_selection import train_test_split  
x_train,x_test,y_train,y_test=train_test_split(x,y,test_size=0.3)
```

```
In [13]: from sklearn.linear_model import LinearRegression  
lr=LinearRegression()  
lr.fit(x_train,y_train)
```

```
Out[13]: ▾ LinearRegression  
LinearRegression()
```

```
In [14]: print(lr.intercept_)  
0.38564190651315755
```


```
In [15]: coeff = pd.DataFrame(lr.coef_,x.columns,columns=['Co-efficient'])  
coeff
```

Out[15]:

	Co-efficient
cgpa	0.018215
placement_exam_marks	-0.000874

```
In [16]: prediction=lr.predict(x_test)  
plt.scatter(y_test,prediction)
```

Out[16]: <matplotlib.collections.PathCollection at 0x2cfde3e2490>



```
In [17]: print(lr.score(x_test,y_test))  
-0.0007266943491739397
```

In []: