

# PRACTICAL NO 01

## PART 1

```
#include <iostream>
```

```
#include <string>
```

```
using namespace std;
```

```
// Caesar Cipher Encryption
```

```
string caesarEncrypt(string text, int key) {
```

```
    string result = "";
```

```
    for (char c : text) {
```

```
        if (isalpha(c)) {
```

```
            char base = isupper(c) ? 'A' : 'a';
```

```
            result += (c - base + key) % 26 +  
base;
```

```
        } else {
```

```
            result += c;
```

```
        }
```

```
    }
```

```
    return result;
```

```
}
```

```
// Caesar Cipher Decryption
```

```
string caesarDecrypt(string text, int key)
```

```
{
```

```
    return caesarEncrypt(text, 26 - (key %  
26));
```

```
}
```

```
// Modified Caesar Cipher Encryption
```

```
string modifiedCaesarEncrypt(string text,  
int key) {
```

```
    string result = "";
```

```
    for (size_t i = 0; i < text.length(); ++i) {
```

```
        char c = text[i];
```

```
        if (isalpha(c)) {
```

```
            char base = isupper(c) ? 'A' : 'a';
```

```
            int shift = (key + i % 5) % 26;
```

```
            result += (c - base + shift) % 26 +  
base;
```

```
        } else {
```

```
            result += c;
```

```
        }
```

```
    }
```

```
    return result;
```

```
}
```

```
// Modified Caesar Cipher Decryption
```

```
string modifiedCaesarDecrypt(string text,  
int key) {
```

```
    string result = "";
```

```
    for (size_t i = 0; i < text.length(); ++i) {
```

```
        char c = text[i];
```

```
        if (isalpha(c)) {
```

```
            char base = isupper(c) ? 'A' : 'a';
```

```
            int shift = (key + i % 5) % 26;
```

```
            result += (c - base - shift + 26) %  
26 + base;
```

```
        } else {
```

```
            result += c;
```

```
        }
```

```
    }
```

```
    return result;
```

```
}
```

***// Vigenère Cipher Encryption***

```
string vigenereEncrypt(string text, string
key) {

    string result = "";

    int keyLen = key.length();

    int j = 0;

    for (char c : text) {

        if (isalpha(c)) {

            char base = isupper(c) ? 'A' : 'a';

            char keyChar = toupper(key[j %
keyLen]) - 'A';

            result += (c - base + keyChar) % 26
+ base;

            j++;

        } else {

            result += c;

        }

    }

    return result;

}
```

***// Vigenère Cipher Decryption***

```
string vigenereDecrypt(string text, string
key) {

    string result = "";

    int keyLen = key.length();

    int j = 0;

    for (char c : text) {

        if (isalpha(c)) {

            char base = isupper(c) ? 'A' : 'a';

            char keyChar = toupper(key[j %
keyLen]) - 'A';
```

```
            result += (c - base - keyChar + 26)
% 26 + base;

            j++;

        } else {

            result += c;

        }

    }

    return result;

}
```

```
int main() {

    int choice;

    string plaintext, keyStr;

    int keyInt;

    cout << "===== CIPHER MENU
=====\\n";

    cout << "1. Caesar Cipher\\n";

    cout << "2. Modified Caesar Cipher\\n";

    cout << "3. Vigenère Cipher\\n";

    cout << "Enter your choice (1-3): ";

    cin >> choice;

    cin.ignore(); // Clear input buffer

    switch (choice) {

        case 1:

            cout << "Enter plaintext: ";

            getline(cin, plaintext);

            cout << "Enter key (int): ";

            cin >> keyInt;

            {

                string encrypted =
caesarEncrypt(plaintext, keyInt);
```

```

        string decrypted =
caesarDecrypt(encrypted, keyInt);

        cout << "Encrypted text: " <<
encrypted << endl;

        cout << "Decrypted text: " <<
decrypted << endl;

    }

    break;

case 2:

    cout << "Enter plaintext: ";

    getline(cin, plaintext);

    cout << "Enter base key (int): ";

    cin >> keyInt;

    {

        string encrypted =
modifiedCaesarEncrypt(plaintext, keyInt);

        string decrypted =
modifiedCaesarDecrypt(encrypted,
keyInt);

        cout << "Encrypted text: " <<
encrypted << endl;

        cout << "Decrypted text: " <<
decrypted << endl;

    }

    break;

```

```

case 3:

    cout << "Enter plaintext: ";

    getline(cin, plaintext);

    cout << "Enter keyword: ";

    getline(cin, keyStr);

    {

        string encrypted =
vigenereEncrypt(plaintext, keyStr);

        string decrypted =
vigenereDecrypt(encrypted, keyStr);

        cout << "Encrypted text: " <<
encrypted << endl;

        cout << "Decrypted text: " <<
decrypted << endl;

    }

    break;

default:

    cout << "Invalid choice!" << endl;

}

return 0;

}

```

```
PS E:\Practicals\Practicals 7th Sem\CNS\Practical 1> cd "e:\Practicals\Practicals 7th Sem\CNS\Practical 1\" ; if ($?) { g++ practical1.cpp -o practical1
if ($?) { .\practical1 }
===== CIPHER MENU =====
1. Caesar Cipher
2. Modified Caesar Cipher
3. Vigenere Cipher
Enter your choice (1-3): 1
Enter plaintext: helloworld
Enter key (int): 3
Encrypted text: khoodruog
Decrypted text: helloworld
```

```
PS E:\Practicals\Practicals 7th Sem\CNS\Practical 1> cd "e:\Practicals\Practicals 7th Sem\CNS\Practical 1\" ; if ($?) { g++ practical1.cpp -o practical1
if ($?) { .\practical1 }
===== CIPHER MENU =====
1. Caesar Cipher
2. Modified Caesar Cipher
3. Vigenere Cipher
Enter your choice (1-3): 2
Enter plaintext: music
Enter base key (int): 1,2
Encrypted text: nwmvh
Decrypted text: music
PS E:\Practicals\Practicals 7th Sem\CNS\Practical 1> |
```

```
PS E:\Practicals\Practicals 7th Sem\CNS\Practical 1> cd "e:\Practicals\Practicals 7th Sem\CNS\Practical 1\" ; if ($?) { g++ practical1.cpp -o practical1
if ($?) { .\practical1 }
===== CIPHER MENU =====
1. Caesar Cipher
2. Modified Caesar Cipher
3. Vigenere Cipher
Enter your choice (1-3): 3
Enter plaintext: apple
Enter keyword: snow
Encrypted text: scdhw
Decrypted text: apple
```

# PLAYFIRE CIPHER

```
//PLAYFIRE CIPHER
```

```
#include <iostream>
```

```
#include <vector>
```

```
#include <algorithm>
```

```
#include <cctype>
```

```
using namespace std;
```

```
char matrix[5][5];
```

```
// Check if character already exists in the  
key matrix
```

```
bool exists(char c, string& used) {  
    return used.find(c) != string::npos;  
}
```

```
// Create 5x5 Playfair matrix from key
```

```
void generateMatrix(string key) {  
    string used = "";  
    key.erase(remove(key.begin(),  
key.end(), 'J'), key.end()); // Replace J with  
I rule
```

```
    key +=  
"ABCDEFGHIJKLMNOPQRSTUVWXYZ";
```

```
    int idx = 0;
```

```
    for (char c : key) {
```

```
        c = toupper(c);
```

```
        if (isalpha(c) && !exists(c, used)) {
```

```
            used += c;
```

```
            matrix[idx / 5][idx % 5] = c;
```

```
            idx++;
```

```
        }
```

```
    }
```

```
// Find row and column of a character in  
matrix
```

```
void findPosition(char c, int &row, int  
&col) {
```

```
    if (c == 'J') c = 'I';
```

```
    for (int i = 0; i < 5; i++)
```

```
        for (int j = 0; j < 5; j++)
```

```
            if (matrix[i][j] == c) {
```

```
                row = i;
```

```
                col = j;
```

```
                return;
```

```
            }
```

```
    }
```

```
// Prepare text into digraphs, insert bogus  
letter if needed
```

```
vector<pair<char, char>>
```

```
prepareText(string text, char bogus) {
```

```
    vector<pair<char, char>> pairs;
```

```
    text.erase(remove(text.begin(),  
text.end(), ' '), text.end());
```

```
    for (char &c : text) {
```

```
        if (c == 'J') c = 'I';
```

```
        c = toupper(c);
```

```
    }
```

```
    for (size_t i = 0; i < text.length(); ) {
```

```
        char a = text[i];
```

```
        char b;
```

```
        if (i + 1 < text.length()) {
```

```
            b = text[i + 1];
```

```
            if (a == b) {
```

```
                b = bogus;
```

```
                i++;
```

```
            } else {
```

```
                i += 2;
```

```

    }
} else {
    b = bogus;
i++;
}
pairs.push_back({a, b});
}
return pairs;
}

// Encrypt text using Playfair rules
string encrypt(string text, char bogus) {
    vector<pair<char, char>> pairs =
prepareText(text, bogus);

    string cipher = "";
    for (auto p : pairs) {
        int r1, c1, r2, c2;

        findPosition(p.first, r1, c1);
        findPosition(p.second, r2, c2);

        if (r1 == r2) {
            cipher += matrix[r1][(c1 + 1) % 5];
            cipher += matrix[r2][(c2 + 1) % 5];
        } else if (c1 == c2) {
            cipher += matrix[(r1 + 1) % 5][c1];
            cipher += matrix[(r2 + 1) % 5][c2];
        } else {
            cipher += matrix[r1][c2];
            cipher += matrix[r2][c1];
        }
    }
    return cipher;
}

```

**// Decrypt ciphertext using Playfair rules**

```

string decrypt(string cipher) {
    string plain = "";
    for (size_t i = 0; i < cipher.length(); i +=
2) {
        char a = cipher[i];
        char b = cipher[i + 1];
        int r1, c1, r2, c2;
        findPosition(a, r1, c1);
        findPosition(b, r2, c2);
        if (r1 == r2) {
            plain += matrix[r1][(c1 + 4) % 5];
            plain += matrix[r2][(c2 + 4) % 5];
        } else if (c1 == c2) {
            plain += matrix[(r1 + 4) % 5][c1];
            plain += matrix[(r2 + 4) % 5][c2];
        } else {
            plain += matrix[r1][c2];
            plain += matrix[r2][c1];
        }
    }
    return plain;
}

int main() {
    string key, plaintext, ciphertext;
    char bogus;

    cout << "Enter the key: ";
    getline(cin, key);

    cout << "Enter the bogus/filler letter
(e.g. X): ";

    cin >> bogus;

    bogus = toupper(bogus);

    cin.ignore(); // to consume newline after
bogus letter input
    cout << "Enter the plaintext: ";
}

```

```

getline(cin, plaintext);

generateMatrix(key);

cout << "\nPlayfair Matrix:\n";

for (int i = 0; i < 5; i++) {
    for (int j = 0; j < 5; j++) {
        cout << matrix[i][j] << " ";
    }

    cout << endl;
}

```

```

ciphertext = encrypt(plaintext, bogus);

cout << "\nEncrypted Ciphertext: " <<
ciphertext << endl;

string decrypted = decrypt(ciphertext);

cout << "Decrypted Text: " <<
decrypted << endl;

return 0;
}

```

```

PS E:\Practicals\Practicals 7th Sem\CNS\Practical 1> cd "e:\Practicals\Practicals 7th Sem\CNS\Practical 1\" ; if ($?) { g++ playfire.cpp -o playfire } ;
$?) { .\playfire }
Enter the key: computer
Enter the bogus/filler letter (e.g. X): X
Enter the plaintext: tables

Playfair Matrix:
C O M P U
T E R A B
D F G H I
K L N Q S
V W X Y Z

Encrypted Ciphertext: EBESBL
Decrypted Text: TABLES

```