Machine Learning Exercise Sheet 11

Dimensionality Reduction & Matrix Factorization

In-class Exercise

There is no in-class exercise this week.

Homework

t-SNE

Problem 1: Figure 1 shows a scatter plot of your two-dimensional data (N=13 instances). You want to apply a non-linear dimensionality reduction technique based on neighbor graphs (e.g. T-SNE or UMAP). As a first step you compute the $N \times N$, weighted adjacency matrix representing the neighbor graph. Assume that the weights are computed as

$$p_{j|i} = \frac{\exp\left(-\|\mathbf{x}_{i} - \mathbf{x}_{j}\|^{2} / 2\sigma^{2}\right)}{\sum_{k \neq i} \exp\left(-\|\mathbf{x}_{i} - \mathbf{x}_{k}\|^{2} / 2\sigma^{2}\right)}$$

where $x_i \in \mathbb{R}^2$ and you set $p_{i|i} = 0$. Finally, you obtain the similarity between instances i and j with $p_{ij} = \frac{p_{i|j} + p_{j|i}}{2}$.





Figure 1: Scatter plot of the data

Which of the following neighbor graph plots (pixel in position i, j shows the value of p_{ij}) corresponds to the given dataset and the stated formula for $\sigma = 2$? What is your answer for $\sigma = 5$? Justify your answers!



Autoencoders

Problem 2: We train a linear autoencoder to *D*-dimensional data. The autoencoder has a single *K*-dimensional hidden layer, there are no biases, and all activation functions are identity $(\sigma(x) = x)$.

- Why is it usually impossible to get zero reconstruction error in this setting if K < D?
- Under which conditions is this possible?

Coding Exercise

Problem 3: Download the notebook exercise_11_notebook.ipynb and exercise_11_matrix_factorization_ratings.npy from Moodle. Fill in the missing code and run the notebook. Convert the evaluated notebook to PDF and append it to your other solutions before uploading.