


# Computer Vision II: Multiple View Geometry (IN2228)

## Chapter 05 Correspondence Estimation (Part 3 Clarification and SIFT)

Dr. Haoang Li

31 May 2023 12:00-13:30



# Announcement before Class

## ➤ Exam

### ✓ Cheat sheet

- We will hold a lecture for knowledge review in July (highlighting knowledge important for our exam). The review scope will be narrowed down. Accordingly, we tentatively do not allow the cheat sheet in our exam.

### ✓ Document for reviewing Chapters 01--05

- We uploaded a document to highlight important knowledge in Chapters 00—05. It will be highly relevant to the final exam. If you want, you can start to review Chapters 00-05 from now on. Please download this document from our course website or Moodle.
- The other pages related to the highlighted knowledge should be also reviewed. I will give you a more precise scope in the future review class.
- This document is subject to “slight” change since our exam questions have not been finalized.

# Announcement before Class

## ➤ Updated Lecture Schedule

For updates, slides, and additional materials:

<https://cvg.cit.tum.de/teaching/ss2023/cv2>

90-minute course; 45-minute course

Wed 19.04.2023	Chapter 00: Introduction	Foundation
Thu 20.04.2023	Chapter 01: Mathematical Backgrounds	
Wed 26.04.2023	Chapter 02: Motion and Scene Representation (Part 1)	
Thu 27.04.2023	Chapter 02: Motion and Scene Representation (Part 2)	
Wed 03.05.2023	Chapter 03: Image Formation (Part 1)	
Thu 04.05.2023	Chapter 03: Image Formation (Part 2)	
Wed 10.05.2023	Chapter 04: Camera Calibration	
Thu 11.05.2023	Chapter 05: Correspondence Estimation (Part 1)	
Wed 17.05.2023	Chapter 05: Correspondence Estimation (Part 2)	
Thu 18.05.2023	No lecture (Public Holiday)	

Wed 24.05.2023 No lecture (Conference)  
 Thu 25.05.2023 No lecture (Conference)

} Videos and reading materials  
 about the combination of deep  
 learning and multi-view geometry

Wed 31.05.2023 Chapter 05: Correspondence Estimation (Part 3)

Thu 01.06.2023 Chapter 06: 2D-2D Geometry (Part 1)

Wed 07.06.2023 Chapter 06: 2D-2D Geometry (Part 2)

Thu 08.06.2023 No lecture (Public Holiday)

Wed 14.06.2023 Chapter 06: 2D-2D Geometry (Part 3)

Thu 15.06.2023 Chapter 07: 3D-2D Geometry (Part 1)

Wed 21.06.2023 Chapter 07: 3D-2D Geometry (Part 2)

Thu 22.06.2023 Chapter 08: 3D-3D Geometry

Wed 28.06.2023 Chapter 09: Single-view Geometry (Part 1)

Thu 29.06.2023 Chapter 09: Single-view Geometry (Part 2)

Core part

Wed 05.07.2023 Chapter 10: Photometric Error (Direct Method)

Thu 06.07.2023 Chapter 11: Bundle Adjustment and Optimization

Wed 12.07.2023 Chapter 12: Robot Estimation

Thu 13.07.2023 Knowledge Review

Wed 19.07.2023 Chapter 13: SLAM and SFM (Part 2)

Thu 20.07.2023 Chapter 13: SLAM and SFM (Part 1)

Advanced topics and  
high-level task

## Today's Outline

- Recap on Feature Matching Problem
- Recap on Patch Descriptor-based Method
- Response to Frequently-asked Questions
- A More Effective Method: SIFT
- Other Methods


# Recap on Feature Matching Problem

## ➤ Problem Formulation

✓ Given a detected point in  $I_1$ , how to find the best match in  $I_2$ ?

Here, we assume that **detected points (Harris)**, **points' descriptions (scale, rotation etc.)** are both known. A naive matching strategy is **brute force matching**.

- **Based on descriptor similarity**, compare each feature in  $I_1$  against all the features in  $I_2$  ( $N^2$  comparisons, where  $N$  is the number of features in each image). Select the point pair with the minimum distance.
- **How to define descriptor? How to measure similarity?**




# Recap on Feature Matching Problem

## ➤ Two types of descriptions


### ✓ Patch descriptor (i.e., patch of **intensity values**)

- Introduced in our last class
- Patch need to be warped to the canonical space




### ✓ Census descriptor (a vector with integer/float values)

- Introduced today



# Recap on Feature Matching Problem

## ➤ Descriptor similarity measurement (2D patch)



2D patches

- ✓ **Sum of Squared Differences (SSD):** always  $\geq 0$ . It's exactly 0 only if  $H$  and  $F$  are identical

$$SSD = \sum_{u=-k}^k \sum_{v=-k}^k (H(u, v) - F(u, v))^2$$

- ✓ **Sum of Absolute Differences (SAD):** always  $\geq 0$ . It's 0 only if  $H$  and  $F$  are identical

$H$  and  $F$  denote left and right patches respectively

$$SAD = \sum_{u=-k}^k \sum_{v=-k}^k |H(u, v) - F(u, v)|$$

- ✓ To account for the difference in the average intensity of two images (typically caused by additive illumination changes), we subtract the mean value of each image:

$$\mu_H = \frac{1}{n} \sum_{u=-k}^k \sum_{v=-k}^k H(u, v) \quad \mu_F = \frac{1}{n} \sum_{u=-k}^k \sum_{v=-k}^k F(u, v)$$



Zero-mean

$$ZSSD = \sum_{u=-k}^k \sum_{v=-k}^k ((H(u, v) - \mu_H) - (F(u, v) - \mu_F))^2$$

# Recap on Feature Matching Problem

- Descriptor Similarity measurement (1D census vector)
- ✓ Normalized Cross Correlation (NCC): ranges between -1 and +1 and is exactly 1 if  $H$  and  $F$  are identical

(1,1) and (1,1):  
NCC = 1

$$NCC = \frac{\sum_{u=-k}^k \sum_{v=-k}^k H(u,v)F(u,v)}{\sqrt{\sum_{u=-k}^k \sum_{v=-k}^k H(u,v)^2} \sqrt{\sum_{u=-k}^k \sum_{v=-k}^k F(u,v)^2}}$$

(1,1) and (-1,-1):  
NCC = -1





1D descriptors

- ✓ Cosine Euclidean, or Hamming distance are also applicable

$$d(\mathbf{p}, \mathbf{q}) = \sqrt{\sum_{i=1}^n (q_i - p_i)^2}$$

Euclidean distance






# Recap on Feature Matching Problem

➤ Structure of Knowledge Introduction


✓ Two types of methods



# Recap on Patch Descriptor-based Method

## ➤ General pipeline

- ✓ It is based on the patch descriptor (scale, rotation, etc.).
- ✓ Warp each patch into a canonical patch.
- ✓ Establish point correspondences based on similarity (SSD) of the warped patch.




# Recap on Patch Descriptor-based Method

## ➤ Properties of Patch Descriptor

- ✓ Distinctiveness of a feature descriptor
  - A descriptor is a “description” of the pixel information **around** a feature.
  - “Distinctiveness” means that the descriptor can uniquely distinguish a feature from the other features **without ambiguity**.
- ✓ Robustness to geometric changes
  - **Scale**-invariant (for zooming)
  - **Rotation**-invariant
  - View point-invariant (for perspective changes)



Distinctiveness



Geometric changes

# Recap on Patch Descriptor-based Method

Normalize

## ➤ Scale of Patch Descriptor

直接但低效的补丁比例搜索（依靠两张图像）。


- 假设我们在左右两幅图像中独立地检测到一些具有不同尺度的关键点（在此，我们只考虑尺度）。

- 我们的目的是使用蛮力匹配，根据其相关补丁特征的平方距离之和（SSD）来匹配点。

- 问题是：两个大小相同的斑块由于尺度不同而有不同的外观（即使它们是对应的斑块），因此我们不能直接使用SSD（见下文）。

### ✓ Straightforward but inefficient patch scale search (relying on two images)



- Assume that we have independently detected some key points in the left and right *images with different scales* (here, we only consider scale).
- We aim to use **brute force matching** to match points based on sum of squared distances (SSD) of their associated patch features.
- Problem: Two patches with **the same size have different appearances due to different scales (even if they are corresponding patches)**, and thus we cannot **directly** use SSD (see below).



# Recap on Patch Descriptor-based Method

## ➤ Scale of Patch Descriptor


- ✓ Straightforward but inefficient patch scale search (relying on two images)
- A straightforward solution is to keep the **left patch unchanged**, and **resize the right patch** with different tentative sizes.



# Recap on Patch Descriptor-based Method

## ➤ Scale of Patch Descriptor


- ✓ Straightforward but inefficient patch scale search (relying on two images)
- In practice, for **each** left patch, we have to **validate all the right patches** using **all the tentative scales**.
- We take **a patch in the left image** for example.



# Recap on Patch Descriptor-based Method

## ➤ Scale of Patch Descriptor

- ✓ Straightforward but inefficient patch scale search (relying on two images)
- Drawback 1: Scale determination depends on tentative matching.  
Algorithm complexity is  $N^2S$  assuming  $N$  features per image and  $S$  tentative sizes per feature.  
First  $N$ : number of left patches; Second  $N$ : number of right patches
- Drawback 2: We fix the scale of left patch, but cannot guarantee this scale is optimal (distinctive enough).



# Recap on Patch Descriptor-based Method

## ➤ Scale of Patch Descriptor


❓ 直截了当但效率低下的补丁比例搜索（依靠两张图片）。

- 与已知尺度的蛮力匹配的关系（之前介绍过）：在蛮力匹配中，我们假设每个补丁的比例是预先知道的。因此，复杂度只有  $NN^2$

- 如果我们能在匹配前确定比例（与匹配无关），那就太好了。如何实现这一点？（如何在一张图片中自动确定比例？）

## ✓ Straightforward but inefficient patch scale search (relying on two images)

- Relationship with brute force matching with **known** scales (introduced before): In brute force matching, we assume that scale of each **patch is known a priori**. So, the complexity is only  $N^2$
- It would be great if we can determine the scale before matching (**independent of matching**). How to achieve this? (How to **automatically** determine the scale in **a single image**?)






# Recap on Patch Descriptor-based Method

## ➤ Scale of Patch Descriptor

### ✓ Automatic scale determination


- We aim to “**automatically**” assign each patch (both left and right) its own size.
- In other words, we assign scale based on **a single image**. Our scale assignment is **independent of tentative matching**.



Scale is determined using **a single** image

# Recap on Patch Descriptor-based Method

- Scale of Patch Descriptor
- ✓ Automatic scale determination
  - 如果我们实现了自动标度的确定，之前介绍的直接但低效的方法就会退化为与已知标度的蛮力匹配（没有暂定标度测试）。
  - 这只是一个概述。我将在后面回顾自动比例确定的细节。
- If we achieve the automatic scale determination, the straightforward but inefficient method introduced before **degenerate into** the brute force matching with known scales (no tentative scale test).
- This is just an overview. I will review **details of automatic scale determination** later.



# Explanations for FAQ


## ➤ Patch Descriptor about Rotating

*Derotate patch.*

### ✓ Two strategies to rotate patch (first)

- The Harris detector is rotation invariant
- Eigenvectors of M matrix correspond to the directions of quickest and slowest changes of SSD

direction of quickest change  
of SSD



direction of the slowest  
change of SSD

Image 1





Image 2



Ellipse rotates but its shape (i.e., eigenvalues of M) remains the same.




# Response to FAQ

## ➤ Patch Descriptor about Rotating

### ✓ Two strategies to rotate patch (second)

- Compute gradients vectors **at each pixel** within a patch.
- Build a histogram of gradient orientations, weighted by the gradient magnitudes (norm of vector).
- Extract all local maxima in the histogram: each local maximum above a threshold is a candidate dominant orientation. (Typically, we have up to three directions.)

One patch with multiple pixels




# Response to FAQ

## ➤ Understanding Blob with Scale

### ✓ Formal definition of blob (introduced in our previous class)

- A blob is a group of connected pixels in an image that share some common property (e.g, grayscale value).
- In the image below, the colored regions are blobs. Given **a single image**, we aim to detect blobs and **"automatically" assign them "appropriate" scales**.



not always ○  
maybe □△

**"Automatically"** obtained  
scale in a single image

❓ blob的正式定义（在我们的上一堂课中介绍过）

- blob是指图像中一组具有某种共同属性（如灰度值）的相连像素。

- 在下面的图片中，彩色区域就是blob。给定一个单一的图像，我们的目标是检测blob，并"自动"为其分配"适当"的尺度。



Different blob scales in two images

**Appropriate:** Circles correspond to the  
same 3D area

blob is much not circle

## Response to FAQ

### ➤ Understanding Blob with Scale


#### ✓ Reason for blob detection/marking

- In feature **matching** problem, a blob inherently encodes the **scale** information (corner can hardly encode this information). Accordingly, we can directly resize the two patches and evaluate them by SSD.
- Mathematically, scale can be expressed by the radius of circle.

#### ❓ 探测/标记blob的原因

- 在特征匹配问题中，blob本质上编码了比例信息（角落很难编码这一信息）。因此，我们可以直接调整两个补丁的大小，并通过SSD来评估它们。

- 在数学上，比例可以用圆的半径来表示。



## Response to FAQ


### ➤ Understanding Blob with Scale

#### ✓ From blob matching to point correspondence

- Given a pair of matched blobs, their centers constitute a point correspondence.
- A small drawback: Blob centers may not be very precise, compared with corners

- 给出一对匹配的布卢，它们的中心构成一个点的对应关系。

- 一个小小的缺点：与角落相比，Blob中心可能不是非常精确的




Blob centers constitute a point correspondence


# Response to FAQ

## ➤ Understanding Blob with Scale

- ✓ First type of misunderstanding
  - Some students may misunderstand that we aim to find the precise contours to tightly enclose blobs with different shapes (see below).
  - Instead, in our context, we focus on finding a **circle** to appropriately **mark** each blob (circle is unnecessarily an inscribed or circumscribed circle).



Misunderstanding



Our goal



## 第二种类型的误解

# Response to FAQ

## ➤ Understanding Blob with Scale


- 有些学生可能误以为我们只能处理圆形blob。事实并非如此。在实践中，我们可以处理任意形状的blob。

- 在谈论比例计算时，我考虑用圆形的blob来说明。

- 我原本想用这个简化的案例来帮助你理解整个管道，而不去讨论太多的细节。然而，这似乎可能会误导你。在下文中，我将澄清这个问题，然后用另一种方式来介绍知识。

### ✓ Second type of misunderstanding

- Some students may misunderstand that we can only handle circular blob. It is not the case. In practice, we can deal with blobs with arbitrary shapes.
- When talking about scale computation, I consider the **circular blob** for illustration.
- I originally want to use this simplified case to help you understand the overall pipeline without going into too many details. **However, it seems that it may mislead you. In the following, I will clarify this issue and then use another way to introduce knowledge.**



# Response to FAQ

## ➤ Understanding Blob with Scale

### ✓ Simplified but not general case (introduced in the last class)

- Assume that we have detected a circular blob. Which scale will lead to the maximum convolution response?

A conclusion introduced in the class. Relationship between scale  $\sigma$  and radius  $r$  is  $\sigma = r / \sqrt{2}$ .





image  
A known  
circular blob



Configuration for  
maximum response

Simplified case

$$\begin{aligned}\nabla^2 G(x, y) &= \frac{\partial^2 G(x, y)}{\partial x^2} + \frac{\partial^2 G(x, y)}{\partial y^2} = \frac{\partial}{\partial x} \left[ \frac{-x}{\sigma^2} e^{-\frac{x^2+y^2}{2\sigma^2}} \right] + \frac{\partial}{\partial y} \left[ \frac{-y}{\sigma^2} e^{-\frac{x^2+y^2}{2\sigma^2}} \right] \\ &= \left[ \frac{x^2}{\sigma^4} - \frac{1}{\sigma^2} \right] e^{-\frac{x^2+y^2}{2\sigma^2}} + \left[ \frac{y^2}{\sigma^4} - \frac{1}{\sigma^2} \right] e^{-\frac{x^2+y^2}{2\sigma^2}} \\ \nabla^2 G(x, y) &= \left[ \frac{x^2 + y^2 - 2\sigma^2}{\sigma^4} \right] e^{-\frac{x^2+y^2}{2\sigma^2}} \\ (x^2 + y^2 - 2\sigma^2) \cdot \exp\left(-\frac{x^2+y^2}{2\sigma^2}\right) \\ r^2 - 2\sigma^2 &= 0\end{aligned}$$



General case

- In practice, we do not know circular blob a priori. So, 1) how can we detect a blob with an arbitrary shape? 2) Can we still use a circle to mark such a blob? 3) What's the practicality of the above conclusion?

# Response to FAQ

## ➤ Understanding Blob with Scale

### ✓ How to detect a blob and determine its optimal scale $\sigma$ ?



- Main idea: we have to try a set of candidates.
- Only a single image is enough. We take a patch for example.
- Briefly, we apply a kernel (Laplacian of Gaussian) w.r.t. a single parameter  $\sigma$  to **an image patch**.
- We validate **a set of candidate scales**  $\sigma$ . A scale leading to the **maximum response** is the optimal scale of patch (**characteristic scale**).

$$f = \text{Kernel} * \text{Image}$$


Function (response)      Patch

↓

Laplacian of Gaussian (LoG) w.r.t. a single unknown parameter  $\sigma$




Function extremum




# Response to FAQ

## ➤ Understanding Blob with Scale

- ✓ How to detect a blob and determine its optimal scale  $\sigma$ ?
- Intuitive illustration of convolution between patch and LoG



- From optimal scale to circle that is used to mark blob



We draw circles based on the conclusion


$$\sigma = r / \sqrt{2}.$$

# Response to FAQ

## ➤ Understanding Blob with Scale

### ✓ How to detect a blob and determine its optimal scale $\sigma$ ?

- A more detailed explanation: We take a pixel for example (it and its neighbors have similar brightness)
  - We try several candidate scales
  - Save the scale achieving the extremum
- 一个更详细的解释：我们以一个像素为例（它和它的邻居有相似的亮度）
- 我们尝试几个候选尺度
- 保存达到极值的比例




# Response to FAQ

## ➤ Understanding Blob with Scale

- ✓ Intuitive illustration of reason for selecting LoG kernel
  - Human can easily determine the scale of a **patch with sufficient textures** (significant gradient).
  - We extract **edge** based on Laplace.
  - By extension, we detect **blob** with scale based on LoG.




Discontinuity



Smoothness

Human can determine the scale by perceiving the change of patch appearance.



$\sigma = 1.4$  (adjustable)

$$LoG = -\frac{1}{\pi\sigma^4} \left[ 1 - \frac{x^2 + y^2}{2\sigma^2} \right] e^{-\frac{x^2 + y^2}{2\sigma^2}}$$

Laplacian of Gaussian (LoG) w.r.t.  
a single unknown parameter  $\sigma$

# Response to FAQ

## ➤ Understanding Blob with Scale


### ✓ Discarding too close patches with the same scale

- Assume that pixel 1 achieves the maximum response at a certain candidate scale  $\sigma_i$ . At the same time, pixels 2 also achieves the maximum response at this scale.
- If pixel 1 and pixel 2 are too close, how to discard one of them?
- We can exploit non-maximum suppression (NMS). We compare their respective extrema and only save the largest extremum.

- 假设像素1在某一候选尺度 $\sigma_i$ 处达到最大响应。同时，像素2也在这个尺度上达到了最大响应。

- 如果像素1和像素2过于接近，如何舍弃其中一个？

- 我们可以利用非极大值抑制（NMS）。我们比较它们各自的极值，只保存最大的极值。



# Response to FAQ

## ➤ Understanding Blob with Scale

### ✓ Summary of Algorithm to detect blobs with scales in a single image

1. Build a Laplacian scale space, starting with some initial scale and going for  $n$  iterations:

- 1.1. Generate a (scale-normalized) Laplacian of Gaussian (LoG) filter at a given scale “sigma”.
- 1.2. Filter image with the LoG kernel.
- 1.3. Save square of Laplacian filter response for current level of scale space.
- 1.4. Increase scale by a factor  $k$ .

2. Perform non-maximum suppression in scale space.

3. Display resulting circles at their characteristic scales.



Input



Result of candidate  
scale validation  
and NMS



# Response to FAQ


See also the previous slide “Straightforward scale search” vs. “automatic scale determination”

## ➤ Understanding Blob with Scale

- ✓ Clarification of **a statement about “known” scale** (introduced in the last class)
  - My statement: Before matching, we have known the scale of each patch a priori. So, we **do NOT need to try several candidate scales when matching** (like straightforward method with complexity  $N^2S$ ).
  - My original meaning: We can first assume that scales of both left and right patch has been obtained. So, we can directly rescale patches and evaluate their difference. (I conceal the detail of scale determination on purpose).
- However, to determine the scale **before matching**, we **still have to try a set of candidate scales**. So, what is the total complexity?



Determine scale **when** matching



Scale determination **before** matching

# Recap on Patch Descriptor-based Method

## ➤ Scale of Patch Descriptor

### ✓ “Straightforward scale search” vs. “automatic scale determination”



Simultaneously find the optimal patch correspondence and optimal scale

Complexity:  $N^2 \cdot S$  = *scale of patch*

Brute force matching with **straightforward** scale search (one-step method)



First step: Scale determination



Second step: brute force matching based on rescaled patches

Complexity:  $S + S + N^2$


Brute force matching with **automatic** scale determination (two-step method)

# Scale-invariant Feature Transform (SIFT)

## ➤ Motivation

### ➤ Disadvantages of patch descriptor-based method

- First: If the warping is not estimated accurately, very small errors in rotation, scale, and view point will affect matching score based on SSD.
- An alternative strategy: census descriptor-based method (to generate a descriptor, we still need to warp patch. However, instead of directly comparing patches by SSD, we compare their associated vector descriptors—less sensitive to noise.)



$$NCC = \frac{\sum_{u=-k}^k \sum_{v=-k}^k H(u,v) F(u,v)}{\sqrt{\sum_{u=-k}^k \sum_{v=-k}^k H(u,v)^2} \sqrt{\sum_{u=-k}^k \sum_{v=-k}^k F(u,v)^2}}$$

1D descriptors

# Scale-invariant Feature Transform (SIFT)


## ➤ Motivation

### ➤ Disadvantages of patch descriptor-based method

- Second: Laplacian of Gaussian (LoG) is relative inefficient.
- An alternative strategy: difference of Gaussian (DoG) kernel\*

$$LOG(x, y) \approx DoG(x, y) = G_{k\sigma}(x, y) - G_{\sigma}(x, y)$$

↓      ↓  
Gaussian at  
different scales




\*The proof that LoG can be approximated by a difference of Gaussian comes from the Heat Equation:  $\frac{\partial G_{\sigma}}{\partial \sigma} = \sigma \nabla^2 G_{\sigma}$


# Scale-invariant Feature Transform (SIFT)

## ➤ Overview

- ✓ Step 1: Key point extraction based on extreme detection using DoG
- ✓ Step 2: Census descriptor assignment by Histogram of Oriented Gradients



First step (Dog instead of LoG)



Second step

# Scale-invariant Feature Transform (SIFT)

## ➤ Key Point Extraction

### ✓ Image blurring based on Gaussian kernel

- This operation blurs the image, but maintains the image size.
- This operation is the **first of two steps** to generate DoG for validation of **a set of candidate scales**.


$$LOG(x, y) \approx DoG(x, y) = G_{k\sigma}(x, y) - G_{\sigma}(x, y)$$

First step of DoG generation

Second step of DoG generation

$$G(x, y) = \frac{1}{2\pi\sigma^2} e^{-\frac{x^2+y^2}{2\sigma^2}}$$

A graphical representation of the 2D Gaussian distribution with mean(0,0) and  $\sigma = 1$  is shown to the right.




# Scale-invariant Feature Transform (SIFT)


## ➤ Key Point Extraction

### ✓ Image down-sampling

- This operation keeps the sharpness, but reduces the image size
- This step is **not a compulsory** step. Even if we only have a single octave, we can still detect key points. This step can be used to find more key points (at each octave, we can find some).



Down-sampled images



Space-scale pyramid




Blurred images

# Scale-invariant Feature Transform (SIFT)

## ➤ Key Point Extraction


- ✓ Building a space-scale pyramid

Adjacent blurred images are subtracted to produce the **Difference of Gaussian (DoG)** images.



These images are similar to the images convolved by a set of LoG with different scales

We take one octave for example






# Scale-invariant Feature Transform (SIFT)

## ➤ Key Point Extraction


### ✓ Scale space extrema detection

SIFT key points: local extrema in DoG images

- Each pixel is compared to 26 neighbors (below in green): its **8 neighbors in the current image (NMS)** + **9 neighbors in the adjacent upper scale** + **9 neighbors in the adjacent lower scale** (9+9: local extremum at different scales—**keep window size unchanged on multiple images**)
- If the pixel is an **extremum** with respect to its **26 neighbors** then it is selected as SIFT **feature**.



We take one octave for example




*same filter size 3x3  
different scale encompassed by different layers*

For each extrema, the output of the SIFT detector is the **location**  $(x, y)$  and the **scale**  $s$

# Scale-invariant Feature Transform (SIFT)

## ➤ Key Point Extraction

### ✓ Representative result



Input image

DoG Images at  
different octaves  
(different resolutions)



Magnitude of  $(G(\sigma x) - G(\sigma/2 x))$  |  $\sigma = 4; \sigma/2 = 1.6$  |



Magnitude of  $(G(\sigma^2 x) - G(\sigma x))$  |  $\sigma = 4; \sigma = 1.6$  |  
(second octave shown at the input resolution for convenience)



Magnitude of  $(G(\sigma^3 x) - G(\sigma^2 x))$  |  $\sigma = 4; \sigma = 1.6$  |  
(third octave shown at the input resolution for convenience)

Multiple octaves can be used to find more key points (at each octave, we can find some).

*different resolution*

Size of circle represents scale






Local extrema of DoG images across  
**Scale** (different  $\sigma$  of Gaussian) and  
**Space** (different resolutions)

# Scale-invariant Feature Transform (SIFT)

## ➤ Descriptor Computation

### ✓ Preprocessing step

- For a blob, consider a circular region around it. The radius of circle is determined by scale of this blob. (**scale-invariant**)
- Compute dominant orientation, and de-rotate the patch. (**rotation-invariant**)
- Reason for **adaptive circle radius** and **de-rotation**: regardless of type of descriptor (patch or census), only **two axis-aligned patches with the same scale** can be compared.




# Scale-invariant Feature Transform (SIFT)

## ➤ Descriptor Computation

### ✓ Compute **histogram of oriented gradients descriptor** (census descriptor)

- Input: a de-rotated patch
- Divide patch into  $4 \times 4$  cells
- For each cell, generate an 8-bin histograms (i.e., 8 directions)




# Scale-invariant Feature Transform (SIFT)

## ➤ Descriptor Computation

### ✓ Compute **histogram of oriented gradients** descriptor (census descriptor)


- Concatenate all histograms into a single 1D vector, resulting SIFT descriptor:  $4 \times 4 \times 8 = 128$  values  
**16 cells** **8 bins**



# Scale-invariant Feature Transform (SIFT)

## ➤ Output of Algorithm

- ✓ Location (pixel coordinates of the center of the patch): 2D vector
- ✓ Scale (i.e., size) of the patch: 1 scalar value (high scale corresponds to high blur in the space scale pyramid)
- ✓ Orientation (dominant direction): 1 scalar value (i.e., angle of the patch)
- ✓ Descriptor:  $4 \times 4 \times 8 = 128$  element 1D vector




HOG Descriptor:  
(1D vector)




# Scale-invariant Feature Transform (SIFT)

- Dominant Direction Determination vs. Census Descriptor Generation
- ✓ Dominant direction determination: pixel-level
- ✓ Descriptor generation: we should first de-rotate the patch based on dominant direction. Then we generate descriptors on cell-level



Pixel-level



Cell-level

# Other Descriptors and Detectors

## ➤ Overview

- ✓ FAST: **F**eatures from **A**ccelerated **S**egment **T**est
- ✓ SURF: **S**peeded **U**p **R**obust **F**eatures
- ✓ BRIEF: **B**inary **R**obust **I**ndependent **E**lementary **F**eatures
- ✓ ORB: **O**riented FAST and **R**otated **B**RIEF
- ✓ BRISK: **B**inary **R**obust **I**nvariant **S**calable **K**eypoints
- ✓ SuperPoint: Deep learning-based method



# Other Descriptors and Detectors

➤ “SURF” Blob Detector & Descriptor


- ✓ SURF: Speeded Up Robust Features
- ✓ Similar to SIFT but much faster
- ✓ Results comparable with SIFT:
  - Faster computation
  - Generally shorter descriptors




# Other Descriptors and Detectors

- “SURF” Blob Detector & Descriptor
- ✓ Basic idea: approximate Gaussian and DoG filters using box filters

Original second order partial derivatives of a Gaussian






$$\frac{\partial^2 G(x,y)}{\partial y^2}$$



$$\frac{\partial^2 G(x,y)}{\partial x \partial y}$$

SURF Approximation using box filters




$$\Sigma = A - B - C + D$$

Integral image

# Other Descriptors and Detectors


## ➤ “SuperPoint”: A Deep Learning-based Method

- ✓ Joint regression of keypoint location and descriptor.



# Other Descriptors and Detectors

- “SuperPoint”: A Deep Learning-based Method
  - ✓ Trained on synthetic images and refined on homographies of real images.
  - ✓ Detector is less accurate than SIFT, but descriptor outperforms SIFT.
  - ✓ For efficiency, it is slower than SIFT.



# Summary

- Recap on Feature Matching Problem
- Recap on Patch Descriptor-based Method
- Response to Frequently-asked Questions
- A More Effective Method: SIFT
- Other Methods

Thank you for your listening!  
If you have any questions, please come to me :-)