

Receiver console audit

Right pillar, response actions, and the post-incident report

2026-10-06

Contents

How to read this	1
Status	1
Decisions	3
1. Severity-ranked findings	5
2. The right-hand pillar	6
3. The ten response buttons	8
4. The contributor chapters panel	11
5. Cross-cutting findings	13
Appendix: how this was verified	13

How to read this

Three screenshots raised three questions. This audit answers all three and reports what else was found on the way.

Every claim here was read out of the code and verified a second time directly. Nothing in this document is inferred from behaviour alone. File and line references are given so any claim can be checked in one jump.

The scenario throughout is the one in the screenshots: an incident at Billund Airport, escalated to **Syddøstjyllands Politi** (politi-sydøstjyl), viewed in that profile's receiver console.

Read the Decisions section and stop. It is the only part that asks anything of the reader. Everything after it is evidence, there so any single claim can be checked without taking the rest on trust. The visual problems that prompted this audit are real but cosmetic. The correctness problems are not.

Status

This audit is a point-in-time record. The findings below describe the code as it stood on 2026-10-06 before any change, and they are left as written so the evidence stays checkable. What has since been decided and done:

Item	Decision	State
Bug A, note timestamp	fix	done
Bug B, notes absent from the audit trail	fix	done
Bug C, dead class and the chapter grid bug	fix	done
D1, dispatch buttons with no assets behind them	a, then b per district	a done
D2, counters that can only read zero	a	done
D3, chapter headline archetype	a	done
D4, identifier drift	a	done
D5, role-blind site gate	a	done
D6, action rail onto the archetype engine	a, sequenced after D4	done
D7, four arrow idioms	a	behavioural half done , idioms still four
D8, colour	a	done
Step 1 missing from the ladder	fix	done
Pillar sectioning	divider-based	done
Panels as cards, bodies recessed	raised after review	done

Every decision is acted on. One thing is deliberately unfinished: D7's four disclosure-arrow idioms are now the same SIZE but are still four separate mechanisms. Merging them is cosmetic refactoring with no behaviour attached, and it was not worth the risk alongside the rest.

Found and fixed while acting on the above, not part of the original audit:

- The simulation clock could be frozen into a state with no way to resume it. Freezing the sim and then cancelling the threat ended every track, which hid the pause control and disabled its keyboard path while the clock was still stopped. Everything on that clock then stayed stopped for the session, which is what left a dispatched helicopter parked in mid-air. The runtime clock check gained a case for it.
- Four separate disclosure-arrow idioms were drawn at different sizes once one of them was enlarged. All four now match, which is a stopgap rather than D7.

Consequently these passages describe code that no longer exists: the --sec-accent top rule on the historical-pattern panel and on the attribution panel has been removed in favour of labelled dividers, so the

colour-budget table in section 2.4 now undercounts what changed. Eight per-step coloured rules remain, which is the unfinished half of D8.

Decisions

Just fix these

Plain bugs. No decision needed, they will be fixed unless you object.

- **Bug A.** Every note ever written carries the same frozen timestamp.
- **Bug B.** Notes do not appear in the Audit trail that the button says it appends to.
- **Bug C.** A dead CSS class, and a layout bug that squashes the chapter meta line to one word per line.

Then answer these eight

Each is a real choice. The recommendation is my opinion, not a finding of the audit. Reply with the number and letter, for example D1 a.

D1. Two dispatch buttons that do nothing

“Deploy patrol” and “Set up perimeter cordon” are shown to a profile precisely because the system has no record of it owning any units.

- a. Hide the dispatch group for profiles with no asset inventory. *Honest immediately. 18 districts lose two buttons they could not use.*
- b. Write real asset inventories for all 18 police districts. *Correct end state. Needs inventory data we do not have yet.*
- c. Leave as is. *A demo risk every time a district profile is opened.*

Recommend a now, and **b** per district as each one is onboarded.

D2. Four report counters that can only ever read zero

CATALOG ENTRIES is never written. CASCADES IN and RESPONSES SENT compare the wrong two kinds of identifier.

- a. Hide counters that cannot yet be populated. *The report shrinks but stops lying.*
- b. Wire them properly. *The report becomes true. Roughly a week of work.*

Recommend a now, **b** once D4 lands.

D3. The chapter headline names the wrong archetype

A police chapter is headlined KINETIC RESPONSE on an event where they dispatched nothing and only coordinated.

- a. Headline what the role actually did on this event. *Becomes event-specific and true.*
- b. Keep both rows, relabel so the difference is readable. *Keeps the organisation’s standing taxonomy visible.*

Recommend a.

D4. The same agency is keyed differently in different files

Six of twelve police districts have two different identifiers. Only 14 of 44 national-pool entries match a role.

- a. Converge on one scheme now. *Cheap today. Touches three files.*
- b. Add a mapping layer and keep both. *A translation surface we maintain forever.*

Recommend a, before any real district is onboarded. This is the one that gets expensive if left.

D5. The site capability gate does not know who is asking

It checks whether a patrol is plausible at a site, never whether this particular agency owns patrols.

- a. Add a role dimension to the gate. *Small. Stops Bornholm being offered patrols at Copenhagen.*
- b. Defer.

Recommend a.

D6. Move the action rail onto the archetype engine

A rule engine covering all 386 agencies already exists. The button rail ignores it and uses a hand-written ladder instead.

- a. Do it now. *Largest item here. Stops each new agency type costing a code change.*
- b. Defer.

Recommend b. Right destination, wrong week.

D7. Four different arrow styles in one panel

Plus three separate systems remembering what is collapsed, one of which silently forgets.

- a. Unify to one. *Mostly deletion.*
- b. Defer.

Recommend a.

D8. Colour

- a. Finish the single-accent pass, and spend the colour on the eight archetype badges, which already have the hooks and today are all the same colour. *Structure separates sections. Colour carries meaning.*
- b. Colour the section arrows instead. *Rebuilds the rainbow that --sec-accent was introduced to remove.*

Recommend a. The design tokens already state the rule: colour is for state, one accent, not many.

1. Severity-ranked findings

Tier 1: the product states things that are not true

These are what a customer notices in a demo.

#	Finding	Where
1	“Deploy patrol” and “Set up perimeter cordon” are captioned “Units this profile controls directly” and are rendered because the system has no record of the profile controlling anything	main.js:24685
2	Both buttons fire a mock adapter. Nothing spawns, nothing moves, no route is drawn	adapters/dispatch_mock.js
3	They write an audit record with flow: 'action-dispatched'. That string appears only inside the mock adapter . Nothing reads it	dispatch_mock.js:56
4	CATALOG ENTRIES in the incident report is permanently zero. Nothing in the entire code-base ever writes into event.catalog	events.js:33
5	CASCADES IN and RESPONSES SENT compare a destination id against a role id. Only 27 of 165 destination ids are also role ids, so for the other 138 these silently read zero	chapter_composer.js:301
6	Every note ever written gets the same hard-coded timestamp, 2026-07-24T14:32:41Z	events.js:915
7	“Add note - Append to audit trail” does not appear in the Audit trail section directly below it	main.js:24931
8	A chapter’s loudest label advertises an archetype the role contributed nothing to	chapter_composer.js:161

Tier 2: scalability

#	Finding	Scale
9	Only 28 of 386 receiver profiles have an asset inventory	7.3 percent
10	Of 21 police-branch roles, 3 have one. 18 districts land on the stub rail	86 percent uncovered
11	The site capability gate takes no role parameter. It is role-blind	main.js:24426
12	The action list is a hardcoded branch ladder, while a working 386-role archetype engine sits unused beside it	main.js:24523
13	Three data files key the same agency differently. 6 of 12 police districts diverge	see 5.3

Tier 3: visual and structural

#	Finding	Where
14	Four different disclosure-arrow idioms in one pillar	see 2.3
15	Three independent collapse-state stores, one with inverted polarity	main.js:25563
16	.c-row-collapsible is applied in markup and has zero CSS rules	main.js:22095
17	Collapse state is keyed by title text, so a title change silently resets it	main.js:25577
18	The single-accent rule is about 20 percent applied: 2 panels against 8	see 2.4
19	A pseudo-element consumes a grid cell, collapsing a column to one word wide	style.css:8405
20	All 8 archetype badge classes set the identical colour	style.css:7882

2. The right-hand pillar

2.1 The brown line is not where it appears to be

The salmon rule reads as though it belongs to RESPONSE OPTIONS. It does not.

#c0817c is the **top border of PRIOR ACTIVITY AT THIS SITE**:

style.css:9372

```
.hist-pattern-panel { border-top: 3px solid var(--sec-accent); }
```

It only looks like a rule under Response Options because Steps 3 through 6 all return an empty string on a live event, so Prior Activity collapses upward and sits directly beneath it.

The only other panel carrying that colour is Attribution, set inline at `attribution.js:301`.

2.2 Why the bottom section has no arrow

It is not a missing arrow. “Request from other agencies” is **structurally not a disclosure**.

`main.js:22235`

```
<div class="c-panel">
  <div class="c-panel-title" ...>Request from other agencies</div>
```

Three things make that final:

1. The wrapper is `c-panel`, not `c-panel c-panel-collapsible`. The arrow exists only as `.c-panel-collapsible > .c-panel-title::before`, so no selector matches and nothing renders.
2. There is no `c-panel-body` wrapper. Adding the class would produce an arrow that collapses nothing.
3. The click binding only attaches to `.c-panel-collapsible > .c-panel-title`, so the title is not clickable.

2.3 Four arrow idioms, three state stores

Section		Collapsible	Arrow mechanism	State store
Mission	Con-sole	no	none	none
Response	Op-tions	yes	CSS <code>::before</code> , one glyph ro-tated	<code>_collapsedPanels</code> , keyed by title text
Prior activity		yes	same CSS pseudo-element	same
Other agencies on case		yes	hand-rolled glyph span in <code>JS_otherAgenciesPanelCollapsed</code> ,	keyed by event id
Request from other agencies		no	none	none
... its child rows		yes	third idiom, fully inline, no class	<code>_otherAgenciesExpanded</code> , inverted polarity

Across the file: 1 CSS pseudo-element against 10 hand-rolled chevron spans.

Three consequences:

- `.c-row-collapsible` is applied at `main.js:22095` and has **zero** CSS rules anywhere. Dead class.
- `_collapsedPanels` keys on title text. The Step 2 title changes between “Step 2 - Select response option” and “Your Response Options” when the event is acknowledged, so collapsing it silently resets.
- Section 5’s rows have no first-child suppression, so the first row draws a hairline directly under the lede paragraph.

2.4 The single-accent rule is 20 percent applied

The token file states the intent at `style.css:41-47`:

One accent for every section and step in an event’s right-hand pillar. Replaces a per-archetype palette of purple, pink, teal, blue, amber and green, which made a case file read as eight unrelated colours rather than one document.

The pillar’s actual 3px top rules:

Colour	Panels
#ffb84d amber	3 (Steps 1, 4, 7)
cyan	2 (Steps 3, 5)
green	2 (Step 6)
grey	1 (admin)
--sec-accent	2 (Prior activity, Attribution)

Eight panels still carry the old per-step palette. The comment describes an intention, not the current state.

2.5 Recommendation on colour

Do not colour the arrows. The design header states the rule plainly: “*semantic colour for state only*” and “*One accent, not many.*” --sec-accent was introduced specifically to kill a per-section rainbow. Colouring arrows per section rebuilds that rainbow somewhere else.

Segment by structure instead:

- One arrow idiom everywhere, the CSS pseudo-element, on every collapsible section without exception.
- Make the two non-collapsible sections look deliberately non-collapsible, rather than looking like collapsibles missing a part.
- Group the five by purpose using weight and spacing, not hue: the brief you read, the actions you take, the context you consult.
- Keep the 3px coloured rule for state only, which is what the token file already says.

The colour budget is better spent on the eight archetype classes, which already have CSS hooks and would carry real meaning. See section 4.4.

3. The ten response buttons

3.1 Why those two dispatch buttons exist

main.js:24681-24685

```
// Politi actors - legacy stub buttons. Only rendered when the
// role does NOT have a defined asset library yet (older Politi
// districts pending real asset spec). Once assetsForReceiverRole
// returns a spec for the role, these stubs are skipped.
if (isActive && isPolitiBranch && !_receiverAssetSpec) {
```

A button group captioned “*Units this profile controls directly*” is gated on the system having **no record of this profile controlling anything**.

The original instinct was correct, and more precisely correct than expected: the buttons are not merely disconnected, they are the fallback shown when the connection is known to be absent.

3.2 What each button does today

Button	Wired	Effect on click
Deploy patrol	Cosmetic	Mock adapter. No entity, no route, no asset state. Flips own escalation to in-progress
Set up perimeter cordon	Cosmetic	Same. A real cordon engine exists in <code>perimeter.js</code> and is never called from here
Request tactical intervention	Wired	Real escalation to <code>politi-aks</code> carrying an assessment package
Cascade to intelligence services	Wired	Real escalation, scoped to destinations configured for the site
Cascade to any agency	Wired	Real escalation across the full 386-role pool
Reply	Wired	Pushes to <code>rec.responses[]</code> , renders back, flips status to acknowledged
Update status	Wired	Real <code>progressStatus</code> plus history, visible in three render sites
Decline cascade	Wired, barely surfaced	Sets status and writes a note. No decline UI exists anywhere
Loop in observer	Wired	Real participant entry, visible in the participants strip
Add note	Wired to store, broken downstream	See 3.3

3.3 Three confirmed defects

The dispatch audit record is write-only exhaust. The mock adapter writes an interaction with flow: 'action-dispatched'. Searching the whole of `src/` for that string returns hits **only inside `dispatch_mock.js` itself**. Nothing consumes it.

Every note carries a frozen timestamp.

```
events.js:915
e.notes.push({
  timestamp: new Date('2026-07-24T14:32:41Z').toISOString(), // demo reference time
  author, text: text.trim(), type: 'note',
});
```

The note does not reach the audit trail it names. `_buildAuditJournal` at `main.js:24931` reads `event.createdAt`, `rec.statusHistory`, `rec.response` and `event.closedAt`. It never reads `event.notes`. So a button labelled “Append to audit trail”, clicked from a panel whose final section is titled “Audit trail”, produces no visible change in that section.

3.4 The site gate is role-blind

```
main.js:24426
function _siteAllowsAction(event, action) {
  if (!event?.siteId) return true;
  const siteCtx = contextForSite(event.siteId);
  const caps = siteCtx?.response_capabilities;
```

```

    if (!Array.isArray(caps)) return true;    // permissive fallback
    return caps.includes(action);
}

```

Two parameters: the event and the action. No role. It asks “is a patrol plausible at this site” and never “does this role own patrols”. Bornholms Politi is offered Deploy patrol at Copenhagen Airport.

Site capability data is real and well-formed. All nine declared sites carry `response_capabilities`. The six Energinet substations declare only `['brs-standby', 'hjb-reinforce']`, so a police profile there correctly sees no dispatch buttons. The gate works. It is simply only half the question.

3.5 Scalability: two lanes

The lane that scales. `receiver_assets.js` is a clean plug-in: add a top-level key per role with `dispatchable[]` and `requestable[]`, and the generic handlers do the rest. No code change. Coverage today:

Measure	Count
Receiver profiles total	386
With an asset inventory	28 (7.3 percent)
Police-branch roles	21
Police with an inventory	3 (politi-kbh, politi-aks, rigspoliti)
Police districts on the stub rail	18

The lane that does not scale. Everything else in `availableCTAsForReceiver` is a literal branch ladder: `isPolitiBranch`, `isBrsBranch`, `isFlyv`, `isHaer`, `isIntel`, `isKommune`, `isHjbBranch`, `isRegionBranch`, plus exact-id tests such as `roleId === 'agency-traf'`. The function’s own header claims it “*replaces every if role === X hardcoded in the UI*”. It relocated them. A new agency type needs a new `else if` block plus an entry in a 16-item `STUB_DISPATCH_ACTIONS` set.

The engine already built and unused. `archetypes.js` is a prefix-rule engine that stamps all 386 receivers at boot, documented as doing exactly that. The action rail does not consult it at all. Archetypes are used only for report chapters and the cascade picker’s grouping.

3.6 Flows that are off

Decline cascade appears on things that were never cascades. The record is chosen at `main.js:23567` as `_cascades[0] || _matching[0]`, where `_matching` includes plain operator escalations with no assessment package. The decline gate at `main.js:24900` checks only status, never `assessmentPackage`. So a profile that received a direct operator dispatch is offered “Decline cascade”, with a tooltip saying the reason is visible to “operator”.

Cascade to any agency strictly contains Cascade to intelligence services. Both call `escalateEvent` the same way. The second uses a hardcoded two-entry list. They differ in exactly two literal defaults, `cascadeReason` and `defaultPriority`. The code calls the narrower one a “legacy shortcut”.

Four overlapping cordon concepts coexist. The cosmetic `set-cordon stub`; the real `buildCordon / assignPatrols` engine driven only by automatic wreckage flows; a genuinely wired “Record scene released” that stands down cordons; and, for Copenhagen only, a real `cordon-squad` asset. A profile can release a cordon the Set up cordon button never created.

Dead set membership. request-aks is listed in STUB_DISPATCH_ACTIONS but is unreachable there, because its explicit branch fires earlier in the same chain. The set's own header asserts that every entry must route through the adapter seam.

4. The contributor chapters panel

4.1 What it is

Not a stray panel. It is the Post-Incident Report, generated at `closeEvent` and designed in `docs/report-shape-overview.md`: one chapter per agency that touched the event, the reader's own chapter pinned to the top and expanded.

A chapter is not a stored object. There is no `event.chapters`. It is derived at render time from `live.event.escalations`, `event.counterDispatches` and `event.catalog`. The report object itself is never consulted for chapters.

4.2 Four of six counters cannot report a real number

Counter	Status
CASCADES OUT	Works. The 7 is real
DISPATCHES OWNED	Works, but only the real dispatch path writes it, which the stub buttons are not
DISPATCHES OPEN	Works, same caveat
CATALOG ENTRIES	Permanently zero. The 13 sub-arrays are created and backfilled. Nothing anywhere ever pushes into them
CASCADES IN	Mostly unreachable. Compares <code>escalation.destinationId</code> against a role id
RESPONSES SENT	Mostly unreachable. Derived from the same filter

Destination ids and role ids are different namespaces. Destination ids look like `cph-t4-forsvar`; role ids look like `politi-sydostjyl`. Only **27 of 165** destination ids are also role ids. For the remaining 138 the counter silently reads zero.

`post_incident_report.js:210` documents the mismatch and compensates by resolving `dest.ownerRoleId`. That field **does not exist on any destination**, so the compensation is inert as well.

A reading of `0 / 7 / 0 / 0 / 0 / 0` therefore does not mean “nothing happened”. It largely means “cannot be counted”.

4.3 The archetype pills contradict each other, and both are right

The white pill reads KINETIC RESPONSE. POPULATED ARCHETYPES reads Coordination and command. They measure different things:

- The pills beside the role name are **static taxonomy**: what a police district *is*, from the rule `prefix('politi-') -> primary KINETIC`. Independent of the event.

- POPULATED ARCHETYPES is **what this role produced on this event**. The kinetic sub-section needs dispatches owned by the role, of which there were none, so it rendered empty. The coordination sub-section fires on cascades initiated with an assessment package, of which there were seven.

So the most prominent label on the card advertises an archetype the role contributed nothing to, while the archetype it did contribute to is rendered dimmed. They are not redundant. They are worse than redundant.

There is a load-bearing note at `archetypes.js:121` confirming that reclassifying a role does not change the report, because chapter composition never reads archetype at all.

4.4 Eight colour hooks doing nothing

```
style.css:7882-7889
.chapter-arch-badge-kinetic-response      { border-left: 2px solid var(--sec-accent); }
... six more ...
.chapter-arch-badge-international-liaison { border-left: 2px solid var(--sec-accent); }
```

Eight selectors, one colour. The markup implies per-archetype colour-coding that does not exist. This is where a colour budget would buy real meaning, rather than on the pillar's section arrows.

4.5 There is no commenting feature

Searching the chapter composer, the sub-section renderers and the report module for `textarea`, `button`, `contenteditable`, `input`, `comment`, `annotate` and `remark` returns **zero** matches. Both modules declare themselves read-only. The only interactive element in the whole report panel is a JSON download.

What appears to be a comment affordance is the “Add note” button in the **centre** pane. The workspace is two panes: the centre holds the event report and its action rail, the right aside holds the mission console and the post-incident report.

And notes never reach the report. Operator notes render in exactly three places, none of which is the post-incident report or any chapter.

4.6 Why the meta line wraps one word per line

```
style.css:8393
.chapter-card-summary {
  display: grid;
  grid-template-columns: 1fr auto auto; /* three columns */
  gap: var(--space-3);
  ...
}
style.css:8405
.chapter-card-summary::before { content: "►"; ... }
```

`display: grid` makes the `::before` pseudo-element a **grid item**, not a marker. So four items are placed into three columns:

1. the arrow takes row 1, column 1, the 1fr track
2. the role name takes row 1, column 2
3. the archetype label takes row 1, column 3
4. the stats text wraps to **row 2, column 1**

That 1fr track is starved. The rail is a fixed 380px, leaving roughly 300px of grid width, and the two auto columns claim max-content first. With no free space, the fr track falls back to its automatic minimum, which is the longest unbreakable word in the stats string.

It is not a min-width. It is a pseudo-element consuming a grid cell.

5. Cross-cutting findings

5.1 Stale architecture documentation

docs/agentric-receiver-asset-plugin-architecture.md closes with “Current profiles configured” listing three: Politi København, Aktionsstyrken, Rigspolitiet. The file now has 28. The document is stale by 25 profiles.

5.2 Stale count comments in code

main.js:17015 says “242 receiver profiles”. The number is 386.

5.3 Three identifier schemes for the same agency

roles.js, response_assets.js and receiver_assets.js do not share keys. Six of twelve police districts diverge:

District	roles.js	response_assets.js
Syddøstjyllands	politi-sydostjyl	politi-sydoest
Østjyllands	politi-ostjyl	politi-oestjyl
Nordsjællands	politi-nordsj	politi-nord
Midt- og Vestjyllands	politi-midtvestjyl	politi-midtvest
Midt- og Vestsjællands	politi-midvestsjaelland	politi-midtsjael
Sydsjællands	politi-sydsjaelland	politi-syd

Only 14 of 44 national-pool ids match a role id. The national asset pool and the role tree cannot be joined by key today. This is the same class of problem as the destination-versus-role mismatch in 4.2, and it is the single most load-bearing thing to fix before onboarding a real district.

5.4 Two dispatch systems, which is easy to confuse

Per docs/agentric-receiver-asset-plugin-architecture.md these are separate by design:

- **Your Response**, centre pane, reads department-owned assets from receiver_assets.js. Answers “what does this department own”.
- **Request from other agencies**, right pillar, reads the national pool in response_assets.js, ranked by real distance. Answers “what national assets can respond to this threat class”.

An empty right pillar therefore does not imply the left pane is unwired. In the audited case neither had data for this profile.

Appendix: how this was verified

Three independent code surveys were run in parallel across src/main.js (26,817 lines), src/style.css, and the supporting modules. Every load-bearing claim was then re-checked directly against the source rather than accepted from the survey.

Claims verified a second time by direct inspection:

- the element carrying the #c0817c rule

- that `.c-row-collapsible` has no CSS rules
- that “Request from other agencies” has no collapsible class or body wrapper
- the stub-button gate at `main.js:24685` and its comment
- the contents of `STUB_DISPATCH_ACTIONS`
- that `flow: 'action-dispatched'` is never read
- the hardcoded note timestamp
- that `_siteAllowsAction` takes no role parameter
- the decline-cascade gate and the record-selection fallback
- that nothing writes into `event.catalog`
- the destination-id versus role-id namespace overlap, measured at 27 of 165
- that `ownerRoleId` does not exist on destinations
- that all eight archetype badge classes use one colour
- every count in this document, recomputed from the source files

The file `src/main 2.js` was excluded throughout. It is a 23,519-line duplicate of `main.js`, imported by nothing, committed by accident in `f1526db`.