



DD2437 – Artificial Neural Networks and Deep Architectures (annda)

Lecture 8: Hopfield networks and introduction to stochastic networks

Pawel Herman

Computational Science and Technology (CST)
KTH Royal Institute of Technology

September 2018



- Associative memory
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Lecture overview

- Associative memory, learning
- Hopfield networks
- Storage capacity
- Optimisation with Hopfield networks
 - travelling salesman problem (TSP) example



- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Associative pattern recognition



- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Associative pattern recognition




boat




- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Associative pattern recognition



- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine


Associative pattern recognition



- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Linear associative memory networks

- Simple single layer networks




without feedback
(recall is a feedforward step)

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine


Linear associative memory networks

- Simple single layer or recurrent networks

$$\mathbf{W}\mathbf{X}=\mathbf{Y}$$



without feedback
(recall is a feedforward step)



autoassociative recurrent network, with feedback
(recall is an iterative process)

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine


Autoassociative memory network with feedback

- Eigenvector automaton

$$\mathbf{W}\vec{x}_i = \lambda_i \vec{x}_i, \quad \vec{x}_1, \dots, \vec{x}_n - \text{eigenvectors of } \mathbf{W}_{n \times n}$$

For any vector \vec{v}_0 and simultaneous computations:

$$\vec{v}_0 = \sum_i \alpha_i \vec{x}_i$$



with feedback, **recurrent**
(iterative recall)

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Autoassociative memory network with feedback

- Eigenvector automaton


$$\mathbf{W}\vec{x}_i = \lambda_i \vec{x}_i, \quad \vec{x}_1, \dots, \vec{x}_n - \text{eigenvectors of } \mathbf{W}_{n \times n}$$

For any vector \vec{v}_0 and simultaneous computations:

$$\vec{v}_0 = \sum_i \alpha_i \vec{x}_i$$

$$\vec{v}_1 = \mathbf{W}\vec{v}_0 = \sum_i \alpha_i \lambda_i \vec{x}_i$$

$$\vec{v}_t = \mathbf{W}\vec{v}_{t-1} = \sum_i \alpha_i \lambda_i^t \vec{x}_i$$



with feedback, **recurrent**
(iterative recall)

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Autoassociative memory network with feedback

- Eigenvector automaton

$$\mathbf{W}\vec{x}_i = \lambda_i \vec{x}_i, \quad \vec{x}_1, \dots, \vec{x}_n - \text{eigenvectors of } \mathbf{W}_{n \times n}$$

For any vector \vec{v}_0 and simultaneous computations:


$$\vec{v}_0 = \sum_i \alpha_i \vec{x}_i$$

$$\vec{v}_1 = \mathbf{W}\vec{v}_0 = \sum_i \alpha_i \lambda_i \vec{x}_i$$

$$\vec{v}_t = \mathbf{W}\vec{v}_{t-1} = \sum_i \alpha_i \lambda_i^t \vec{x}_i$$

$$\vec{v}_t \rightarrow \vec{x}_k$$

Eigenvector with the highest eigenvalue provided that the corresponding α is non-zero.




with feedback, **recurrent**
(iterative recall)

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Associative learning in a single layer network

- Bipolar coding $\{-1, 1\}$ with sign transform:

$$\text{sgn}(x) = \begin{cases} 1, & x \geq 0 \\ -1, & x < 0 \end{cases}$$




- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Associative learning in a single layer network

- Bipolar coding $\{-1, 1\}$ with sign transform:


$$\text{sgn}(x) = \begin{cases} 1, & x \geq 0 \\ -1, & x < 0 \end{cases}$$



- Hebbian learning (correlation learning, outer product)

$$\mathbf{W} = \mathbf{W}^1 + \mathbf{W}^2 + \dots + \mathbf{W}^m$$

$$\mathbf{W}^k = [w_{ij}] = [x_j^k \ y_i^k] \quad (\text{outer product})$$




- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Associative learning in a single layer network

- Bipolar coding $\{-1, 1\}$ with sign transform:


$$\text{sgn}(x) = \begin{cases} 1, & x \geq 0 \\ -1, & x < 0 \end{cases}$$



- Hebbian learning (correlation learning, outer product)

$$\mathbf{W} = \mathbf{W}^1 + \mathbf{W}^2 + \dots + \mathbf{W}^m$$

$$\mathbf{W}^k = [w_{ij}] = [x_j^k \ y_i^k] \quad (\text{outer product})$$



$$\vec{y}_p (\vec{x}_p^T \vec{x}_p) + \sum_{p \neq k}^m \vec{y}_k (\vec{x}_p^T \vec{x}_k)$$

crosstalk

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Hebbian learning for associative memory

- Autoassociative case

$$\mathbf{W} = \mathbf{X}\mathbf{X}^T$$

$$\text{sgn}(\mathbf{W}\vec{x}) = \vec{x}, \quad \text{sgn}(\mathbf{W}\mathbf{X}) = \mathbf{X}$$

Essentially, \vec{x} are the eigenvectors of nonlinear sgn operation so the idea is to find \mathbf{W} for which $\text{sgn}(\mathbf{W}\mathbf{X})$ has these patterns as eigenvectors, but we do not want $\mathbf{W} = \mathbf{I}$ as a trivial solution of $\text{sgn}(\mathbf{W}\mathbf{X}) = \mathbf{X}$

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Hebbian learning for associative memory

- Autoassociative case

$$\mathbf{W} = \mathbf{X}\mathbf{X}^T$$

$$\text{sgn}(\mathbf{W}\vec{x}) = \vec{x}, \quad \text{sgn}(\mathbf{W}\mathbf{X}) = \mathbf{X}$$

Essentially, \vec{x} are the eigenvectors of nonlinear sgn operation so the idea is to find \mathbf{W} for which $\text{sgn}(\mathbf{W}\mathbf{X})$ has these patterns as eigenvectors,

but we do not want $\mathbf{W} = \mathbf{I}$ as a trivial solution of $\text{sgn}(\mathbf{W}\mathbf{X}) = \mathbf{X}$

for $\mathbf{W} = \mathbf{X}\mathbf{X}^T$, $\text{sgn}(\mathbf{W}\mathbf{X}) = \text{sgn}(\mathbf{X}\mathbf{X}^T\mathbf{X})$

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Hebbian learning for associative memory

- Autoassociative case

$$\mathbf{W} = \mathbf{X}\mathbf{X}^T$$

$$\text{sgn}(\mathbf{W}\vec{x}) = \vec{x}, \quad \text{sgn}(\mathbf{W}\mathbf{X}) = \mathbf{X}$$

Essentially, \vec{x} are the eigenvectors of nonlinear sgn operation so the idea is to find \mathbf{W} for which $\text{sgn}(\mathbf{W}\mathbf{X})$ has these patterns as eigenvectors,

but we do not want $\mathbf{W} = \mathbf{I}$ as a trivial solution of $\text{sgn}(\mathbf{W}\mathbf{X}) = \mathbf{X}$

$$\text{for } \mathbf{W} = \mathbf{X}\mathbf{X}^T, \quad \text{sgn}(\mathbf{W}\mathbf{X}) = \text{sgn}(\underbrace{\mathbf{X}\mathbf{X}^T}_{\text{scaled identity}} \mathbf{X})$$

For orthogonal \mathbf{X} (or nearly),
 $\mathbf{X}^T\mathbf{X}$ is a scaled identity \mathbf{I} matrix

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Hebbian learning for associative memory

- Autoassociative case

$$\mathbf{W} = \mathbf{X}\mathbf{X}^T$$

$$\text{sgn}(\mathbf{W}\vec{x}) = \vec{x}, \quad \text{sgn}(\mathbf{W}\mathbf{X}) = \mathbf{X}$$

Essentially, \vec{x} are the eigenvectors of nonlinear sgn operation so the idea is to find \mathbf{W} for which $\text{sgn}(\mathbf{W}\mathbf{X})$ has these patterns as eigenvectors,

but we do not want $\mathbf{W} = \mathbf{I}$ as a trivial solution of $\text{sgn}(\mathbf{W}\mathbf{X}) = \mathbf{X}$

$$\text{for } \mathbf{W} = \mathbf{X}\mathbf{X}^T, \quad \text{sgn}(\mathbf{W}\mathbf{X}) = \text{sgn}(\underbrace{\mathbf{X}\mathbf{X}^T}_{\mathbf{I}}\mathbf{X}) = \text{sgn}(\mathbf{X}) = \mathbf{X}$$

For orthogonal \mathbf{X} (or nearly),
 $\mathbf{X}^T\mathbf{X}$ is a scaled identity \mathbf{I} matrix

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Hebbian learning for associative memory

- Autoassociative case

$$\mathbf{W} = \mathbf{X}\mathbf{X}^T$$

$$\text{sgn}(\mathbf{W}\vec{x}) = \vec{x}, \quad \text{sgn}(\mathbf{W}\mathbf{X}) = \mathbf{X}$$

Essentially, \vec{x} are the eigenvectors of nonlinear sgn operation so the idea is to find \mathbf{W} for which $\text{sgn}(\mathbf{W}\mathbf{X})$ has these patterns as eigenvectors,

$$\mathbf{W} = \mathbf{X}\mathbf{X}^T$$

From a geometrical perspective:

\mathbf{W} describes *non-orthogonal* projection on the subspace spanned by \vec{x} .

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Pseudoinverse-based learning

- For a linear associator $\mathbf{WX} = \mathbf{Y}$

If \mathbf{W} is rectangular, we are looking to minimise $\|\mathbf{WX} - \mathbf{Y}\|$

Pseudoinverse:

$$\mathbf{X}^+ = \min_{\mathbf{W}} \|\mathbf{WX} - \mathbf{Y}\|$$

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Pseudoinverse-based learning

- For a linear associator $\mathbf{WX} = \mathbf{Y}$

If \mathbf{W} is rectangular, we are looking to minimise $\|\mathbf{WX} - \mathbf{Y}\|$

Pseudoinverse:

$$\mathbf{X}^+ = \min_{\mathbf{W}} \|\mathbf{WX} - \mathbf{Y}\|$$

- Pseudoinverse for learning \mathbf{W}

$$\mathbf{W} = \mathbf{YX}^+ \Rightarrow \min \mathbf{E} = \|\mathbf{WX} - \mathbf{Y}\|$$

Minimising \mathbf{E} implies minimisation of the error (deviation from

perfect recall): $\min \sum_i \|\mathbf{w}\vec{x}_i - \vec{y}_i\|^2$

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Pseudoinverse-based learning

- For a linear associator $\mathbf{WX} = \mathbf{Y}$


If \mathbf{W} is rectangular, we are looking to minimise $\|\mathbf{WX} - \mathbf{Y}\|$

Pseudoinverse:

$$\mathbf{X}^+ = \min_{\mathbf{W}} \|\mathbf{WX} - \mathbf{I}\| \Rightarrow \mathbf{W} = \mathbf{YX}^+ = \min_{\arg \mathbf{W}} \{\|\mathbf{WX} - \mathbf{Y}\|\}$$

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Pseudoinverse-based learning



One way to estimate the pseudoinverse is by means of generalized delta rule

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine


Pseudoinverse-based learning

Geometrical interpretation:

$\mathbf{W} = \mathbf{X}\mathbf{X}^+$ represents an orthogonal projection on the space spanned by vectors \vec{x}_i that constitute \mathbf{X} .

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Pseudoinverse-based learning



$\vec{x}_p \mathbf{X}\mathbf{X}^+$ gives the projection closest to memory pattern
with lowest error deviation (in Euclidean and Hamming sense)

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Learning for associative memory networks

Hebbian (outer product) vs pseudoinverse matrix approach


$$\mathbf{W} = \mathbf{X}\mathbf{X}^T \quad \text{vs} \quad \mathbf{W} = \mathbf{Y}\mathbf{X}^+$$

- **Associative memory**
- Hopfield networks
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine


Learning for associative memory networks

Hebbian (outer product) vs pseudoinverse matrix approach

$$\mathbf{W} = \mathbf{X}\mathbf{X}^T \quad \text{vs} \quad \mathbf{W} = \mathbf{Y}\mathbf{X}^+$$



Fast computations and direct
biological interpretation
but non-orthogonal projection causing
memory recall problems





Better reliability and storage capacity (less
problems with crosstalk) with orthogonal
projections mitigating crosstalk problems
when recalling memories

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Bidirectional associative memory (resonance)

Builds on the concept of memory networks with feedback (recursive)

- bipolar $\{-1, 1\}$ coding
- sign activation function




B. Kosko, 1988

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Bidirectional associative memory (resonance)


Builds on the concept of memory networks with feedback (recursive)

- bipolar $\{-1, 1\}$ coding
- sign activation function



Bidirectionality (feedback) imposes extra challenges

- synchronous vs asynchronous update
- different properties depending on updating mode



B. Kosko, 1988

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine


Bidirectional associative memory (resonance)

Builds on the concept of memory networks with feedback (recursive)

- bipolar $\{-1, 1\}$ coding
- sign activation function

$$\vec{y}(t) = \text{sgn}(\mathbf{W}\vec{x}(t))$$


$$\vec{x}(t+1) = \text{sgn}(\mathbf{W}\vec{y}(t))$$



Does it converge?
What are stable points?

Bidirectionality (feedback) imposes extra challenges


- synchronous vs asynchronous update
- different properties depending on updating mode



B. Kosko, 1988

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine


Concept of energy in BAM



If (\vec{x}, \vec{y}) is a stable point, then nearby points like (\vec{x}_0, \vec{y}_0) should converge.

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Concept of energy in BAM




If (\vec{x}, \vec{y}) is a stable point, then nearby points like (\vec{x}_0, \vec{y}_0) should converge.

$$\vec{y}_0 = \mathbf{W}\vec{x}_0, \text{ next } \vec{e} = \mathbf{W}^T \vec{y}_0$$

How far is \vec{e} from \vec{x}_0 ?

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Concept of energy in BAM



If (\vec{x}, \vec{y}) is a stable point, then nearby points like (\vec{x}_0, \vec{y}_0) should converge.


$$\vec{y}_0 = \mathbf{W}\vec{x}_0, \text{ next } \vec{e} = \mathbf{W}^T \vec{y}_0$$

How far is \vec{e} from \vec{x}_0 ?

$$E = -\vec{x}_0^T \vec{e} = -\vec{x}_0^T \mathbf{W}^T \vec{y}_0 = -\vec{y}_0^T \mathbf{W} \vec{x}_0$$

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Concept of energy in BAM



If (\vec{x}, \vec{y}) is a stable point, then nearby points like (\vec{x}_0, \vec{y}_0) should converge.

$$\vec{y}_0 = \mathbf{W}\vec{x}_0, \text{ next } \vec{e} = \mathbf{W}^T \vec{y}_0$$

How far is \vec{e} from \vec{x}_0 ?

$$E = -\vec{x}_0^T \vec{e} = -\vec{x}_0^T \mathbf{W}^T \vec{y}_0 = -\vec{y}_0^T \mathbf{W} \vec{x}_0$$


For the autoassociative BAM with \mathbf{W} , energy in the state \vec{x} :

$$E(\vec{x}, \vec{x}) = -\frac{1}{2} \vec{x}^T \mathbf{W} \vec{x}$$

$$E(\vec{x}) = -\frac{1}{2} \sum_{i,j=1}^n w_{i,j} x_i x_j$$

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Concept of energy in BAM



If (\vec{x}, \vec{y}) is a stable point, then nearby points like (\vec{x}_0, \vec{y}_0) should converge.

$$\vec{y}_0 = \mathbf{W}\vec{x}_0, \text{ next } \vec{e} = \mathbf{W}^T \vec{y}_0$$

How far is \vec{e} from \vec{x}_0 ?

$$E = -\vec{x}_0^T \vec{e} = -\vec{x}_0^T \mathbf{W}^T \vec{y}_0 = -\vec{y}_0^T \mathbf{W} \vec{x}_0$$

For the autoassociative BAM with \mathbf{W} , energy in the state \vec{x} :


$$E(\vec{x}, \vec{x}) = -\frac{1}{2} \vec{x}^T \mathbf{W} \vec{x} + \vec{x}^T \vec{\theta}$$

If bias is added

$$E(\vec{x}) = -\frac{1}{2} \sum_{i,j=1}^n w_{i,j} x_i x_j + \sum_{i=1}^n \theta_i x_i$$

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Hopfield network




$$\forall_i w_{i,i} = 0 \quad \text{no self-connections}$$

$$\vec{x}' = \text{sgn}(\mathbf{W}\vec{x} + \vec{\theta})$$

$$E(\text{state} = \vec{x}) = -\frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n w_{i,j} x_i x_j + \sum_{i=1}^n \theta_i x_i$$

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Hopfield network



$$\forall_i w_{i,i} = 0 \quad \text{no self-connections}$$


$$\vec{x}' = \text{sgn}(\mathbf{W}\vec{x} + \vec{\theta})$$

$$E(\text{state} = \vec{x}) = -\frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n w_{i,j} x_i x_j + \sum_{i=1}^n \theta_i x_i$$

Iterative recall with asynchronous update

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Hopfield network



$$\forall_i w_{i,i} = 0 \quad \text{no self-connections}$$

$$\vec{x}' = \text{sgn}(\mathbf{W}\vec{x} + \vec{\theta})$$


$$E(\text{state} = \vec{x}) = -\frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n w_{i,j} x_i x_j + \sum_{i=1}^n \theta_i x_i$$

Iterative recall with asynchronous update

1) Apply input probe $\xi_p = [\xi_{1,p}, \xi_{2,p}, \dots, \xi_{n,p}]$, i.e. $x_j(0) = \xi_{j,p}$

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Hopfield network



$$\forall_i w_{i,i} = 0 \quad \text{no self-connections}$$

$$\vec{x}' = \text{sgn}(\mathbf{W}\vec{x} + \vec{\theta})$$

$$E(\text{state} = \vec{x}) = -\frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n w_{i,j} x_i x_j + \sum_{i=1}^n \theta_i x_i$$


Iterative recall with asynchronous update

- 1) Apply input probe $\xi_p = [\xi_{1,p}, \xi_{2,p}, \dots, \xi_{n,p}]$, i.e. $x_j(0) = \xi_{j,p}$
- 2) Iterate *asynchronous* update until convergence (until the state \mathbf{x} remains unchanged)

$$x_j(t+1) = \text{sgn}\left(\sum_{i=1}^n w_{j,i} x_i(t)\right) \quad j=1,\dots,n \text{ is randomly selected one at a time}$$

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Hopfield network



$$\forall_i w_{i,i} = 0 \quad \text{no self-connections}$$

$$\vec{x}' = \text{sgn}(\mathbf{W}\vec{x} + \vec{\theta})$$


$$E(\text{state} = \vec{x}) = -\frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n w_{i,j} x_i x_j + \sum_{i=1}^n \theta_i x_i$$

Update occurs only when the state changes, so.....

$$\Delta E_{x_j \rightarrow x_j^*} = -\frac{1}{2} \left(\sum_i^n w_{i,j} x_i x_j^* - \sum_i^n w_{i,j} x_i x_j \right) = -\frac{1}{2} (x_j^* - x_j) \sum_i^n w_{i,j} x_i \leq 0$$

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Hopfield network



$$\forall_i w_{i,i} = 0 \quad \text{no self-connections}$$

$$\vec{x}' = \text{sgn}(\mathbf{W}\vec{x} + \vec{\theta})$$

$$E(\text{state} = \vec{x}) = -\frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n w_{i,j} x_i x_j + \sum_{i=1}^n \theta_i x_i$$

W should be symmetric with diag=0 for convergence


Update occurs only when the state changes, so.....

$$\Delta E_{x_j \rightarrow x_j^*} = -\frac{1}{2} \left(\sum_i w_{i,j} x_i x_j^* - \sum_i w_{i,j} x_i x_j \right) = -\frac{1}{2} (x_j^* - x_j) \sum_i w_{i,j} x_i \leq 0$$

towards lower energy – convergence!

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Hopfield network




$$\forall_i w_{i,i} = 0 \quad \text{no self-connections}$$

$$\vec{x}' = \text{sgn}(\mathbf{W}\vec{x} + \vec{\theta})$$

$$E(\text{state} = \vec{x}) = -\frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n w_{i,j} x_i x_j + \sum_{i=1}^n \theta_i x_i$$


\mathbf{W} should be symmetric with $\text{diag}=0$ for convergence

How many states are candidates for fixed states?



- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Hopfield network





$$\forall_i w_{i,i} = 0 \quad \text{no self-connections}$$

$$\vec{x}' = \text{sgn}(\mathbf{W}\vec{x} + \vec{\theta})$$


$$E(\text{state} = \vec{x}) = -\frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n w_{i,j} x_i x_j + \sum_{i=1}^n \theta_i x_i$$

\mathbf{W} should be symmetric with $\text{diag}=0$ for convergence



- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Hopfield network




$$\forall_i w_{i,i} = 0 \quad \text{no self-connections}$$


$$\vec{x}' = \text{sgn}(\mathbf{W}\vec{x} + \vec{\theta})$$

$$E(\text{state} = \vec{x}) = -\frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n w_{i,j} x_i x_j + \sum_{i=1}^n \theta_i x_i$$

\mathbf{W} should be symmetric with diag=0 for convergence




Only 2 out of 8 turn out to be stable!



- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Attractor dynamics



Memory cue


(within the basin of attractor)

Memory state

(local energy minimum,
stable point, attractor)

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Attractor dynamics




Memory cue

(within the basin of attractor)

Memory state

(local energy minimum, stable point, **fixed-point attractor**)


Dynamics travelling in the energy landscape and attracted to the energy minimum



In *discrete* Hopfield network, the energy landscape is discrete!

- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Attractor dynamics




Memory cue

(within the basin of attractor)

Memory state


(local energy minimum, stable point, **fixed-point attractor**)

In *discrete* Hopfield network, the energy landscape is discrete!



- Associative memory
- **Hopfield networks**
- Memory storage and TSP example
- Stochastic networks – Boltzmann machine

Attractor dynamics




Memory cue

(within the basin of attractor)

Memory state

(local energy minimum,
stable point, **fixed-point attractor**)

Around each fixed point (attractor), there is
a ***basin of attraction***



- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine

How do we learn memories for storage?

Hopfield network as a content addressable memory

A set of memory patterns $\{\xi_1, \xi_2, \dots, \xi_M\}$ to be learnt.

$$\xi_k = [\xi_{k,1}, \xi_{k,2}, \dots, \xi_{k,n}], \quad k=1, \dots, M$$

Outer product rule (Hebbian-like learning) is used to compute **W**:

$$w_{j,i} = \begin{cases} \frac{1}{n} \sum_{k=1}^M \xi_{k,j} \cdot \xi_{k,i}, & j \neq i \\ 0, & j = i \end{cases}$$


- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine

Pattern storage and recall example


- ▶ The following patterns ξ^1 , ξ^2 , ξ^3 were stored in the weight matrix W :




- ▶ Four snapshots of the state evolution $x(t)$:




$t = 0$



$t = 50$




$t = 100$



$t = 300$


- ▶ Evolution of the energy $E(x(t))$:



adapted from L. Busing (TU Graz)

- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine



Pattern storage and recall example



adapted from McKay


- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine

Pattern storage and recall example



Common problems



1. Corruption of individual bits.
2. Lack of encoded memory or a very small basin of attraction.
3. Appearance of spurious additional memories.



adapted from McKay


- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine

Pattern storage and recall example



Common problems


1. [Corruption of individual bits.](#)
2. Lack of encoded memory or a very small basin of attraction.
3. Appearance of spurious additional memories.



adapted from McKay

- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine

Pattern storage and recall example



Common problems


1. Corruption of individual bits.
2. Lack of encoded memory or a very small basin of attraction.
3. Appearance of spurious additional memories.

Spurious states often arise out of degenerate eigenvectors.

adapted from McKay

- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine

Pattern storage and recall example



Common problems

1. Corruption of individual bits.
2. Lack of encoded memory or a very small basin of attraction.
3. Appearance of spurious additional memories.

Generally, Hopfield network is robust to noise, data corruption and “brain damage” (zeroed subset of weights).



adapted from McKay

- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine

Memory capacity


- Cross-talk between memory patterns is key to limited capacity
- Memory capacity is usually tested on independent random patterns
 - Hopfield network can store roughly $M \leq 0.138 n$ of such random patterns (sharp discontinuity)
 - for large M/n , unstable bits may unfold into an avalanche effect
 - for sparse patterns in the order of $n \cdot \log(n)$
- To guarantee stability of all patterns with high probability, we must ensure

$$M \leq \frac{n}{4 \ln n}$$



- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine


Catastrophic forgetting effect



Convergence rate is defined based on the convergence criterion, often expressed as the upper bound on *Hamming distance*.

- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine

Catastrophic forgetting effect




Convergence rate is defined based on the convergence criterion, often expressed as the upper bound on *Hamming distance*.

Network properties are not robust for synchronous updates.

- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine

Catastrophic forgetting effect



Convergence rate is defined based on the convergence criterion, often expressed as the upper bound on *Hamming distance*.


Network properties are not robust for synchronous updates.

Also, problems for continuous networks.

$$a_i = \sum_j w_{ij} x_j \quad x_i = \tanh(a_i).$$

- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine

Catastrophic forgetting effect



Convergence rate is defined based on the convergence criterion, often expressed as the upper bound on *Hamming distance*.

Network properties are not robust for synchronous updates.

Also, problems for continuous networks.

$$a_i = \sum_j w_{ij} x_j \quad x_i = \tanh(a_i).$$

Better behaviour for continuous continuous –time Hopfield network

$$a_i(t) = \sum_j w_{ij} x_j(t). \quad \frac{d}{dt} x_i(t) = -\frac{1}{\tau} (x_i(t) - f(a_i)),$$

- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine


Hopfield networks for optimisation problems

- Hopfield network's dynamics minimises an energy function
- Some optimisation problems could be mapped to the quadratic energy function (particularly constrain satisfaction problems(CSPs))

- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine

Hopfield networks for optimisation problems

- Hopfield network's dynamics minimises an energy function
- Some optimisation problems could be mapped to the quadratic energy function (particularly constrain satisfaction problems(CSPs))
- Travelling salesman problem (TSP) as a classic CSP problem




$$E = \underbrace{\frac{1}{2} \sum_{i,j,k} d_{ij} x_{ik} x_{j,k+1}}_{\text{sum of distances}} + \underbrace{\frac{\gamma}{2} \left(\sum_{j=1}^n \left(\sum_{i=1}^n x_{ij} - 1 \right)^2 + \sum_{i=1}^n \left(\sum_{j=1}^n x_{ij} - 1 \right)^2 \right)}_{\text{validity: single 1s in each column and row}}$$






- Associative memory
- Hopfield networks
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine

Hopfield networks for optimisation problems

- Hopfield network's dynamics minimises an energy function
- Some optimisation problems could be mapped to the quadratic energy function (particularly constrain satisfaction problems(CSPs))
- Travelling salesman problem (TSP) as a classic CSP problem



validity



- Associative memory
- **Hopfield networks**
- **Memory storage and TSP example**
- Stochastic networks – Boltzmann machine

Hopfield networks

In summary

- Hopfield network is a nice model for memory with biological features including Hebbian learning
- It is a very simple, stable and mathematically tractable model
- It has limited capacity however
- It does not allow for storing time series
- The attractor dynamics is limited to fixed points

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

From Hopfield networks to Boltzmann machines

- Continuous Hopfield network

$$x_i = \frac{1}{1 + e^{-a}} \quad \text{instead of} \quad x_i = \text{sgn}(a)$$

- Stochastic component

$$x_i = \begin{cases} 1 & \text{with probability } p_i \\ -1, & \text{with probability } 1-p_i \end{cases} \quad p = \frac{1}{1 + e^{-\frac{1}{T} \sum_j w_{i,j} x_j}}$$

T is a positive temperature const.

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

From Hopfield networks to Boltzmann machines

- Stochastic component

$$x_i = \begin{cases} 1 & \text{with probability } p_i \\ -1, & \text{with probability } 1-p_i \end{cases}$$

$$p = \frac{1}{1 + e^{-\frac{1}{T} \sum_j w_{i,j} x_j}}$$

$$p(\nu) = \frac{1}{1 + e^{-\nu}} \quad \text{where} \quad \nu = \frac{1}{T} \sum_j w_{i,j} x_j$$

T controls the level of randomness

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**



From Hopfield networks to Boltzmann machines

- Stochastic component

$$x_i = \begin{cases} 1 & \text{with probability } p_i \\ -1, & \text{with probability } 1-p_i \end{cases}$$

$$p = \frac{1}{1 + e^{-\frac{1}{T} \sum_j w_{i,j} x_j}}$$

$$p(v) = \frac{1}{1 + e^{-v}} \quad \text{where} \quad v = \frac{1}{T} \sum_j w_{i,j} x_j$$



- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**


From Hopfield networks to Boltzmann machines

- Stochastic component

$$x_i = \begin{cases} 1 & \text{with probability } p_i \\ -1, & \text{with probability } 1-p_i \end{cases}$$

$$p = \frac{1}{1 + e^{-\frac{1}{T} \sum_j w_{i,j} x_j}}$$

Analogy to **simulated annealing** (relaxation technique common in metallurgy)




$$p_{\Delta E} = \frac{1}{1 + e^{\Delta E/T}}$$

“When optimising a large complex system with many degrees of freedom, instead of always going downhill, try to go downhill most of the time”

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

Simulated annealing to reach the global energy min

The critical role of temperature T .





$$p_{\Delta E} = \frac{1}{1 + e^{\Delta E / T}}$$

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

Simulated annealing to reach the global energy min

The critical role of temperature T .



$$p_{\Delta E} = \frac{1}{1 + e^{\Delta E/T}}$$

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

From Hopfield networks to Boltzmann machines

- Energy of this stochastic network is the same as before

$$E = -\frac{1}{2} \vec{x}^T \mathbf{W} \vec{x} = -\frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n w_{i,j} x_i x_j$$

- The key difference is a stochastic nature of transitions

from state $s1$ to $s2$:

$$p_{s1 \rightarrow s2} = \frac{1}{1 + e^{(E_2 - E_1)/T}} = \frac{1}{1 + e^{\Delta E/T}}$$

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

From Hopfield networks to Boltzmann machines

- Energy of this stochastic network is the same as before

$$E = -\frac{1}{2} \vec{x}^T \mathbf{W} \vec{x} = -\frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n w_{i,j} x_i x_j$$

- The key difference is a stochastic nature of transitions

Boltzmann (Gibbs) distribution defines the probability, p_i , that a system assumes the energy level E_i during thermal equilibrium:

$$p_i = \frac{e^{-E_i/T}}{\sum_j^m e^{-E_j/T}} \quad \left. \vphantom{\sum_j^m} \right\} Z$$

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

From Hopfield networks to Boltzmann machines

- Energy of this stochastic network is the same as before


$$E = -\frac{1}{2} \vec{x}^T \mathbf{W} \vec{x} = -\frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n w_{i,j} x_i x_j$$

- Given a set of examples $\{\vec{x}_i\}_1^m$ the idea is to adjust \mathbf{W} to describe data distribution (well matched to these examples)

$$P(\vec{x} | \mathbf{W}) = \frac{e^{-E}}{Z} = \frac{1}{Z(\mathbf{W})} \exp\left(\frac{1}{2} \vec{x}^T \mathbf{W} \vec{x}\right)$$

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**


Hidden and visible units



- Symmetric connections between visible, v , and hidden neurons, h
- Hidden neurons help account for higher-order correlations in the input vectors (data)
- Visible units provide interface to the external world – environment (data, $v=x$)
- Hidden units operate freely and are used to explain environmental input vectors

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**


Hidden and visible units



- Symmetric connections between visible, v , and hidden neurons, h
- Hidden neurons help account for higher-order correlations in the input vectors (data)
- Visible units provide interface to the external world – environment (data, $v=x$)
- Hidden units operate freely and are used to explain environmental input vectors

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**


Hidden and visible units



- Symmetric connections between visible, v , and hidden neurons, h
- Hidden neurons help account for higher-order correlations in the input vectors (data)
- Visible units provide interface to the external world – environment (data, $v=x$)
- Hidden units operate freely and are used to explain environmental input vectors

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

Hidden and visible units



$$v^{(p)} = x^{(p)}$$

$$\Downarrow$$

$$y^{(p)} = [x^{(p)}, h]$$

- Symmetric connections between visible, v , and hidden neurons, h
- Hidden neurons help account for higher-order correlations in the input vectors (data)
- Visible units provide interface to the external world – environment (data, $v=x$)
- Hidden units operate freely and are used to explain environmental input vectors
- Modelling a probability distribution (and hidden representation) by clamping patterns onto the visible units $v^{(p_i)} = x^{(p_i)}$

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

Boltzmann learning

- The primary goal is to correctly model input patterns according to Boltzmann distribution
 - each input pattern is assumed to last long enough (it might have to be clamped for long) for the network to reach thermal equilibrium (converge) at temperature T
 - to reduce this time, simulated annealing is used with a sequence decreasing temperatures (from “hot” to “cold”)
- Essentially, hidden units learn probabilistically representation of data (seen through visible units)

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

Boltzmann learning

- The idea is to maximise log-likelihood, $L(\mathbf{W}) = \log (P(\mathbf{X})|\mathbf{W})$

$$\Delta w_{ji} = \varepsilon \frac{\partial L(\mathbf{W})}{\partial w_{ji}} = \eta (\rho_{j,i}^+ - \rho_{j,i}^-), \quad \eta = \varepsilon / T$$

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

Boltzmann learning

- The idea is to maximise log-likelihood, $L(\mathbf{W}) = \log(P(\mathbf{X})|\mathbf{W})$

$$\Delta w_{ji} = \varepsilon \frac{\partial L(\mathbf{W})}{\partial w_{ji}} = \eta(\rho_{j,i}^+ - \rho_{j,i}^-), \quad \eta = \varepsilon / T$$

$$\frac{\partial L(\mathbf{W})}{\partial w_{i,j}} = \frac{\partial}{\partial w_{i,j}} \log P(\{\mathbf{x}^{(p)}\}_1^M | \mathbf{W}) = \sum_p \left\{ \underbrace{\langle y_i y_j \rangle_{P(\mathbf{h}|\mathbf{v}=\mathbf{x}^{(p)}, \mathbf{W})}}_{\text{positive phase (awake), with clamping, } \mathbf{v}^{(p)}=\mathbf{x}^{(p)}} - \underbrace{\langle y_i y_j \rangle_{P(\mathbf{v}, \mathbf{h}|\mathbf{W})}}_{\text{negative phase (sleep) free running}} \right\}$$

$$\langle y_i y_j \rangle_{P(\mathbf{h}|\mathbf{v}=\mathbf{x}^{(p)}, \mathbf{W})} = \sum_p \sum_h P(\mathbf{h} | \mathbf{v} = \mathbf{x}^{(p)}) y_i y_j$$

$$\langle y_i y_j \rangle_{P(\mathbf{v}, \mathbf{h}|\mathbf{W})} = \sum_p \sum_y P(\mathbf{y}) y_i y_j$$

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

Boltzmann learning – two phases

$$\frac{\partial L(\mathbf{W})}{\partial w_{i,j}} = \frac{\partial}{\partial w_{i,j}} \log P(\{\mathbf{x}^{(p)}\}_1^M \mid \mathbf{W}) = \sum_p \left\{ \langle y_i y_j \rangle_{P(\mathbf{h}|\mathbf{v}=\mathbf{x}^{(p)}, \mathbf{W})} - \langle y_i y_j \rangle_{P(\mathbf{v}, \mathbf{h}|\mathbf{W})} \right\}$$

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

Boltzmann learning – two phases

$$\frac{\partial L(\mathbf{W})}{\partial w_{i,j}} = \frac{\partial}{\partial w_{i,j}} \log P(\{\mathbf{x}^{(p)}\}_1^M \mid \mathbf{W}) = \sum_p \left\{ \langle y_i y_j \rangle_{P(\mathbf{h}|\mathbf{v}=\mathbf{x}^{(p)}, \mathbf{W})} - \langle y_i y_j \rangle_{P(\mathbf{v}, \mathbf{h}|\mathbf{W})} \right\}$$

$$\Delta w_{i,j} \propto \langle y_i, y_j \rangle_{\text{data}} - \langle y_i, y_j \rangle_{\text{model}}$$

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

Boltzmann learning – two phases

$$\frac{\partial L(\mathbf{W})}{\partial w_{i,j}} = \frac{\partial}{\partial w_{i,j}} \log P(\{\mathbf{x}^{(p)}\}_1^M | \mathbf{W}) = \sum_p \left\{ \langle y_i y_j \rangle_{P(\mathbf{h}|\mathbf{v}=\mathbf{x}^{(p)}, \mathbf{W})} - \langle y_i y_j \rangle_{P(\mathbf{v}, \mathbf{h}|\mathbf{W})} \right\}$$

$$\Delta w_{i,j} \propto \langle y_i, y_j \rangle_{\text{data}} - \langle y_i, y_j \rangle_{\text{model}}$$

- **Positive** phase implies clamping the inputs (relative fast)

$$\langle y_i, y_j \rangle_{\text{data}} \longleftarrow \text{Expected value at thermal equilibrium}$$

- **Negative** phase involves updating all the units (can be very slow)

$$\langle y_i, y_j \rangle_{\text{model}}$$

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

Boltzmann learning – two phases

$$\frac{\partial L(\mathbf{W})}{\partial w_{i,j}} = \frac{\partial}{\partial w_{i,j}} \log P(\{\mathbf{x}^{(p)}\}_1^M | \mathbf{W}) = \sum_p \left\{ \langle y_i y_j \rangle_{P(\mathbf{h}|\mathbf{v}=\mathbf{x}^{(p)}, \mathbf{W})} - \langle y_i y_j \rangle_{P(\mathbf{v}, \mathbf{h}|\mathbf{W})} \right\}$$

$$\Delta w_{i,j} \propto \langle y_i, y_j \rangle_{\text{data}} - \langle y_i, y_j \rangle_{\text{model}}$$

- **Positive** phase implies clamping the inputs (relative fast)

Thermal equilibrium does not imply only that the system settles down into the lowest energy state.

Expected value at thermal equilibrium

- **Nega**

It is about the convergence of probability distribution over different configurations.

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

Boltzmann learning – two phases

$$\frac{\partial L(\mathbf{W})}{\partial w_{i,j}} = \frac{\partial}{\partial w_{i,j}} \log P(\{\mathbf{x}^{(p)}\}_1^M | \mathbf{W}) = \sum_p \left\{ \langle y_i y_j \rangle_{P(\mathbf{h}|\mathbf{v}=\mathbf{x}^{(p)}, \mathbf{W})} - \langle y_i y_j \rangle_{P(\mathbf{v}, \mathbf{h}|\mathbf{W})} \right\}$$

$$\Delta w_{i,j} \propto \langle y_i, y_j \rangle_{\text{data}} - \langle y_i, y_j \rangle_{\text{model}}$$

- **Positive** phase implies clamping the inputs (relative fast)

“Hebbian learning” $\langle y_i, y_j \rangle_{\text{data}}$


- **Negative** phase involves updating all the units (can be very slow)

“Hebbian forgetting” $\langle y_i, y_j \rangle_{\text{model}}$ prevent from learning false, spontaneously generated states

- Associative memory
- Hopfield networks
- Memory storage and TSP example
- **Stochastic networks – Boltzmann machine**

Next step to decrease the complexity

- Restricted Boltzmann machines



- Deep belief networks

