Boneless-III Architecture Reference Manual

Contents

Ta	able o	of Contents	2
1	Gui	de to Instruction Set	3
2	List	of Instructions	4
	2.1	ADC (Add Register with Carry)	5
	2.2	ADCI (Add Immediate with Carry)	6
	2.3	ADD (Add Register)	7
	2.4	ADDI (Add Immediate)	8
	2.5	ADJW.1 (Adjust Window)	9
	2.6	ADJW.2 (Adjust Window, Store Previous Address)	10
	2.7	AND (Bitwise AND with Register)	11
	2.8	ANDI (Bitwise AND with Immediate)	12
	2.9	CMP (Compare to Register)	13
	2.10	CMPI (Compare to Immediate)	14
	2.11	ENTR (Enter Frame)	15
		EXTI (Extend Immediate)	16
	2.13	J (Jump)	17
	2.14	JAL (Jump And Link)	18
	2.15	JC (Jump if Carry)	19
	2.16	JE (Jump if Equal)	20
	2.17	JN (Jump Never)	21
	2.18	JNC (Jump if Not Carry)	22
	2.19	JNE (Jump if Not Equal)	23
	2.20	JNO (Jump if Not Overflow)	24
	2.21	JNS (Jump if Not Sign)	25
	2.22	JNZ (Jump if Not Zero)	26
	2.23	JO (Jump if Overflow)	27
		JR (Jump to Register)	
	2.25	JS (Jump if Sign)	29
	2.26	JSGE (Jump if Signed Greater or Equal)	30
	2.27	JSGT (Jump if Signed Greater Than)	31
	2.28	JSLE (Jump if Signed Less or Equal)	32
	2.29	JSLT (Jump if Signed Less Than)	33
	2.30	JUGE (Jump if Unsigned Greater or Equal)	34
	2.31	JUGT (Jump if Unsigned Greater Than)	35
	2.32	JULE (Jump if Unsigned Less or Equal)	36
	2.33	JULT (Jump if Unsigned Less Than)	37
	2.34	JZ (Jump if Zero)	38
	2.35	LD (Load with Address in Register)	39
		LDI (Load PC-relative with Immediate Offset)	40
	2.37	LDX (Load External with Address in Register)	41
		LDXI (Load External with Immediate Address)	42
	2.39	LEAV (Leave Frame)	43
	2.40	MOV (Move)	44
		MOVA (Move Address PC-relative)	45
		MOVI (Move Immediate)	

2.43	OR (Bitwise OR with Register)	47
2.44	ORI (Bitwise OR with Immediate)	48
2.45	ROLI (Rotate Left Immediate)	49
2.46	RORI (Rotate Right Immediate)	50
2.47	ROT (Rotate)	51
2.48	ROTI (Rotate Immediate)	52
2.49	(53
2.50		54
	()	55
2.52	SLLI (Shift Left Logical Immediate)	56
	SRA (Shift Right Arithmetical)	57
2.54	(58
	()	59
	\	60
2.57	ST (Store with Address in Register)	61
2.58	STI (Store PC-relative with Immediate Offset)	62
2.59	STX (Store External with Address in Register)	63
		64
2.61	SUB (Subtract Register)	65
		66
	(0 0)	67
2.64	XOR (Bitwise XOR with Register)	68
2.65	XORI (Bitwise XOR with Immediate)	69

1	Cida ta	Tagtagatian	C -4
L	- Նուսյաբ եՕ	Instruction	ı set

TBD

2 List of Instructions

The following pages provide a detailed description of instructions, arranged in alphabetical order.

Executing any instruction with an encoding not present on the following pages has ${f UNPREDICTABLE}$ behavior.

2.1 ADC

Add Register with Carry

Encoding:

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
ADC	OC 000			0	1		Rd			Ra		0	1		Rb	

Assembly:

Purpose:

To add 16-bit integers in registers, with carry input.

Restrictions:

None.

Operation:

```
opA ← mem[W|Ra]
opB ← mem[W|Rb]
res ← opA + opB + C
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← res[16]
V ← (opA[15] = opB[15]) and (opA[15] <> res[15])
```

Remarks:

A 32-bit addition with both operands in registers can be performed as follows:

```
; Perform (R1|R0) \leftarrow (R3|R2) + (R5|R4) ADD R0, R2, R4 ADC R1, R3, R5
```

2.2 ADCI

Add Immediate with Carry

Encoding (short form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
ADCI		001		0	1		$\overline{\mathrm{Rd}}$			Ra		0	1	iı	mm	3

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ex	t13						
ADCI	001			0	1		Rd			Ra		0	1	iı	mm	3

Assembly:

ADCI Rd, Ra, imm

Purpose:

To add a constant to a 16-bit integer in a register, with carry input.

Restrictions:

None.

Operation:

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA + opB + C
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← res[16]
V ← (opA[15] = opB[15]) and (opA[15] <> res[15])
```

Remarks:

A 32-bit addition with a register and an immediate operand can be performed as follows:

```
; Perform (R1|R0) \leftarrow (R3|R2) + 0x40001 ADDI R0, R2, 1 ADCI R1, R3, 4
```

2.3 ADD

Add Register

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
ADD	OD 000			0	1		Rd			Ra		0	0		Rb	

Assembly:

ADD Rd, Ra, Rb

Purpose:

To add 16-bit integers in registers.

Restrictions:

None.

2.4 ADDI Add Immediate

Encoding (short form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
ADDI		001		0	1		Rd			Ra		0	0	iı	mm	3

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ex	ct13						
ADDI	001			0	1		Rd			Ra		0	0	iı	mm	3

Assembly:

ADDI Rd, Ra, imm

Purpose:

To add a constant to a 16-bit integer in a register.

Restrictions:

None.

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA + opB
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← res[16]
V ← (opA[15] = opB[15]) and (opA[15] <> res[15])
```

2.5 ADJW.1

Adjust Window

Encoding:

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
ADJW.1	001		1	1		000			000		1	1	iı	mm	3	

Assembly:

ADJW size

Purpose:

To adjust the position of register window.

Restrictions:

None.

Operation:

```
if (has_ext13)
then imm 
olimit ext13|imm3
else imm 
olimit sign_extend(imm3)
W 
olimit W 
olimit with the sign_extend(imm3)
```

Remarks:

See also LEAV.

Notice:

The exact encoding of this instruction is not final.

2.6 ADJW.2 Adjust Window, Store Previous Address

Encoding:

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
ADJW.2	001		1	1		Rd			001		1	1	iı	mm	3	

Assembly:

ADJW Rd, size

Purpose:

To adjust the position of register window and store the previous window position to a register.

Restrictions:

None.

Operation:

```
if (has_ext13)
then imm ← ext13|imm3
else imm ← sign_extend(imm3)
tmp ← W
W ← W + imm
mem[W|Rd] ← tmp|000
```

Remarks:

See also **ENTR**.

Notice:

The exact encoding of this instruction is not final.

2.7 AND

Bitwise AND with Register

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
AND	ND 000			0	0		Rd			Ra		0	0		Rb	

Assembly:

AND Rd, Ra, Rb

Purpose:

To perform bitwise AND between 16-bit integers in registers.

Restrictions:

None.

Operation:

 $\begin{array}{l} \text{opA} \leftarrow \text{mem}[\mathbb{W}|\text{Ra}] \\ \text{opB} \leftarrow \text{mem}[\mathbb{W}|\text{Rb}] \\ \text{res} \leftarrow \text{opA} \text{ and } \text{opB} \\ \text{mem}[\mathbb{W}|\text{Rd}] \leftarrow \text{res} \\ \text{Z} \leftarrow \text{res} = \mathbf{0} \\ \text{S} \leftarrow \text{res}[15] \\ \text{C} \leftarrow \text{UNDEFINED} \end{array}$

 $V \leftarrow UNDEFINED$

2.8 ANDI

Bitwise AND with Immediate

Encoding (short form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
ANDI		001		0	0		Rd			Ra		0	0	iı	mm	3

Encoding (long form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	t13						
ANDI		001		0	0		Rd			Ra		0	0	iı	mm	3

Assembly:

ANDI Rd, Ra, imm

Purpose:

To perform bitwise AND between a constant and a 16-bit integer in a register.

Restrictions:

None.

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA and opB
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← UNDEFINED
V ← UNDEFINED
```

2.9 CMP

Compare to Register

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
CMP		000		0	0	(000			Ra		1	1		Rb	

Assembly:

Purpose:

To compare 16-bit integers in registers.

Restrictions:

None.

Operation:

```
opA ← mem[W|Ra]
opB ← mem[W|Rb]
res ← opA - opB
Z ← res = 0
S ← res[15]
C ← not res[16]
V ← (opA[15] = not opB[15]) and (opA[15] <> res[15])
```

Remarks:

This instruction is identical to SUB, with the exception that it discards the computed value.

2.10 CMPI

Compare to Immediate

Encoding (short form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
CMPI		001		0	0	(000			Ra		1	1	iı	mm	3

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ex	ct13						
CMPI		001		0	0	(000			Ra		1	1	iı	mm	3

Assembly:

CMPI Rd, Ra, imm

Purpose:

To compare a constant to a 16-bit integer in a register.

Restrictions:

None.

Operation:

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA - opB
Z ← res = 0
S ← res[15]
C ← not res[16]
V ← (opA[15] = not opB[15]) and (opA[15] <> res[15])
```

Remarks:

This instruction is identical to SUBI, with the exception that it discards the computed value.

2.11 ENTR Enter Frame

Assembly:

ENTR Rd, size

Purpose:

To set up a working area at an entry to a function.

Restrictions:

None.

Remarks:

The assembler translates ${\tt ENTR}$ to

ADJW Rd, -size

See the description of ADJW.2. See also LEAV.

2.12 EXTI

Extend Immediate

Encoding:

Assembly:

EXTI Rd, Ra, Rb

Purpose:

To extend the range of immediate in the next executed instruction.

Restrictions:

None.

Operation:

 $\begin{array}{l} \texttt{ext13} \leftarrow \texttt{imm13} \\ \texttt{has_ext13} \leftarrow \texttt{1} \end{array}$

Remarks:

This instruction is exclusively emitted by the assembler while translating other instructions. As it changes both the meaning of and the constraints placed on the immediate field in the following instruction, the assembler does not accept a mnemonic for **EXTI**.

2.13 J Jump

Encoding (short form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
J		101		1		111	11					of	f8			

Encoding (long form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
J		101		1		111	11					of	f 8			

Assembly:

J label

Purpose:

To unconditionally transfer control.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off \( \to \) ext13|off8[3:0]
else off \( \to \) sign_extend(off8)
PC \( \to \) PC + 1 + off
```

2.14 JAL

Jump And Link

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JAL		100		1	0		$\overline{\mathrm{Rd}}$					of	f8			

Encoding (long form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0	
EXTI		110			ext13												
JAL		100		1	0		Rd					Ot.	f8				

Assembly:

JAL label

Purpose:

To transfer control to a subroutine.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off \leftarrow ext13|off8[3:0]
else off \leftarrow sign_extend(off8)
mem[W|Rd] \leftarrow PC + 1
PC \leftarrow PC + 1 + off
```

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JC		101		1		101	10					of	f 8			

Encoding (long form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0	
EXTI		110			ext13												
JC		101		1		10	f8										

Assembly:

JC label

Purpose:

To transfer control if an arithmetic or shift operation resulted in unsigned overflow.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (C)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JUGE.

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
JE		101		1		100	00					ot.	f 8			

Encoding (long form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
JE		101		1		100	90					of	f 8			

Assembly:

JE label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is equal to Rb.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (Z)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JZ.

2.17 JN Jump Never

Encoding (short form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
JN		101		1		01	11					of	f8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0	
EXTI		110			ext13												
JN		101		1		01	11					of	f8				

Assembly:

JN label

Purpose:

To serve as a placeholder for a jump instruction.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

 $PC \leftarrow PC + 1$

Remarks:

The JN instruction has no effect. It may be used as a placeholder for a different jump instruction with a predefiend offset when the exact condition is unknown, such as in certain self-modifying code.

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JNC		101		1		002	10					of	f 8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0	
EXTI		110			ext13												
JNC		101		1		00	10					of	f8				

Assembly:

JNC label

Purpose:

To transfer control if an arithmetic or shift operation did not result in unsigned overflow.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not C)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JULT.

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JNE		101		1		000	00					of	f 8			

Encoding (long form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
JNE		101		1		000	90					of	f 8			

Assembly:

JNE label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is not equal to Rb.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not Z)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JNZ.

2.20 JNO

Jump if Not Overflow

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JNO		101		1		002	11					of	f8			

Encoding (long form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0	
EXTI		110			ext13												
JNO		101		1		001	11					of	f 8				

Assembly:

JNO label

Purpose:

To transfer control if an arithmetic or shift operation did not result in signed overflow.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not V)
then PC ← PC + 1 + off
else PC ← PC + 1
```

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JNS		101		1		000	01					of	f 8			

Encoding (long form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13		•				
JNS		101		1		000	01					Ot.	f8			

Assembly:

JNS label

Purpose:

To transfer control if an arithmetic or shift operation produced a non-negative result.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not S)
then PC ← PC + 1 + off
else PC ← PC + 1
```

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JNZ		101		1		000	00					of	f 8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
JNZ		101		1		000	90					of	f 8			

Assembly:

JNZ label

Purpose:

To transfer control if an arithmetic or shift operation produced a non-zero result.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not Z)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JNE.

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
JO		101		1		101	11					of	f 8			

Encoding (long form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	t13						
JO		101		1		101	11					of	f8			

Assembly:

JO label

Purpose:

To transfer control if an arithmetic or shift operation resulted in signed overflow.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (V)
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.24 JR

Jump to Register

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JR		101			1		Ra				0	000	000	0		

Assembly:

JR Rd

Purpose:

To transfer control to an absolute address contained in a register.

Restrictions:

None.

Operation:

$$\begin{array}{l} addr \; \leftarrow \; mem[\texttt{W} \, | \, \texttt{Ra}] \\ PC \; \leftarrow \; addr \end{array}$$

Notice:

The exact encoding of this instruction is not final.

2.25 JS

Jump if Sign

Encoding (short form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
JS		101		1		100	01					of	f 8			

Encoding (long form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110					•		ex	ct13		•				
JS		101		1		100	01					of	f 8			

Assembly:

JS label

Purpose:

To transfer control if an arithmetic or shift operation produced a negative result.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (S)
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.26 JSGE

Jump if Signed Greater or Equal

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JSGE		101		1		010	01					of	f 8			

Encoding (long form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110		ext13												
JSGE		101		1		010	01					of	f 8			

Assembly:

JSGE label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is greater than or equal to Rb when interpreted as signed integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not (S xor V))
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.27 JSGT

Jump if Signed Greater Than

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JSGT		101		1		013	10					of	f 8			

Encoding (long form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110		ext13												
JSGT		101		1		01	10					of	f8			

Assembly:

JSGT label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is greater than to Rb when interpreted as signed integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not ((S xor V) or Z))
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.28 JSLE

Jump if Signed Less or Equal

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JSLE		101		1		111	10					of	f 8			

Encoding (long form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13		•				
JSLE		101		1		11:	10					of	f8			

Assembly:

JSLE label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is less than or equal to Rb when interpreted as signed integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (((S xor V) or Z))
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.29 JSLT

Jump if Signed Less Than

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JSLT		101		1		110	01					of	f 8			

Encoding (long form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110			$\mathrm{ext}13$											
JSLT		101		1	1 1101 off8											

Assembly:

JSLT label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is less than Rb when interpreted as signed integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if ((S xor V))
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.30 JUGE

Jump if Unsigned Greater or Equal

Encoding (short form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JUGE		101		1		101	10					of	f8			

Encoding (long form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13		•				
JUGE		101		1	1 1010 off8											

Assembly:

JUGE label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is greater than or equal to Rb when interpreted as unsigned integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (C)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JC.

2.31 JUGT

Jump if Unsigned Greater Than

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JUGT		101		1		013	10					of	f 8			

Encoding (long form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13		•				
JUGT		101		1	1 0110 off8											

Assembly:

JUGT label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is greater than to Rb when interpreted as unsigned integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not ((not C) or V))
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.32 JULE

Jump if Unsigned Less or Equal

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JULE		101		1		113	10					of	f 8			

Encoding (long form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ex	ct13		•				
JULE		101		1	ext13 1 1110 off8											

Assembly:

JULE label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is less than or equal to Rb when interpreted as unsigned integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if ((not C) or V)
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.33 JULT

Jump if Unsigned Less Than

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JULT		101		1		002	10					of	f 8			

Encoding (long form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13		•				
JULT		101		1	1 0010 off8											

Assembly:

JULT label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is less than Rb when interpreted as unsigned integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not C)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JNC.

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JZ		101		1		100	00					of	f8			

Encoding (long form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
JZ		101		1		100	90					of	f 8			

Assembly:

JZ label

Purpose:

To transfer control if an arithmetic or shift operation produced a zero result.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (Z)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JE.

2.35 LD

Load with Address in Register

Encoding (short form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
LD		010		0	0		Rd			Ra				off5		

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ex	t13						
LD		010		0	0		Rd			Ra				off5		

Assembly:

LD Rd, Ra, off

Purpose:

To load a word from memory at an absolute address contained in a register, with a constant offset.

Restrictions:

If the long form is used, and off5[5:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off5[3:0]
else off ← sign_extend(off5)
addr ← mem[W|Ra] + off
temp ← mem[addr]
mem[W|Rd] ← temp
```

2.36 LDI Load PC-relative with Immediate Offset

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
LDI		011		0			$\overline{\mathrm{Rd}}$					of	f 8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110					•		ех	ct13						
LDI	110 ext13 011 00 Rd off8															

Assembly:

LDI Rd, off

Purpose:

To load a word from memory at an address relative to PC with a constant offset.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
addr ← PC + off
temp ← mem[addr]
mem[W|Rd] ← temp
```

2.37 LDX Load External with Address in Register

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
LDX		010		1	0		Rd			Ra				off5		

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ex	t13						
LDX		010		1	0		Rd			Ra				off5		

Assembly:

LDX Rd, Ra, off

Purpose:

To complete a load cycle on external bus at an absolute address contained in a register, with a constant offset.

Restrictions:

If the long form is used, and off5[5:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off5[3:0]
else off ← sign_extend(off5)
addr ← mem[W|Ra] + off
temp ← ext[addr]
mem[W|Rd] ← temp
```

2.38 LDXI Load External with Immediate Address

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
LDXI		011		1	0		$\overline{\mathrm{Rd}}$					of	f 8			

Encoding (long form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
LDXI		011		1	0		Rd					of	f8			

Assembly:

LDXI Rd, off

Purpose:

To complete a load cycle on external bus at a constant absolute address.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off \leftarrow ext13|off8[3:0]
else off \leftarrow sign_extend(off8)
temp \leftarrow ext[off]
mem[W|Rd] \leftarrow temp
```

2.39 LEAV Leave Frame

Assembly:

LEAV Rd, size

Purpose:

To tear down a working area at an exit from a function.

Restrictions:

None.

Remarks:

The assembler translates ${\tt LEAV}$ to

ADJW size

See the description of ADJW.1. See also ENTR.

2.40 MOV Move

Assembly:

MOV Rd, Rs

Purpose:

To move a value from register to register.

Restrictions:

None.

Remarks:

The assembler does not translate any instructions for MOV with identical Rd and Rs, and translates MOV with any other register combination to

ANDI Rd, Rs, Rs

Notice:

The exact translation of this mnemonic is not final.

2.41 MOVA

Move Address PC-relative

Encoding (short form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
MOVA		100		0	0		Rd					ot.	f8			

Encoding (long form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110					•		ех	t13						
MOVA		100		0	0		Rd					of	f8			

Assembly:

MOVA Rd, off

Purpose:

To load a register with an address relative to PC with a constant offset..

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off \leftarrow ext13|off8[3:0]
else off \leftarrow sign_extend(off8)
mem[W|Rd] \leftarrow PC + 1 + off
```

2.42 MOVI

Move Immediate

Encoding (short form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
MOVI		100		0	1		$\overline{\mathrm{Rd}}$					im	$\overline{\mathrm{m8}}$			

Encoding (long form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0	
EXTI		110			ext13												
MOVI		100		0	1		Rd					im	m8				

Assembly:

MOVI Rd, imm

Purpose:

To load a register with a constant.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then imm 
olimit ext13|imm8[3:0]
else imm 
olimit sign_extend(imm8)
mem[W|Rd] 
olimit imm
```

2.43 OR

Bitwise OR with Register

Encoding:

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
OR		000		0	0		Rd			Ra		0	1		Rb	

Assembly:

OR Rd, Ra, Rb

Purpose:

To perform bitwise OR between 16-bit integers in registers.

Restrictions:

None.

Operation:

 $opA \leftarrow mem[W|Ra]$

 $opB \leftarrow mem[W|Rb]$

 $\texttt{res} \; \leftarrow \; \texttt{opA} \; \; \textbf{or} \; \; \texttt{opB}$

 $mem[W|Rd] \leftarrow res$

 $Z \leftarrow res = 0$

 $S \leftarrow res[15]$

 $C \leftarrow \textbf{UNDEFINED}$

 $V \leftarrow UNDEFINED$

2.44 ORI

Bitwise OR with Immediate

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
ORI		001		0	0		Rd			Ra		0	1	iı	mm	3

Encoding (long form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	t13						
ORI		001		0	0		Rd			Ra		0	1	iı	mm	3

Assembly:

ORI Rd, Ra, imm

Purpose:

To perform bitwise OR between a constant and a 16-bit integer in a register.

Restrictions:

None.

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA or opB
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← UNDEFINED
V ← UNDEFINED
```

2.45 ROLI

Rotate Left Immediate

Assembly:

ROLI Rd, Ra, amount

Purpose:

To perform a left rotate of a 16-bit integer in a register by a constant bit amount.

Restrictions:

The amount may be between 0 and 15, inclusive.

Remarks:

This instruction is an alias for ROTI.

2.46 RORI

Rotate Right Immediate

Assembly:

RORI Rd, Ra, amount

Purpose:

To perform a right rotate of a 16-bit integer in a register by a constant bit amount.

Restrictions:

The amount may be between 0 and 15, inclusive.

Remarks:

The assembler translates RORI with amount of 0 to

MOV Rd, Ra

and RORI with any other amount to

ROTI Rd, Rd, (15 - amount)

2.47 ROT Rotate

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
ROT		000		1	0		Rd			Ra		0	1		Rb	

Assembly:

ROT Rd, Ra, Rb

Purpose:

To perform a left rotate of a 16-bit integer in a register by a variable bit amount.

Restrictions:

If Rb contains a value greater than 15, the behavior is UNPREDICTABLE.

Operation:

opA ← mem[W|Ra]
opB ← mem[W|Rb]
res ← opA[16-opB:0]|opA[16:16-opB]
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← UNDEFINED
V ← UNDEFINED

2.48 ROTI

Rotate Immediate

Encoding:

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
ROTI		001		1	0		Rd			Ra		0	1	iı	nm	3

Assembly:

ROTI Rd, Ra, amount

Purpose:

To perform a left rotate of a 16-bit integer in a register by a constant bit amount.

Restrictions:

The amount may be between 0 and 15, inclusive.

Operation:

```
opA ← mem[W|Ra]
res ← opA[15-imm3:0]|opA[16:15-imm3]
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← UNDEFINED
V ← UNDEFINED
```

Remarks:

The instruction encoding allows directly representing any **amount** between 1 and 8, inclusive. The assembler translates **ROTI** with **amount** of 0 to

```
MOV Rd, Ra and ROTI with amount greater than 8 to ROTI Rd, Ra, 8
```

ROTI Rd, Rd, (amount - 8)

2.49 SBB

Subtract Register with Borrow

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
SBB		000		0	1		$\overline{\mathrm{Rd}}$			Ra		1	1		Rb	

Assembly:

SBB Rd, Ra, Rb

Purpose:

To subtract 16-bit integers in registers, with borrow input.

Restrictions:

None.

Operation:

```
opA ← mem[W|Ra]
opB ← mem[W|Rb]
res ← opA - opB - not C
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← not res[16]
V ← (opA[15] = not opB[15]) and (opA[15] <> res[15])
```

Remarks:

A 32-bit subtraction with both operands in registers can be performed as follows:

```
; Perform (R1|R0) \leftarrow (R3|R2) - (R5|R4) SUB R0, R2, R4 SBB R1, R3, R5
```

2.50 SBBI

Subtract Immediate with Borrow

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
SBBI		001		0	1		Rd			Ra		1	1	iı	mm	3

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ex	t13						
SBBI	001		0	1		Rd			Ra		1	1	iı	mm	3	

Assembly:

SBBI Rd, Ra, imm

Purpose:

To subtract a constant from a 16-bit integer in a register, with borrow input.

Restrictions:

None.

Operation:

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA - opB - not C
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← not res[16]
V ← (opA[15] = not opB[15]) and (opA[15] <> res[15])
```

Remarks:

A 32-bit subtraction with a register and an immediate operand can be performed as follows:

```
; Perform (R1|R0) \leftarrow (R3|R2) - 0x40001 SUBI R0, R2, 1 SBBI R1, R3, 4
```

Encoding:

Assembly:

Purpose:

To perform a left logical shift of a 16-bit integer in a register by a variable bit amount.

Restrictions:

If Rb contains a value greater than 15, the behavior is UNPREDICTABLE.

```
\begin{array}{l} opA \leftarrow mem[\mathbb{W}|Ra] \\ opB \leftarrow mem[\mathbb{W}|Rb] \\ res \leftarrow opA[16-opB:0]|0\{opB\} \\ mem[\mathbb{W}|Rd] \leftarrow res \\ Z \leftarrow res = 0 \\ S \leftarrow res[15] \\ C \leftarrow \textbf{UNDEFINED} \\ V \leftarrow \textbf{UNDEFINED} \end{array}
```

2.52 SLLI

Shift Left Logical Immediate

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
SLLI		001		1	0		Rd			Ra		0	0	iı	mm	3

Assembly:

SLLI Rd, Ra, amount

Purpose:

To perform a left logical shift of a 16-bit integer in a register by a constant bit amount.

Restrictions:

The amount may be between 0 and 15, inclusive.

Operation:

```
opA ← mem[W|Ra]
res ← opA[15-imm3:0]|0{imm3+1}
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← UNDEFINED
V ← UNDEFINED
```

Remarks:

The instruction encoding allows directly representing any **amount** between 1 and 8, inclusive. The assembler translates **SLLI** with **amount** of 0 to

```
MOV Rd, Ra
```

and SLLI with amount greater than 8 to

2.53 SRA

Shift Right Arithmetical

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
SRA		000		1	0		Rd			Ra		1	1		Rb	

Assembly:

SRA Rd, Ra, Rb

Purpose:

To perform a right arithmetical shift of a 16-bit integer in a register by a variable bit amount.

Restrictions:

If Rb contains a value greater than 15, the behavior is UNPREDICTABLE.

```
\begin{array}{l} opA \;\leftarrow\; mem[\mathbb{W}|Ra] \\ opB \;\leftarrow\; mem[\mathbb{W}|Rb] \\ res \;\leftarrow\; opA[15]\{opB\}|opA[16:16-opB] \\ mem[\mathbb{W}|Rd] \;\leftarrow\; res \\ Z \;\leftarrow\; res \;=\; 0 \\ S \;\leftarrow\; res[15] \\ C \;\leftarrow\; \textbf{UNDEFINED} \\ V \;\leftarrow\; \textbf{UNDEFINED} \end{array}
```

2.54 SRAI

Shift Right Arithmetical Immediate

Encoding:

	F	E	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
SRAI		000		1	0		Rd			Ra		1	1	iı	mm	3

Assembly:

SRAI Rd, Ra, amount

Purpose:

To perform a right arithmetical shift of a 16-bit integer in a register by a constant bit amount.

Restrictions:

The amount may be between 0 and 15, inclusive.

Operation:

```
\begin{array}{l} opA \;\leftarrow\; mem[\mathbb{W}|Ra] \\ opB \;\leftarrow\; mem[\mathbb{W}|Rb] \\ res \;\leftarrow\; opA[15]\{imm3+1\}|opA[16:15-imm3] \\ mem[\mathbb{W}|Rd] \;\leftarrow\; res \\ Z \;\leftarrow\; res \;=\; 0 \\ S \;\leftarrow\; res[15] \\ C \;\leftarrow\; \textbf{UNDEFINED} \\ V \;\leftarrow\; \textbf{UNDEFINED} \end{array}
```

Remarks:

The instruction encoding allows directly representing any **amount** between 1 and 8, inclusive. The assembler translates **SRAI** with **amount** of 0 to

```
MOV Rd, Ra
```

and SRAI with amount greater than 8 to

```
SRAI Rd, Ra, 8
SRAI Rd, Rd, (amount - 8)
```

Encoding:

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
SRL		000		1	0		Rd			Ra		1	0		Rb	

Assembly:

Purpose:

To perform a right logical shift of a 16-bit integer in a register by a variable bit amount.

Restrictions:

If Rb contains a value greater than 15, the behavior is UNPREDICTABLE.

```
\begin{array}{lll} opA & \leftarrow & mem[\mathbb{W}|Ra] \\ opB & \leftarrow & mem[\mathbb{W}|Rb] \\ res & \leftarrow & 0\{opB\}|opA[16:16-opB] \\ mem[\mathbb{W}|Rd] & \leftarrow & res \\ Z & \leftarrow & res & = 0 \\ S & \leftarrow & res[15] \\ C & \leftarrow & \textbf{UNDEFINED} \\ V & \leftarrow & \textbf{UNDEFINED} \end{array}
```

2.56 SRLI

Shift Right Logical Immediate

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
SRLI		001		1	0		Rd			Ra		1	0	iı	mm	3

Assembly:

Purpose:

To perform a right logical shift of a 16-bit integer in a register by a constant bit amount.

Restrictions:

The amount may be between 0 and 15, inclusive.

Operation:

```
opA ← mem[W|Ra]
res ← 0{imm3+1}|opA[16:15-imm3]
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← UNDEFINED
V ← UNDEFINED
```

Remarks:

The instruction encoding allows directly representing any **amount** between 1 and 8, inclusive. The assembler translates **SRLI** with **amount** of 0 to

```
MOV Rd, Ra
and SRLI with amount greater than 8 to
SRLI Rd, Ra, 8
SRLI Rd, Rd, (amount - 8)
```

2.57 ST

Store with Address in Register

Encoding (short form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
ST		010		0	1		Rs			Ra				off5		

Encoding (long form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
ST	010			0	1		Rs			Ra				off5		

Assembly:

ST Rs, Ra, off

Purpose:

To store a word to memory at an absolute address contained in a register, with a constant offset.

Restrictions:

If the long form is used, and off5[5:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off5[3:0]
else off ← sign_extend(off5)
addr ← mem[W|Ra] + off
temp ← mem[W|Rs]
mem[addr] ← temp
```

2.58 STI Store PC-relative with Immediate Offset

Encoding (short form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
STI		011		0	1		Rs					of	f 8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
STI		011		0	1		Rs					of	f 8			

Assembly:

STI Rs, off

Purpose:

To store a word to memory at an address relative to PC with a constant offset.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
addr ← PC + off
temp ← mem[W|Rs]
mem[addr] ← temp
```

2.59 STX Store External with Address in Register

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
STX		010		1	1		Rs			Ra				off5		

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	t13						
STX		010		1	1		Rs			Ra				off5		

Assembly:

STX Rs, Ra, off

Purpose:

To complete a store cycle on external bus at an absolute address contained in a register, with a constant offset.

Restrictions:

If the long form is used, and off5[5:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off5[3:0]
else off ← sign_extend(off5)
addr ← mem[W|Ra] + off
temp ← mem[W|Rs]
ext[addr] ← temp
```

2.60 STXI Store External with Immediate Address

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
STXI	011			1	1		Rs					ot.	f 8			

Encoding (long form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ex	ct13		•				
STXI		011		1	1		Rs					of	f 8			

Assembly:

STXI Rs, off

Purpose:

To complete a store cycle on external bus at a constant absolute address.

Restrictions:

If the long form is used, and off5[5:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
temp ← mem[W|Rs]
ext[off] ← temp
```

Encoding:

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
SUB	000		0	1		$\overline{\mathrm{Rd}}$			Ra		1	0		Rb		

Assembly:

SUB Rd, Ra, Rb

Purpose:

To subtract 16-bit integers in registers.

Restrictions:

None.

```
opA ← mem[W|Ra]
opB ← mem[W|Rb]
res ← opA - opB
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← not res[16]
V ← (opA[15] = not opB[15]) and (opA[15] <> res[15])
```

2.62 SUBI

Subtract Immediate

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
SUBI	001		0	1		Rd			Ra		1	0	iı	nm	3	

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ex	ct13						
SUBI	001			0	1		Rd			Ra		1	0	iı	mm	3

Assembly:

SUBI Rd, Ra, imm

Purpose:

To subtract a constant from a 16-bit integer in a register.

Restrictions:

None.

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA - opB
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← not res[16]
V ← (opA[15] = not opB[15]) and (opA[15] <> res[15])
```

2.63 XCHG

Exchange Registers

Assembly:

XCHG Ra, Rb

Purpose:

To exchange the values of two registers.

Restrictions:

None.

Remarks:

The assembler does not translate any instructions for XCHG with identical Ra and Rb, and translates XCHG with any other register combination to

XOR Ra, Ra, Rb

XOR Rb, Rb, Ra

XOR Ra, Ra, Rb

2.64 XOR

Bitwise XOR with Register

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
XOR	000		0	0		$\overline{\mathrm{Rd}}$			Ra		1	0		Rb		

Assembly:

XOR Rd, Ra, Rb

Purpose:

To perform bitwise XOR between 16-bit integers in registers.

Restrictions:

None.

Operation:

 $opA \leftarrow mem[W|Ra]$ $opB \leftarrow mem[W|Rb]$

res ← opA **xor** opB

 $mem[W|Rd] \leftarrow res$

 $Z \leftarrow res = 0$

 $S \leftarrow res[15]$

 $\mathsf{C} \; \leftarrow \; \textbf{UNDEFINED}$

 $V \leftarrow UNDEFINED$

2.65 XORI

Bitwise XOR with Immediate

Encoding (short form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
XORI		001		0	0		Rd			Ra		1	0	iı	mm	3

Encoding (long form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI	110								ех	ct13						
XORI	001			0	0		Rd			Ra		1	0	iı	mm	3

Assembly:

XORI Rd, Ra, imm

Purpose:

To perform bitwise XOR between a constant and a 16-bit integer in a register.

Restrictions:

None.

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA xor opB
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← UNDEFINED
V ← UNDEFINED
```