Boneless-III Architecture Reference Manual

Notice:

This document is a work in progress and subject to change without warning. However, the parts that are *especially* subject to change carry a notice similar to this one.

Contents

Ta	able o	of Contents	3
1	Gui	de to Instruction Set	4
2	List	of Instructions	5
	2.1	ADC (Add Register with Carry)	6
	2.2	ADCI (Add Immediate with Carry)	7
	2.3	ADD (Add Register)	8
	2.4	ADDI (Add Immediate)	
	2.5	ADJW.1 (Adjust Window)	10
	2.6	ADJW.2 (Adjust Window, Store Previous Address)	11
	2.7	AND (Bitwise AND with Register)	12
	2.8	ANDI (Bitwise AND with Immediate)	13
	2.9	CMP (Compare to Register)	14
	2.10	CMPI (Compare to Immediate)	15
		ENTR (Enter Frame)	16
		EXTI (Extend Immediate)	17
	2.13	J (Jump)	18
		JAL (Jump And Link)	19
	2.15	JC (Jump if Carry)	20
		JE (Jump if Equal)	
	2.17	JN (Jump Never)	22
	2.18	JNC (Jump if Not Carry)	23
	2.19	JNE (Jump if Not Equal)	24
	2.20	JNO (Jump if Not Overflow)	25
	2.21	JNS (Jump if Not Sign)	26
	2.22	JNZ (Jump if Not Zero)	27
		JO (Jump if Overflow)	
		JR (Jump to Register)	
	2.25	JS (Jump if Sign)	30
		JSGE (Jump if Signed Greater or Equal)	
	2.27	JSGT (Jump if Signed Greater Than)	32
		JSLE (Jump if Signed Less or Equal)	
	2.29	JSLT (Jump if Signed Less Than)	34
	2.30	JUGE (Jump if Unsigned Greater or Equal)	35
		JUGT (Jump if Unsigned Greater Than)	36
		JULE (Jump if Unsigned Less or Equal)	37
	2.33	JULT (Jump if Unsigned Less Than)	38
		JZ (Jump if Zero)	39
		LD (Load)	40
		LDI (Load Indexed)	41
		LDX (Load External)	42
		LDXZ (Load External Absolute)	43
		LEAV (Leave Frame)	44
		MOV (Move)	45
		MOVA (Move Address PC-relative)	
		MOVI (Move Immediate)	

2.43	OR (Bitwise OR with Register)	18
2.44	ORI (Bitwise OR with Immediate)	19
2.45	ROLI (Rotate Left Immediate)	60
		51
2.47	ROT (Rotate)	52
2.48	ROTI (Rotate Immediate)	53
2.49	SBB (Subtract Register with Borrow)	54
2.50		55
2.51	SLL (Shift Left Logical)	6
2.52	SLLI (Shift Left Logical Immediate)	57
2.53	SRA (Shift Right Arithmetical)	8
	()	59
2.55	SRL (Shift Right Logical)	60
2.56	SRLI (Shift Right Logical Immediate)	31
2.57	ST (Store)	52
2.58	STI (Store Indexed)	53
2.59	STX (Store External with Address in Register) 6	34
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	35
2.61	SUB (Subtract Register)	66
2.62	SUBI (Subtract Immediate)	57
2.63	XCHG (Exchange Registers)	8
2.64	XOR (Bitwise XOR with Register) 6	69
2.65	XORI (Bitwise XOR with Immediate)	70

1	O1- 4-	T 4 4	0 - 1
	Guide to	Instruction	set

TBD

2 List of Instructions

The following pages provide a detailed description of instructions, arranged in alphabetical order.

Executing any instruction with an encoding not present on the following pages has ${f UNPREDICTABLE}$ behavior.

2.1 ADC

Add Register with Carry

Encoding:

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
ADC		000		0	1		Rd			Ra		0	1		Rb	

Assembly:

Purpose:

To add 16-bit integers in registers, with carry input.

Restrictions:

None.

Operation:

```
opA ← mem[W|Ra]
opB ← mem[W|Rb]
res ← opA + opB + C
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← res[16]
V ← (opA[15] = opB[15]) and (opA[15] <> res[15])
```

Remarks:

A 32-bit addition with both operands in registers can be performed as follows:

```
; Perform (R1|R0) \leftarrow (R3|R2) + (R5|R4) ADD R0, R2, R4 ADC R1, R3, R5
```

2.2 ADCI

Add Immediate with Carry

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
ADCI	I		0	1		Rd			Ra		0	1	iı	nm	3	

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
ADCI	001			0	1		Rd			Ra		0	1	iı	mm	3

Assembly:

ADCI Rd, Ra, imm

Purpose:

To add a constant to a 16-bit integer in a register, with carry input.

Restrictions:

None.

Operation:

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA + opB + C
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← res[16]
V ← (opA[15] = opB[15]) and (opA[15] <> res[15])
```

Remarks:

A 32-bit addition with a register and an immediate operand can be performed as follows:

```
; Perform (R1|R0) \leftarrow (R3|R2) + 0x40001 ADDI R0, R2, 1 ADCI R1, R3, 4
```

2.3 ADD

Add Register

Encoding:

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
ADD		000		0	1		$\overline{\mathrm{Rd}}$			Ra		0	0		Rb	

Assembly:

ADD Rd, Ra, Rb

Purpose:

To add 16-bit integers in registers.

Restrictions:

None.

2.4 ADDI Add Immediate

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
ADDI		001		0	1		$\overline{\mathrm{Rd}}$			Ra		0	0	iı	nm	3

Encoding (long form):

	F	E	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
ADDI	001			0	1		Rd			Ra		0	0	iı	mm	3

Assembly:

ADDI Rd, Ra, imm

Purpose:

To add a constant to a 16-bit integer in a register.

Restrictions:

None.

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA + opB
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← res[16]
V ← (opA[15] = opB[15]) and (opA[15] <> res[15])
```

2.5 ADJW.1

Adjust Window

Encoding:

	F	E	D	С	В	A	9	8	7	6	5	4	3	2	1	0
ADJW.1	001			1	1	(000			000		1	1	iı	mm	3

Assembly:

ADJW size

Purpose:

To adjust the position of register window.

Restrictions:

None.

Operation:

```
if (has_ext13)
then imm 
olimit ext13|imm3
else imm 
olimit sign_extend(imm3)
W 
olimit W 
olimit with the sign_extend(imm3)
```

Remarks:

See also **LEAV**.

Notice:

The exact encoding of this instruction is not final.

2.6 ADJW.2 Adjust Window, Store Previous Address

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
ADJW.2	001		1	1		Rd			001		1	1	iı	nm	3	

Assembly:

ADJW Rd, size

Purpose:

To adjust the position of register window and store the previous window position to a register.

Restrictions:

None.

Operation:

```
if (has_ext13)
then imm ← ext13|imm3
else imm ← sign_extend(imm3)
tmp ← W
W ← W + imm
mem[W|Rd] ← tmp|000
```

Remarks:

See also **ENTR**.

Notice:

The exact encoding of this instruction is not final.

2.7 AND

Bitwise AND with Register

Encoding:

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
AND		000		0	0		$\overline{\mathrm{Rd}}$			Ra		0	0		Rb	

Assembly:

AND Rd, Ra, Rb

Purpose:

To perform bitwise AND between 16-bit integers in registers.

Restrictions:

None.

Operation:

 $opA \leftarrow mem[W|Ra]$

 $opB \leftarrow mem[W|Rb]$

 $\texttt{res} \leftarrow \texttt{opA} \; \; \textbf{and} \; \; \texttt{opB}$

 $\texttt{mem[W|Rd]} \; \leftarrow \; \texttt{res}$

 $Z \leftarrow res = 0$

 $S \leftarrow res[15]$

 $\mathsf{C} \; \leftarrow \; \textbf{UNDEFINED}$

 $V \leftarrow UNDEFINED$

2.8 ANDI

Bitwise AND with Immediate

Encoding (short form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
ANDI	001		0	0		$\overline{\mathrm{Rd}}$			Ra		0	0	iı	mm	3	

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI	110 ext13															
ANDI		001		0	0		Rd			Ra		0	0	iı	mm	3

Assembly:

ANDI Rd, Ra, imm

Purpose:

To perform bitwise AND between a constant and a 16-bit integer in a register.

Restrictions:

None.

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA and opB
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← UNDEFINED
V ← UNDEFINED
```

2.9 CMP

Compare to Register

Encoding:

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
CMP				0	0	(000			Ra		1	1		Rb	

Assembly:

Purpose:

To compare 16-bit integers in registers.

Restrictions:

None.

Operation:

```
opA ← mem[W|Ra]
opB ← mem[W|Rb]
res ← opA - opB
Z ← res = 0
S ← res[15]
C ← not res[16]
V ← (opA[15] = not opB[15]) and (opA[15] <> res[15])
```

Remarks:

This instruction is identical to SUB, with the exception that it discards the computed value.

2.10 CMPI

Compare to Immediate

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
CMPI		001		0	0	(000			Ra		1	1	iı	nm	3

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI	L 110 EX119															
CMPI		001		0	0	(000			Ra		1	1	iı	mm	3

Assembly:

CMPI Rd, Ra, imm

Purpose:

To compare a constant to a 16-bit integer in a register.

Restrictions:

None.

Operation:

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA - opB
Z ← res = 0
S ← res[15]
C ← not res[16]
V ← (opA[15] = not opB[15]) and (opA[15] <> res[15])
```

Remarks:

This instruction is identical to SUBI, with the exception that it discards the computed value.

2.11 ENTR Enter Frame

Assembly:

ENTR Rd, size

Purpose:

To set up a working area at an entry to a function.

Restrictions:

None.

Remarks:

The assembler translates ${\tt ENTR}$ to

ADJW Rd, -size

See the description of ADJW.2. See also LEAV.

2.12 EXTI

Extend Immediate

Encoding:

Assembly:

EXTI Rd, Ra, Rb

Purpose:

To extend the range of immediate in the next executed instruction.

Restrictions:

None.

Operation:

 $\begin{array}{l} \texttt{ext13} \leftarrow \texttt{imm13} \\ \texttt{has_ext13} \leftarrow \texttt{1} \end{array}$

Remarks:

This instruction is exclusively emitted by the assembler while translating other instructions. As it changes both the meaning of and the constraints placed on the immediate field in the following instruction, the assembler does not accept a mnemonic for **EXTI**.

2.13 J Jump

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
J	101			1		113	11					of	f8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110		ext13												
J		101		1						of	f 8					

Assembly:

J label

Purpose:

To unconditionally transfer control.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off \( \to \) ext13|off8[3:0]
else off \( \to \) sign_extend(off8)
PC \( \to \) PC + 1 + off
```

2.14 JAL

Jump And Link

Encoding (short form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
JAL		100		1	0		$\overline{\mathrm{Rd}}$					of	f 8			

Encoding (long form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110 ext13														
JAL	100 10 Rd off8															

Assembly:

JAL label

Purpose:

To transfer control to a subroutine.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off \leftarrow ext13|off8[3:0]
else off \leftarrow sign_extend(off8)
mem[W|Rd] \leftarrow PC + 1
PC \leftarrow PC + 1 + off
```

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
JC		101		1		101	10					of	f 8			

Encoding (long form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110		ext13												
JC	101 1 1010 01										f8					

Assembly:

JC label

Purpose:

To transfer control if an arithmetic or shift operation resulted in unsigned overflow.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (C)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JUGE.

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JE		101		1		100	00					of	f 8			

Encoding (long form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
JE		101		1		100	90					of	f 8			

Assembly:

JE label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is equal to Rb.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (Z)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JZ.

2.17 JN Jump Never

Encoding (short form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
JN		101		1		01	11					of	f8			

Encoding (long form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
JN		101		1		01	11					of	f8			

Assembly:

JN label

Purpose:

To serve as a placeholder for a jump instruction.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

 $PC \;\leftarrow\; PC \;+\; 1$

Remarks:

The JN instruction has no effect. It may be used as a placeholder for a different jump instruction with a predefiend offset when the exact condition is unknown, such as in certain self-modifying code.

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
JNC		101		1		00	10					_ ot	f 8			

Encoding (long form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110					•		ех	ct13						
JNC		101		1		00	10					of	f8			

Assembly:

JNC label

Purpose:

To transfer control if an arithmetic or shift operation did not result in unsigned overflow.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not C)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JULT.

Jump if Not Equal

Encoding (short form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
JNE		101		1		000	90					of	f 8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
JNE		101		1		000	00					of	f8			

Assembly:

JNE label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is not equal to Rb.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not Z)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JNZ.

2.20 JNO

Jump if Not Overflow

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JNO		101		1		002	11					of	f 8			

Encoding (long form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110					•		ех	ct13						
JNO		101		1		00	11					of	f 8			

Assembly:

JNO label

Purpose:

To transfer control if an arithmetic or shift operation did not result in signed overflow.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not V)
then PC ← PC + 1 + off
else PC ← PC + 1
```

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
JNS		101		1		000	01					of	f 8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
JNS		101		1		000	01					of	f8			

Assembly:

JNS label

Purpose:

To transfer control if an arithmetic or shift operation produced a non-negative result.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not S)
then PC ← PC + 1 + off
else PC ← PC + 1
```

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
JNZ		101		1		000	90					ot	f 8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0	
EXTI		110			ext13												
JNZ		101		1 0000 off8													

Assembly:

JNZ label

Purpose:

To transfer control if an arithmetic or shift operation produced a non-zero result.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not Z)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JNE.

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
JO		101		1		101	11					of	f 8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110			ext13											
JO		101 1 1011 off8														

Assembly:

JO label

Purpose:

To transfer control if an arithmetic or shift operation resulted in signed overflow.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (V)
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.24 JR

Jump to Register

Encoding:

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
JR		101		1	1		Ra				0	000	000	0		

Assembly:

JR Rd

Purpose:

To transfer control to an absolute address contained in a register.

Restrictions:

None.

Operation:

$$\begin{array}{l} addr \; \leftarrow \; mem[\texttt{W} \, | \, \texttt{Ra}] \\ PC \; \leftarrow \; addr \end{array}$$

Notice:

The exact encoding of this instruction is not final.

2.25 JS

Jump if Sign

Encoding (short form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JS		101		1		100	01					of	f 8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110			ext13											
JS		101 1 1001 off8														

Assembly:

JS label

Purpose:

To transfer control if an arithmetic or shift operation produced a negative result.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (S)
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.26 JSGE

Jump if Signed Greater or Equal

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JSGE		101		1		010	01					of	f8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0	
EXTI		110			ext13												
JSGE		101	1 0101 off8														

Assembly:

JSGE label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is greater than or equal to Rb when interpreted as signed integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not (S xor V))
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.27 JSGT

Jump if Signed Greater Than

Encoding (short form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JSGT		101		1		01	10					of	f8			

Encoding (long form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110 ext13														
JSGT	101 1 0110 off8															

Assembly:

JSGT label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is greater than to Rb when interpreted as signed integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not ((S xor V) or Z))
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.28 JSLE

Jump if Signed Less or Equal

Encoding (short form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JSLE		101		1		113	10					of	f8			

Encoding (long form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110 ext13														
JSLE	101 1 1110 off8															

Assembly:

JSLE label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is less than or equal to Rb when interpreted as signed integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (((S xor V) or Z))
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.29 JSLT

Jump if Signed Less Than

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0		
JSLT	101			1	1 1101					off8								

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0	
EXTI	110 ext13									}							
JSLT		101		1		110	01		off8								

Assembly:

JSLT label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is less than Rb when interpreted as signed integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if ((S xor V))
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.30 JUGE

Jump if Unsigned Greater or Equal

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0	
JUGE	101			1 1010					off8								

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110			ext13											
JUGE		101		1		10	10		off8							

Assembly:

JUGE label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is greater than or equal to Rb when interpreted as unsigned integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (C)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JC.

2.31 JUGT

Jump if Unsigned Greater Than

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JUGT		101		1		01	10					of	f8			

Encoding (long form):

	F	E	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110		ext13												
JUGT																

Assembly:

JUGT label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is greater than to Rb when interpreted as unsigned integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not ((not C) or V))
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.32 JULE

Jump if Unsigned Less or Equal

Encoding (short form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JULE		101		1		113	10					of	f8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110	ext13													
JULE		101		1	1 1110 off8											

Assembly:

JULE label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is less than or equal to Rb when interpreted as unsigned integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if ((not C) or V)
then PC ← PC + 1 + off
else PC ← PC + 1
```

2.33 JULT

Jump if Unsigned Less Than

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JULT		101		1		001	10					of	f 8			

Encoding (long form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110 ext13														
JULT	Γ 101 1 0010 off8															

Assembly:

JULT label

Purpose:

To transfer control after a CMP Ra, Rb instruction if Ra is less than Rb when interpreted as unsigned integer.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (not C)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JNC.

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
JZ		101		1		100	00					of	f 8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110			ext13											
JZ	101 1 1000 off8															

Assembly:

JZ label

Purpose:

To transfer control if an arithmetic or shift operation produced a zero result.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

Operation:

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
if (Z)
then PC ← PC + 1 + off
else PC ← PC + 1
```

Remarks:

This instruction has the same encoding as JE.

2.35 LD Load

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
LD		010		0	0		Rd			Ra				off5		

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI	110 ext13															
LD	0 010 00 Dd Da													off5		

Assembly:

LD Rd, Ra, off

Purpose:

To load a word from memory at a variable address, with a constant offset.

Restrictions:

If the long form is used, and off5[5:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off5[3:0]
else off ← sign_extend(off5)
addr ← mem[W|Ra] + off
temp ← mem[addr]
mem[W|Rd] ← temp
```

2.36 LDI Load Indexed

Encoding (short form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
LDI		011		0	0		$\overline{\mathrm{Rd}}$			Ra				off5		

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI	110 ext13															
LDI		011		0	0		Rd			Ra				off5		

Assembly:

LDI Rd, Ra, off

Purpose:

To load a word from memory at a constant PC-relative address, with a variable offset.

Restrictions:

If the long form is used, and off5[5:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off \( - \text{ext13} \) off8[3:0]
else off \( - \text{sign_extend(off8)} \)
addr \( - \text{PC} + \text{mem[W|Ra]} + \text{off} \)
temp \( - \text{mem[addr]} \)
mem[W|Rd] \( - \text{temp} \)
```

2.37 LDX Load External

Encoding (short form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
LDX		010		1	0		Rd			Ra				off5		

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110		ext13												
LDX	010 10 Rd Ra												off5			

Assembly:

LDX Rd, Ra, off

Purpose:

To complete a load cycle on external bus at a variable address, with a constant offset.

Restrictions:

If the long form is used, and off5[5:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off5[3:0]
else off ← sign_extend(off5)
addr ← mem[W|Ra] + off
temp ← ext[addr]
mem[W|Rd] ← temp
```

2.38 LDXZ

Load External Absolute

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
LDXZ		011		1	0		$\overline{\mathrm{Rd}}$					of	f8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0	
EXTI		110			ext13												
LDXZ		011		1	10 Rd off8												

Assembly:

LDXZ Rd, off

Purpose:

To complete a load cycle on external bus at a constant absolute address.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off \leftarrow ext13|off8[3:0]
else off \leftarrow sign_extend(off8)
temp \leftarrow ext[off]
mem[W|Rd] \leftarrow temp
```

2.39 LEAV Leave Frame

Assembly:

LEAV Rd, size

Purpose:

To tear down a working area at an exit from a function.

Restrictions:

None.

Remarks:

The assembler translates ${\tt LEAV}$ to

ADJW size

See the description of ADJW.1. See also ENTR.

2.40 MOV Move

Assembly:

MOV Rd, Rs

Purpose:

To move a value from register to register.

Restrictions:

None.

Remarks:

The assembler does not translate any instructions for MOV with identical Rd and Rs, and translates MOV with any other register combination to

ANDI Rd, Rs, Rs

Notice:

The exact translation of this mnemonic is not final.

2.41 MOVA

Move Address PC-relative

Encoding (short form):

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
MOVA		100		0	0		Rd					of	f 8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0		
EXTI		110			ext13													
MOVA		100		0	0		Rd					of	f 8					

Assembly:

MOVA Rd, off

Purpose:

To load a register with an address relative to PC with a constant offset..

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off \leftarrow ext13|off8[3:0]
else off \leftarrow sign_extend(off8)
mem[W|Rd] \leftarrow PC + 1 + off
```

2.42 MOVI

Move Immediate

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
MOVI		100		0	1		$\overline{\mathrm{Rd}}$					im	m8			

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0	
EXTI		110			ext13												
MOVI		100		ext13 01 Rd imm8													

Assembly:

MOVI Rd, imm

Purpose:

To load a register with a constant.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then imm 
olimit ext13|imm8[3:0]
else imm 
olimit sign_extend(imm8)
mem[W|Rd] 
olimit imm
```

2.43 OR

Bitwise OR with Register

Encoding:

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
OR		000		0	0		Rd			Ra		0	1		Rb	

Assembly:

OR Rd, Ra, Rb

Purpose:

To perform bitwise OR between 16-bit integers in registers.

Restrictions:

None.

Operation:

 $opA \leftarrow mem[W|Ra]$

 $opB \leftarrow mem[W|Rb]$

 $\texttt{res} \; \leftarrow \; \texttt{opA} \; \; \textbf{or} \; \; \texttt{opB}$

 $mem[W|Rd] \leftarrow res$

 $Z \leftarrow res = 0$

 $S \leftarrow res[15]$

 $\mathsf{C} \; \leftarrow \; \textbf{UNDEFINED}$

 $V \leftarrow UNDEFINED$

2.44 ORI

Bitwise OR with Immediate

Encoding (short form):

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
ORI		001		0	0		Rd			Ra		0	1	iı	mm	3

Encoding (long form):

	F	E	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110 ext13														
ORI		001		0	0		Rd			Ra		0	1	iı	mm	3

Assembly:

ORI Rd, Ra, imm

Purpose:

To perform bitwise OR between a constant and a 16-bit integer in a register.

Restrictions:

None.

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA or opB
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← UNDEFINED
V ← UNDEFINED
```

2.45 ROLI

Rotate Left Immediate

Assembly:

ROLI Rd, Ra, amount

Purpose:

To perform a left rotate of a 16-bit integer in a register by a constant bit amount.

Restrictions:

The amount may be between 0 and 15, inclusive.

Remarks:

This instruction is an alias for ROTI.

2.46 RORI

Rotate Right Immediate

Assembly:

RORI Rd, Ra, amount

Purpose:

To perform a right rotate of a 16-bit integer in a register by a constant bit amount.

Restrictions:

The amount may be between 0 and 15, inclusive.

Remarks:

The assembler translates RORI with amount of 0 to

MOV Rd, Ra

and RORI with any other amount to

ROTI Rd, Rd, (15 - amount)

2.47 ROT Rotate

Encoding:

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
ROT		000		1	0		Rd			Ra		0	1		Rb	

Assembly:

ROT Rd, Ra, Rb

Purpose:

To perform a left rotate of a 16-bit integer in a register by a variable bit amount.

Restrictions:

If Rb contains a value greater than 15, the behavior is UNPREDICTABLE.

Operation:

 $\begin{array}{l} opA \leftarrow \texttt{mem[W|Ra]} \\ opB \leftarrow \texttt{mem[W|Rb]} \\ res \leftarrow opA[16-opB:0] | opA[16:16-opB] \\ mem[W|Rd] \leftarrow res \\ Z \leftarrow res = 0 \\ S \leftarrow res[15] \\ C \leftarrow \textbf{UNDEFINED} \\ V \leftarrow \textbf{UNDEFINED} \end{array}$

2.48 ROTI

Rotate Immediate

Encoding:

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
ROTI		001		1	0		$\overline{\mathrm{Rd}}$			Ra		0	1	iı	nm	3

Assembly:

ROTI Rd, Ra, amount

Purpose:

To perform a left rotate of a 16-bit integer in a register by a constant bit amount.

Restrictions:

The amount may be between 0 and 15, inclusive.

Operation:

```
opA ← mem[W|Ra]
res ← opA[15-imm3:0]|opA[16:15-imm3]
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← UNDEFINED
V ← UNDEFINED
```

Remarks:

The instruction encoding allows directly representing any **amount** between 1 and 8, inclusive. The assembler translates **ROTI** with **amount** of 0 to

```
MOV Rd, Ra
and ROTI with amount greater than 8 to
ROTI Rd, Ra, 8
ROTI Rd, Rd, (amount - 8)
```

2.49 SBB

Subtract Register with Borrow

Encoding:

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
SBB		000		0	1		$\overline{\mathrm{Rd}}$			Ra		1	1		Rb	

Assembly:

SBB Rd, Ra, Rb

Purpose:

To subtract 16-bit integers in registers, with borrow input.

Restrictions:

None.

Operation:

```
opA ← mem[W|Ra]
opB ← mem[W|Rb]
res ← opA - opB - not C
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← not res[16]
V ← (opA[15] = not opB[15]) and (opA[15] <> res[15])
```

Remarks:

A 32-bit subtraction with both operands in registers can be performed as follows:

```
; Perform (R1|R0) \leftarrow (R3|R2) - (R5|R4) SUB R0, R2, R4 SBB R1, R3, R5
```

2.50 SBBI

Subtract Immediate with Borrow

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
SBBI		001		0	1		Rd			Ra		1	1	iı	nm	3

Encoding (long form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110 ext13														
SBBI		001		0	1		Rd			Ra		1	1	iı	mm	3

Assembly:

SBBI Rd, Ra, imm

Purpose:

To subtract a constant from a 16-bit integer in a register, with borrow input.

Restrictions:

None.

Operation:

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA - opB - not C
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← not res[16]
V ← (opA[15] = not opB[15]) and (opA[15] <> res[15])
```

Remarks:

A 32-bit subtraction with a register and an immediate operand can be performed as follows:

```
; Perform (R1|R0) \leftarrow (R3|R2) - 0x40001 SUBI R0, R2, 1 SBBI R1, R3, 4
```

Encoding:

Assembly:

Purpose:

To perform a left logical shift of a 16-bit integer in a register by a variable bit amount.

Restrictions:

If Rb contains a value greater than 15, the behavior is UNPREDICTABLE.

```
\begin{array}{l} opA \leftarrow mem[\mathbb{W}|Ra] \\ opB \leftarrow mem[\mathbb{W}|Rb] \\ res \leftarrow opA[16-opB:0]|0\{opB\} \\ mem[\mathbb{W}|Rd] \leftarrow res \\ Z \leftarrow res = 0 \\ S \leftarrow res[15] \\ C \leftarrow \textbf{UNDEFINED} \\ V \leftarrow \textbf{UNDEFINED} \end{array}
```

2.52 SLLI

Shift Left Logical Immediate

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
SLLI		001		1	0		Rd			Ra		0	0	iı	mm	3

Assembly:

SLLI Rd, Ra, amount

Purpose:

To perform a left logical shift of a 16-bit integer in a register by a constant bit amount.

Restrictions:

The amount may be between 0 and 15, inclusive.

Operation:

```
opA ← mem[W|Ra]
res ← opA[15-imm3:0]|0{imm3+1}
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← UNDEFINED
V ← UNDEFINED
```

Remarks:

The instruction encoding allows directly representing any **amount** between 1 and 8, inclusive. The assembler translates **SLLI** with **amount** of 0 to

```
MOV Rd, Ra and SLLI with amount greater than 8 to SLLI Rd, Ra, 8
```

SLLI Rd, Rd, (amount - 8)

2.53 SRA

Shift Right Arithmetical

Encoding:

	F	Ε	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
SRA		000		1	0		$\overline{\mathrm{Rd}}$			Ra		1	1		Rb	

Assembly:

SRA Rd, Ra, Rb

Purpose:

To perform a right arithmetical shift of a 16-bit integer in a register by a variable bit amount.

Restrictions:

If Rb contains a value greater than 15, the behavior is UNPREDICTABLE.

```
\begin{array}{l} opA \;\leftarrow\; mem[\mathbb{W}|Ra] \\ opB \;\leftarrow\; mem[\mathbb{W}|Rb] \\ res \;\leftarrow\; opA[15]\{opB\}|opA[16:16-opB] \\ mem[\mathbb{W}|Rd] \;\leftarrow\; res \\ Z \;\leftarrow\; res \;=\; 0 \\ S \;\leftarrow\; res[15] \\ C \;\leftarrow\; \textbf{UNDEFINED} \\ V \;\leftarrow\; \textbf{UNDEFINED} \end{array}
```

2.54 SRAI

Shift Right Arithmetical Immediate

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
SRAI		000		1	0		$\overline{\mathrm{Rd}}$			Ra		1	1	iı	nm	3

Assembly:

SRAI Rd, Ra, amount

Purpose:

To perform a right arithmetical shift of a 16-bit integer in a register by a constant bit amount.

Restrictions:

The amount may be between 0 and 15, inclusive.

Operation:

```
\begin{array}{l} opA \;\leftarrow\; mem[\mathbb{W}|Ra] \\ opB \;\leftarrow\; mem[\mathbb{W}|Rb] \\ res \;\leftarrow\; opA[15]\{imm3+1\}|opA[16:15-imm3] \\ mem[\mathbb{W}|Rd] \;\leftarrow\; res \\ Z \;\leftarrow\; res \;=\; 0 \\ S \;\leftarrow\; res[15] \\ C \;\leftarrow\; \textbf{UNDEFINED} \\ V \;\leftarrow\; \textbf{UNDEFINED} \end{array}
```

Remarks:

The instruction encoding allows directly representing any **amount** between 1 and 8, inclusive. The assembler translates **SRAI** with **amount** of 0 to

```
MOV Rd, Ra
```

and SRAI with amount greater than 8 to

```
SRAI Rd, Ra, 8
SRAI Rd, Rd, (amount - 8)
```

Encoding:

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
SRL		000		1	0		$\overline{\mathrm{Rd}}$			Ra		1	0		Rb	

Assembly:

Purpose:

To perform a right logical shift of a 16-bit integer in a register by a variable bit amount.

Restrictions:

If Rb contains a value greater than 15, the behavior is UNPREDICTABLE.

```
\begin{array}{lll} opA &\leftarrow mem[\mathbb{W}|Ra] \\ opB &\leftarrow mem[\mathbb{W}|Rb] \\ res &\leftarrow \emptyset \{opB\} | opA[16:16-opB] \\ mem[\mathbb{W}|Rd] &\leftarrow res \\ Z &\leftarrow res = 0 \\ S &\leftarrow res[15] \\ C &\leftarrow \textbf{UNDEFINED} \\ V &\leftarrow \textbf{UNDEFINED} \end{array}
```

2.56 SRLI

Shift Right Logical Immediate

Encoding:

	F	Ε	D	С	В	A	9	8	7	6	5	4	3	2	1	0
SRLI		001		1	0		$\overline{\mathrm{Rd}}$			Ra		1	0	iı	mm	3

Assembly:

SRLI Rd, Ra, amount

Purpose:

To perform a right logical shift of a 16-bit integer in a register by a constant bit amount.

Restrictions:

The amount may be between 0 and 15, inclusive.

Operation:

```
opA ← mem[W|Ra]
res ← 0{imm3+1}|opA[16:15-imm3]
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← UNDEFINED
V ← UNDEFINED
```

Remarks:

The instruction encoding allows directly representing any **amount** between 1 and 8, inclusive. The assembler translates **SRLI** with **amount** of 0 to

```
MOV Rd, Ra
```

and SRLI with amount greater than 8 to

2.57 ST Store

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
ST		010		0	1		Rs			Ra				off5		

Encoding (long form):

	F	E	D	С	В	A	9	8	7	6	5	4	3	2	1	0	
EXTI		110			ext13												
ST	010 01 Rg Ra												off5				

Assembly:

ST Rs, Ra, off

Purpose:

To store a word to memory at a variable address, with a constant offset.

Restrictions:

If the long form is used, and off5[5:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off5[3:0]
else off ← sign_extend(off5)
addr ← mem[W|Ra] + off
temp ← mem[W|Rs]
mem[addr] ← temp
```

2.58 STI Store Indexed

Encoding (short form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
STI		010		0	1		Rs			Ra				off5		

Encoding (long form):

	F	E	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
STI		010		0	1		Rs			Ra				off5		

Assembly:

STI Rs, Ra, off

Purpose:

To store a word to memory at a constant PC-relative address, with a variable offset.

Restrictions:

If the long form is used, and off5[5:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
addr ← PC + mem[W|Ra] + off
temp ← mem[W|Rs]
mem[addr] ← temp
```

2.59 STX Store External with Address in Register

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
STX		010		1	1		Rs			Ra				off5		

Encoding (long form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
STX		010		1	1		Rs			Ra				off5		

Assembly:

STX Rs, Ra, off

Purpose:

To complete a store cycle on external bus at a variable address, with a constant offset.

Restrictions:

If the long form is used, and off5[5:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off5[3:0]
else off ← sign_extend(off5)
addr ← mem[W|Ra] + off
temp ← mem[W|Rs]
ext[addr] ← temp
```

2.60 STXZ

Store External Absolute

Encoding (short form):

	F	Е	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
STXZ		011		1	1		Rs					of	f 8			

Encoding (long form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	xt13						
STXZ		011		1	1		Rs					of	f8			

Assembly:

STXZ Rs, off

Purpose:

To complete a store cycle on external bus at a constant absolute address.

Restrictions:

If the long form is used, and off8[8:3] are non-zero, the behavior is UNPREDICTABLE.

```
if (has_ext13)
then off ← ext13|off8[3:0]
else off ← sign_extend(off8)
temp ← mem[W|Rs]
ext[off] ← temp
```

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
SUB		000		0	1		$\overline{\mathrm{Rd}}$			Ra		1	0		Rb	

Assembly:

SUB Rd, Ra, Rb

Purpose:

To subtract 16-bit integers in registers.

Restrictions:

None.

```
opA ← mem[W|Ra]
opB ← mem[W|Rb]
res ← opA - opB
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← not res[16]
V ← (opA[15] = not opB[15]) and (opA[15] <> res[15])
```

2.62 SUBI

Subtract Immediate

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
SUBI		001		0	1		Rd			Ra		1	0	iı	mm	3

Encoding (long form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	t13						
SUBI	001			0	1		Rd			Ra		1	0	iı	mm	3

Assembly:

SUBI Rd, Ra, imm

Purpose:

To subtract a constant from a 16-bit integer in a register.

Restrictions:

None.

```
opA ← mem[W|Ra]
if (has_ext13)
then opB ← ext13|imm3
else opB ← decode_immediate(imm3)
res ← opA - opB
mem[W|Rd] ← res
Z ← res = 0
S ← res[15]
C ← not res[16]
V ← (opA[15] = not opB[15]) and (opA[15] <> res[15])
```

2.63 XCHG

Exchange Registers

Assembly:

XCHG Ra, Rb

Purpose:

To exchange the values of two registers.

Restrictions:

None.

Remarks:

The assembler does not translate any instructions for XCHG with identical Ra and Rb, and translates XCHG with any other register combination to

XOR Ra, Ra, Rb

XOR Rb, Rb, Ra

XOR Ra, Ra, Rb

2.64 XOR

Bitwise XOR with Register

Encoding:

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
XOR		000		0	0		$\overline{\mathrm{Rd}}$			Ra		1	0		Rb	

Assembly:

XOR Rd, Ra, Rb

Purpose:

To perform bitwise XOR between 16-bit integers in registers.

Restrictions:

None.

Operation:

 $opA \leftarrow mem[W|Ra]$

 $\texttt{opB} \; \leftarrow \; \texttt{mem[W|Rb]}$

 $\texttt{res} \; \leftarrow \; \texttt{opA} \; \; \textbf{xor} \; \; \texttt{opB}$

 $\texttt{mem[W|Rd]} \; \leftarrow \; \texttt{res}$

 $Z \leftarrow res = 0$

 $S \leftarrow res[15]$

 $\mathsf{C} \; \leftarrow \; \textbf{UNDEFINED}$

 $V \leftarrow UNDEFINED$

2.65 XORI

Bitwise XOR with Immediate

Encoding (short form):

	F	Е	D	С	В	A	9	8	7	6	5	4	3	2	1	0
XORI		001		0	0		$\overline{\mathrm{Rd}}$			Ra		1	0	iı	mm	3

Encoding (long form):

	F	E	D	С	В	Α	9	8	7	6	5	4	3	2	1	0
EXTI		110							ех	ct13						
XORI	001			0	0		Rd			Ra		1	0	iı	mm	3

Assembly:

XORI Rd, Ra, imm

Purpose:

To perform bitwise XOR between a constant and a 16-bit integer in a register.

Restrictions:

None.