11/14/2017 CodeCrunch



NUS WebMail IVLE LIBRARY MAPS

Search for	in	NUS Websites	lacksquare	GO
------------	----	--------------	------------	----

CodeCrunch

Home	My Courses	Browse Tutorials	Browse Tasks	Search	My Submissions	Logout	Logged in as: e0175527
------	------------	------------------	--------------	--------	----------------	--------	-------------------------------

CS1010E Practice Exercise: Temperature Distribution

Tags & Categories

Related Tutorials

Tags:

Categories:

Task Content

Temperature Distribution

A metal plate represented by a n-by-n grid is heated at it's four edges at a constant temperature t. To compute the temperature of each internal grid cell on the metal plate, simply take the average of the neighboring four grid cells located at the top, bottom, left and right. An example is shown below for a n=6 plate that is initially heated at the edges with temperature t=5.

5	5	5	5	5	5
5	0	0	0	0	5
5	0	0	0	0	5
5	0	0	0	0	5
5	0	0	0	0	5
5	5	5	5	5	5

Averaging the internal grid cells above produces the following new values in iteration 1 (note the use of integer division):

5 5	5	5	5	5
5 (5+5+0+0)/4=2	(5+0+0+0)/4=1	(5+0+0+0)/4=1	(5+5+0+0)/4=2	5
5 (5+0+0+0)/4=1	(0+0+0+0)4=0	(0+0+0+0)/4=0	(5+0+0+0)/4=1	5
5 (5+0+0+0)/4=1	(0+0+0+0)4=0	(0+0+0+0)/4=0	(5+0+0+0)/4=1	5
5 (5+5+0+0)/4=2	(5+0+0+0)/4=1	(5+0+0+0)/4=1	(5+5+0+0)/4=2	5
5 5	5	5	5	5

Averaging the internal grid cells above produces the following new values in iteration 2:

5	5	5	5	5	5
5	3	2	2	3	5
5	2	0	0	2	5
5	2	0	0	2	5
5	3	2	2	3	5
5	5	5	5	5	5

Averaging the internal grid cells above produces the following new values in iteration 3:

11/14/2017 CodeCrunch

5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	

Averaging the internal grid cells above produces the following new values in iteration 4:

5 5 5 5 5 5 3 2 2 3 5 5 2 1 1 2 5 5 3 2 2 3 5 5 5 5 5 5 5

Notice that the plate temperature no longer changes, i.e. the system has reached steady state at iteration 4.

Write a program that reads the plate dimension n and temperature t, and determines the iteration at which steady-state occurs. Assume that $3 \le n \le 10$ and 0 < t < 1000.

Sample Runs

The following are sample runs of the program. User input is <u>underlined</u>. Ensure that the last line of output is followed by a newline character.

• Sample run #1:

```
Enter n: <u>6</u>
Enter t: <u>5</u>
Steady state iteration: 4
```

• Sample run #2:

```
Enter n: <u>6</u>
Enter t: <u>50</u>
Steady state iteration: 17
```

Submission (Course)

Select course: CS1010E (2017/2018 Sem 1) - Programming Methodology ▼

Your Files:

SUBMIT (only .java, .c, .cpp and .h extensions allowed)

To submit multiple files, click on the Browse button, then select one or more files. The selected file(s) will be added to the upload queue. You can repeat this step to add more files. Check that you have all the files needed for your submission. Then click on the Submit button to upload your submission.

MySoC | Computing Facilities | Search | Campus Map School of Computing, National University of Singapore

Terms of Use | Privacy | Non-discrimination