

Semantic segmentation in remote sensing



GRETSI 2027, historical session [1]

Josiane ZERUBIA

Inria Centre at Université Côte d'Azur, AYANA project-team

in collaboration with Martina PASTORINO and Gabriele MOSER

Università di Genova, DITEN

[1] M. Pastorino et al. "Segmentation sémantique en télédétection". In: *Traitement du Signal et des Images (TSI), GRETSI* (). Also available as Inria RR-9631 <https://inria.hal.science/hal-05742224> (Sept. 2026)



Outline

1. Introduction
2. From pixel to context
3. Markov and Bayesian models
4. Spectral-spatial and variational representations
5. Deep learning and foundation models
6. Open challenges



From image to thematic map

- ▶ Assign to **every pixel** a label from a predefined set of semantic classes [2] [3] [4]: a problem studied for decades under the names *supervised*, *per-pixel* and *contextual* classification
- ▶ Produces a **dense map**, to be distinguished from segmentation, which partitions the image into homogeneous regions *without* attaching any meaning to them
- ▶ In remote sensing: turning satellite observations into **land-cover and land-use maps**



(a) aerial image



(b) segmentation map

Zeebruges dataset, IEEE GRSS IADF Technical Committee; imagery and ground truth: Belgian Royal Military Academy and ONERA.

- [2] R. O. Duda and P. E. Hart. *Pattern Classification and Scene Analysis*. Wiley, 1973
- [3] P. H. Swain and S. M. Davis. *Remote Sensing: The Quantitative Approach*. McGraw-Hill, 1978
- [4] J. A. Richards. *Remote Sensing Digital Image Analysis*. Springer, 1986




What sets remote sensing apart

- ▶ Heterogeneous **sensors**: optical, synthetic aperture radar (SAR), LiDAR.
- ▶ Variable spatial and spectral **resolutions**; **multitemporal** and **multimodal** acquisitions.
- ▶ **Complex geographical scenes** whose properties vary with region, season and acquisition conditions.
- ▶ The field is therefore not a simple adaptation of computer vision: it combines **statistical pattern recognition**, **signal processing**, **probabilistic modeling** and **deep learning**.

$$I : \Omega \longrightarrow \mathbb{R}^d \quad \text{then} \quad f : \Omega \longrightarrow \mathcal{C}$$

- ▶ Ω : the image domain; d : variables derived from spectral bands, SAR polarizations, LiDAR measurements, indices, DTMs, etc.
- ▶ $\mathcal{C}$: the finite set of semantic classes.
- ▶ The history of the field can be read as a **progressive integration** of spectral, spatial, contextual and then multimodal information.





The first approaches: per-pixel

- ▶ In the late 1970s: Landsat (optical) and SeaSat (radar) create the need for automatic land-cover maps [5] [6] [7]
- ▶ Each pixel is an observation vector $\mathbf{x} = (x_1, \dots, x_d)^T$: radiometric responses, SAR intensities, indices, ancillary data [2].


$$\hat{\omega} = \arg \max_{\omega_i} P(\omega_i | \mathbf{x})$$

- ▶ Under a multivariate Gaussian assumption: the **MAP classifier**, “maximum a posteriori”, the reference method for several decades [3] [4] [8]

- [2] R. O. Duda and P. E. Hart. *Pattern Classification and Scene Analysis*. Wiley, 1973
- [3] P. H. Swain and S. M. Davis. *Remote Sensing: The Quantitative Approach*. McGraw-Hill, 1978
- [4] J. A. Richards. *Remote Sensing Digital Image Analysis*. Springer, 1986
- [5] R. Schowengerdt. *Remote Sensing: Models and Methods for Image Processing*. Academic Press, 2007
- [6] D. A. Landgrebe. *Signal Theory Methods in Multispectral Remote Sensing*. John Wiley & Sons, Ltd, 2003
- [7] F. Ulaby and D. Long. *Microwave Radar and Radiometric Remote Sensing*. 1st ed. Artech House, 2015
- [8] P. M. Mather. *Computer Processing of Remotely-Sensed Images*. Wiley, 2004

Two limitations: dimensionality and independence

- **Curse of dimensionality** (Hughes phenomenon) [9]: more variables do not guarantee better performance when few samples are available.
- **Independence assumption on the observations**: each pixel is decided in isolation, without using its neighborhood, yet geographical objects are strongly spatially correlated: agricultural fields, forests, urban areas, road networks
- Consequence: **noisy maps**, all the more so as spatial resolution increases



Per-pixel classification: the salt-and-pepper effect [13]

[9] G. Hughes. "On the mean accuracy of statistical pattern recognizers". In: *IEEE Trans. Inf. Theory* (1968)

[13] G. Moser et al. "Land-cover mapping by Markov modeling of spatial-contextual information in very-high-resolution remote sensing images". In: *Proc. IEEE* (2013)



Discriminative and ensemble methods

- ▶ From the late 1990s: estimating **the decision boundaries directly**, rather than the distribution of the observations.
- ▶ **SVMs**: margin maximization; good generalization in high dimension [14] [15] [17] [18].
- ▶ **Kernels**: nonlinearity without losing convexity; many developments for geospatial observations [16].
- ▶ **Random forests**: a vote of decision trees learned on random subsets; robustness, little tuning, variable importance [19] [20].
- ▶ But these methods remain **essentially per-pixel** classifiers when they are applied to local observations.

[14] V. N. Vapnik. *Statistical Learning Theory*. Wiley, 1998

[15] C. Cortes and V. Vapnik. "Support-vector networks". In: *Machine Learn.* (1995)

[16] B. Schölkopf and A. J. Smola. *Learning with Kernels*. MIT Press, 2002

[17] G. Camps-Valls and L. Bruzzone. *Kernel Methods for Remote Sensing Data Analysis*. Wiley, 2009

[18] G. Mountrakis et al. "Support vector machines in remote sensing: A review". In: *ISPRS J. Photogram. Remote Sens.* (2011)

[19] L. Breiman. "Random forests". In: *Machine Learning* (2001)


[20] P. O. Gislason et al. "Random forests for land cover classification". In: *Pattern Recognit. Lett.* (2006)




The contribution of spatial context



(a) IKONOS image



(b) per-pixel



(c) contextual

IKONOS image, 4 m, 3 bands, false-color composite; segmentation maps [13].

- In remote sensing, geographical objects exhibit **strong spatial consistency**: fields, forests, urban areas, road networks.
- Labels must be estimated **jointly**, not one pixel at a time.

[4] J. A. Richards. *Remote Sensing Digital Image Analysis*. Springer, 1986

[12] A. H. S. Solberg et al. "A Markov random field model for classification of multisource satellite imagery". In: *IEEE Trans. Geosci. Remote Sens.* (1996)

[13] G. Moser et al. "Land-cover mapping by Markov modeling of spatial-contextual information in very-high-resolution remote sensing images". In: *Proc. IEEE* (2013)

Markov random fields: the first formalization

- ▶ Labels become random variables defined on a **neighborhood graph** [10] [11] [22].
- ▶ Under the Markov assumptions and the equivalence with Gibbs distributions, MAP estimation becomes an **energy minimization**.

$$\hat{Y} = \arg \max_Y P(Y | X) \quad \Longleftrightarrow \quad \hat{Y} = \arg \min_Y U(Y | X)$$

- ▶ X : the observations; Y : the label map to be estimated.
- ▶ MRFs provide a general framework linking local data and spatial consistency.

[10] S. Geman and D. Geman. "Stochastic relaxation, Gibbs distributions, and the Bayesian restoration of images". In: *IEEE Trans. Pattern Anal. Mach. Intell.* (1984)

[11] J. Besag. "On the statistical analysis of dirty pictures". In: *J. Royal Stat. Soc.: Series B* (1986)


[22] Z. Kato and J. Zerubia. "Markov random fields in image segmentation". In: *Found. Trends Signal Process.* (2012)



Data term + regularization

$$U(Y | X) = U_d(Y | X) + \beta U_r(Y | X)$$

- ▶ U_d : the **data term**, derived from the likelihood.
- ▶ U_r : **spatial regularization**, promoting consistency between neighboring pixels.
- ▶ β : the trade-off between fidelity and regularity.
- ▶ 1st- or 2nd-order neighborhoods; clique potentials **penalize class changes** between **adjacent pixels** [22]



Pixel neighborhoods on a grid and the associated cliques [22].



Optimization and uses of MRFs

- ▶ Finding the optimal configuration is a hard combinatorial optimization problem.
- ▶ Strategies: **ICM**, **simulated annealing** [23], the **Gibbs sampler** [10], **graph cuts** [24], loopy belief propagation [25].
- ▶ Applications: contextual classification, multisource segmentation, restoration, change detection, optical / radar / LiDAR fusion [12] [26] [27].
- ▶ Beyond these applications: a **general probabilistic formulation** of spatial regularization.

- [10] S. Geman and D. Geman. "Stochastic relaxation, Gibbs distributions, and the Bayesian restoration of images". In: *IEEE Trans. Pattern Anal. Mach. Intell.* (1984)
- [12] A. H. S. Solberg et al. "A Markov random field model for classification of multisource satellite imagery". In: *IEEE Trans. Geosci. Remote Sens.* (1996)
- [23] S. Kirkpatrick. "Optimization by simulated annealing: Quantitative studies". In: *J. Stat. Phys.* (1984)
- [24] Y. Boykov et al. "Fast approximate energy minimization via graph cuts". In: *IEEE Trans. Pattern Anal. Mach. Intell.* (2001)
- [25] K. Tanaka et al. "Loopy belief propagation and probabilistic image processing". In: *IEEE NNISP*. 2003
- [26] H. Derin and H. Elliott. "Modeling and segmentation of noisy and textured images using Gibbs random fields". In: *IEEE Trans. Pattern Anal. Mach. Intell.* (1987)
- [27] G. Moser and S. B. Serpico. "Combining support vector machines and Markov random fields in an integrated framework for contextual image classification". In: *IEEE Trans. Geosci. Remote Sens.* (2013)

From MRFs to CRFs: a bridge to deep learning

- ▶ Conditional random fields model $P(Y | X)$ directly rather than the joint distribution [28]: this makes **complex discriminative features** easier to use.
- ▶ **Fully connected CRFs**: better preserved object boundaries [29].
- ▶ Integration into deep networks: refinement modules, **differentiable layers** [30]; hierarchical Markov frameworks and learned CRFs [31] [32] [33] [34].
- ▶ **The idea that runs through the field**: a map must be consistent both with the local observations *and* with the spatial organization of the scene.

[28] J. Lafferty et al. "Conditional random fields: Probabilistic models for segmenting and labeling sequence data". In: *ICML*. 2001

[29] P. Krähenbühl and V. Koltun. "Efficient inference in fully connected CRFs with Gaussian edge potentials". In: *NeurIPS*. 2011

[30] S. Zheng et al. "Conditional random fields as recurrent neural networks". In: *IEEE ICCV*. 2015

[31] M. Pastorino et al. "Multisensor and multiresolution remote sensing image classification through a causal hierarchical Markov framework and decision tree ensembles". In: *Remote Sensing* (2021)

[32] M. Pastorino et al. "Semantic segmentation of remote-sensing images through fully convolutional neural networks and hierarchical probabilistic graphical models". In: *IEEE Trans. Geosci. Remote Sens.* (2022)

[33] M. Pastorino et al. "CRFNet: A deep convolutional network to learn the potentials of a CRF for the semantic segmentation of remote sensing images". In: *IEEE Trans. Geosci. Remote Sens.* (2024)

[34] A. Voisin et al. "Classification of very high resolution SAR images of urban areas using copulas and texture in a hierarchical Markov random field model". In: *IEEE Geosci. Remote Sens. Lett.* (2013)

Enriching the representation, not only the labels


- ▶ Contextual models regularize the **labels**; spectral-spatial methods enrich the **features** before classification [6]
- ▶ As resolutions increase, radiometric signatures alone become insufficient.
- ▶ Texture, shape, size, spatial organization and neighborhood relations become **as discriminative as the spectral values themselves** [35].
- ▶ This rationale paves the way for the multiscale representations learned by deep networks [21].

[6] D. A. Landgrebe. *Signal Theory Methods in Multispectral Remote Sensing*. John Wiley & Sons, Ltd, 2003

[21] T. Blaschke. "Object based image analysis for remote sensing". In: *ISPRS J. Photogram. Remote Sens.* (2010)

[35] S. Dellepiane et al. "SAR image recognition by integration of intensity and textural information". In: *International Journal of Remote Sensing* (1991)

Mathematical morphology and multiscale profiles



erosion



original RGB image



dilation

Erosion and dilation of the original RGB satellite image.

- ▶ Operators: erosion, dilation, openings, closings [36] [37].
- ▶ **Extended morphological profiles** and **attribute profiles** describe shape, size and contrast at several scales [38] [39] [40].

[36] J. Serra. *Image Analysis and Mathematical Morphology*. Academic Press, 1982

[37] P. Soille. *Morphological Image Analysis*. Springer, 2003

[38] J. A. Benediktsson et al. "Classification of hyperspectral data from urban areas based on extended morphological profiles". In: *IEEE Trans. Geosci. Remote Sens.* (2005)

[39] M. Dalla Mura et al. "Morphological attribute profiles for the analysis of very high resolution images". In: *IEEE Trans. Geosci. Remote Sens.* (2010)

[40] M. Fauvel et al. "Spectral and spatial classification of hyperspectral data using SVMs and morphological profiles". In: *IEEE Trans. Geosci. Remote Sens.* (2008)

Variational methods: regularizing the solution

- ▶ A complementary approach: integrating spatial consistency directly into the formulation of the problem.
- ▶ Segmentation is formulated as an **energy minimization** combining fidelity to the observations with spatial or geometric regularity [42].

$$E(u) = \text{data fidelity} + \lambda \text{ spatial/geometric regularity}$$


- ▶ The **Mumford–Shah** functional is one of the founding models [41].
- ▶ The principles of data/regularity trade-off, multiscale analysis and fusion will reappear in learned forms in deep learning.

[41] D. Mumford and J. Shah. "Optimal approximations by piecewise smooth functions and associated variational problems". In: *Commun. Pure Appl. Math.* (1989)

[42] C. Samson et al. "A variational model for image classification and restoration". In: *IEEE Trans. Pattern Anal. Mach. Intell.* (2000)

Going deep

- ▶ 2012, the turning point: **AlexNet** demonstrates a dramatic improvement in natural-image classification [43]
- ▶ The change: learning the representations and the decision function jointly, directly from the data.
- ▶ **FCNs**: dense, pixel-level prediction.
- ▶ **U-Net**: skip connections to restore spatial information.
- ▶ **DeepLab**: dilated convolutions and multiscale representations to enlarge the receptive field.




FCN architecture applied to Potsdam

- [43] A. Krizhevsky et al. "ImageNet classification with deep convolutional neural networks". In: *NeurIPS*. 2012
- [44] J. Long et al. "Fully convolutional networks for semantic segmentation". In: *IEEE/CVF CVPR*. 2015
- [46] O. Ronneberger et al. "U-Net: Convolutional networks for biomedical image segmentation". In: *MICCAI*. 2015
- [48] L.-C. Chen et al. "Encoder-decoder with atrous separable convolution for semantic image segmentation". In: *ECCV*. 2018
- [47] N. Audebert et al. "Beyond RGB: Very high resolution urban remote sensing with multimodal deep networks". In: *ISPRS J. Photogram. Remote Sens.* (2018)
- [49] L. Ma et al. "Deep learning in remote sensing applications: A meta-analysis and review". In: *ISPRS J. Photogram. Remote Sens.* (2019)

Transformers, self-supervision and foundation models

- ▶ CNNs remain limited by the need for annotations and by the modeling of long-range dependencies.
- ▶ **Attention** mechanisms and transformers better represent the interactions between distant regions [50] [51].
- ▶ **Self-supervision** exploits large volumes of unlabeled satellite images to learn transferable representations [52].
- ▶ The goal: moving from a specialized model to **general, multimodal and transferable representations (geospatial foundation models)** [53].



Principle of a geospatial foundation model

- [50] A. Vaswani et al. "Attention is all you need". In: *NeurIPS*. 2017
- [51] A. Dosovitskiy et al. "An image is worth 16x16 words: Transformers for image recognition at scale". In: *ICLR*. 2021
- [52] K. He et al. "Masked autoencoders are scalable vision learners". In: *IEEE/CVF CVPR*. 2022
- [53] A. Xiao et al. "Foundation Models for Remote Sensing and Earth Observation: A Survey". In: *IEEE Geosci. Remote Sens. Mag.* (2025)


Open challenges

- ▶ **Generalization** across regions, seasons, sensors and resolutions.
- ▶ **Lack of annotations**: high cost of ground-truth data, class imbalance, noisy labels.
- ▶ **Multimodal fusion**: optical, SAR, LiDAR, time series and ancillary data.
- ▶ **Robustness**: distribution shift, clouds, noise, artifacts, rare events.
- ▶ **Interpretability**: understanding and controlling the decisions of increasingly large models.



Conclusion: a nonlinear history

- ▶ Not a simple trajectory from statistical classifiers to deep networks, but the **convergence of several families of methods**: statistical classification, kernel methods, ensemble methods, contextual models, Markov random fields, variational methods, stochastic geometry, deep learning, foundation models
- ▶ One unifying reading: the **progressive integration of increasing levels of context**



- ▶ One recurring principle: **data term + regularization**, from Markov random fields to the loss functions of deep networks

Thank you for your attention.



References I

- [1] M. Pastorino, G. Moser, and J. Zerubia. "Segmentation sémantique en télédétection". In: *Traitement du Signal et des Images (TSI)*, GRETSI (). Also available as Inria RR-9631 <https://inria.hal.science/hal-05742224> (Sept. 2026).
- [2] R. O. Duda and P. E. Hart. *Pattern Classification and Scene Analysis*. Wiley, 1973.
- [3] P. H. Swain and S. M. Davis. *Remote Sensing: The Quantitative Approach*. McGraw-Hill, 1978.
- [4] J. A. Richards. *Remote Sensing Digital Image Analysis*. Springer, 1986.
- [5] R. Schowengerdt. *Remote Sensing: Models and Methods for Image Processing*. Academic Press, 2007.
- [6] D. A. Landgrebe. *Signal Theory Methods in Multispectral Remote Sensing*. John Wiley & Sons, Ltd, 2003.
- [7] F. Ulaby and D. Long. *Microwave Radar and Radiometric Remote Sensing*. 1st ed. Artech House, 2015.
- [8] P. M. Mather. *Computer Processing of Remotely-Sensed Images*. Wiley, 2004.
- [9] G. Hughes. "On the mean accuracy of statistical pattern recognizers". In: *IEEE Trans. Inf. Theory* 14.1 (1968), pp. 55–63.
- [10] S. Geman and D. Geman. "Stochastic relaxation, Gibbs distributions, and the Bayesian restoration of images". In: *IEEE Trans. Pattern Anal. Mach. Intell.* 6.6 (1984), pp. 721–741.
- [11] J. Besag. "On the statistical analysis of dirty pictures". In: *J. Royal Stat. Soc.: Series B* 48.3 (1986), pp. 259–302.
- [12] A. H. S. Solberg, T. Taxt, and A. K. Jain. "A Markov random field model for classification of multisource satellite imagery". In: *IEEE Trans. Geosci. Remote Sens.* 34.1 (1996), pp. 100–113.
- [13] G. Moser, S. B. Serpico, and J. A. Benediktsson. "Land-cover mapping by Markov modeling of spatial-contextual information in very-high-resolution remote sensing images". In: *Proc. IEEE* 101.3 (2013), pp. 631–651.
- [14] V. N. Vapnik. *Statistical Learning Theory*. Wiley, 1998.
- [15] C. Cortes and V. Vapnik. "Support-vector networks". In: *Machine Learn.* 20 (1995), pp. 273–297.
- [16] B. Schölkopf and A. J. Smola. *Learning with Kernels*. MIT Press, 2002.
- [17] G. Camps-Valls and L. Bruzzone. *Kernel Methods for Remote Sensing Data Analysis*. Wiley, 2009.
- [18] G. Mountrakis, J. Im, and C. Ogole. "Support vector machines in remote sensing: A review". In: *ISPRS J. Photogram. Remote Sens.* 66.3 (2011), pp. 247–259.
- [19] L. Breiman. "Random forests". In: *Machine Learning* 45.1 (2001), pp. 5–32.
- [20] P. O. Gislason, J. A. Benediktsson, and J. R. Sveinsson. "Random forests for land cover classification". In: *Pattern Recognit. Lett.* 27.4 (2006), pp. 294–300.
- [21] T. Blaschke. "Object based image analysis for remote sensing". In: *ISPRS J. Photogram. Remote Sens.* 65.1 (2010), pp. 2–16.
- [22] Z. Kato and J. Zerubia. "Markov random fields in image segmentation". In: *Found. Trends Signal Process.* 5.1 (2012), pp. 1–155.
- [23] S. Kirkpatrick. "Optimization by simulated annealing: Quantitative studies". In: *J. Stat. Phys.* 34.5 (1984), pp. 975–986.

References II

- [24] Y. Boykov, O. Veksler, and R. Zabih. "Fast approximate energy minimization via graph cuts". In: *IEEE Trans. Pattern Anal. Mach. Intell.* 23.11 (2001), pp. 1222–1239.
- [25] K. Tanaka, J.-i. Inoue, and D. M. Titterton. "Loopy belief propagation and probabilistic image processing". In: *IEEE NNSP.* 2003, pp. 329–338.
- [26] H. Derin and H. Elliott. "Modeling and segmentation of noisy and textured images using Gibbs random fields". In: *IEEE Trans. Pattern Anal. Mach. Intell.* 9.1 (1987), pp. 39–55.
- [27] G. Moser and S. B. Serpico. "Combining support vector machines and Markov random fields in an integrated framework for contextual image classification". In: *IEEE Trans. Geosci. Remote Sens.* 51.5 (2013), pp. 2734–2752.
- [28] J. Lafferty, A. McCallum, and F. Pereira. "Conditional random fields: Probabilistic models for segmenting and labeling sequence data". In: *ICML.* 2001.
- [29] P. Krähenbühl and V. Koltun. "Efficient inference in fully connected CRFs with Gaussian edge potentials". In: *NeurIPS.* 2011.
- [30] S. Zheng, S. Jayasumana, B. Romera-Paredes, et al. "Conditional random fields as recurrent neural networks". In: *IEEE ICCV.* 2015.
- [31] M. Pastorino, A. Montaldo, L. Fronda, et al. "Multisensor and multiresolution remote sensing image classification through a causal hierarchical Markov framework and decision tree ensembles". In: *Remote Sensing* 13.5 (2021), p. 849.
- [32] M. Pastorino, G. Moser, S. B. Serpico, and J. Zerubia. "Semantic segmentation of remote-sensing images through fully convolutional neural networks and hierarchical probabilistic graphical models". In: *IEEE Trans. Geosci. Remote Sens.* 60 (2022), pp. 1–16.
- [33] M. Pastorino, G. Moser, S. B. Serpico, and J. Zerubia. "CRFNet: A deep convolutional network to learn the potentials of a CRF for the semantic segmentation of remote sensing images". In: *IEEE Trans. Geosci. Remote Sens.* (2024).
- [34] A. Voisin, V. A. Krylov, G. Moser, et al. "Classification of very high resolution SAR images of urban areas using copulas and texture in a hierarchical Markov random field model". In: *IEEE Geosci. Remote Sens. Lett.* 10.1 (2013), pp. 96–100.
- [35] S. Dellepiane, D. D. Giusto, S. B. Serpico, and G. Vernazza. "SAR image recognition by integration of intensity and textural information". In: *International Journal of Remote Sensing* 12.9 (1991), pp. 1915–1932.
- [36] J. Serra. *Image Analysis and Mathematical Morphology.* Academic Press, 1982.
- [37] P. Soille. *Morphological Image Analysis.* Springer, 2003.
- [38] J. A. Benediktsson, J. A. Palmason, and J. R. Sveinsson. "Classification of hyperspectral data from urban areas based on extended morphological profiles". In: *IEEE Trans. Geosci. Remote Sens.* 43.3 (2005), pp. 480–491.
- [39] M. Dalla Mura, J. A. Benediktsson, B. Waske, and L. Bruzzone. "Morphological attribute profiles for the analysis of very high resolution images". In: *IEEE Trans. Geosci. Remote Sens.* (2010).
- [40] M. Fauvel, J. A. Benediktsson, J. Chanussot, and J. R. Sveinsson. "Spectral and spatial classification of hyperspectral data using SVMs and morphological profiles". In: *IEEE Trans. Geosci. Remote Sens.* 46.11 (2008), pp. 3804–3814.

References III

- [41] D. Mumford and J. Shah. "Optimal approximations by piecewise smooth functions and associated variational problems". In: *Commun. Pure Appl. Math.* 42.5 (1989), pp. 577–685.
- [42] C. Samson, L. Blanc-Féraud, G. Aubert, and J. Zerubia. "A variational model for image classification and restoration". In: *IEEE Trans. Pattern Anal. Mach. Intell.* 22.5 (2000), pp. 460–472.
- [43] A. Krizhevsky, I. Sutskever, and G. E. Hinton. "ImageNet classification with deep convolutional neural networks". In: *NeurIPS*. 2012.
- [44] J. Long, E. Shelhamer, and T. Darrell. "Fully convolutional networks for semantic segmentation". In: *IEEE/CVF CVPR*. 2015, pp. 3431–3440.
- [45] M. Pastorino, G. Moser, S. B. Serpico, and J. Zerubia. "Probabilistic graphical models meet deep learning for semantic segmentation: Mathematical connections and recent developments". In: *IEEE Signal Process. Mag.* 43.2 (2026), pp. 51–63.
- [46] O. Ronneberger, P. Fischer, and T. Brox. "U-Net: Convolutional networks for biomedical image segmentation". In: *MICCAI*. 2015, pp. 234–241.
- [47] N. Audebert, B. Le Saux, and S. Lefèvre. "Beyond RGB: Very high resolution urban remote sensing with multimodal deep networks". In: *ISPRS J. Photogram. Remote Sens.* 140 (2018), pp. 20–32.
- [48] L.-C. Chen, Y. Zhu, G. Papandreou, et al. "Encoder-decoder with atrous separable convolution for semantic image segmentation". In: *ECCV*. 2018, pp. 801–818.
- [49] L. Ma, Y. Liu, X. Zhang, et al. "Deep learning in remote sensing applications: A meta-analysis and review". In: *ISPRS J. Photogram. Remote Sens.* 152 (2019), pp. 166–177.
- [50] A. Vaswani, N. Shazeer, N. Parmar, et al. "Attention is all you need". In: *NeurIPS*. 2017.
- [51] A. Dosovitskiy et al. "An image is worth 16x16 words: Transformers for image recognition at scale". In: *ICLR*. 2021.
- [52] K. He, X. Chen, S. Xie, et al. "Masked autoencoders are scalable vision learners". In: *IEEE/CVF CVPR*. 2022, pp. 16000–16009.
- [53] A. Xiao, W. Xuan, J. Wang, et al. "Foundation Models for Remote Sensing and Earth Observation: A Survey". In: *IEEE Geosci. Remote Sens. Mag.* 13.4 (2025), pp. 297–324.
- [54] A. Kirillov, E. Mintun, N. Ravi, et al. "Segment anything". In: *IEEE ICCV*. 2023, pp. 4015–4026.