

24 January 2013 — Version 0.9.9

To set your auth key from a file, use: `msession$setAuth("my-key-file")`
If you store your key on a shared machine, set file permissions appropriately.

Annotation hierarchies are available with: `rownames(collection, view, sep)`
`sep` should be a separator character, omitted, or `FALSE`. In the last case, the result is a matrix, with one row per annotation, and one column per hierarchy level.

21 January 2013 — Version 0.9.9

For auth keys and other session configuration, use: `msession` (formerly `mconfig`)

For bug reporting, use: `msession$debug()`

Collections now have four default views:

raw counts (**raw**)

normed counts (**nrm**)

no singletons, raw counts (**nsc**)

no singletons, normed counts (**nsn**)

Command reference now available with: `vignette("matR-quick-reference")`

The same document is available via:

<https://github.com/MG-RAST/matR/raw/master/inst/doc/matR-quick-reference.pdf>

Runtime R-style help now available, such as: `?collection`

For the moment, docs are by and large limited to series of examples.

Significance testing of annotations available with: `?sigtest`.

14 January 2013 — Version 0.9.9

This file available with: `vignette("matR-change-log")`

And at:

<https://github.com/MG-RAST/matR/raw/master/inst/doc/matR-change-log.pdf>