

```

/system reset-configuration
/interface vlan
add name=VLAN100 vlan-id=100 interface=bridge
add name=VLAN200 vlan-id=200 interface=bridge
add name=VLAN300 vlan-id=300 interface=bridge
/ip address
add address=109.44.129.66/27 interface=VLAN100
add address=109.44.129.1/26 interface=VLAN200
add address=109.44.128.1/24 interface=VLAN300
/interface bridge
add name=bridge
/interface bridge port
add interface=ether0/1/0 bridge=bridge
add interface=ether0/1/1 bridge=bridge
/ip route
add dst-address=8.8.4.4 gateway=127.0.0.1 scope=30 target-
scope=30 comment="isp1route" disabled=yes
add dst-address=0.0.0.0/0 gateway=8.8.4.4%sfpl distance=1 check-
gateway=ping comment="Основной маршрут"
/ip route
add dst-address=8.8.8.8 gateway=127.0.0.1 scope=30 target-
scope=30 comment="isp2route" disabled=yes
add dst-address=0.0.0.0/0 gateway=8.8.8.8%sfp2 distance=2 check-
gateway=ping comment="Резервный маршрут"
/system script
add name=UpdateISP1Route source="
:local gw [/ip dhcp-client get [find interface=sfp1] gateway-
address];
/ip route set [find comment='isp1route'] gateway=\$gw
disabled=no;
:log info "\"Обновлен основной маршрут: \$gw\"";"
/system script
add name=UpdateISP2Route source="
:local gw [/ip dhcp-client get [find interface=sfp2] gateway-
address];
/ip route set [find comment='isp2route'] gateway=\$gw
disabled=no;
:log info "\"Обновлен резервный маршрут: \$gw\"";"
/ip dhcp-client
add interface=sfp1 default-route-distance=255
comment="route1isp"
add interface=sfp2 default-route-distance=255
comment="route2isp"
set [find interface=sfp1] script="UpdateISP1Route"
set [find interface=sfp2] script="UpdateISP2Route"
/ip firewall nat
add chain=srcnat action=masquerade out-interface=sfp1 src-
address=109.44.129.64/27
add chain=srcnat action=masquerade out-interface=sfp1 src-
address=109.44.129.0/26
add chain=srcnat action=masquerade out-interface=sfp1 src-
address=109.44.128.0/24

```

```
add chain=srcnat action=masquerade out-interface=sfp2 src-
address=109.44.129.64/27
add chain=srcnat action=masquerade out-interface=sfp2 src-
address=109.44.129.0/26
add chain=srcnat action=masquerade out-interface=sfp2 src-
address=109.44.128.0/24
ip dhcp-server
add name=dhcp_vlan300 interface=vlan300 address-
pool=dhcp_pool_vlan300 lease-time=1h
/ip dhcp-server network
add address=109.44.128.0/24 gateway=109.44.128.1
/caps-man security
add name=vlan300_security authentication-types=wpa2-psk
encryption=aes-ccm passphrase=racer1626
/caps-man configuration
add name=vlan300_config ssid="Web-design deps"
security=vlan300_security datapath.vlan-id=300 datapath.vlan-
mode=use-tag
/caps-man provisioning
add action=create-enabled master-configuration=vlan300_config
/ip firewall filter add chain=forward src-
address=109.44.128.0/24 dst-address=109.44.129.2 action=drop
/ip firewall filter add chain=forward src-
address=109.44.129.0/26 dst-address=109.44.129.2 action=accept
/ip pool add name=dhcp_pool_vlan200 ranges=109.44.129.3-
109.44.129.47
/ip dhcp-server
add name=dhcp_vlan200 interface=vlan200 address-
pool=dhcp_pool_vlan200 lease-time=24h
/ip dhcp-server network
add address=109.44.129.0/26 gateway=109.44.129.1
/ipv6 address
add address=2001:67c:18a8:1::1/64 interface=vlan100
add address=2001:67c:18a8:2::1/64 interface=vlan200
add address=2001:67c:18a8:3::1/64 interface=vlan300
add address=2001:67c:18a8:4::2/64 interface=sfp1
add address=2001:67c:18a8:5::2/64 interface=sfp2
/ipv6 route add dst-address=::/0 gateway=2001:67c:18a8:4::1% sfp1
distance=1
/ipv6 route add dst-address=::/0 gateway=2001:67c:18a8:5::1% sfp2
distance=2
ipv6 dhcp-server> add name=dhcp_server200v6 interface=vlan300
address-pool=dhcp_pool300v6, exclude-pool=
dhcp_pool300v6_exclude
ipv6 pool> add name=dhcp_pool300v6 prefix=2001:67c:18a8:2::/64
ipv6 dhcp-server> add name=dhcp_wireless300v6 interface=vlan300
address-pool=dhcp_pool300v6, exclude-pool=
dhcp_pool300v6_exclude
ipv6 pool> add name=dhcp_pool300v6 prefix=2001:67c:18a8:3::/64
```

Коммутатор SW1.1

```
/system reset-configuration
/interface bridge
add name=bridge1 vlan-filtering=yes
/interface bridge port
add interface=ether1 bridge=bridge1
add interface=ether2 bridge=bridge1 pvid=300
add interface=ether3 bridge=bridge1 pvid=300
add interface=ether4 bridge=bridge1 pvid=300
add interface=ether5 bridge=bridge1 pvid=300
add interface=ether6 bridge=bridge1 pvid=300
add interface=ether7 bridge=bridge1 pvid=300
add interface=ether8 bridge=bridge1 pvid=200
add interface=ether9 bridge=bridge1 pvid=200
add interface=ether10 bridge=bridge1 pvid=200
add interface=ether11 bridge=bridge1 pvid=200
add interface=ether12 bridge=bridge1 pvid=200
add interface=ether13 bridge=bridge1 pvid=200
add interface=ether14 bridge=bridge1 pvid=200
add interface=ether15 bridge=bridge1 pvid=200
add interface=ether16 bridge=bridge1
/interface bridge vlan
add bridge=bridge1 tagged=ether1,ether16 vlan-ids=100
add bridge=bridge1 tagged=ether1,ether16
untagged=ether8,ether9,ether10,ether11,ether12,ether13,ether14,
ether15 vlan-ids=200
add bridge=bridge1 tagged=ether1,ether16
untagged=ether2,ether3,ether4,ether5,ether6,ether7 vlan-ids=300
/interface ethernet switch port
set ether2 default-vlan-id=300 vlan-header=always-strip
set ether3 default-vlan-id=300 vlan-header=always-strip
set ether4 default-vlan-id=300 vlan-header=always-strip
set ether5 default-vlan-id=300 vlan-header=always-strip
set ether6 default-vlan-id=300 vlan-header=always-strip
set ether7 default-vlan-id=300 vlan-header=always-strip
set ether8 default-vlan-id=200 vlan-header=always-strip
set ether9 default-vlan-id=200 vlan-header=always-strip
set ether10 default-vlan-id=200 vlan-header=always-strip
set ether11 default-vlan-id=200 vlan-header=always-strip
set ether12 default-vlan-id=200 vlan-header=always-strip
set ether13 default-vlan-id=200 vlan-header=always-strip
set ether14 default-vlan-id=200 vlan-header=always-strip
set ether15 default-vlan-id=200 vlan-header=always-strip
set ether16 vlan-header=add-if-missing
set ether17 disabled=yes
set ether18 disabled=yes
set ether19 disabled=yes
set ether20 disabled=yes
set ether21 disabled=yes
set ether22 disabled=yes
set ether23 disabled=yes
set ether24 disabled=yes
```

```

/interface bridge filter
add action=drop chain=forward in-interface=ether14 src-mac-
address=!00:1A:2B:3C:4D:5E
add action=drop chain=forward in-interface=ether8 src-mac-
address=!00:1B:2C:3D:4E:5F
add action=drop chain=forward in-interface=ether9 src-mac-
address=!00:1C:2D:3E:4F:5A
add action=drop chain=forward in-interface=ether10 src-mac-
address=!00:1D:2E:3F:4A:5B
add action=drop chain=forward in-interface=ether11 src-mac-
address=!00:1E:2F:3A:4B:5C
add action=drop chain=forward in-interface=ether12 src-mac-
address=!00:1F:2A:3B:4C:5D
add action=drop chain=forward in-interface=ether13 src-mac-
address=!00:2A:3B:4C:5D:6E
add action=drop chain=forward in-interface=ether15 src-mac-
address=!00:2B:3C:4D:5E:6F
/interface vlan
add name=VLAN100 vlan-id=100 interface=bridge1
/ip address
add address=109.44.129.77/27 interface=VLAN100
/ipv6 address
add address=2001:67c:18a8:1::13 interface=VLAN100

```

Коммутатор SW1.2

```

/system reset-configuration
/interface bridge
add name=bridge1 vlan-filtering=yes
/interface bridge port
add interface=ether0 bridge=bridge1
add interface=ether1 bridge=bridge1 pvid=200
add interface=ether2 bridge=bridge1 pvid=200
add interface=ether3 bridge=bridge1 pvid=200
add interface=ether4 bridge=bridge1 pvid=200
add interface=ether5 bridge=bridge1 pvid=200
add interface=ether6 bridge=bridge1 pvid=200
add interface=ether7 bridge=bridge1 pvid=200
add interface=ether8 bridge=bridge1 pvid=200
add interface=ether9 bridge=bridge1 pvid=200
add interface=ether10 bridge=bridge1 pvid=200
add interface=ether11 bridge=bridge1 pvid=200
add interface=ether12 bridge=bridge1 pvid=200
add interface=ether13 bridge=bridge1 pvid=200
add interface=ether14 bridge=bridge1 pvid=200
add interface=ether15 bridge=bridge1 pvid=200
add interface=ether16 bridge=bridge1 pvid=200
/interface bridge vlan
add bridge=bridge1 tagged=ether0 vlan-ids=100
add bridge=bridge1 tagged=ether0
untagged=ether1,ether2,ether3,ether4,ether5,ether6,ether7,ether8
,ether9,ether10,ether11,ether12,ether13,ether14,ether15,ether16
vlan-ids=200

```

```

/interface ethernet switch port
set ether1 default-vlan-id=200 vlan-header=always-strip
set ether2 default-vlan-id=200 vlan-header=always-strip
set ether3 default-vlan-id=200 vlan-header=always-strip
set ether4 default-vlan-id=200 vlan-header=always-strip
set ether5 default-vlan-id=200 vlan-header=always-strip
set ether6 default-vlan-id=200 vlan-header=always-strip
set ether7 default-vlan-id=200 vlan-header=always-strip
set ether8 default-vlan-id=200 vlan-header=always-strip
set ether9 default-vlan-id=200 vlan-header=always-strip
set ether10 default-vlan-id=200 vlan-header=always-strip
set ether11 default-vlan-id=200 vlan-header=always-strip
set ether12 default-vlan-id=200 vlan-header=always-strip
set ether13 default-vlan-id=200 vlan-header=always-strip
set ether14 default-vlan-id=200 vlan-header=always-strip
set ether15 default-vlan-id=200 vlan-header=always-strip
set ether16 default-vlan-id=200 vlan-header=always-strip
set ether0 vlan-header=add-if-missing
/interface ethernet
set ether17 disabled=yes
set ether18 disabled=yes
set ether19 disabled=yes
set ether20 disabled=yes
set ether21 disabled=yes
set ether22 disabled=yes
set ether23 disabled=yes
set ether24 disabled=yes
/interface bridge filter
add action=drop chain=forward in-interface=ether1 src-mac-
address=!00:2C:3D:4E:5F:6A
add action=drop chain=forward in-interface=ether2 src-mac-
address=!00:2D:3E:4F:5A:6B
add action=drop chain=forward in-interface=ether3 src-mac-
address=!00:2E:3F:4A:5B:6C
add action=drop chain=forward in-interface=ether4 src-mac-
address=!00:2F:3A:4B:5C:6D
add action=drop chain=forward in-interface=ether5 src-mac-
address=!00:3A:4B:5C:6D:7E
add action=drop chain=forward in-interface=ether6 src-mac-
address=!00:3B:4C:5D:6E:7F
add action=drop chain=forward in-interface=ether7 src-mac-
address=!00:3C:4D:5E:6F:7A
add action=drop chain=forward in-interface=ether8 src-mac-
address=!00:3D:4E:5F:6A:7B
add action=drop chain=forward in-interface=ether9 src-mac-
address=!00:3E:4F:5A:6B:7C
add action=drop chain=forward in-interface=ether10 src-mac-
address=!00:3F:4A:5B:6C:7D
add action=drop chain=forward in-interface=ether11 src-mac-
address=!00:4A:5B:6C:7D:8E
add action=drop chain=forward in-interface=ether12 src-mac-
address=!00:4B:5C:6D:7E:8F

```

```

add action=drop chain=forward in-interface=ether13 src-mac-
address=!00:4C:5D:6E:7F:8A
add action=drop chain=forward in-interface=ether14 src-mac-
address=!00:4D:5E:6F:7A:8B
add action=drop chain=forward in-interface=ether15 src-mac-
address=!00:4E:5F:6A:7B:8C
add action=drop chain=forward in-interface=ether16 src-mac-
address=! 00:5A:6B:7C:8D:9E
/interface vlan
add name=VLAN100 vlan-id=100 interface=bridge1
/ip address
add address=109.44.129.78/27 interface=VLAN100
/ipv6 address
add address=2001:67c:18a8:1::14 interface=VLAN100

```

Коммутатор SW2.1

```

/system reset-configuration
/interface bridge
add name=bridge1 vlan-filtering=yes
/interface bridge port
add interface=ether0 bridge=bridge1
add interface=ether1 bridge=bridge1 pvid=300
add interface=ether2 bridge=bridge1 pvid=300
add interface=ether3 bridge=bridge1 pvid=300
add interface=ether4 bridge=bridge1 pvid=300
add interface=ether5 bridge=bridge1 pvid=300
add interface=ether6 bridge=bridge1 pvid=200
add interface=ether7 bridge=bridge1 pvid=200
add interface=ether8 bridge=bridge1 pvid=200
add interface=ether9 bridge=bridge1 pvid=200
add interface=ether10 bridge=bridge1 pvid=200
add interface=ether11 bridge=bridge1
/interface bridge vlan
add bridge=bridge1 tagged=ether0,ether11 vlan-ids=100
add          bridge=bridge1          tagged=ether0,          ether11
untagged=ether1,ether2,ether3,ether4,ether5 vlan-ids=300
add          bridge=bridge1          tagged=ether0,          ether11
untagged=ether6,ether7,ether8,ether9,ether10 vlan-ids=200
/interface ethernet switch port
set ether1 default-vlan-id=300 vlan-header=always-strip
set ether2 default-vlan-id=300 vlan-header=always-strip
set ether3 default-vlan-id=300 vlan-header=always-strip
set ether4 default-vlan-id=300 vlan-header=always-strip
set ether5 default-vlan-id=300 vlan-header=always-strip
set ether6 default-vlan-id=200 vlan-header=always-strip
set ether7 default-vlan-id=200 vlan-header=always-strip
set ether8 default-vlan-id=200 vlan-header=always-strip
set ether9 default-vlan-id=200 vlan-header=always-strip
set ether10 default-vlan-id=200 vlan-header=always-strip
set ether0 vlan-header=add-if-missing
/interface ethernet
set ether12 disabled=yes

```

```

set ether13 disabled=yes
set ether14 disabled=yes
set ether15 disabled=yes
set ether16 disabled=yes
set ether17 disabled=yes
set ether18 disabled=yes
set ether19 disabled=yes
set ether20 disabled=yes
set ether21 disabled=yes
set ether22 disabled=yes
set ether23 disabled=yes
set ether24 disabled=yes
/interface bridge filter
add action=drop chain=forward in-interface=ether6 src-mac-
address=!00:5C:6D:7E:8F:9A
add action=drop chain=forward in-interface=ether7 src-mac-
address=!00:5D:6E:7F:8A:9B
add action=drop chain=forward in-interface=ether8 src-mac-
address=!00:5E:6F:7A:8B:9C
add action=drop chain=forward in-interface=ether9 src-mac-
address=!00:5F:6A:7B:8C:9D
add action=drop chain=forward in-interface=ether10 src-mac-
address=!00:6A:7B:8C:9D:AE
/interface vlan
add name=VLAN100 vlan-id=100 interface=bridge1
/ip address
add address=109.44.129.79/27 interface=VLAN100
/ipv6 address
add address=2001:67c:18a8:1::15 interface=VLAN100

```

Коммутатор SW2.2

```

/system reset-configuration
/interface bridge
add name=bridge1 vlan-filtering=yes
/interface bridge port
add interface=ether0 bridge=bridge1
add interface=ether1 bridge=bridge1 pvid=200
add interface=ether2 bridge=bridge1 pvid=200
add interface=ether3 bridge=bridge1 pvid=200
add interface=ether4 bridge=bridge1 pvid=200
add interface=ether5 bridge=bridge1 pvid=200
add interface=ether6 bridge=bridge1 pvid=200
add interface=ether7 bridge=bridge1 pvid=200
add interface=ether8 bridge=bridge1 pvid=200
add interface=ether9 bridge=bridge1 pvid=200
add interface=ether10 bridge=bridge1 pvid=200
add interface=ether11 bridge=bridge1 pvid=200
add interface=ether12 bridge=bridge1 pvid=200
add interface=ether13 bridge=bridge1 pvid=200
add interface=ether14 bridge=bridge1 pvid=200
add interface=ether15 bridge=bridge1 pvid=200
add interface=ether16 bridge=bridge1 pvid=200

```

```

/interface bridge vlan
add bridge=bridge1 tagged=ether0 vlan-ids=100
add                                bridge=bridge1                                tagged=ether0
untagged=ether1,ether2,ether3,ether4,ether5,ether6,ether7,ether8
,ether9,ether10,ether11,ether12,ether13,ether14,ether15,ether16
vlan-ids=200
/interface ethernet switch port
set ether1 default-vlan-id=200 vlan-header=always-strip
set ether2 default-vlan-id=200 vlan-header=always-strip
set ether3 default-vlan-id=200 vlan-header=always-strip
set ether4 default-vlan-id=200 vlan-header=always-strip
set ether5 default-vlan-id=200 vlan-header=always-strip
set ether6 default-vlan-id=200 vlan-header=always-strip
set ether7 default-vlan-id=200 vlan-header=always-strip
set ether8 default-vlan-id=200 vlan-header=always-strip
set ether9 default-vlan-id=200 vlan-header=always-strip
set ether10 default-vlan-id=200 vlan-header=always-strip
set ether11 default-vlan-id=200 vlan-header=always-strip
set ether12 default-vlan-id=200 vlan-header=always-strip
set ether13 default-vlan-id=200 vlan-header=always-strip
set ether14 default-vlan-id=200 vlan-header=always-strip
set ether15 default-vlan-id=200 vlan-header=always-strip
set ether16 default-vlan-id=200 vlan-header=always-strip
set ether0 vlan-header=add-if-missing
/interface ethernet
set ether17 disabled=yes
set ether18 disabled=yes
set ether19 disabled=yes
set ether20 disabled=yes
set ether21 disabled=yes
set ether22 disabled=yes
set ether23 disabled=yes
set ether24 disabled=yes
/interface bridge filter
add action=drop chain=forward in-interface=ether1 src-mac-
address=!00:6B:7C:8D:9E:AF
add action=drop chain=forward in-interface=ether2 src-mac-
address=!00:6C:7D:8E:9F:AA
add action=drop chain=forward in-interface=ether3 src-mac-
address=!00:6D:7E:8F:9A:AB
add action=drop chain=forward in-interface=ether4 src-mac-
address=!00:6E:7F:8A:9B:AC
add action=drop chain=forward in-interface=ether5 src-mac-
address=!00:6F:7A:8B:9C:AD
add action=drop chain=forward in-interface=ether6 src-mac-
address=!00:7A:8B:9C:AD:BE
add action=drop chain=forward in-interface=ether7 src-mac-
address=!00:7B:8C:9D:AE:BF
add action=drop chain=forward in-interface=ether8 src-mac-
address=!00:7C:8D:9E:AF:BA
add action=drop chain=forward in-interface=ether9 src-mac-
address=!00:7D:8E:9F:AA:BB

```



```
add action=drop chain=forward in-interface=ether10 src-mac-  
address=!00:7E:8F:9A:AB:BC  
add action=drop chain=forward in-interface=ether11 src-mac-  
address=!00:7F:8A:9B:AC:BD  
add action=drop chain=forward in-interface=ether12 src-mac-  
address=!00:8A:9B:AC:BD:CE  
add action=drop chain=forward in-interface=ether13 src-mac-  
address=!00:8B:9C:AD:BE:CF  
add action=drop chain=forward in-interface=ether14 src-mac-  
address=!00:8C:9D:AE:BF:CA  
add action=drop chain=forward in-interface=ether15 src-mac-  
address=!00:5D:6E:7F:8A:9B  
add action=drop chain=forward in-interface=ether16 src-mac-  
address=!00:4F:5A:6B:7C:8D/interface vlan  
add name=VLAN100 vlan-id=100 interface=bridge1  
/ip address  
add address=109.44.129.80/27 interface=VLAN100  
/ipv6 address  
add address=2001:67c:18a8:1::16 interface=VLAN10
```

Точка доступа AP1.1

```
/interface wireless cap
set enabled=yes caps-man-addresses=109.44.128.1
/ip address add address=109.44.128.2/24 interface=ether2
/ipv6 address add address=2001:67c:18a8:1::3/64 interface=ether2
/ipv6 route add gateway=2001:67c:18a8:1::1/64
```

Точка доступа AP1.2

```
/interface wireless cap
set enabled=yes caps-man-addresses=109.44.128.1
/ip address add address=109.44.128.3/24 interface=ether3
/ipv6 address add address=2001:67c:18a8:1::4/64 interface=ether3
/ipv6 route add gateway=2001:67c:18a8:1::1/64
```

Точка доступа AP1.3

```
/interface wireless cap
set enabled=yes caps-man-addresses=109.44.128.1
/ip address add address=109.44.128.4/24 interface=ether4
/ipv6 address add address=2001:67c:18a8:1::5/64 interface=ether4
/ipv6 route add gateway=2001:67c:18a8:1::1/64
```

Точка доступа AP1.4

```
/interface wireless cap
set enabled=yes caps-man-addresses=109.44.128.1
/ip address add address=109.44.128.5/24 interface=ether5
/ipv6 address add address=2001:67c:18a8:1::6/64 interface=ether5
/ipv6 route add gateway=2001:67c:18a8:1::1/64
```

Точка доступа AP1.5

```
/interface wireless cap
set enabled=yes caps-man-addresses=109.44.128.1
/ip address add address=109.44.128.6/24 interface=ether6
/ipv6 address add address=2001:67c:18a8:1::7/64 interface=ether6
/ipv6 route add gateway=2001:67c:18a8:1::1/64
```

Точка доступа AP2.1

```
/interface wireless cap
set enabled=yes caps-man-addresses=109.44.128.1
/ip address add address=109.44.128.7/24 interface=ether1
/ipv6 address add address=2001:67c:18a8:1::8/64 interface=ether1
/ipv6 route add gateway=2001:67c:18a8:1::1/64
```

Точка доступа AP2.2

```
/interface wireless cap
```

```
set enabled=yes caps-man-addresses=109.44.128.1
/ip address add address=109.44.128.8/24 interface=ether2
/ipv6 address add address=2001:67c:18a8:1::9/64 interface=ether2
/ipv6 route add gateway=2001:67c:18a8:1::1/64
```

Точка доступа AP2.3

```
/interface wireless cap
set enabled=yes caps-man-addresses=109.44.128.3
/ip address add address=109.44.128.9/24 interface=ether3
/ipv6 address add address=2001:67c:18a8:1::10/64
interface=ether1
/ipv6 route add gateway=2001:67c:18a8:1::1/64
```

Точка доступа AP2.4

```
/interface wireless cap
set enabled=yes caps-man-addresses=109.44.128.4
/ip address add address=109.44.128.10/24 interface=ether4
/ipv6 address add address=2001:67c:18a8:1::11/64
interface=ether1
/ipv6 route add gateway=2001:67c:18a8:1::1/64
```

Точка доступа AP2.5

```
/interface wireless cap
set enabled=yes caps-man-addresses=109.44.128.5
/ip address add address=109.44.128.11/24 interface=ether5
/ipv6 address add address=2001:67c:18a8:1::12/64
interface=ether1
/ipv6 route add gateway=2001:67c:18a8:1::1/64
```

```
sudo apt update
sudo apt install samba
sudo nano /etc/network/interfaces
```

Файл interfaces

```
auto eth0
iface eth0 inet static
    address 109.44.129.2
    netmask 255.255.255.192
    gateway 109.44.129.1

iface eth0 inet6 static
    address 2001:67c:18a8:2::2
    netmask 64
    gateway 2001:67c:18a8:2::1

sudo systemctl restart networking
sudo groupadd samba_admins
sudo groupadd samba_users
sudo useradd user1 -s /sbin/nologin
echo "racer1626" | sudo smbpasswd -a user1
sudo usermod -aG samba_admins user1
sudo useradd user2 -s /sbin/nologin
echo "webdsg24" | sudo smbpasswd -a user2
sudo usermod -aG samba_users user2
sudo mkdir -p /srv/samba/admin_share
sudo mkdir -p /srv/samba/user_share
sudo chown :samba_admins /srv/samba/admin_share
sudo chmod 770 /srv/samba/admin_share
sudo chown :samba_users /srv/samba/user_share
sudo chmod 770 /srv/samba/user_share
sudo setfacl -m g:samba_admins:rwx /srv/samba/user_share
```

Файл smb.conf

```
[global]
    workgroup = WORKGROUP
    server string = Samba Server %v
    netbios name = samba
    security = user
    map to guest = Bad User
    dns proxy = no

[AdminShare]
    path = /srv/samba/admin_share
    available = yes
    valid users = @samba_admins
    read only = no
    browsable = yes
    public = no
    writable = yes
```

```
[UserShare]
    path = /srv/samba/user_share
    available = yes
    valid users = @samba_users, @samba_admins
    read only = no
    browsable = yes
    public = no
    writable = yes
```

```
sudo systemctl restart smbd
sudo systemctl restart nmbd
```