

Пример конфигурирования маршрутизатора

```
Router>enable
Router#configure terminal
Router(config)#interface GigabitEthernet0/0/0
Router(config-if)#ip address 209.208.88.25 255.255.255.128
Router(config-if)#exit
Router(config)#exit
Router#vlan database
Router(vlan)#vtp server
Router(vlan)#vtp domain server
Router(vlan)#vtp password lpigxlCGE4govj07
Router(vlan)#vlan 30 name web_server
Router(vlan)#vlan 10 name administrative
Router(vlan)#vlan 100 name stationary
Router(vlan)#vlan 200 name wireless
Router(vlan)#vlan 20 name manage
Router(vlan)#exit

Router#configure terminal
Router(config)#interface Vlan 30
Router(config-if)#ip address 192.168.25.33 255.255.255.252
Router(config-if)#ipv6 address fd00:0:0:30::1011/64
Router(config)#interface Vlan 10
Router(config-if)#ip address 192.168.25.53 255.255.255.240
Router(config-if)#ipv6 address fd00:0:0:10::1011/64
Router(config)#interface Vlan 100
Router(config-if)#ip address 192.168.25.10 255.255.255.240
Router(config-if)#ipv6 address fd00:0:0:100::1011/64
Router(config)#interface Vlan 200
Router(config-if)#ip address 192.168.25.200 255.255.255.128
Router(config-if)#ipv6 address fd00:0:0:200::1011/64
Router(config)#interface Vlan 20
Router(config-if)#ip address 192.168.25.20 255.255.255.248
Router(config-if)#ipv6 address fd00:0:0:20::1011/64
Router(config-if)#exit

Router(config)#interface GigabitEthernet0/1/0
Router(config-if)#switchport mode trunk
Router(config-if)#switchport trunk allowed vlan 10,20,30,100,200
Router(config)#interface GigabitEthernet0/1/1
Router(config-if)#switchport mode trunk
Router(config-if)#switchport trunk allowed vlan 10,20,30,100,200
Router(config-if)#exit

Router(config)#ip dhcp pool dhcp-vlan-200
Router(dhcp-config)#excluded-address 192.168.25.200
Router(dhcp-config)#excluded-address 192.168.25.129
Router(dhcp-config)#excluded-address 192.168.25.130
Router(dhcp-config)#excluded-address 192.168.25.131
Router(dhcp-config)#excluded-address 192.168.25.132
```

```

Router(dhcp-config)#dns-server Router1_1_Server
Router(dhcp-config)#default-router 192.168.25.200
Router(dhcp-config)#network 192.168.25.128 255.255.255.128
Router(dhcp-config)#exit
Router(config)#ipv6 dhcp pool dhcp6-vlan-200
Router(config-dhcpv6)#domain-name Router1_1_ServerV6
Router(config-dhcpv6)#dns-server fd00:0:0:200::1011
Router(config-dhcpv6)#exit
Router(config)#interface vlan200
Router(config-if)#ipv6 dhcp server Router1_1_ServerV6
Router(config-if)#ipv6 nd other-config flag
Router(config-if)#exit

Router(config)#ip nat pool outside_pool 209.208.88.25 netmask
255.255.255.128
Router(config)#access-list 1 permit 192.168.25.0 255.255.255.0
Router(config)#ip nat inside source list 1 pool outside_pool
Router(config)#interface GigabitEthernet0/0/0
Router(config-if)#ip nat outside
Router(config)#interface GigabitEthernet0/1/0
Router(config-if)#ip nat inside
Router(config)#interface GigabitEthernet0/1/1
Router(config-if)#ip nat inside

Router(config)#hostname Router1_1
Router1_1(config)#ip domain-name Router1_1
Router1_1(config)#enable password HXDpfgNT_130903
Router1_1(config)#crypto key generate ssh rsa bit 512
Router1_1(config)#username Router1_1 password HXDpfgNT_130903
Router1_1(config)#line vty 0 15
Router1_1(config-line)#transport input ssh
Router1_1(config-line)#login local

```

Пример конфигурирования коммутатора

```

Switch>enable
Switch#configure terminal
Switch(config)#vtp mode client
Switch(config)#vtp domain server
Switch(config)#vtp password 1pigxlCGE4govj07

Switch(config)#interface GigabitEthernet0/1
Switch(config-if)#switchport mode trunk
Switch(config-if)#switchport trunk allowed vlan 10,20,30,100,200
Switch(config)#interface range FastEthernet0/1-5
Switch(config-if-range)#switchport mode access
Switch(config-if-range)#switchport access vlan 100
Switch(config)#interface range FastEthernet0/6-7
Switch(config-if-range)#switchport mode access
Switch(config-if-range)#switchport access vlan 200
Switch(config)#interface FastEthernet0/8

```

```
Switch(config-if)#switchport mode access  
Switch(config-if)#switchport access vlan 30
```

Пример настройки веб-сервера

```
sudo apt update  
apt install apache2  
sudo ip addr add 192.168.25.34/30 dev eth1  
sudo ip -6 addr add fd00:0:0:30::5011/64 dev eth1
```