SDLS044

SN54125, SN54126, SN54LS125A, SN54LS126A, SN74125, SN74126, SN74LS125A, SN74LS126A
QUADRUPLE BUS BUFFERS WITH 3-STATE OUTPUTS

DECEMBER 1983 — REVISED MARCH 1988

- **Quad Bus Buffers**
- **3-State Outputs**
- **Separate Control for Each Channel**

SN54125, SN54126, SN54LS125A, SN54LS126A . . . J OR W PACKAGE
SN74125, SN74126 . . . N PACKAGE
SN74LS125A, SN74LS126A . . . D OR N PACKAGE
(TOP VIEW)



SN54LS125A, SN54LS126A . . . FK PACKAGE
(TOP VIEW)



*G̅ on '125 and 'LS125A; G on 126 and 'LS126A

NC — No internal connection

description

These bus buffers feature three-state outputs that, when enabled, have the low impedence characteristics of a TTL output with additional drive capability at high logic levels to permit driving heavily loaded bus lines without external pull-up resistors, when disabled, both output transistors are turned off presenting a high-impedance state to the bus so the output will act neither as a significant load nor as a driver. The '125 and 'LS125A outputs are disabled when $\overline{G}$ is high. The '126 and 'LS126A outputs are disabled when G is low.

logic diagram (each gate)

'125, 'LS125A



'126, LS126A



positive logic Y = A

logic symbols†

'125



'LS125A



'126



'LS126A



†These symbols are in accordance with ANSI/IEEE Std. 91-1984 and IEC Publication 617-12.
Pin numbers shown are for D, J, N, and W packages.

PRODUCTION DATA documents contain information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

TEXAS INSTRUMENTS
POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

schematics (each gate)



'125 CIRCUITS



'126 CIRCUITS

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC} (See Note 1)		7 V
Input voltage		5.5 V
Operating free-air temperature range:	SN54'	−55°C to 125°C
	SN74'	0°C to 70°C
Storage temperature range		−65°C to 150°C

NOTE 1: Voltage values are with respect to network ground terminal.

schematics (each gate)



'LS125A CIRCUITS



'LS126A CIRCUITS

Resistor values shown are nominal.

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC} (see Note 1) . . . . . 7 V
Input voltage . . . . . 7 V
Operating free-air temperature range: SN54' . . . . . −55°C to 125°C
SN74' . . . . . 0°C to 70°C
Storage temperature range . . . . . −65°C to 150°C

NOTE 1: Voltage values are with respect to network ground terminals.

recommended operating conditions

		SN54125, SN54126			SN74125, SN74126			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5	5.5	4.75	5	5.25	V
V_{IH}	High-level input voltage	2			2			V
V_{IL}	Low-level input voltage			0.8			0.8	V
I_{OH}	High-level output current			−2			−5.2	mA
I_{OL}	Low-level output current			16			16	mA
T_A	Operating free-air temperature	−55		125	0		70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS †		SN54125, SN54126			SN74125, SN74126			UNIT
			MIN	TYP‡	MAX	MIN	TYP‡	MAX	
V_{IK}	V_{CC} = MIN, I_I = −12 mA				1.5			1.5	V
V_{OH}	V_{CC} = MIN, V_{IH} = 2 V, V_{IL} = 0.8 V	I_{OH} = −2 mA	2.4	3.3					V
		I_{OH} = −5.2 mA				2.4	3.1		
V_{OL}	V_{CC} = MIN, V_{IH} = 2 V, I_{OL} = 16 mA	V_{IL} = 0.8 V,			0.4			0.4	V
I_{OZ}	V_{CC} = MAX, V_{IH} = 2 V, V_{IL} = 0.8 V	V_O = 2.4 V			40			40	μA
		V_O = 0.4 V			−40			−40	
I_I	V_{CC} = MAX, V_I = 6.5 V				1			1	mA
I_{IH}	V_{CC} = MAX, V_I = 2.4 V				40			40	μA
I_{IL}	V_{CC} = MAX, V_I = 0.4 V				−1.6			−1.6	mA
I_{OS}§	V_{CC} = MAX		−30		−70	−28		−70	mA
I_{CC}	V_{CC} = MAX, (see Note 2)	'125		32	54		32	54	mA
		'126		36	62		36	62	

† For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.
‡ All typical values are at V_{CC} = 5 V, T_A = 25°C.
§ Not more than one output should be shorted at a time.
NOTE 2: Data inputs = 0.V; output control = 4.5 V for '125 and 0 V for '126.

switching characteristics, V_{CC} = 5 V, T_A = 25°C (see note 3)

PARAMETER	TEST CONDITIONS		SN54/74125			SN54/74126			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
t_{PLH}	R_L = 400 Ω,	C_L = 50 pF		8	13		8	13	ns
t_{PHL}				12	18		12	18	ns
t_{PZH}				11	17		11	18	ns
t_{PZL}				16	25		16	25	ns
t_{PHZ}	R_L = 400 Ω,	C_L = 5 pF		5	8		10	16	ns
t_{PLZ}				7	12		12	18	ns

NOTE 3: Load circuits and voltage waveforms are shown in Section 1.

recommended operating conditions

		SN54LS125A SN54LS126A			SN74LS125A SN74LS126A			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5	5.5	4.75	5	5.25	V
V_{IH}	High-level input voltage	2			2			V
V_{IL}	Low-level input voltage			0.7			0.8	V
I_{OH}	High-level output current			−1			−2.6	mA
I_{OL}	Low-level output current			12			24	mA
T_A	Operating free-air temperature	−55		125	0		70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS†			SN54LS125A SN54LS126A			SN74LS125A SN74LS126A			UNIT
				MIN	TYP‡	MAX	MIN	TYP‡	MAX	
V_{IK}	V_{CC} = MIN, I_I = −18 mA					−1.5			−1.5	V
V_{OH}	V_{CC} = MIN, V_{IH} = 2 V	V_{IL} = 0.7 V,	I_{OH} = −1 mA	2.4						V
		V_{IL} = 0.8 V,	I_{OH} = −2.6 mA				2.4			
V_{OL}	V_{CC} = MIN, V_{IH} = 2 V	V_{IL} = 0.7 V,	I_{OL} = 12 mA		0.25	0.4				V
		V_{IL} = 0.8 V,	I_{OL} = 12 mA					0.25	0.4	
		V_{IL} = 0.8 V,	I_{OL} = 24 mA					0.35	0.5	
I_{OZ}	V_{CC} = MAX, V_{IH} = 2 V	V_{IL} = 0.7 V	V_O = 2.4 V			20				μA
			V_O = 0.4 V			−20				
		V_{IL} = 0.8 V	V_O = 2.4 V						20	
			V_O = 0.4 V						−20	
I_I	V_{CC} = MAX, V_I = 7 V					0.1			0.1	mA
I_{IH}	V_{CC} = MAX, V_I = 2.7 V					20			20	μA
I_{IL}	V_{CC} = MAX, V_I = 0.4 V	'LS125A-$\overline{G}$ inputs				−0.2			−0.2	mA
		'LS125A-A inputs; 'LS126A All inputs				−0.4			−0.4	mA
I_{OS}§	V_{CC} = MAX			−40		−225	−40		−225	mA
I_{CC}	V_{CC} = MAX, (see Note 2)	'LS125A			11	20		11	20	mA
		'LS126A			12	22		12	22	

† For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.
‡ All typical values are at V_{CC} = 5 V, T_A = 25°C.
§ Not more than one output should be shorted at a time, and duration of the short circuit should not exceed one second.
NOTE 2: Data inputs = 0 V; Output controls = 4.5 V for 'LS125A and 0 V for 'LS126A.

switching characteristics, V_{CC} = 5 V, T_A = 25°C (see note 3)

PARAMETER	TEST CONDITIONS		SN54/74LS125A			SN54/74LS126A			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
t_{PLH}	R_L = 667 Ω,	C_L = 45 pF		9	15		9	15	ns
t_{PHL}				7	18		8	18	ns
t_{PZH}				12	20		16	25	ns
t_{PZL}				15	25		21	35	ns
t_{PHZ}	R_L = 667 Ω,	C_L = 5 pF			20			25	ns
t_{PLZ}					20			25	ns

NOTE 3: Load circuits and voltage waveforms are shown in Section 1.

IMPORTANT NOTICE

Texas Instruments (TI) reserves the right to make changes to its products or to discontinue any semiconductor product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

TI warrants performance of its semiconductor products and related software to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

Certain applications using semiconductor products may involve potential risks of death, personal injury, or severe property or environmental damage ("Critical Applications").

TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS.

Inclusion of TI products in such applications is understood to be fully at the risk of the customer. Use of TI products in such applications requires the written approval of an appropriate TI officer. Questions concerning potential risk applications should be directed to TI through a local SC sales office.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards should be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein. Nor does TI warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used.

Copyright © 1996, Texas Instruments Incorporated

IMPORTANT NOTICE

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.

Copyright © 1998, Texas Instruments Incorporated

This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.