

# Package StQT

*Luis Sanguiao Sande*

*13 de abril de 2016*

## Introduction

The StQT package is an attempt to standardize the representation of data transformations, in the same sense that StQ standardizes the representation of data. In fact, it stands for StQ Transformation. But, what do we understand by data transformation? In this context, it means a process that calculates a new data set from an old data set. For example, an imputation, a summary or even a forecast are transformations. But a data merge **is not** a transformation since we are using a second data set (except for a self data merge which will be explained later). If we would happen to need a transformation that uses information from two data sets, we would have to join them into a single data set before.

The

## The representation

It is strongly inspired in the syntax of operator `:=` from `data.table` package. The main idea is to apply a set of rules according to the sentence `data[<domain>,<output>:=<fun>(<input>),by=<by>]` where each `<>` surrounded item is an element of the rule. As long as function definition is included in the object, it is obvious that we can represent this way almost everything. Almost, because the number of rows of `data.table` data, would not be changed. The consequence was to allow a direct assignation in `<output>` field which when present, will create new rows. For a more detailed view of the syntax of the rules read next section.

Note that if we remove `<domain>` and `<by>` and put `<fun>` and `<input>` as the only elements of the rule we still can get any transformation (even with one rule). But this rules representation would be useless in that case, since you have a function (an R function) that does all the work. So, generally speaking: keep the functions as simple as possible and try to use the other fields of the rule to achieve that. And be conscious that a lower number of rules **is not** necessarily better.

## Detailed syntax

There are three types of rules in StQT:

- Horizontal: These are by far the more common rules and they are applied as we had said with a command like `data[<domain>,<output>:=<fun>(<input>),by=<by>]`. This creates new or override `<output>` columns with one element per row applying the usual recycling. Next, an elementary example.

```
require(data.table)
require(StQT)
dt <- data.table(Stratum = c("1","2","3"), SD = c(1.54,1.12,1.88))
dt
```

```
##      Stratum    SD
## 1:         1 1.54
## 2:         2 1.12
## 3:         3 1.88
```

```
T1 <- NewStQT(data.frame(
  domain = "",
  output = "VAR",
  fun = "*",
  input = "SD,SD",
  by = "",
  order = "",
  key = "",
  stringsAsFactors = FALSE))
TApply(dt,T1)[,]
```

```
##      Stratum   SD   VAR
## 1:         1 1.54 2.3716
## 2:         2 1.12 1.2544
## 3:         3 1.88 3.5344
```

We had a table with strata identified and its standard deviation. The transformation binds a new column with the variance of the correspondent strata. We could have defined a function returning the square of its argument. But we don't need to do that, because we can use R primitive function `*` calculating  $VAR$  as  $SD \times SD$ .

- Vertical: Similar to horizontal rules, but output includes some assignments (one or more). For each `<by>` group an additional row is created which copies the variables in `<by>`, sets the assigned variables and calculates the unassigned in a similar way to an horizontal rule. Let's see an easy example.

```
require(data.table)
require(StQT)
dt <- data.table(Region = c("1","2","3"), GDP = c(1.38,0.94,1.23))
dt
```

```
##      Region  GDP
## 1:         1 1.38
## 2:         2 0.94
## 3:         3 1.23
```

```
T1 <- NewStQT(data.frame(
  domain = "",
  output = "Region='Total',GDP",
  fun = "sum",
  input = "GDP",
  by = "",
  order = "",
  key = "",
  stringsAsFactors = FALSE))
TApply(dt,T1)
```

```
##      Region  GDP
## 1:         1 1.38
## 2:         2 0.94
## 3:         3 1.23
## 4:   Total 3.55
```

In this case `<by>` is empty, so we have only one group (the whole table) and in consequence we only bind one new row.

- Internal: These are not real functions but *special* codes in `<fun>` field that trigger concrete behaviors different to usual horizontal or vertical rules. They are *FunDelVar*, *FunDelRow* and *FunAutoLink* so far. Except for *FunDelRow*, we could write functions to get the same behavior (at least when applied to `data.table` objects), but they are anyways useful because implement common tasks in a standard way.

There is also an `<order>` field which if not empty, orders the data by the variables specified.

Note that `<key>` field is ignored unless we are transforming an StQ object (see next section).

## How does a transformation work on StQ objects

We are assuming that the reader is familiarized with StQ objects and its internal representation. First of all, we have to ask ourselves what a variable is. When you dcast an StQ object, you get a lot of columns with long "\_" separated names. For us, those **are not** variables. For us, a variable is an IDDD-sort element of the data slots from a DD object. Moreover it would be useful to think in it as a vector with a component for each qualifiers combination.

But we have to make some concessions to the qualifiers, because they are the “dimensions” of our vector variable. So we have to allow them in the rules, but we should avoid them when possible in `<input>` and `<output>` field, specially `<input>`. In `<by>` and `<domain>` they are perfectly acceptable. Let’s say we have a variable by unit and region, and we want the total by unit. Then we only have to sum the variable by unit and that’s it. In this example, we have had to use the unit qualifier in the `<by>` field, and the rule seems quite clear. By the way, we have to specify that the resulting variable has unit as only qualifier (and not unit *and* region). This is what `<key>` field is intended for. We know that R sum function returns a single value, and since we are grouping by unit, the `<key>` should be unit. But if we substitute sum by another function, and we only have its closure and arguments, it would be very difficult to find an automatic way to decide if it returns a single value. So we specify `<key>` as unit.

A second question is what do we do with more than one variable. Let’s see. If we have two or more variables whose qualifiers are exactly the same, we only have to put them as columns and we have a `data.table` where to apply the rule as usual. It is natural to associate values of both variables when they have the same key. When their qualifiers are different, we look for a variable whose qualifiers are the union of all the qualifiers of all the variables. We are going to name this variable as main variable, and we are going to use it to link them all. If such variable does not exist, that means that there are more than one maximal variables (in the sense that its qualifiers are not included in the other qualifiers), and there is not an unique way to link them. In this case the rule is considered no valid, and an error is shown. If we need to link this way, we have to use auxiliary variables.

## Other methods